PLAN-09 - Rollout, Observability, and Recovery

POS-DGFY - Global Location Switching | Plan v1.0 | Revision 2026-09-27

Field	Value
Project	POS-DGFY - Global Location Switching
Plan version	1.0
Section	PLAN-09 - Rollout, Observability, and Recovery
Revision date	2026-09-27
Plan status	NOT EXECUTION READY
Purpose	Define the safest release strategy, measurable signals, stop conditions, rollback, and operational recovery.
Dependencies	PLAN-07 and PLAN-08; deployment policy; existing monitoring and reconciliation tooling.

Release strategy

Use a server-authoritative feature flag and pilot rollout for one representative multi-location tenant before broader release. The flag must not bypass backend authorization or change historical data.

Release sequence

- Run repository checks, migration rehearsal, security tests, regression tests, and E2E evidence.
- Deploy compatible backend and migration preparation.
- Enable the feature for internal users or one pilot tenant.
- Observe transition, stock, queue, report, permission, and audit signals.
- Expand location-by-location or tenant-by-tenant only after the observation gate passes.

Success signals

Signal	Expected behavior
Switch success rate	Authorized valid switches succeed without retries or manual repair.
Authorization failures	Only expected denials; no unexpected cross-location access.
Inventory parity	Stock movements and reports reconcile by location.
Cash/shift parity	Closing/opening values and transitions reconcile.
Queue isolation	Incoming orders appear only for the active operating scope.
Audit completeness	Every transition has actor, source, destination, reason, and outcome.
UX errors	Users can understand and recover from blocked transitions.

Immediate stop conditions

- Cross-tenant or cross-location data leakage.
- Incorrect inventory movement, cash total, or financial report.
- Missing or incorrect audit attribution.
- Partial shift transition or duplicate shift opening.
- Parked sale or incoming queue appears under the wrong location.

- Critical security, migration, or API failure.

Rollback and recovery

- Disable the feature flag and restore safe application code/configuration.
- Keep additive schema changes in place until written data is reconciled.
- Reconcile transactions, stock, shifts, queue records, and audit events created during the incident.
- Preserve evidence, document root cause, update the plan and tests, and retry only after corrective verification.

Operational evidence

Capture deployment SHA, application/database version, feature-flag state, migration result, test evidence, metrics snapshot, audit sample, and rollback readiness before declaring release success.