

## Specifying the Behavior of Expressions

### Exercise 3.1

$\lfloor (\text{value-of } \langle\langle x \rangle\rangle \rho) \rfloor = 10$

$\lfloor (\text{value-of } \langle\langle 3 \rangle\rangle \rho) \rfloor = 3$

$\lfloor (\text{value-of } \langle\langle v \rangle\rangle \rho) \rfloor = 5$

$\lfloor (\text{value-of } \langle\langle i \rangle\rangle \rho) \rfloor = 1$

### Exercise 3.2

A  $val \in ExpVal$  must be that which is in  $Int + Bool$ . Then a  $val \in ExpVal$  for which  $\lfloor [val] \rfloor \neq val$  is where  $val \in Bool$ , such as  $val = true$ .

### Exercise 3.3

We are able to describe the arithmetic operations in terms of subtraction. We cannot do so if we chose addition.

### Exercise 3.4

Let  $\rho = [x=[33], y=[22]]$ .

$$\frac{\frac{\text{(value-of-program } \langle\langle \text{if zero? } (-(x, 11)) \text{ then } -(y, 2) \text{ else } -(y, 4) \rangle\rangle)}{\text{(value-of } \langle\langle \text{if zero? } (-(x, 11)) \text{ then } -(y, 2) \text{ else } -(y, 4) \rangle\rangle \rho)}}{\text{(value-of } \langle\langle \text{zero? } (-(x, 11)) \rangle\rangle \rho) = (\text{bool-val } \#f)}}{\text{(value-of } \langle\langle -(y, 4) \rangle\rangle \rho)}$$

[18]

### Exercise 3.5

$$\frac{\begin{array}{l} \text{(value-of } \langle\langle \text{let } x = 7 \\ \quad \text{in let } y = 2 \\ \text{in let } y = \text{let } x = -(x, 1) \text{ in } -(x, y) \\ \quad \text{in } -(-(x, 8), y) \rangle\rangle \rho_0) \end{array}}{skib}$$

### Exercise 3.6

```

(minus-exp (exp1 expression?))

(minus-exp (exp1)
  (value-of (diff-exp (const-exp 0)
    exp1)
    env))

```

### Exercise 3.7

```

(add-exp
  (exp1 expression?)
  (exp2 expression?))
(mul-exp
  (exp1 expression?)
  (exp2 expression?))
(div-exp
  (exp1 expression?)
  (exp2 expression?))

(add-exp (exp1 exp2)
  (num-val (+ (expval->num (value-of exp1 env))
    (expval->num (value-of exp2 env))))))
(mul-exp (exp1 exp2)
  (num-val (* (expval->num (value-of exp1 env))
    (expval->num (value-of exp2 env))))))

```

```
                (expval->num (value-of exp2 env))))))
(div-exp (exp1 exp2)
  (let ((val2 (expval->num (value-of exp2 env))))
    (if (= 0 val2)
        (report-division-by-zero)
        (num-val (/ (expval->num (value-of exp1 env))
                     val2))))))
```