

SelcomPay/Masterpass eCommerce API Specification

Version 1.3 Last updated 30 November 2018



Change log

2018-11-30 Added qr string in the paymentCreate api response

2018-11-18 Updated base URL from https://paypoint.selcommobile.com/v1/ to https://api.selcommobile.com/v1/



Base URL

https://api.selcommobile.com/v1/

Authentication

Authenticate your request by including your API key and hashed digest of your API key, API secret and timestamp in your request HTTP headers. You will receive your API key and API secret directly from Selcom. Your API key and API secret carry many privileges, so be sure to keep them secure and do not share them in publicly accessible areas such as GitHub, client-side code, and so forth.

All API requests must be made over HTTPS. Calls made over plain HTTP will fail. API requests without authentication will also fail.

HTTP headers required

Content-type	application/json	Required
api_key	API key provided by Selcom	Required
digest	Digest calculated by the digest function shown below	Required
request_timestamp	Timestamp in Y-m-d H:i:s format	Required



Digest function

```
function getDigest($timestamp, $api key, $api secret) {
        return md5($timestamp . $api_secret) . sha1(sha1($timestamp . $api_key . $api_secret, true));
}
Post function
function postRequest($url, $request, $api_key, $api_digest, $timestamp) {
        $ch = curl init();
        curl setopt($ch, CURLOPT URL, $url);
        curl_setopt($ch, CURLOPT_HTTPAUTH, CURLAUTH_ANY);
        curl_setopt($ch, CURLOPT_SSL_VERIFYPEER, false);
        curl setopt($ch, CURLOPT SSL VERIFYHOST, 0);
        curl_setopt($ch, CURLOPT_RETURNTRANSFER, 1);
        curl setopt($ch, CURLOPT SSLVERSION,1);
        curl setopt($ch, CURLOPT POSTFIELDS, $request);
        curl_setopt($ch, CURLOPT_HTTPHEADER, array(
                 "Content-type: application/json",
                 "api key: $api key",
                 "digest: $api_digest",
                 "request_timestamp: $timestamp"
        ));
        $response = curl exec($ch);
        curl close($ch);
        return $response;
}
Sample API call
$url = "https://paypoint.selcommobile.com/v1/paymentCreate";
$request = array(
        "order_id" => "2018092502",
        "amount" => "500",
        "currency" => "TZS",
        "payer remarks" => "None",
        "merchant_remarks" => "None",
        "payer_email" => "test@email.net",
        "payer phone" => "255784123456"
);
$api key = "testmerchant";
$api_secret = "ffd4fac7-4a7a-422a-8d5a-70912d57442a";
$timestamp = gmdate("Y-m-d H:i:s");
$api_digest = getDigest($timestamp, $api_key, $api_secret);
$request_string = json_encode($request);
$response string = postRequest($url, $request string, $api key, $api digest, $timestamp);
```



Methods

1. paymentCreate

Request a payments token from the gateway to be redeemed using Selcompay/Masterpass payment option through mobile money, mobile banking and Selcom Card.

Request attributes

order_id	Unique identifier from the merchant system	Required
		String (1-100)
amount	Amount of the transaction to be collected	Required
		Integer
currency	Three letter ISO currency code (TZS)	Required
		String (3)
payer_remarks	Any remarks or instructions from the customer	Optional
		String (0-100)
merchant_remarks	Any remarks or instructions from the merchant	Optional
		String (0-100)
payer_email	Customer's email address	Optional
		String (0-50)
payer_phone	Customers' phone number	Optional
		String (0 12)

Response attributes

Result	Result of the request submitted	SUCCESS FAIL
message	Description of the result	
order_id	Unique identifier echoed back	
payment_token	Payment token to be used by the customer to make the payment	
payment_status	Status of the payment	PENDING CANCELLED COMPLETED
qr	QR String to be used for Scan and Pay	

Sample API call

https://paypoint.selcommobile.com/v1/paymentCreate

Request JSON

{"order_id":"2018092301","amount":"1000","currency":"TZS","payer_remarks":"Any remarks from the payer during payment","merchant_remarks":"Order for payment of 3x12in cheeze pizzas","payer_email":"payee@mail.com","payer_phone":"255784670921"}

Response JSON

{"result":"SUCCESS","message":"Payment notification

logged","order_id":"2018092301","amount":"1000","currency":"TZS","payment_token":"80001746","payment_st atus":"PENDING", "qr":"00020101021104155254542999000205204581253038345802TZ5920SELCOM PAY DEMO TILL6003DSM6106000000622401088000174603086001462863040662"}





2. paymentStatus/{order_id}

Query the status of a payment token

Request attributes

order_id	Unique identifier from the merchant system	Required String (1-100)
Response attribute	es ·	
result	Result of the request submitted	SUCCESS FAIL
message	Description of the result	
order_id	Unique identifier echoed back	
payment_status	Status of the payment	PENDING CANCELLED COMPLETED

Sample 1

API call

https://paypoint.selcommobile.com/v1/paymentStatus/123456

Request JSON

NA

Response JSON

{"result":"FAIL","message":"123456 not found"}

Sample 2

API call

https://paypoint.selcommobile.com/v1/paymentStatus/2018092301

Request JSON

NA

Response JSON

 $\{"result":"SUCCESS","order_id":"2018092301","payment_status":"PENDING"\}$

Sample 3

API call

https://paypoint.selcommobile.com/v1/paymentStatus/2018092501

Request JSON

NA

Response JSON

 $\label{thm:success} $$ {\tt "result": "SUCCESS", "order_id": "2018092501", "transid": "20180924232308", "reference": "6695843844", "channel": "SELCOMCARD", "amount": "500", "phone": "255786455554", "payment_status": "COMPLETED" }$





3. paymentCancel/{order_id}

Cancel a payment token

Request attributes

order_id	Unique identifier from the merchant system	Required String (1-100)
Response attributes	:	
result	Result of the request submitted	SUCCESS FAIL
message	Description of the result	
order_id	Unique identifier echoed back	
payment_status	Status of the payment	PENDING CANCELLED COMPLETED

Sample 1

API call

https://paypoint.selcommobile.com/v1/paymentCancel/123456

Request JSON

NA

Response JSON

{"result":"FAIL","message":"123456 not found"}

Sample 2

API call

https://paypoint.selcommobile.com/v1/paymentCancel/2018092301

Request JSON

NA

Response JSON

{"result":"SUCCESS","order_id":"2018092301","payment_status":"CANCELLED"}

Sample 3

API call

https://paypoint.selcommobile.com/v1/paymentCancel/2018092501

Request JSON

NA

Response JSON

{"result":"FAIL","message":"2018092501 has already been completed","order_id":"2018092501","payment_status":"COMPLETED"}





Callbacks/webhooks

On successful payment or redemption of a payment token Selcom can post back a JSON notification to a callback URL provided by the merchant. The JSON content posted back is shown below.

Callback attributes

result	Result of the payment	SUCCESS
order_id	Unique identifier echoed back	
transid	Unique transaction identifier from the payment channel used to make the payment	
reference	Unique transaction identifier from the Selcom gateway	
channel	Channel used to pay	
amount	Payment amount	
phone	Phone number of the customer	
payment_status	Status of the payment	COMPLETED

Sample

Request callback JSON

{"result":"SUCCESS","order_id":"2018092501","transid":"20180924232308","reference":"6695843844","channel": "SELCOMCARD","amount":"500","phone":"255786455554","payment_status":"COMPLETED"}

Response JSON expected from merchant

{"response":"OK"}