



Joshnavi K B 251801122-2025-AIDS ▾

J2

Started on Thursday, 24 September 2026, 10:25 AM**State** Finished**Completed on** Thursday, 24 September 2026, 10:34 AM**Time taken** 9 mins 3 secs**Marks** 1.00/1.00**Grade** 10.00 out of 10.00 (100%)

Question 1 | Correct | Mark 1.00 out of 1.00

Find Duplicate in Array.

Given a read only array of n integers between 1 and n, find one number that repeats.

Input Format:

First Line - Number of elements

n Lines - n Elements

Output Format:

Element x - That is repeated

For example:

Input	Result
5 1 1 2 3 4	1

Answer: (penalty regime: 0 %)

```

1  #include<stdio.h>
2  int main(){
3      int n;
4      scanf("%d",&n);
5      int a[n];
6      for(int i=0;i<n;i++){
7          scanf("%d",&a[i]);
8      }
9      for(int i=0;i<n;i++){
10         for(int j=i+1;j<n;j++){
11             if(a[i]==a[j]){
12                 printf("%d",a[i]);
13                 return 0;
14             }
15         }
16     }
17 }
```

	Input	Expected	Got	
✓	11 10 9 7 6 5 1 2 3 8 4 7	7	7	✓
✓	5 1 2 3 4 4	4	4	✓
✓	5 1 1 2 3 4	1	1	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

[Back to Course](#)



Joshnavi K B 251801122-2025-AIDS ▾

J2

Started on Thursday, 24 September 2026, 10:34 AM**State** Finished**Completed on** Thursday, 24 September 2026, 10:38 AM**Time taken** 3 mins 36 secs**Marks** 1.00/1.00**Grade** 10.00 out of 10.00 (100%)

Question 1 | Correct | Mark 1.00 out of 1.00

Find Duplicate in Array.

Given a read only array of n integers between 1 and n, find one number that repeats.

Input Format:

First Line - Number of elements

n Lines - n Elements

Output Format:

Element x - That is repeated

For example:

Input	Result
5 1 1 2 3 4	1

Answer: (penalty regime: 0 %)

```

1  #include<stdio.h>
2  int main(){
3      int n;
4      scanf("%d",&n);
5      int a[n];
6      for(int i=0;i<n;i++){
7          scanf("%d",&a[i]);
8      }
9      for(int i=0;i<n;i++){
10         for(int j=i+1;j<n;j++){
11             if(a[i]==a[j]){
12                 printf("%d",a[i]);
13                 return 0;
14             }
15         }
16     }
17 }
```

	Input	Expected	Got	
✓	11 10 9 7 6 5 1 2 3 8 4 7	7	7	✓
✓	5 1 2 3 4 4	4	4	✓
✓	5 1 1 2 3 4	1	1	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

[Back to Course](#)



Joshnavi K B 251801122-2025-AIDS ▾

J2

Started on Thursday, 24 September 2026, 10:38 AM**State** Finished**Completed on** Thursday, 24 September 2026, 10:55 AM**Time taken** 16 mins 43 secs**Marks** 1.00/1.00**Grade** 10.00 out of 10.00 (100%)

Question 1 | Correct | Mark 1.00 out of 1.00

Find the intersection of two sorted arrays.

OR in other words,

Given 2 sorted arrays, find all the elements which occur in both the arrays.

Input Format

· The first line contains T, the number of test cases. Following T lines contain:

1. Line 1 contains N1, followed by N1 integers of the first array
2. Line 2 contains N2, followed by N2 integers of the second array

Output Format

The intersection of the arrays in a single line

Example

Input:

1

3 10 17 57

6 2 7 10 15 57 246

Output:

10 57

Input:

1

6 1 2 3 4 5 6

2 1 6

Output:

1 6

For example:

Input	Result
1 3 10 17 57 6 2 7 10 15 57 246	10 57

Answer: (penalty regime: 0 %)

```

1  #include<stdio.h>
2  int main(){
3      int t;
4      scanf("%d",&t);
5      while(t--){
6          int n1,n2;
7          scanf("%d",&n1);
8          int a[n1];
9          for(int i=0;i<n1;i++){
10             scanf("%d",&a[i]);
11         }
12         scanf("%d",&n2);
13         int b[n2];
14         for(int i=0;i<n2;i++){
15             scanf("%d",&b[i]);
16         }
17         for(int i=0;i<n1;i++){
18             for(int j=0;j<n2;j++){
19                 if(a[i]==b[j]){
20                     printf("%d ",a[i]);
21                     break;
22                 }

```



```
23     }
24     }
25     printf("\n");
26 }return 0;
27 }
```

	Input	Expected	Got	
✓	1 3 10 17 57 6 2 7 10 15 57 246	10 57	10 57	✓
✓	1 6 1 2 3 4 5 6 2 1 6	1 6	1 6	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.



[Back to Course](#)



Joshnavi K B 251801122-2025-AIDS ▾

J2

Started on Thursday, 24 September 2026, 10:55 AM**State** Finished**Completed on** Thursday, 24 September 2026, 10:57 AM**Time taken** 1 min 29 secs**Marks** 1.00/1.00**Grade** 10.00 out of 10.00 (100%)

Question 1 | Correct Mark 1.00 out of 1.00

Find the intersection of two sorted arrays.

OR in other words,

Given 2 sorted arrays, find all the elements which occur in both the arrays.

Input Format

· The first line contains T, the number of test cases. Following T lines contain:

1. Line 1 contains N1, followed by N1 integers of the first array
2. Line 2 contains N2, followed by N2 integers of the second array

Output Format

The intersection of the arrays in a single line

Example

Input:

1

3 10 17 57

6 2 7 10 15 57 246

Output:

10 57

Input:

1

6 1 2 3 4 5 6

2 1 6

Output:

1 6

For example:

Input	Result
1 3 10 17 57 6 2 7 10 15 57 246	10 57

Answer: (penalty regime: 0 %)

```

1  #include <stdio.h>
2
3  int main() {
4      int T;
5      scanf("%d", &T);
6
7      while (T--) {
8          int n1, n2;
9          scanf("%d", &n1);
10
11          int a[n1];
12          for (int i = 0; i < n1; i++)
13              scanf("%d", &a[i]);
14
15          scanf("%d", &n2);
16
17          int b[n2];
18          for (int i = 0; i < n2; i++)
19              scanf("%d", &b[i]);
20
21          int i = 0, j = 0;
22

```

```
23 while (i < n1 && j < n2) {
24     if (a[i] == b[j]) {
25         printf("%d ", a[i]);
26         i++;
27         j++;
28     }
29     else if (a[i] < b[j]) {
30         i++;
31     }
32     else {
33         j++;
34     }
35 }
36
37 printf("\n");
38 }
39
40 return 0;
41 }
```

	Input	Expected	Got	
✓	1 3 10 17 57 6 2 7 10 15 57 246	10 57	10 57	✓
✓	1 6 1 2 3 4 5 6 2 1 6	1 6	1 6	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.



[Back to Course](#)



Joshnavi K B 251801122-2025-AIDS ▾

J2

Started on Thursday, 24 September 2026, 10:57 AM**State** Finished**Completed on** Thursday, 24 September 2026, 10:59 AM**Time taken** 1 min 27 secs**Marks** 1.00/1.00**Grade** 10.00 out of 10.00 (100%)

Question 1 | Correct | Mark 1.00 out of 1.00

Given an array A of sorted integers and another non negative integer k, find if there exists 2 indices i and j such that $A[j] - A[i] = k$, $i \neq j$.

Input Format:

First Line n - Number of elements in an array

Next n Lines - N elements in the array

k - Non - Negative Integer

Output Format:

1 - If pair exists

0 - If no pair exists

Explanation for the given Sample Testcase:

YES as $5 - 1 = 4$

So Return 1.

For example:

Input	Result
3 1 3 5 4	1

Answer: (penalty regime: 0 %)

```

1  #include <stdio.h>
2
3  int main() {
4      int n, k;
5      scanf("%d", &n);
6
7      int a[n];
8
9      for (int i = 0; i < n; i++)
10         scanf("%d", &a[i]);
11
12     scanf("%d", &k);
13
14     int i = 0, j = 1;
15
16     while (i < n && j < n) {
17         if (i == j) {
18             j++;
19         }
20         else if (a[j] - a[i] == k) {
21             printf("1");
22             return 0;
23         }
24         else if (a[j] - a[i] < k) {
25             j++;
26         }
27         else {
28             i++;
29         }
30     }
31
32     printf("0");
33
34     return 0;
35 }
```

	Input	Expected	Got	
✓	3 1 3 5 4	1	1	✓
✓	10 1 4 6 8 12 14 15 20 21 25 1	1	1	✓
✓	10 1 2 3 5 11 14 16 24 28 29 0	0	0	✓
✓	10 0 2 3 7 13 14 15 20 24 25 10	1	1	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

[Back to Course](#)



Joshnavi K B 251801122-2025-AIDS ▾

J2

Started on Thursday, 24 September 2026, 10:59 AM**State** Finished**Completed on** Thursday, 24 September 2026, 11:01 AM**Time taken** 1 min 43 secs**Marks** 1.00/1.00**Grade** 10.00 out of 10.00 (100%)

Question 1 | Correct | Mark 1.00 out of 1.00

Given an array A of sorted integers and another non negative integer k, find if there exists 2 indices i and j such that $A[j] - A[i] = k$, $i \neq j$.

Input Format:

First Line n - Number of elements in an array

Next n Lines - N elements in the array

k - Non - Negative Integer

Output Format:

1 - If pair exists

0 - If no pair exists

Explanation for the given Sample Testcase:

YES as $5 - 1 = 4$

So Return 1.

For example:

Input	Result
3 1 3 5 4	1

Answer: (penalty regime: 0 %)

```

1  #include <stdio.h>
2
3  int main() {
4      int n, k;
5      scanf("%d", &n);
6
7      int a[n];
8
9      for (int i = 0; i < n; i++)
10         scanf("%d", &a[i]);
11
12     scanf("%d", &k);
13
14     int i = 0, j = 1;
15
16     while (i < n && j < n) {
17         if (i == j) {
18             j++;
19         }
20         else if (a[j] - a[i] == k) {
21             printf("1");
22             return 0;
23         }
24         else if (a[j] - a[i] < k) {
25             j++;
26         }
27         else {
28             i++;
29         }
30     }
31
32     printf("0");
33
34     return 0;
35 }
```

	Input	Expected	Got	
✓	3 1 3 5 4	1	1	✓
✓	10 1 4 6 8 12 14 15 20 21 25 1	1	1	✓
✓	10 1 2 3 5 11 14 16 24 28 29 0	0	0	✓
✓	10 0 2 3 7 13 14 15 20 24 25 10	1	1	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

[Back to Course](#)