

Modification for Non-Conventional Projects:

Delete the above sentence and insert the following:
For special structures (e.g. cable, suspension, and other structures not normally used by FDOT), submit the redundancy factor in the ATC, unless otherwise noted in the RFP.

Commentary: The intent is to apply η_R at the component level. For example, η_R of 1.2 for two steel box girders without exterior diaphragms is applicable to the design of the box girders only and not to other bridge components such as the bearings, substructure and foundation. Furthermore, several NCHRP reports (e.g. 406 and 776) have addressed redundancy in highway bridge superstructures. Due to NCHRP Report 776 findings that continuous steel girders with non-compact negative moment sections may not substantiate a decreased redundancy factor, the previous distinction between simple and continuous girders has been eliminated.

B. Ductility **LRFD** 1.3.3 and Operational Importance **LRFD** 1.3.5. Delete the values for Ductility, η_D , and Operational Importance, η_I , in **LRFD** 1.3.3 and 1.3.5 and use $\eta_D = 1.0$ and $\eta_I = 1.0$

Modification for Non-Conventional Projects:

Delete **SDG** 2.10.B and see the RFP for requirements.

*Commentary: The redundancy factor section first appeared in the **SDG** by the implementation of Temporary Design Bulletin C06-01 and was revised in subsequent years. The original and current intent is to apply the redundancy factor only at the component level. Furthermore, research through several NCHRP reports (e.g. 406 and 776) have addressed redundancy in highway bridge superstructures. Due to NCHRP Report 776 findings that continuous steel girders with non-compact negative moment areas may not substantiate a decreased redundancy factor, the previous distinction between simple and continuous girders has been eliminated for now.*

2.11 VESSEL COLLISION (LRFD 3.14)

2.11.1 General (LRFD 3.14.1)

A. The design of all bridges over navigable waters must include consideration for possible Vessel Collision (usually from barges or ocean going ships). Conduct a vessel risk analysis to determine the most economical method for protecting the bridge. The marine vessel traffic characteristics are available for bridges located across inland waterways and rivers carrying predominately barges. The number of vessel passages and the vessel sizes are embedded as an integral part of the Department's Vessel Collision Risk Analysis Software. The vessel traffic provided is