
Project*

First Saved	Friday, July 24, 2026
Last Saved	Friday, July 24, 2026
Product Version	2025 R2
Save Project Before Solution	No
Save Project After Solution	No



Contents

- Units
- Model (A4)
  - Geometry Imports
    - Geometry Import (A3)
  - Geometry
    - Parts
  - Materials
  - Coordinate Systems
  - Connections
    - Contacts
      - Contact Region
      - Frictionless - FLAT TOP ROD|Body2 To FLAT TOP ROD|Body3
  - Mesh
  - Static Structural (A5)
    - Analysis Settings
    - Loads
    - Solution (A6)
      - Solution Information
      - Results
      - Contact Tool
        - Status
      - Probes
- Material Data
  - ECOFLEX-0045
  - Plastic, ABS (high-impact)

Units

TABLE 1

Unit System	Metric (m, kg, N, s, V, A) Degrees rad/s Celsius
Angle	Degrees
Rotational Velocity	rad/s
Temperature	Celsius

Model (A4)

TABLE 2
Model (A4) > Geometry Imports

Object Name	*Geometry Imports*
State	Solved

TABLE 3
Model (A4) > Geometry Imports > Geometry Import (A3)

Object Name	*Geometry Import (A3)*
State	Solved
Definition	
Source	C:\Users\DLSU\Downloads\TEST RODS\FLAT TOP ROD.step
Type	Step
Basic Geometry Options	
Solid Bodies	Yes
Surface Bodies	Yes
Line Bodies	No
Parameters	Independent
Parameter Key	ANS;DS
Attributes	No
Named Selections	No
Material Properties	No
Advanced Geometry Options	
Use Associativity	Yes
Coordinate Systems	No
Reader Mode Saves Updated File	No
Use Instances	Yes
Smart CAD Update	Yes
Compare Parts On Update	No
Analysis Type	3-D

Mixed Import Resolution	None
Import Facet Quality	Source
Clean Bodies On Import	No
Stitch Surfaces On Import	None
Decompose Disjoint Geometry	Yes
Enclosure and Symmetry Processing	Yes

Geometry

TABLE 4
Model (A4) > Geometry

Object Name	*Geometry*
State	Fully Defined
Definition	
Source	C:\Users\DLSU\Downloads\TEST RODS\FLAT TOP ROD.step
Type	Step
Length Unit	Millimeters
Element Control	Program Controlled
Display Style	Body Color
Bounding Box	
Length X	1.e-002 m
Length Y	1.e-002 m
Length Z	4.375e-002 m
Properties	
Volume	8.7679e-007 m³
Mass	9.1116e-004 kg
Scale Factor Value	1.
Statistics	
Bodies	3
Active Bodies	3
Nodes	2219
Elements	604
Mesh Metric	None
Update Options	
Assign Default Material	No
Basic Geometry Options	
Solid Bodies	Yes
Surface Bodies	Yes
Line Bodies	No
Parameters	Independent
Parameter Key	ANS;DS
Attributes	No
Named Selections	No
Material Properties	No
Advanced Geometry Options	
Use Associativity	Yes
Coordinate Systems	No
Reader Mode Saves Updated File	No
Use Instances	Yes
Smart CAD Update	Yes
Compare Parts On Update	No
Analysis Type	3-D
Mixed Import Resolution	None
Import Facet Quality	Source
Clean Bodies On Import	No
Stitch Surfaces On Import	None
Decompose Disjoint Geometry	Yes
ID_GeometryPrefProcessPhysicsDefinition	No
Enclosure and Symmetry Processing	Yes

TABLE 5
Model (A4) > Geometry > Parts

Object Name	*FLAT TOP ROD|Body1*	*FLAT TOP ROD|Body2*	*FLAT TOP ROD|Body3*
State	Meshed		
Graphics Properties			
Visible	Yes		
Transparency	1		
Definition			
Suppressed	No		
Stiffness Behavior	Flexible		
Coordinate System	Default Coordinate System		
Reference Temperature	By Environment		

Treatment	None		
Material			
Assignment	ECOFLEX-0045		Plastic, ABS (high-impact)
Nonlinear Effects	Yes		
Thermal Strain Effects	Yes		
Bounding Box			
Length X	1.e-002 m	7.e-003 m	4.e-003 m
Length Y	1.e-002 m	7.e-003 m	4.e-003 m
Length Z	1.75e-003 m	3.5e-003 m	3.8e-002 m
Properties			
Volume	1.5819e-007 m³	1.106e-007 m³	6.08e-007 m³
Mass	1.6768e-004 kg	1.1723e-004 kg	6.2624e-004 kg
Centroid X	1.2048e-020 m	4.1831e-020 m	0. m
Centroid Y	-8.0008e-020 m	-1.2397e-019 m	0. m
Centroid Z	-8.75e-004 m	1.8587e-003 m	2.3e-002 m
Moment of Inertia Ip1	1.575e-009 kg·m²	5.4206e-010 kg·m²	7.6193e-008 kg·m²
Moment of Inertia Ip2	1.575e-009 kg·m²	5.4206e-010 kg·m²	7.6193e-008 kg·m²
Moment of Inertia Ip3	3.0644e-009 kg·m²	8.348e-010 kg·m²	1.67e-009 kg·m²
Statistics			
Nodes	828	800	591
Elements	120	408	76
Mesh Metric	None		

TABLE 6
Model (A4) > Materials

Object Name	*Materials*
State	Fully Defined
Statistics	
Materials	3
Material Assignments	0

Coordinate Systems

TABLE 7
Model (A4) > Coordinate Systems > Coordinate System

Object Name	*Global Coordinate System*
State	Fully Defined
Definition	
Type	Cartesian
Coordinate System ID	0.
Origin	
Origin X	0. m
Origin Y	0. m
Origin Z	0. m
Directional Vectors	
X Axis Data	[1. 0. 0.]
Y Axis Data	[0. 1. 0.]
Z Axis Data	[0. 0. 1.]
Transfer Properties	
Source	
Read Only	No

Connections

TABLE 8
Model (A4) > Connections

Object Name	*Connections*
State	Fully Defined
Auto Detection	
Generate Automatic Connection On Refresh	Yes
Transparency	
Enabled	Yes
Statistics	
Contacts	2
Active Contacts	2
Joints	0
Active Joints	0
Beams	0
Active Beams	0
Bearings	0
Active Bearings	0
Springs	0

Active Springs	0
Body Interactions	0
Active Body Interactions	0

TABLE 9
Model (A4) > Connections > Contacts

Object Name	*Contacts*	*Contacts 2*
State	Fully Defined	
Definition		
Connection Type	Contact	
Scope		
Scoping Method	Geometry Selection	
Geometry	All Bodies	
Auto Detection		
Tolerance Type	Slider	
Tolerance Slider	0.	
Tolerance Value	1.1495e-004 m	
Use Range	No	
Face/Face	Yes	
Face-Face Angle Tolerance	75. °	
Face Overlap Tolerance	Off	
Cylindrical Faces	Include	
Face/Edge	No	
Edge/Edge	No	
Priority	Include All	
Group By	Bodies	
Search Across	Bodies	
Statistics		
Connections	1	
Active Connections	1	

TABLE 10
Model (A4) > Connections > Contacts > Contact Regions

Object Name	*Contact Region*
State	Fully Defined
Scope	
Scoping Method	Geometry Selection
Contact	1 Face
Target	1 Face
Contact Bodies	FLAT TOP ROD|Body1
Target Bodies	FLAT TOP ROD|Body2
Protected	No
Definition	
Type	Bonded
Scope Mode	Automatic
Behavior	Program Controlled
Trim Contact	Program Controlled
Trim Tolerance	1.1495e-004 m
Contact APDL Name	
Target APDL Name	
Suppressed	No
Display	
Element Normals	No
Advanced	
Formulation	Program Controlled
Small Sliding	Program Controlled
Detection Method	Program Controlled
Penetration Tolerance	Program Controlled
Elastic Slip Tolerance	Program Controlled
Normal Stiffness	Program Controlled
Update Stiffness	Program Controlled
Pinball Region	Program Controlled
Geometric Modification	
Contact Geometry Correction	None
Target Geometry Correction	None

TABLE 11
Model (A4) > Connections > Contacts 2 > Contact Regions

Object Name	*Frictionless - FLAT TOP ROD|Body2 To FLAT TOP ROD|Body3*
State	Fully Defined
Scope	
Scoping Method	Geometry Selection

Contact	1 Face
Target	1 Face
Contact Bodies	FLAT TOP ROD|Body2
Target Bodies	FLAT TOP ROD|Body3
Protected	No
Definition	
Type	Frictionless
Scope Mode	Manual
Behavior	Asymmetric
Trim Contact	Program Controlled
Contact APDL Name	
Target APDL Name	
Suppressed	No
Display	
Element Normals	No
Advanced	
Formulation	Augmented Lagrange
Small Sliding	Program Controlled
Detection Method	Program Controlled
Penetration Tolerance	Program Controlled
Normal Stiffness	Program Controlled
Update Stiffness	Program Controlled
Stabilization Damping Factor	0.
Pinball Region	Program Controlled
Time Step Controls	None
Geometric Modification	
Interface Treatment	Add Offset, No Ramping
Offset	0. m
Contact Geometry Correction	None
Target Geometry Correction	None

Mesh

TABLE 12
Model (A4) > Mesh

Object Name	*Mesh*
State	Solved
Display	
Display Style	Use Geometry Setting
Defaults	
Physics Preference	Mechanical
Element Order	Program Controlled
Element Size	Default
Sizing	
Mesh Sizing	Adaptive
Resolution	Default (2)
Mesh Defeaturing	Yes
Defeature Size	1.1459e-005 m
Transition	Fast
Span Angle Center	Coarse
Initial Size Seed	Assembly
Bounding Box Diagonal	4.5979e-002 m
Average Surface Area	6.0634e-005 m²
Minimum Edge Length	1.75e-003 m
Quality	
Check Mesh Quality	Yes, Errors
Error Limits	Aggressive Mechanical
Target Element Quality	Default (0.1)
Smoothing	Medium
Mesh Metric	None
Inflation	
Use Automatic Inflation	None
Inflation Option	Smooth Transition
Transition Ratio	0.272
Maximum Layers	5
Growth Rate	1.2
Inflation Algorithm	Pre
Inflation Element Type	Wedges
View Advanced Options	No
Advanced	
Number of CPUs for Parallel Part Meshing	Program Controlled
Straight Sided Elements	No

Rigid Body Behavior	Dimensionally Reduced
Triangle Surface Mesher	Program Controlled
Topology Checking	Yes
Pinch Tolerance	Please Define
Generate Pinch on Refresh	No
Auto-Map Fillets	No
Automatic Methods	
Sheet Body Method	Prime Quad Dominant
Sweepable Body Method	Sweep
Statistics	
Nodes	2219
Elements	604
Show Detailed Statistics	No

Static Structural (A5)

TABLE 13
Model (A4) > Analysis

Object Name	*Static Structural (A5)*
State	Solved
Definition	
Physics Type	Structural
Analysis Type	Static Structural
Solver Target	Mechanical APDL
Options	
Environment Temperature	22. °C
Generate Input Only	No

TABLE 14
Model (A4) > Static Structural (A5) > Analysis Settings


Object Name	*Analysis Settings*
State	Fully Defined
Step Controls	
Number Of Steps	1.
Current Step Number	1.
Step End Time	1. s
Auto Time Stepping	On
Define by	Substeps
Initial Substeps	20.
Minimum Substeps	5.
Maximum Substeps	500.
Maximum Iterations Per Substep	Program Controlled
Solver Controls	
Solver Type	Program Controlled
Weak Springs	On
Spring Stiffness	Program Controlled
Solver Pivot Checking	Program Controlled
Large Deflection	On
Inertia Relief	Off
Quasi-Static Solution	Off
Rotordynamics Controls	
Coriolis Effect	Off
Restart Controls	
Generate Restart Points	Program Controlled
Retain Files After Full Solve	No
Combine Restart Files	Program Controlled
Nonlinear Controls	
Newton-Raphson Option	Program Controlled
Force Convergence	Program Controlled
Moment Convergence	Program Controlled
Displacement Convergence	Program Controlled
Rotation Convergence	Program Controlled
Line Search	Program Controlled
Stabilization	Program Controlled
Advanced	
Inverse Option	No
Contact Split (DMP)	Program Controlled
Output Controls	
Output Selection	None
Stress	Yes
Back Stress	No

Strain	Yes
Contact Data	Yes
Nonlinear Data	No
Nodal Forces	No
Volume and Energy	Yes
Euler Angles	Yes
General Miscellaneous	No
Contact Miscellaneous	No
Store Results At	All Time Points
Result File Options	
Result File Compression	Program Controlled
Analysis Data Management	
Solver Files Directory	C:\Users\DLSU\Downloads\THESIS DATA\ANSYS FOR HOLLOW RODS\TEST OF ROD SHAPES_files\dp0\SYS\MECH\
Future Analysis	None
Scratch Solver Files Directory	
Save MAPDL db	No
Contact Summary	Program Controlled
Delete Unneeded Files	Yes
Nonlinear Solution	Yes
Solver Units	Active System
Solver Unit System	mks

TABLE 15
Model (A4) > Static Structural (A5) > Loads

Object Name	*Fixed Support*	*Displacement*
State	Fully Defined	
Scope		
Scoping Method	Geometry Selection	
Geometry	1 Face	
Definition		
Type	Fixed Support	Displacement
Suppressed	No	
Define by		Components
Coordinate System		Global Coordinate System
X Component		0. m (ramped)
Y Component		0. m (ramped)
Z Component		-1.25e-003 m (ramped)

FIGURE 1
Model (A4) > Static Structural (A5) > Displacement



Solution (A6)

TABLE 16
Model (A4) > Static Structural (A5) > Solution

Object Name	*Solution (A6)*
State	Solved
Adaptive Mesh Refinement	

Max Refinement Loops	1.
Refinement Depth	2.
Information	
Status	Done
MAPDL Elapsed Time	45. s
MAPDL Memory Used	191. MB
MAPDL Result File Size	7.125 MB
Post Processing	
Beam Section Results	No
On Demand Stress/Strain	No

TABLE 17
Model (A4) > Static Structural (A5) > Solution (A6) > Solution Information

Object Name	*Solution Information*
State	Solved
Solution Information	
Solution Output	Solver Output
Newton-Raphson Residuals	0
Identify Element Violations	0
Update Interval	2.5 s
Display Points	All
FE Connection Visibility	
Activate Visibility	Yes
Display	All FE Connectors
Draw Connections Attached To	All Nodes
Line Color	Connection Type
Visible on Results	No
Line Thickness	Single
Display Type	Lines

TABLE 18
Model (A4) > Static Structural (A5) > Solution (A6) > Results

Object Name	*Total Deformation*	*Directional Deformation*	*Directional Deformation 2*	*Directional Deformation 3*	*Equivalent Elastic Strain*	*Maximum Principal Elastic Strain*	*Maximum Shear Elastic Strain*	*Elastic Strain Intensity*	*Equivalent Stress*	*Maximum Principal Stress*	*Maximum Shear Stress*
State	Solved										
Scope											
Scoping Method	Geometry Selection										
Geometry	2 Bodies										
Definition											
Type	Total Deformation	Directional Deformation			Equivalent Elastic Strain	Maximum Principal Elastic Strain	Maximum Shear Elastic Strain	Elastic Strain Intensity	Equivalent (von-Mises) Stress	Maximum Principal Stress	Maximum Shear Stress
By	Time										
Display Time	Last										
Separate Data by Entity	No										
Calculate Time History	Yes										
Identifier											
Suppressed	No										
Orientation		X Axis	Y Axis	Z Axis							
Coordinate System		Global Coordinate System									
Results											
Minimum	0. m	-2.4023e-004 m	-2.5013e-004 m	-8.6522e-004 m	1.2887e-003 m/m	1.1801e-003 m/m	2.0513e-003 m/m		182.98 Pa	-10734 Pa	97.082 Pa
Maximum	8.6531e-004 m	2.3054e-004 m	2.3137e-004 m	2.0906e-005 m	0.25002 m/m	0.16692 m/m	0.39752 m/m		32013 Pa	19050 Pa	18210 Pa
Average	1.8136e-004 m	-3.1924e-006 m	-1.8621e-006 m	-1.3609e-004 m	8.0721e-002 m/m	4.8697e-002 m/m	0.1196 m/m		10026 Pa	516.36 Pa	5485. Pa
Minimum Occurs On	FLAT TOP ROD|Body1	FLAT TOP ROD|Body2			FLAT TOP ROD|Body1					FLAT TOP ROD|Body2	FLAT TOP ROD|Body1
Maximum Occurs On	FLAT TOP ROD|Body2			FLAT TOP ROD|Body1	FLAT TOP ROD|Body2						
Minimum Value Over Time											
Minimum	0. m	-2.4023e-004 m	-2.5013e-004 m	-8.6522e-004 m	2.2204e-016 m/m	-6.1062e-016 m/m	6.1679e-018 m/m		1.3849e-011 Pa	-10734 Pa	7.1489e-012 Pa
		-4.7807e-	-5.4551e-	-6.5914e-	1.2887e-	1.1801e-				-1.5028e-	

Maximum	0. m	018 m	018 m	018 m	003 m/m	003 m/m	2.0513e-003 m/m	182.98 Pa	008 Pa	97.082 Pa
Maximum Value Over Time										
Minimum	9.8386e-018 m	5.0993e-018 m	4.6611e-018 m	8.1382e-018 m	6.0762e-015 m/m	4.0412e-015 m/m	8.7041e-015 m/m	8.9591e-010 Pa	1.6217e-008 Pa	5.1692e-010 Pa
Maximum	8.6531e-004 m	2.3054e-004 m	2.3137e-004 m	2.0906e-005 m	0.25002 m/m	0.16692 m/m	0.39752 m/m	32013 Pa	19050 Pa	18210 Pa
Information										
Time	1. s									
Load Step	1									
Substep	18									
Iteration Number	135									
Integration Point Results										
Display Option	Averaged									
Average Across Bodies	No									

FIGURE 2
Model (A4) > Static Structural (A5) > Solution (A6) > Total Deformation




TABLE 19
Model (A4) > Static Structural (A5) > Solution (A6) > Total Deformation

Time [s]	Minimum [m]	Maximum [m]	Average [m]
5.e-002	0.	9.8386e-018	1.2967e-018
0.1		1.067e-017	1.4049e-018
0.175		1.026e-017	1.3574e-018
0.2875		1.3202e-017	1.3607e-018
0.45625		6.7921e-005	1.0182e-005
0.65625		3.615e-004	7.0912e-005
0.75625		5.0867e-004	1.0447e-004
0.80625		5.8104e-004	1.2138e-004
0.85625		6.525e-004	1.3821e-004
0.86094		6.598e-004	1.3958e-004
0.86563		6.7261e-004	1.3711e-004
0.87031		6.7949e-004	1.3894e-004
0.87734		6.8977e-004	1.4111e-004
0.88789		7.0491e-004	1.4453e-004
0.90371		7.2754e-004	1.4972e-004
0.92744		7.611e-004	1.5757e-004
0.96304		8.1195e-004	1.6925e-004
1.		8.6531e-004	1.8136e-004

FIGURE 3
Model (A4) > Static Structural (A5) > Solution (A6) > Total Deformation > Figure




FIGURE 4
Model (A4) > Static Structural (A5) > Solution (A6) > Directional Deformation




TABLE 20
Model (A4) > Static Structural (A5) > Solution (A6) > Directional Deformation

Time [s]	Minimum [m]	Maximum [m]	Average [m]
5.e-002	-5.2839e-018	7.301e-018	2.4772e-019
0.1	-5.0673e-018	5.0993e-018	-6.659e-020
0.175	-4.7807e-018	6.8945e-018	-1.2234e-019
0.2875	-7.71e-018	9.0277e-018	1.1458e-019
0.45625	-1.2435e-005	1.3108e-005	1.402e-007
0.65625	-8.4306e-005	8.9353e-005	1.0522e-006
0.75625	-1.2615e-004	1.3159e-004	1.3279e-006
0.80625	-1.4745e-004	1.5317e-004	1.5621e-006
0.85625	-1.6873e-004	1.7499e-004	1.8959e-006
0.86094	-1.7058e-004	1.7681e-004	1.9061e-006
0.86563	-1.7377e-004	1.7428e-004	-2.8862e-007
0.87031	-1.7569e-004	1.7697e-004	-5.9509e-008
0.87734	-1.7959e-004	1.7904e-004	-5.0426e-007

0.88789	-1.8436e-004	1.8362e-004	-5.8368e-007
0.90371	-1.9206e-004	1.9015e-004	-9.0353e-007
0.92744	-2.0361e-004	2.0017e-004	-1.3521e-006
0.96304	-2.2149e-004	2.1501e-004	-2.2527e-006
1.	-2.4023e-004	2.3054e-004	-3.1924e-006

FIGURE 5
Model (A4) > Static Structural (A5) > Solution (A6) > Directional Deformation > Figure




FIGURE 6
Model (A4) > Static Structural (A5) > Solution (A6) > Directional Deformation 2




TABLE 21
Model (A4) > Static Structural (A5) > Solution (A6) > Directional Deformation 2

Time [s]	Minimum [m]	Maximum [m]	Average [m]
5.e-002	-8.4206e-018	5.6746e-018	-3.8631e-020
0.1	-5.7393e-018	4.6611e-018	-2.5046e-019
0.175	-5.7414e-018	4.7797e-018	-1.8599e-020
0.2875	-5.4551e-018	4.6635e-018	-2.1118e-019
0.45625	-1.3277e-005	1.2318e-005	1.7429e-009

0.65625	-9.1616e-005	8.5858e-005	-3.2218e-007
0.75625	-1.3717e-004	1.2786e-004	-8.2886e-007
0.80625	-1.5984e-004	1.5065e-004	-7.2898e-007
0.85625	-1.8324e-004	1.7356e-004	-7.8817e-007
0.86094	-1.8508e-004	1.7552e-004	-7.6999e-007
0.86563	-1.8732e-004	1.6842e-004	-2.0425e-006
0.87031	-1.9066e-004	1.7037e-004	-2.4398e-006
0.87734	-1.9255e-004	1.7426e-004	-1.8543e-006
0.88789	-1.9768e-004	1.7875e-004	-2.0213e-006
0.90371	-2.0502e-004	1.8596e-004	-1.9918e-006
0.92744	-2.1584e-004	1.9715e-004	-1.9058e-006
0.96304	-2.3269e-004	2.137e-004	-1.9452e-006
1.	-2.5013e-004	2.3137e-004	-1.8621e-006

FIGURE 7
Model (A4) > Static Structural (A5) > Solution (A6) > Directional Deformation 2 > Figure




FIGURE 8
Model (A4) > Static Structural (A5) > Solution (A6) > Directional Deformation 3




TABLE 22
Model (A4) > Static Structural (A5) > Solution (A6) > Directional Deformation 3

Time [s]	Minimum [m]	Maximum [m]	Average [m]
5.e-002	-6.5914e-018	8.1382e-018	1.0153e-019
0.1	-9.521e-018	8.5025e-018	5.6472e-020
0.175	-7.1626e-018	8.6406e-018	1.0836e-019
0.2875	-9.0774e-018	8.9667e-018	9.7148e-020
0.45625	-6.7887e-005	1.0998e-006	-7.8779e-006
0.65625	-3.6142e-004	7.985e-006	-5.4968e-005
0.75625	-5.086e-004	1.1904e-005	-8.0503e-005
0.80625	-5.8098e-004	1.3904e-005	-9.3174e-005
0.85625	-6.5245e-004	1.5887e-005	-1.0563e-004
0.86094	-6.5974e-004	1.6047e-005	-1.0662e-004
0.86563	-6.7259e-004	1.5477e-005	-1.0428e-004
0.87031	-6.7946e-004	1.5689e-005	-1.0564e-004
0.87734	-6.8977e-004	1.5995e-005	-1.0721e-004
0.88789	-7.049e-004	1.6397e-005	-1.097e-004
0.90371	-7.2753e-004	1.7029e-005	-1.1347e-004
0.92744	-7.6108e-004	1.7993e-005	-1.1915e-004
0.96304	-8.1191e-004	1.9421e-005	-1.2752e-004
1.	-8.6522e-004	2.0906e-005	-1.3609e-004

FIGURE 9
Model (A4) > Static Structural (A5) > Solution (A6) > Directional Deformation 3 > Figure




FIGURE 10
Model (A4) > Static Structural (A5) > Solution (A6) > Equivalent Elastic Strain




TABLE 23
Model (A4) > Static Structural (A5) > Solution (A6) > Equivalent Elastic Strain

Time [s]	Minimum [m/m]	Maximum [m/m]	Average [m/m]
5.e-002	2.6163e-016	6.0762e-015	1.5285e-015
0.1	2.2204e-016	7.0984e-015	1.6053e-015
0.175	2.6984e-016	6.2775e-015	1.5648e-015
0.2875	3.0302e-016	6.4646e-015	1.5654e-015
0.45625	6.6165e-005	1.4059e-002	4.3492e-003
0.65625	4.9699e-004	9.2115e-002	3.0652e-002
0.75625	7.4065e-004	0.13635	4.5606e-002
0.80625	8.616e-004	0.15974	5.3236e-002
0.85625	9.8176e-004	0.18321	6.0878e-002
0.86094	9.9117e-004	0.18519	6.1496e-002
0.86563	9.8727e-004	0.18601	6.0352e-002
0.87031	1.0006e-003	0.18857	6.1187e-002
0.87734	1.0135e-003	0.19154	6.2179e-002
0.88789	1.0378e-003	0.19652	6.3739e-002
0.90371	1.0739e-003	0.20395	6.6118e-002
0.92744	1.1278e-003	0.21536	6.972e-002
0.96304	1.2076e-003	0.23239	7.5111e-002
1.	1.2887e-003	0.25002	8.0721e-002

FIGURE 11
Model (A4) > Static Structural (A5) > Solution (A6) > Equivalent Elastic Strain > Figure




FIGURE 12
Model (A4) > Static Structural (A5) > Solution (A6) > Maximum Principal Elastic Strain




TABLE 24
Model (A4) > Static Structural (A5) > Solution (A6) > Maximum Principal Elastic Strain

Time [s]	Minimum [m/m]	Maximum [m/m]	Average [m/m]
5.e-002	-5.5511e-016	4.0412e-015	4.7039e-016
0.1	-4.8572e-016	5.0182e-015	4.7042e-016
0.175	-6.1062e-016	4.885e-015	4.7493e-016
0.2875	-4.996e-016	4.3965e-015	4.8429e-016
0.45625	5.7247e-005	9.7218e-003	2.6417e-003
0.65625	4.3122e-004	6.417e-002	1.8694e-002
0.75625	6.5004e-004	9.3162e-002	2.7733e-002
0.80625	7.6021e-004	0.10846	3.2325e-002
0.85625	8.7015e-004	0.12391	3.691e-002
0.86094	8.7879e-004	0.12523	3.7278e-002
0.86563	8.6443e-004	0.12486	3.6566e-002
0.87031	8.7627e-004	0.12687	3.7065e-002
0.87734	8.9309e-004	0.12862	3.766e-002

0.88789	9.1667e-004	0.13195	3.8593e-002
0.90371	9.5319e-004	0.13678	4.0014e-002
0.92744	1.0092e-003	0.14427	4.2162e-002
0.96304	1.0933e-003	0.15541	4.537e-002
1.	1.1801e-003	0.16692	4.8697e-002

FIGURE 13
Model (A4) > Static Structural (A5) > Solution (A6) > Maximum Principal Elastic Strain > Figure




FIGURE 14
Model (A4) > Static Structural (A5) > Solution (A6) > Maximum Shear Elastic Strain




TABLE 25
Model (A4) > Static Structural (A5) > Solution (A6) > Maximum Shear Elastic Strain

Time [s]	Minimum [m/m]	Maximum [m/m]	Average [m/m]
5.e-002	2.379e-017	8.7041e-015	9.8213e-016
0.1	6.1679e-018	1.0791e-014	1.0397e-015
0.175	2.6985e-017	9.992e-015	1.0404e-015
0.2875	1.586e-017	9.6145e-015	1.0081e-015
0.45625	1.0807e-004	2.3063e-002	6.4642e-003

0.65625	8.2075e-004	0.14843	4.5893e-002
0.75625	1.2185e-003	0.21601	6.8136e-002
0.80625	1.4114e-003	0.25279	7.9422e-002
0.85625	1.5983e-003	0.28984	9.0677e-002
0.86094	1.6124e-003	0.29291	9.1572e-002
0.86563	1.6084e-003	0.295	8.9843e-002
0.87031	1.6283e-003	0.29971	9.107e-002
0.87734	1.6481e-003	0.3042	9.2532e-002
0.88789	1.685e-003	0.31223	9.4821e-002
0.90371	1.7396e-003	0.32399	9.8309e-002
0.92744	1.8203e-003	0.34227	0.10358
0.96304	1.9372e-003	0.36945	0.11145
1.	2.0513e-003	0.39752	0.1196

FIGURE 15
Model (A4) > Static Structural (A5) > Solution (A6) > Maximum Shear Elastic Strain > Figure




FIGURE 16
Model (A4) > Static Structural (A5) > Solution (A6) > Elastic Strain Intensity




TABLE 26
Model (A4) > Static Structural (A5) > Solution (A6) > Elastic Strain Intensity

Time [s]	Minimum [m/m]	Maximum [m/m]	Average [m/m]
5.e-002	2.379e-017	8.7041e-015	9.8213e-016
0.1	6.1679e-018	1.0791e-014	1.0397e-015
0.175	2.6985e-017	9.992e-015	1.0404e-015
0.2875	1.586e-017	9.6145e-015	1.0081e-015
0.45625	1.0807e-004	2.3063e-002	6.4642e-003
0.65625	8.2075e-004	0.14843	4.5893e-002
0.75625	1.2185e-003	0.21601	6.8136e-002
0.80625	1.4114e-003	0.25279	7.9422e-002
0.85625	1.5983e-003	0.28984	9.0677e-002
0.86094	1.6124e-003	0.29291	9.1572e-002
0.86563	1.6084e-003	0.295	8.9843e-002
0.87031	1.6283e-003	0.29971	9.107e-002
0.87734	1.6481e-003	0.3042	9.2532e-002
0.88789	1.685e-003	0.31223	9.4821e-002
0.90371	1.7396e-003	0.32399	9.8309e-002
0.92744	1.8203e-003	0.34227	0.10358
0.96304	1.9372e-003	0.36945	0.11145
1.	2.0513e-003	0.39752	0.1196

FIGURE 17
Model (A4) > Static Structural (A5) > Solution (A6) > Elastic Strain Intensity > Figure




FIGURE 18
Model (A4) > Static Structural (A5) > Solution (A6) > Equivalent Stress




TABLE 27
Model (A4) > Static Structural (A5) > Solution (A6) > Equivalent Stress

Time [s]	Minimum [Pa]	Maximum [Pa]	Average [Pa]
5.e-002	1.3849e-011	8.9591e-010	1.6544e-010
0.1	1.6593e-011	9.6441e-010	1.7432e-010
0.175	1.5509e-011	9.0612e-010	1.7082e-010
0.2875	1.3898e-011	9.9936e-010	1.691e-010
0.45625	9.3892	1954.3	562.06
0.65625	70.539	12349	3930.3
0.75625	105.13	18027	5793.5
0.80625	122.31	20964	6730.
0.85625	139.38	23874	7658.5
0.86094	140.71	24115	7731.9
0.86563	140.16	24198	7592.2
0.87031	142.06	24517	7693.1
0.87734	143.88	24878	7813.5
0.88789	147.33	25488	8001.5
0.90371	152.46	26394	8287.8
0.92744	160.13	27782	8719.4
0.96304	171.47	29843	9361.9
1.	182.98	32013	10026

FIGURE 19
Model (A4) > Static Structural (A5) > Solution (A6) > Equivalent Stress > Figure




FIGURE 20
Model (A4) > Static Structural (A5) > Solution (A6) > Maximum Principal Stress




TABLE 28
Model (A4) > Static Structural (A5) > Solution (A6) > Maximum Principal Stress

Time [s]	Minimum [Pa]	Maximum [Pa]	Average [Pa]
5.e-002	-1.6889e-008	1.6217e-008	7.3636e-011
0.1	-1.7523e-008	1.6458e-008	-1.8665e-010
0.175	-1.538e-008	1.9683e-008	-1.3993e-010
0.2875	-1.5028e-008	1.8033e-008	2.5041e-010
0.45625	-1056.9	1404.8	12.907
0.65625	-5602.7	6993.	66.069
0.75625	-7644.5	9897.6	131.11
0.80625	-8483.3	11477	179.33
0.85625	-9231.5	13115	238.23
0.86094	-9347.2	13271	245.29
0.86563	-9140.8	14044	285.92
0.87031	-9162.3	14204	291.93
0.87734	-9296.7	14466	300.07

0.88789	-9428.9	14845	315.44
0.90371	-9627.7	15419	339.91
0.92744	-9897.5	16284	378.66
0.96304	-10306	17629	442.83
1.	-10734	19050	516.36

FIGURE 21
Model (A4) > Static Structural (A5) > Solution (A6) > Maximum Principal Stress > Figure




FIGURE 22
Model (A4) > Static Structural (A5) > Solution (A6) > Maximum Shear Stress




TABLE 29
Model (A4) > Static Structural (A5) > Solution (A6) > Maximum Shear Stress

Time [s]	Minimum [Pa]	Maximum [Pa]	Average [Pa]
5.e-002	7.1489e-012	5.1692e-010	9.3054e-011
0.1	9.58e-012	5.4095e-010	9.8194e-011
0.175	8.2121e-012	5.2314e-010	9.6141e-011
0.2875	7.6254e-012	5.7362e-010	9.5025e-011
0.45625	5.1117	1087.4	305.1

0.65625	38.828	6919.1	2141.8
0.75625	57.65	10022	3162.
0.80625	66.781	11670	3675.8
0.85625	75.63	13334	4185.9
0.86094	76.296	13474	4226.3
0.86563	76.103	13584	4146.6
0.87031	77.046	13798	4202.1
0.87734	77.986	13999	4268.2
0.88789	79.732	14362	4371.5
0.90371	82.317	14892	4528.8
0.92744	86.138	15717	4766.1
0.96304	91.676	16942	5119.6
1.	97.082	18210	5485.

FIGURE 23
Model (A4) > Static Structural (A5) > Solution (A6) > Maximum Shear Stress > Figure




TABLE 30
Model (A4) > Static Structural (A5) > Solution (A6) > Results

Object Name	*Stress Intensity*	*Strain Energy*
State	Solved	
Scope		
Scoping Method	Geometry Selection	
Geometry	2 Bodies	
Definition		
Type	Stress Intensity	Strain Energy
By	Time	
Display Time	Last	
Separate Data by Entity	No	
Calculate Time History	Yes	
Identifier		
Suppressed	No	
Integration Point Results		
Display Option	Averaged	
Average Across Bodies	No	
Results		
Minimum	194.16 Pa	1.0095e-008 J
Maximum	36420 Pa	1.7828e-006 J
Average	10970 Pa	
Minimum Occurs On	FLAT TOP ROD|Body1	
Maximum Occurs On	FLAT TOP ROD|Body2	
Total		1.755e-004 J
Minimum Value Over Time		

Minimum	1.4298e-011 Pa	-1.8294e-020 J
Maximum	194.16 Pa	1.0095e-008 J
Maximum Value Over Time		
Minimum	1.0338e-009 Pa	7.3525e-021 J
Maximum	36420 Pa	1.7828e-006 J
Information		
Time	1. s	
Load Step	1	
Substep	18	
Iteration Number	135	

FIGURE 24
Model (A4) > Static Structural (A5) > Solution (A6) > Stress Intensity




TABLE 31
Model (A4) > Static Structural (A5) > Solution (A6) > Stress Intensity

Time [s]	Minimum [Pa]	Maximum [Pa]	Average [Pa]
5.e-002	1.4298e-011	1.0338e-009	1.8611e-010
0.1	1.916e-011	1.0819e-009	1.9639e-010
0.175	1.6424e-011	1.0463e-009	1.9228e-010
0.2875	1.5251e-011	1.1472e-009	1.9005e-010
0.45625	10.223	2174.8	610.2
0.65625	77.656	13838	4283.6
0.75625	115.3	20044	6323.9
0.80625	133.56	23339	7351.5
0.85625	151.26	26669	8371.8
0.86094	152.59	26949	8452.7
0.86563	152.21	27167	8293.3
0.87031	154.09	27597	8404.2
0.87734	155.97	27997	8536.3
0.88789	159.46	28723	8743.
0.90371	164.63	29784	9057.6
0.92744	172.28	31433	9532.3
0.96304	183.35	33884	10239
1.	194.16	36420	10970

FIGURE 25
Model (A4) > Static Structural (A5) > Solution (A6) > Stress Intensity > Figure




FIGURE 26
Model (A4) > Static Structural (A5) > Solution (A6) > Strain Energy




TABLE 32
Model (A4) > Static Structural (A5) > Solution (A6) > Strain Energy

Time [s]	Minimum [J]	Maximum [J]	Total [J]
5.e-002	-1.5185e-020	7.8273e-021	-5.1765e-019
0.1	-1.5511e-020	1.2711e-020	-5.8068e-019
0.175	-1.8294e-020	9.2209e-021	-4.9576e-019
0.2875	-1.6784e-020	7.3525e-021	-5.6735e-019
0.45625	2.6522e-011	6.1622e-009	5.4923e-007
0.65625	1.3775e-009	2.5952e-007	2.5525e-005
0.75625	3.07e-009	5.5235e-007	5.5893e-005
0.80625	4.2008e-009	7.4548e-007	7.5916e-005
0.85625	5.503e-009	9.7277e-007	9.906e-005
0.86094	5.6197e-009	9.9527e-007	1.011e-004
0.86563	5.4354e-009	9.9993e-007	9.8448e-005
0.87031	5.5783e-009	1.0235e-006	1.0114e-004
0.87734	5.8095e-009	1.0594e-006	1.0443e-004

0.88789	6.1121e-009	1.1123e-006	1.097e-004
0.90371	6.605e-009	1.1976e-006	1.1798e-004
0.92744	7.3955e-009	1.3297e-006	1.3109e-004
0.96304	8.6597e-009	1.543e-006	1.5204e-004
1.	1.0095e-008	1.7828e-006	1.755e-004

FIGURE 27
Model (A4) > Static Structural (A5) > Solution (A6) > Strain Energy > Figure




TABLE 33
Model (A4) > Static Structural (A5) > Solution (A6) > Contact Tools

Object Name	*Contact Tool*
State	Solved
Scope	
Scoping Method	Worksheet

Model (A4) > Static Structural (A5) > Solution (A6) > Contact Tool

Name	Contact Side
Contact Region	Both
Frictionless - FLAT TOP ROD|Body2 To FLAT TOP ROD|Body3	Both

TABLE 34
Model (A4) > Static Structural (A5) > Solution (A6) > Contact Tool > Results

Object Name	*Status*
State	Solved
Definition	
Type	Status
By	Time
Display Time	Last
Calculate Time History	Yes
Identifier	
Suppressed	No
Integration Point Results	
Display Option	Averaged
Information	
Time	1. s
Load Step	1
Substep	18
Iteration Number	135

FIGURE 28
Model (A4) > Static Structural (A5) > Solution (A6) > Contact Tool > Status




TABLE 35
Model (A4) > Static Structural (A5) > Solution (A6) > Contact Tool > Status

Time [s]	Minimum	Maximum	Average
5.e-002	0.	3.	1.8879
0.1			
0.175			
0.2875			1.8936
0.45625			2.0049
0.65625			1.959
0.75625			1.9523
0.80625			1.9423
0.85625			1.9379
0.86094			
0.86563			1.9456
0.87031			
0.87734			1.9412
0.88789			
0.90371			
0.92744			1.9346
0.96304			1.9213
1.			

FIGURE 29
Model (A4) > Static Structural (A5) > Solution (A6) > Contact Tool > Status > Figure




TABLE 36
Model (A4) > Static Structural (A5) > Solution (A6) > Probes

Object Name	*Force Reaction*	*Moment Reaction*
State	Solved	
Definition		
Type	Force Reaction	Moment Reaction
Location Method	Boundary Condition	
Boundary Condition	Displacement	
Orientation	Global Coordinate System	
Suppressed	No	
Summation		Centroid
Options		
Result Selection	All	
Display Time	End Time	
Results		
X Axis	-6.9246e-003 N	7.8984e-005 N·m
Y Axis	1.1451e-003 N	6.9554e-005 N·m
Z Axis	-0.51542 N	-2.7137e-007 N·m
Total	0.51547 N	1.0524e-004 N·m
Maximum Value Over Time		
X Axis	-3.9093e-008 N	7.8984e-005 N·m
Y Axis	1.1451e-003 N	6.9554e-005 N·m
Z Axis	-2.4075e-006 N	4.4322e-010 N·m
Total	0.51547 N	1.0524e-004 N·m
Minimum Value Over Time		
X Axis	-6.9246e-003 N	7.4033e-010 N·m
Y Axis	-3.9526e-004 N	-2.3498e-008 N·m
Z Axis	-0.51542 N	-3.6585e-006 N·m
Total	2.4082e-006 N	1.047e-009 N·m
Information		
Time	1. s	
Load Step	1	
Substep	18	
Iteration Number	135	

FIGURE 30
Model (A4) > Static Structural (A5) > Solution (A6) > Force Reaction




TABLE 37
Model (A4) > Static Structural (A5) > Solution (A6) > Force Reaction

Time [s]	Force Reaction (X) [N]	Force Reaction (Y) [N]	Force Reaction (Z) [N]	Force Reaction (Total) [N]
5.e-002	-3.9093e-008	-3.9094e-008	-2.4075e-006	2.4082e-006
0.1	-1.56e-007	-1.56e-007	-4.8303e-006	4.8353e-006
0.175	-4.7467e-007	-4.7467e-007	-8.5256e-006	8.552e-006
0.2875	-1.2606e-006	-1.2606e-006	-1.43e-005	1.4411e-005
0.45625	-7.5475e-006	-6.2232e-006	-2.5886e-002	2.5886e-002
0.65625	-3.9289e-004	-1.6544e-004	-0.19316	0.19317
0.75625	-9.37e-004	-3.9526e-004	-0.29144	0.29144
0.80625	-1.1192e-003	-3.8316e-004	-0.33861	0.33861
0.85625	-1.2823e-003	-3.8731e-004	-0.38832	0.38832
0.86094	-1.3641e-003	-3.7128e-004	-0.40082	0.40082
0.86563	-4.4284e-003	6.6419e-004	-0.39109	0.39112
0.87031	-3.8578e-003	-2.1477e-004	-0.38121	0.38123
0.87734	-3.8167e-003	5.6076e-004	-0.39243	0.39244
0.88789	-3.9924e-003	3.2313e-004	-0.40342	0.40344
0.90371	-4.2652e-003	6.5372e-004	-0.41867	0.41869
0.92744	-4.7515e-003	6.2882e-004	-0.44203	0.44205
0.96304	-5.9826e-003	7.8541e-004	-0.47819	0.47823
1.	-6.9246e-003	1.1451e-003	-0.51542	0.51547

FIGURE 31
Model (A4) > Static Structural (A5) > Solution (A6) > Force Reaction > Figure




FIGURE 32
Model (A4) > Static Structural (A5) > Solution (A6) > Moment Reaction





TABLE 38
Model (A4) > Static Structural (A5) > Solution (A6) > Moment Reaction

Time [s]	Moment Reaction (X) [N·m]	Moment Reaction (Y) [N·m]	Moment Reaction (Z) [N·m]	Moment Reaction (Total) [N·m]
5.e-002	7.4033e-010	-7.4033e-010	1.3783e-016	1.047e-009
0.1	2.9446e-009	-2.9446e-009	-5.0726e-018	4.1642e-009
0.175	8.9148e-009	-8.9148e-009	-1.7084e-016	1.2607e-008
0.2875	2.3498e-008	-2.3498e-008	2.1607e-016	3.3231e-008
0.45625	2.1782e-006	1.5698e-006	4.4322e-010	2.6849e-006
0.65625	1.4535e-005	1.4056e-005	-3.23e-007	2.0222e-005
0.75625	2.1804e-005	2.3542e-005	-1.5355e-006	3.2125e-005
0.80625	2.4999e-005	2.9046e-005	-2.4277e-006	3.8399e-005
0.85625	2.8901e-005	3.4847e-005	-3.5033e-006	4.5408e-005
0.86094	2.9422e-005	3.5789e-005	-3.6585e-006	4.6475e-005
0.86563	5.5288e-005	4.6328e-005	-4.9383e-007	7.2134e-005
0.87031	6.1569e-005	5.0366e-005	-6.5479e-007	7.9548e-005
0.87734	5.673e-005	5.2423e-005	-3.4225e-007	7.7244e-005

0.88789	6.0897e-005	5.4729e-005	-4.7536e-007	8.1877e-005
0.90371	6.1735e-005	5.704e-005	-3.498e-007	8.4053e-005
0.92744	6.6726e-005	6.0708e-005	-3.6296e-007	9.021e-005
0.96304	7.3142e-005	6.3552e-005	-3.3861e-007	9.6895e-005
1.	7.8984e-005	6.9554e-005	-2.7137e-007	1.0524e-004

FIGURE 33
Model (A4) > Static Structural (A5) > Solution (A6) > Moment Reaction > Figure



Material Data

ECOFLEX-0045

TABLE 39
ECOFLEX-0045 > Constants

Density	1060 kg m^-3

TABLE 40
ECOFLEX-0045 > Color

Red	Green	Blue
181	194	156

TABLE 41
ECOFLEX-0045 > Neo-Hookean

Initial Shear Modulus Mu Pa	Incompressibility Parameter D1 Pa^-1	Temperature C
47300	4.24e-007	

Plastic, ABS (high-impact)

TABLE 42
Plastic, ABS (high-impact) > Constants

Density	1030 kg m^-3
Tensile Yield Strength	4.382e+007 Pa
Tensile Ultimate Strength	3.626e+007 Pa
Coefficient of Thermal Expansion	1.84e-004 C^-1
Thermal Conductivity	0.1997 W m^-1 C^-1
Specific Heat	1400 J kg^-1 C^-1
Resistivity	9.95e+013 kg m^3 A^-2 s^-3
Electric Loss Tangent	5.916e-003
Relative Permittivity	2.993

TABLE 43
Plastic, ABS (high-impact) > Opacity

Red	Green	Blue
0	153	255

Opacity
0.9

Metallic Finish
0

TABLE 44
Plastic, ABS (high-impact) > Isotropic Elasticity

Young's Modulus Pa	Poisson's Ratio	Bulk Modulus Pa	Shear Modulus Pa	Temperature C
2.405e+009	0.4089	4.3999e+009	8.535e+008	23

TABLE 45
Plastic, ABS (high-impact) > Isotropic Secant Coefficient of Thermal Expansion

Zero-Thermal-Strain Reference Temperature C
23

TABLE 46
Plastic, ABS (high-impact) > Climate change (CO2-eq)

Climate change (CO2-eq) dBA
3.661

TABLE 47
Plastic, ABS (high-impact) > Embodied energy

Embodied energy J kg^-1
9.64e+007

TABLE 48
Plastic, ABS (high-impact) > Recycle

Recycle
1