# FAB ALUMINUM - Halo Lit PRODUCT STANDARDS





### **Letters**

Depth	Min - Size	Max Size	Min Stroke & Serif
1.0"	12"	30"	1.75"
1.5"	12"	30"	1.75"
2.0"	12"	60"	1.75"
3.0"	12"	60"	2"
3.5"	12"	60"	2"
4.0"	12"	60"	2"
5.0"	12"	60"	2"
6.0"	12"	60"	3"

Min Punctuation
2.75"
2.75"
2.75"
2.75"
2.75"
2.75"
2.75"
2.75"

<b>Bottom Stud</b>	Bars
Max Size	Max One Piece
30"	40"
30"	48"
30"	48"
48"	60"
48"	60"
48"	60"
48"	60"
48"	60"
	•

Max Area sq. in.
900
900
3,600
3,600
3,600
3,600
3,600
3,600

## **Sheet Info**

## **Horizontal Brushed**

42"h x 72"w or 119"h x 36"w +100" will not have clear coat

# **Vertical Brushed**

72"h x 42"w or 36"h x 119"w +100" will not have clear coat

#### **Anod Horiz**

42"h x 72"w or 84"h x 36"w

## **Anod Vert**

72"h x 42"w or 36"h x 84"w

#### **Painted**

59"h x 100"w

# **Prep for paint**

59" x 119"

# **Acrylic Sheet**

48" x 96"

# **Returns (Alum)**

Grain runs front to back (Short Direction)

# **Alum Assembly**

Requires additional structure
Nothing over max letter size

# **Backers**

	Thickness	Gap
Light Diffused	.177"	.06"013"
Clear	.118"	.06"013"

Defualt is Light Diffused

Removable Backs are Recessed 1/8"

Weep Holes are 3/8" Square in Low Point Corners

#### Miscellaneous

1/4" Stokes for masking
No Custom Stud Placements
Removable can required on 40"+
Logos exceeding max letter size
will require added stiffeners
Panels over max letter size
will warp

### **Rails - Painted or Raw**

	Size H x W	Length
C-Chan	1" x 2"	96"
C-Chan	.5" x 1.5"	96"
C-Chan	1" x 3"	96"
C-Chan	.5" x 1"	96"
C-Chan	1" x 1.5"	96"
Angle	1" x 2"	96"





# **Openings**

Straight Return	.25"
Curved Return	.5″

This is a general rule and depends largely on the shape of the opening.

# **Material Gauge**

Face	.09"
Returns	.063"

#### **INTRANET LINKS**

Fabricated Aluminum

UL & LED Info



**LED** 

Wire hole .375" Standard LED .5" x 1.8"

**RGB LED** .625" x 2.75" **Cable** 10' Long Standard

### **RGB LEDS (Halo Lit)**

Min	Min	Min	Min
Stroke	Size	Return	punctuation
2"	16"	1.5"	3"

#### Swoosh

## **Pointed Tip**



.6" stroke needed 1" in from tip -return will have a slight inset-

-OR-

# **Round Tip**



Outside Corners

.3" Fillet

No more then 3/4" overhang on inset swoosh