

ARM Assembly

```
01:    mystery1
02: STMFD    SP!, {R4-R8}    #function prologue Store multiple instruction decrement before
03: LDRB      R3, [R0]        #Loads arg1 into register R3. arg1 is most likely a pointer.
04: CMP      R3, #0x2D        #Compare R3's values to 45
05: BEQ      loc_B348        #If R3 is equal to 45 go to loc_B348 on line 57.
06: CMP      R3, #0x2B        #Compare R3 to 43
07: MOV      R6, #0           #Put 0 into R6
08: LDREQB   R3, [R0,#1]!    #Load R0+1 into R3 and then update R0 to R0+1 if R3 equals 43
09:    loc_B2AC
10: CMP      R3, #0x30        #Compare R3 to 48
11: BNE      loc_B2C8        #If R3 is not equal to 48 go to loc_B2C8 on line 18
12: ADD      R3, R0, #1       # R3 = R0 + 1
13:    loc_B2B8
14: MOV      R0, R3           #R0=R3
15: LDRB     R2, [R3], #1     #R2=R3, R3=R3+1
16: CMP      R2, #0x30        #Compare R2 to 48
17: BEQ      loc_B2B8        #Loop back to line 13 while R2 == 48
18:    loc_B2C8
19: MOV      R12, #0          #R12 = 0
20: MOV      R4, #0           #R4 = 0
21: MOV      R5, #0           #R5 = 0
22: MOV      R8, #0xA         #R8 = 10
23: B        loc_B2E4         #Branch to loc_B2E4 on line 27
24:    loc_B2DC
25: ADDS     R4, R2, R7       # R4 = R2+R7
26: ADC      R5, R3, R7, ASR#31 #R5 = R3 +(R7>>31) with carry
27:    loc_B2E4
28: LDRB     R7, [R0, R12]    # R7 = R0+R12. R0 is bp and R12 is offset
29: ADD      R12, R12, #1     #R12 = R12+1
30: UMULL     R2, R3, R4, R8   # R4xR8. Least significant 32 bits R2 and most significant 32 bits R3.
31: SUBS     R7, R7, #0x30     # R7 = R7 - 48
32: BMI      loc_B318        #branch to loc_B318 on line 43 if R7 is negative
33: CMP      R7, #9           #Compare R7 to 9
34: MLA      R3, R8, R5, R3    #R3 = R8xR5+R3
35: BGT      loc_B318        # branch to loc_B318 on line 43 if R7 greater than 9
36: CMP      R12, #0xB        #Compares R12 to 11
37: BNE      loc_B2DC        #Branch to loc_B2DC on line 24 if R12!=11
38:    loc_B30C
39: MOV      R0, #0           #R0 = 0
40:    loc_B310
41: LDMFD     SP!, {R4-R8}    #function epilogue put from stack back into R4 and R8. IA mode
42: BX       LR               # return
43:    loc_B318
44: SUBS     R2, R4, R6        # R2 = R4-R6
45: SBC      R3, R5, R6, ASR#31 # R3 = R5-(R6>>31) with carry
```

```

46: CMP      R2, #0x80000000 #Compare R2 with #0x80000000
47: SBCS      R0, R3, #0      #R0 = R3 - 0
48: BGE      loc_B30c         #Branch to loc_B30C on line 38 if R2 greater than or equal 0x80000000
49: CMP      R6, #0           #Compare R6 to 0
50: BEQ      loc_B33C         #Branch to loc_B33C on line 53 if 6 equals 0
51: RSBS      R4, R4, #0       #R4 = 0-R4
52: RSC      R5, R5, #0       #R5 = 0-R5
53: loc_B33C
54: STR      R4, [R1]         # Store the value into R4 into R1(our second argument a pointer)
55: MOV      R0, #1           # R0 = 1
56: B        loc_B310         #Branch to loc_B310 on line 40.
57: loc_B348
58: LDRB      R3, [R0, #1]!    #Load R0+1 into R3 and then update R0 to R0+1
59: MOV      R6, #1           #Put 1 into R6
60: B        loc_B2Ac         #Branch to loc_B2Ac on line 09.
61:          ; End of function mystery1

```

Mode

This code is in ARM mode since all the instructions are 32 bits.

Types

R0 type char * when argument. When function returns R0 is a boolean

R1 type int *

R2 type int

R3 type char (one byte) then later is a variable that is a char *

int64_t sum; //R5:R4

R6 type Boolean

R7 type int signed

R8 type int

R12 type int

Function Prototype

```
int mystery1(char * arg1, int * arg2)
```

C Code

```
int atoi(char *arg1, int * arg2)
```

```
{
```

```
    char ch = arg1[0];
```

```
    int neg;
```

```
    if(ch== '-')//check if the number is negative
```

```

        {
            ch = arg1[1];
            arg1++;
        }
        neg = 1;
    }
    else{ //if not negative
        neg = 0;
        if(ch== '+'){ ch=arg1[1]; arg1++;} //if plus in front move over to next digit.
    }

    if(ch=='0') //go through this until you reach a number that is not 0
    {
        char * chp = arg1+1;
        int cur_dig;
        do{
            arg1 = chp;
            cur_dig = *chp;
            chp++;
        } while(cur_dig=='0');
    }

    int i=0;
    int num = 0;
    int ten = 10;
    int digit;
    long long unsigned sum;
    for(i=0;;i++)
    {
        digit = arg1[i];
        sum = num*ten;
        digit = digit - '0';
        if((0<=digit) &&(digit<=9))
        {
            if(i!=11)
            {
                num = sum+digit; //add the digit to the end of the number
            }
            else {
                return 0;
            }
        }
        else break;
    }

    sum = num - neg; //this is here in case the value is -2,147,483,648
    if(sum >= 0x80000000) // if R2 is greater than the highest signed 32 bit value fail. 231-1 is the
greatest signed 32 bit value.
    {
        return 0;
    }
    if(neg)

```

```
    {  
        num = -num;  
    }  
    *arg2 = num;  
    int ret = 1;  
    return ret;  
}
```

Explanation

This function is `atoi`. It takes a string and accepts a pointer to an integer. The output is a Boolean where 0 is failing and 1 is passing. If there is a minus sign, the value is assumed negative. If it is blank or have a plus sign, that means the value will be positive. If there are any 0's before the number, those are omitted. Then while there is a digit between 0 and 9, multiply the current number by ten and then add the digit to the running total. If there is more than 10 digits (greater than 32 bits), return 0 since we cannot have a number with that many digits. Also, if the value is not between $[-2^{31}, 2^{31}-1]$, return 0 as well. Afterwards return 1 and have the second parameter of the function point to the integer. If the value was negative, set the negative sign on the integer.