DATABASE MANAGEMENT SYSTEMS / CASE STUDY • REVIEW 1

FraudLens

Financial Transaction & Fraud Investigation Management System


Relational domain modelling, 3NF architecture, Oracle SQL DDL with named constraints and sequences, controlled DML, and analytical queries.

D JOSHUA DANIEL 24BCE0436 | M SARYU 24BCE2524

Faculty: Kanagaraj K

Review 1 / Relational Schema Design & SQL Foundations

BCSE304L Database Management Systems • SCOPE, VIT Vellore



Fraud data scattered across silos

Banks move tens of thousands of transactions a minute: RTGS, NEFT, IMPS, ATM, POS, UPI.

THE CONTEXT

Fragmented storage

Customers, ledgers, transactions and case notes sit in separate spreadsheets with no foreign-key links.

THE RISK

Drift + weak validation

Duplicated demographics cause update anomalies; negative balances and orphan tickets slip through.

OUR RESPONSE

One 3NF Oracle schema

Six core entities with PK/FK, cascading deletes and engine-level CHECK constraints enforce valid ranges and states.

RESEARCH QUESTION

How can a bank unify customers, accounts, transactions, alerts and investigations so suspicious activity is traceable and data stays correct?

Scope: Review 1 covers relational requirements, ER model, 3NF mapping, Oracle DDL, controlled DML, and baseline analytical queries. Review 2 integrates procedural surveillance, views, stored procedures, functions, triggers, and full audit logs.

Three failures, three fixes

Operational deficiencies mapped to the FraudLens relational solution.

Operational deficiency	Impact on banking operations	FraudLens relational solution
Fragmented storage	Transactions, alerts and case notes live in disparate systems without foreign-key links.	One centralised Oracle schema with strict primary/foreign key relationships.
Redundancy & drift	Customer demographics duplicated across spreadsheets cause update anomalies.	Normalised to 3NF; each customer attribute is stored exactly once.
Weak validation	Spreadsheets allow negative balances, zero amounts and orphan investigation tickets.	Engine-level CHECK constraints enforce valid ranges, balances and statuses.

Engine Enforcement Principle: Every validation rule is enforced inside the Oracle database engine via constraints and triggers, not left to application code.

What the database must enforce

Functional objectives on the left; enforced rules BR-01 to BR-06 on the right.

FUNCTIONAL OBJECTIVES

- **Account hierarchy:** One customer may hold multiple accounts across Savings, Current, Salary, and NRI types.
- **Transaction journal:** Captures type (DEPOSIT, WITHDRAWAL, TRANSFER), timestamp, channel, counterparty, and status.
- **Rule-based alerts:** Dynamic severity scoring across LOW, MEDIUM, HIGH, and CRITICAL brackets.
- **Case lifecycle:** Structured progression through OPEN, UNDER REVIEW, and CLOSED with assigned investigators.
- **Analytical querying:** Comprehensive baseline reporting using character formatting, numeric filters, group metrics, and joins.

ENFORCED BUSINESS RULES

BR-01	Each account belongs to exactly one customer (ON DELETE CASCADE).
BR-02	Account balance must stay strictly non-negative (CHECK balance >= 0).
BR-03	Transaction amount must be strictly greater than zero (CHECK amount > 0).
BR-04	A fraud alert references an existing transaction; cascade deletes on purge.
BR-05	An investigation links one alert to one active investigator.
BR-06	Transactions above INR 50,000 are flagged for compliance review.

ER model of the implemented schema

Six entities designed in Oracle SQL Developer Data Modeler; P = primary, F = foreign, U = unique key.




Figure 1: FraudLens relational diagram (Oracle SQL Developer Data Modeler / Oracle Database 23ai)

Keys and constraints encode the rules

Single-column surrogate keys; every table verified against 1NF, 2NF and 3NF.

Table	Primary key	Foreign key(s)	Key constraints enforced
CUSTOMER	`customer_id`	-	email, phone UNIQUE NOT NULL; kyc_status CHECK; risk_score 0-100
ACCOUNT	`account_id`	`customer_id` → `CUSTOMER`	account_number UNIQUE; balance >= 0; type and status CHECK
TRANSACTIONS	`transaction_id`	`account_id` → `ACCOUNT`	amount > 0; transaction_type, channel, status CHECK
FRAUD_ALERT	`alert_id`	`transaction_id` → `TRANSACTIONS`	severity CHECK (LOW to CRITICAL); status DEFAULT 'PENDING'
INVESTIGATOR	`investigator_id`	-	email UNIQUE NOT NULL; experience_years >= 0; active_status CHECK
INVESTIGATION	`case_id`	`alert_id, investigator_id`	status CHECK; outcome CHECK; end_date >= start_date

1NF

Atomic scalar values

All table attributes store atomic scalar values. No repeating groups or multi-valued phone lists; first and last names separated.

2NF

No partial dependencies

Every relation relies on single-column surrogate primary keys. No non-prime attribute depends on a proper subset of any candidate key.

3NF

No transitive dependencies

Non-key columns depend exclusively on primary keys. Investigator department and customer KYC status live only in home entities.

Oracle DDL with named constraints

From sql/01_schema.sql; named constraints give deterministic error diagnostics.

CREATE: ACCOUNT (DDL Snippet)

```
CREATE TABLE ACCOUNT (
  account_id   NUMBER(10) CONSTRAINT pk_account PRIMARY KEY,
  customer_id  NUMBER(10) NOT NULL
               CONSTRAINT fk_acc_customer
               REFERENCES CUSTOMER(customer_id)
               ON DELETE CASCADE,
  account_number VARCHAR2(20)
               CONSTRAINT uq_acc_number UNIQUE NOT NULL,
  account_type VARCHAR2(20) DEFAULT 'SAVINGS'
               CONSTRAINT chk_acc_type CHECK (account_type
               IN ('SAVINGS','CURRENT','SALARY','NRI')),
  balance      NUMBER(15,2) DEFAULT 0.00
               CONSTRAINT chk_acc_balance CHECK (balance >= 0),
  status       VARCHAR2(15) DEFAULT 'ACTIVE'
               CONSTRAINT chk_acc_status CHECK (status IN
               ('ACTIVE','FROZEN','DORMANT','CLOSED'))
);
```

CREATE: TRANSACTIONS (Abbreviated)

```
CREATE TABLE TRANSACTIONS (
  transaction_id NUMBER(12) CONSTRAINT pk_transactions PRIMARY KEY,
  account_id     NUMBER(10) NOT NULL
                 CONSTRAINT fk_tx_account
                 REFERENCES ACCOUNT(account_id) ON DELETE CASCADE,
  amount         NUMBER(15,2) NOT NULL
                 CONSTRAINT chk_tx_amount CHECK (amount > 0),
  channel        VARCHAR2(20) NOT NULL
                 CONSTRAINT chk_tx_channel CHECK (channel IN
                 ('ATM','POS','NET_BANKING','MOBILE_APP','UPI'))
);
```

SEQUENCES

Six PK sequence generators

START WITH sits above sample IDs (e.g., customer sequence starts at 1011 after sample 1001-1010; transaction sequence at 50019 after sample 50001-50018) to avoid key collision during execution.

Safe schema changes, reversible DML

From sql/02_ddl_dml_demos.sql; structural changes on a staging table, updates under a savepoint.

ALTER / DROP: STAGING TABLE

```
-- 1. Schema Modification on Staging Table
ALTER TABLE FRAUD_RULE_CONFIG
  ADD (rule_description VARCHAR2(250));

ALTER TABLE FRAUD_RULE_CONFIG
  MODIFY (rule_code VARCHAR2(60));

ALTER TABLE FRAUD_RULE_CONFIG
  DROP COLUMN rule_description;

DROP TABLE FRAUD_RULE_CONFIG PURGE;
```

DML UNDER SAVEPOINT

```
-- 2. Transaction Control with Savepoint
SAVEPOINT dml_demo_start;

UPDATE CUSTOMER
  SET kyc_status = 'VERIFIED', risk_score = 5
  WHERE customer_id = 9999;

DELETE FROM CUSTOMER
  WHERE customer_id IN (9998, 9999);

ROLLBACK TO dml_demo_start;
```

WHY A SAVEPOINT?

Baseline stays pristine

The rollback restores the 56-record baseline dataset immediately after the demonstration, ensuring that subsequent analytical queries, joins, and test cases run against known, predictable data.

Single-row functions

UPPER, LOWER, LENGTH and SUBSTR standardise customer profiles.

SQL*Plus - FRAUDLENS_USER@localhost:1521/freepdb1

```
SQL> SELECT customer_id,
  2         UPPER(first_name || ' ' || last_name) AS full_name_uppercase,
  3         LOWER(email) AS standardized_email,
  4         LENGTH(phone) AS phone_len,
  5         SUBSTR(phone, 1, 3) AS country_code
  6  FROM CUSTOMER
  7  WHERE customer_id IN (1001, 1002, 1005);
CUSTOMER_ID FULL_NAME_UPPERCASE    STANDARDIZED_EMAIL          PHONE_LEN COUNTRY_CODE
----------- ---------------------- --------------------------- ---------- ------------
       1001 AARAV SHARMA           aarav.sharma@finmail.in            13 +91
       1002 PRIYA NAIR             priya.nair@corpmail.com            13 +91
       1005 VIKRAM SINGHANIA       vikram.s@apexholdings.in           13 +91

3 rows selected.
```

*Figure 2: Single-row character functions with query results (Executed on Oracle 23ai Free / FREEPDB1 via SQL*Plus)*

IN, BETWEEN and ORDER BY

High-value digital-channel transactions between INR 50,000 and 300,000.




*Figure 3: Range filtering with IN, BETWEEN and descending sort (Executed on Oracle 23ai Free / FREEPDB1 via SQL*Plus)*

GROUP BY and HAVING

Transaction count, turnover and average ticket per channel, channels with 3+ transactions.




*Figure 4: Channel aggregation metrics (Executed on Oracle 23ai Free / FREEPDB1 via SQL*Plus)*

Four-table analytical join

Customer, account, transaction and alert linked to surface high-risk exposure.





*Figure 5: Four-table join tracking high-risk alerts to accounts (Executed on Oracle 23ai Free / FREEPDB1 via SQL*Plus)*

Constraints reject bad data

Negative tests trigger engine-level exceptions; positive tests are accepted.



Type	Constraint	Input tested	Expected	Status
Negative	`CHECK (amount > 0)`	amount = -500.00	Rejected, ORA-02290	PASSED
Negative	`UNIQUE (email)`	existing aarav.sharma@finmail.in	Rejected, ORA-00001	PASSED
Negative	`FOREIGN KEY (customer_id)`	customer_id = 999999	Rejected, ORA-02291	PASSED
Positive	`CHECK (kyc_status)`	kyc_status = 'VERIFIED'	Accepted and updated	PASSED
Positive	`CHECK (risk_score)`	risk_score = 85	Accepted and stored	PASSED

Foundation first, procedures next

Phase 1 delivers a verified 3NF base; Phase 2 adds procedural surveillance.

01 INTEGRITY

Zero orphan records

Cascading FKs ensure no orphan transactions, alerts or cases can exist.

02 NO ANOMALIES

Strict 3NF structure

Customer and investigator details live in one authoritative relation.

03 DOMAIN DEFENCE

Database-level CHECKs

Named CHECKs block negative balances, zero amounts, and invalid statuses.

Review 2 component	Planned implementation	Objective in FraudLens
Advanced subqueries	Correlated and multi-row (IN, ANY, ALL)	Flag accounts far above their own historical average
Database views	VW_HIGH_RISK_TRANSACTIONS, VW_INVESTIGATION_SUMMARY	Dashboards without complex application joins
PL/SQL procedures	SP_ASSIGN_INVESTIGATOR and case progression	Validate constraints before state transitions
User-defined functions	FN_GET_TOTAL_TX_AMOUNT, FN_CALCULATE_RISK_TIER	Dynamic customer risk tiers and account volume scoring
Triggers & audit logs	AFTER UPDATE row-level triggers to audit tables	Non-repudiation and forensic case lifecycle logging

FRAUDLENS • REVIEW 1 COMPLETE

Model correctly. Enforce in the engine.

Keys and constraints protect relationships; queries turn clean data into fraud signals.

D Joshua Daniel

Reg No: 24BCE0436
B.Tech CSE • VIT Vellore

M Saryu

Reg No: 24BCE2524
B.Tech CSE • VIT Vellore

Kanagaraj K

Faculty Guide
SCOPE • VIT Vellore

Thank you / Questions

DATABASE MANAGEMENT SYSTEMS / CASE STUDY • REVIEW 2 EXTENSION

Review 2: Advanced Implementation

Procedural Intelligence, Automated Surveillance & Forensic Audit Defense

Transitioning from static 3NF relational modeling to active procedural database surveillance. Encompasses nested and correlated subqueries, multi-table surveillance views, PL/SQL stored procedures with strict state progression, deterministic scoring functions, row-level audit triggers, and complete exception recovery executed on Oracle 23ai Free.

D Joshua Daniel

Registration No: **24BCE0436**
B.Tech CSE • SCOPE, VIT Vellore

M Saryu

Registration No: **24BCE2524**
B.Tech CSE • SCOPE, VIT Vellore

Faculty Guide: Prof. Kanagaraj K | Course: BCSE304L Database Management Systems

REVIEW 2 MODULES

- 1. Advanced Subqueries
- 2. Database Views
- 3. PL/SQL Procedures
- 4. Stored Functions
- 5. Cursors & Batch Logic
- 6. Audit Triggers
- 7. Transaction Isolation
- 8. Full System Workflow
- 9. 13-Case Test Harness
- 10. Compliance Matrix

Layered procedural surveillance architecture

Active database logic: from raw incoming transaction to tamper-evident audit record.

LAYER 1

Analytical Views

Surveillance & Triage:

• **VW_HIGH_RISK_TRANSACTIONS:** Aggregates transactions >50k or FLAGGED with customer details.

• **VW_INVESTIGATION_SUMMARY:** Computes case duration, severity, and investigator load.

• **VW_CUSTOMER_FRAUD_EXPOSURE:** Evaluates customer exposure.

LAYER 2

Stored Procedures

Lifecycle Enforcement:

• **SP_EVALUATE_AND_ALERT_TRANSACTION:** Checks compliance threshold and generates alert.

• **SP_ASSIGN_INVESTIGATOR:** Validates investigator active status.

• **SP_UPDATE_INVESTIGATION_STATUS:** Enforces valid state progression.

LAYER 3

PL/SQL Functions

Scoring & Aggregation:

• **FN_CALCULATE_RISK_TIER:** Deterministically maps risk score to LOW, MEDIUM, HIGH, CRITICAL brackets.

• **FN_GET_TOTAL_TX_AMOUNT:** Calculates cumulative transacted volume per account.

• **FN_GET_ACCOUNT_ALERT_COUNT:** Sums alert count.

LAYER 4

Audit Triggers

Forensic Audit Trail:

• **TRG_INVESTIGATION_STATUS_AUDIT:** Fires on case status change; writes old/new status, timestamp, and user to INVESTIGATION_AUDIT.

• **TRG_FRAUD_ALERT_AUDIT:** Captures alert severity escalations into ALERT_AUDIT table.

Scalar & multi-row anomaly detection

Comparing transaction amounts against system-wide averages and subquery filtering.

SQL*Plus - FRAUDLENS_USER@localhost:1521/freepdb1 - Subqueries

```
SQL> SELECT t.transaction_id, t.account_id, t.amount, t.channel, t.status,
  2         ROUND((SELECT AVG(amount) FROM TRANSACTIONS), 2) AS sys_avg,
  3         ROUND(t.amount - (SELECT AVG(amount) FROM TRANSACTIONS), 2) AS diff_from_avg
  4  FROM TRANSACTIONS t
  5  WHERE t.amount > (SELECT AVG(amount) FROM TRANSACTIONS)
  6  ORDER BY t.amount DESC;
```

TRANSACTION_ID	ACCOUNT_ID	AMOUNT	CHANNEL	STATUS	SYS_AVG	DIFF_FROM_AVG
50007	2006	650000	NET_BANKING	FLAGGED	126,358.33	523,641.67
50015	2012	500000	NET_BANKING	COMPLETED	126,358.33	373,641.67
50006	2006	250000	ATM	FLAGGED	126,358.33	123,641.67
50008	2002	180000	NET_BANKING	COMPLETED	126,358.33	53,641.67

4 rows selected.

*Figure 6: Subquery identifying transactions exceeding overall system average (Executed on Oracle 23ai Free / FREEPDB1 via SQL*Plus)*

Surveillance & triage dashboards

VW_HIGH_RISK_TRANSACTIONS and VW_INVESTIGATION_SUMMARY for instant operational reporting.




*Figure 7: High-risk transaction view query output in Oracle SQL*Plus (Executed on Oracle 23ai Free / FREEPDB1 via SQL*Plus)*

Investigator allocation & case progression

SP_ASSIGN_INVESTIGATOR and SP_UPDATE_INVESTIGATION_STATUS validating state rules.




*Figure 8: Execution of investigator assignment and case progression procedures (Executed on Oracle 23ai Free / FREEPDB1 via SQL*Plus)*

Risk tier scoring & turnover calculation

FN_CALCULATE_RISK_TIER and FN_GET_TOTAL_TX_AMOUNT providing dynamic scoring.




*Figure 9: Customer risk tier evaluation query using custom PL/SQL function (Executed on Oracle 23ai Free / FREEPDB1 via SQL*Plus)*

Explicit parameter-driven batch surveillance

From sql/09_cursors.sql; row-by-row anomaly analysis across large transaction sets.

PL/SQL EXPLICIT CURSOR IMPLEMENTATION

```
-- Explicit Cursor with Parameter for Account Turnover Sweep
DECLARE
  CURSOR cur_high_ticket (p_min_amount NUMBER) IS
    SELECT t.transaction_id, t.account_id, t.amount, t.channel
    FROM TRANSACTIONS t
    WHERE t.amount >= p_min_amount
    ORDER BY t.amount DESC;
  v_tx cur_high_ticket%ROWTYPE;
BEGIN
  OPEN cur_high_ticket(p_min_amount => 100000.00);
  LOOP
    FETCH cur_high_ticket INTO v_tx;
    EXIT WHEN cur_high_ticket%NOTFOUND;
    DBMS_OUTPUT.PUT_LINE('FLAGGED HIGH TICKET: ' || v_tx.transaction_id ||
                         ' Amount: ' || v_tx.amount);
  END LOOP;
  CLOSE cur_high_ticket;
END;
```

CURSOR DESIGN PATTERNS

Memory efficient record traversal

• **Explicit Cursors:** Utilized for granular transaction inspection where each record requires complex rule evaluation.
• **Parameterization:** Thresholds (such as minimum transaction amounts) are injected dynamically at open time.
• **%ROWTYPE Record Buffering:** Ensures type-safe row retrieval directly mapped to table structure.

EXCEPTION RESILIENCE

Guaranteed cursor resource cleanup

• **Resource Leak Prevention:** All cursor blocks include exception handlers that verify `IF cur%ISOPEN THEN CLOSE cur; END IF;`.
• **Bulk Collect Optimization:** Demonstrated in batch modules with `LIMIT 100` clauses to balance PGA memory usage against context-switching overhead.

Tamper-evident forensic audit trails

TRG_INVESTIGATION_STATUS_AUDIT writing automated change records to INVESTIGATION_AUDIT.




*Figure 10: Forensic audit log records populated automatically by row-level database triggers (Executed on Oracle 23ai Free / FREEPDB1 via SQL*Plus)*

Deterministic isolation & failure recovery

Strict ACID adherence, controlled savepoints, and custom application error ranges.

Exception Code	Error Name	Enforced Business Condition
-20001	**ERR_INVALID_CASE**	Target investigation ID does not exist in database.
-20002	**ERR_CLOSED_CASE**	Attempt to reassign or modify an already CLOSED investigation.
-20003	**ERR_INVALID_INVESTIGATOR**	Investigator ID does not exist in registry.
-20004	**ERR_INACTIVE_OFFICER**	Investigator active_status is 'INACTIVE'; allocation blocked.
-20005	**ERR_INVALID_PROGRESSION**	Illegal status leap (e.g. CLOSED to OPEN without review).
-20030	**ERR_ACC_NOT_FOUND**	Account ID missing during function execution.

ACID ISOLATION

READ COMMITTED Guarantees

• **No Dirty Reads:** Transactions read only committed database rows.
• **Surveillance Consistency:** Automated alert generation procedures run under autonomous transactions when necessary, ensuring alerts persist even if application sessions roll back.

RECOVERY MECHANISMS

Granular Savepoints

• **Partial Rollback Capability:** Multi-step investigations use named savepoints before assigning officers or changing statuses.
• **Data Integrity Guarantee:** Failed batch updates roll back cleanly without leaving orphan alert flags or corrupted ledger states.

End-to-end fraud investigation lifecycle

Step-by-step trace from transaction journal entry to immutable audit archiving.

1. INGEST

Transaction Journal

A financial transaction is posted to TRANSACTIONS. Engine verifies CHK_TX_AMOUNT (>0), valid account FK, and channel domain.

2. SURVEILLANCE

Rule Evaluation

SP_EVALUATE_AND_ALERT_TRANSACTION or VW_HIGH_RISK_TRANSACTIONS detects high value (>50k) or suspicious channel activity.

3. TRIAGE

Alert Generation

FRAUD_ALERT record generated with severity (LOW to CRITICAL). Triage officer reviews unassigned alert queue.

4. ALLOCATION

Investigator Assigned

SP_ASSIGN_INVESTIGATOR validates officer active_status before creating case in INVESTIGATION. Case opens in 'OPEN' state.

5. RESOLUTION

Forensic Audit Log

Officer records outcome ('CONFIRMED_FRAUD'). Trigger fires automatically, logging old/new status, timestamp, and user to INVESTIGATION_AUDIT.

Master 13-case verification test suite

Live execution of 11_test_cases.sql: 7 positive workflows and 6 negative constraint catches.



*Figure 11: Verbatim execution output of master test harness confirming 100% test pass rate (Executed on Oracle 23ai Free / FREEPDB1 via SQL*Plus)*

Technical compliance & verification matrix

Audit of all database objects executed and genuinely verified against Oracle 23ai Free.

Component Category	Oracle Database Object(s)	Verified Count / State	Compliance Verdict
Relational Tables	CUSTOMER, ACCOUNT, TRANSACTIONS, FRAUD_ALERT, INVESTIGATOR, INVESTIGATION	`6 Core Tables (VALID)`	**100% VERIFIED**
Audit Tables	INVESTIGATION_AUDIT, ALERT_AUDIT	`2 Forensic Tables (VALID)`	**100% VERIFIED**
Primary Key Sequences	seq_cust_id, seq_acc_id, seq_tx_id, seq_alert_id, seq_inves_id, seq_inves_audit_id	`6 Sequences (VALID)`	**100% VERIFIED**
Surveillance Views	VW_HIGH_RISK_TRANSACTIONS, VW_INVESTIGATION_SUMMARY, VW_CUSTOMER_FRAUD_EXPOSURE	`4 Views (VALID)`	**100% VERIFIED**
Stored Procedures	SP_ASSIGN_INVESTIGATOR, SP_UPDATE_INVESTIGATION_STATUS, SP_EVALUATE_AND_ALERT_TRANSACTION	`3 Procedures (VALID)`	**100% VERIFIED**
PL/SQL Functions	FN_GET_TOTAL_TX_AMOUNT, FN_CALCULATE_RISK_TIER, FN_GET_ACCOUNT_ALERT_COUNT	`3 Functions (VALID)`	**100% VERIFIED**
Database Triggers	TRG_INVESTIGATION_STATUS_AUDIT, TRG_FRAUD_ALERT_AUDIT	`2 Triggers (ENABLED)`	**100% VERIFIED**
Baseline Data Journal	10 Customers, 12 Accounts, 18 Transactions, 7 Alerts, 4 Investigators, 5 Cases	`56 Baseline Records`	**100% VERIFIED**

Production readiness & future enhancements

Honest engineering assessment of current system deliverables and roadmap.

COMPLETED DELIVERABLES

• **Rigorous 3NF Architecture:** Eliminated data redundancy and update anomalies across customer demographics, accounts, and case allocations.

• **Engine-Enforced Constraints:** Strict CHECK, UNIQUE, and FOREIGN KEY constraints reject invalid or corrupt records at the database kernel.

• **Active Procedural Surveillance:** Multi-tiered PL/SQL procedures and views automate fraud detection thresholds and case assignments.

• **Non-Repudiation Audit Defense:** Automated row-level triggers track case status transitions in forensic audit logs.

• **100% Test Pass Rate:** Fully executed and verified test suite proving both positive operational workflows and negative constraint defense.

LIMITATIONS & FUTURE SCOPE

• **Current Limitation — Synchronous Triggers:** Heavy trigger-based auditing on high-frequency transactions may impact write latency in ultra-high TPS environments.

• **Future Enhancement — Kafka Stream Ingestion:** Decouple ingest via Apache Kafka topics and micro-batched loader routines.

• **Current Limitation — Rule-Based Detection:** Surveillance rules rely on fixed thresholds (>50k INR, channel type) rather than behavioural patterns.

• **Future Enhancement — Machine Learning Inference:** Embed Oracle Machine Learning (OML) algorithms or ONNX models for real-time anomaly inference inside the database.

• **Future Enhancement — Distributed Ledger:** Implement Oracle Blockchain Tables to provide cryptographic immutability for the forensic audit trail.

FRAUDLENS • COMPREHENSIVE REVIEW 1 & REVIEW 2 COMPLETE

FraudLens: Master Project Completion

Financial Transaction & Fraud Investigation Management System

A complete, university-grade Database Management Systems implementation encompassing relational modelling, Third Normal Form schema engineering, named integrity constraints, analytical querying, PL/SQL procedural surveillance, automated case lifecycle triage, and forensic audit logging.

D Joshua Daniel

Registration No: **24BCE0436**
Bachelor of Technology in Computer Science & Engineering
School of Computer Science & Engineering (SCOPE)
Vellore Institute of Technology (VIT), Vellore

M Saryu

Registration No: **24BCE2524**
Bachelor of Technology in Computer Science & Engineering
School of Computer Science & Engineering (SCOPE)
Vellore Institute of Technology (VIT), Vellore

Course: BCSE304L Database Management Systems • Faculty Guide: Prof. Kanagaraj K