

# Assignment 1 Solution

Joshua Guinness, guinnesj

January 25, 2019

In this assignment, a python program was created which automatically reads in data from various files, then allocates first year engineering students into their stream in order of free choice, then GPA. The program consists of three modules; one to read in the student, departement, and free choice data, one to allocate the students and perform operations, and one which acts as a test driver, consisting of test cases.

The rest of this document will outline the methodology behind the testing and serve as a reflection on the assignment.

## 1 Testing of the Original Program

In order to talk about testing results and the methodology used to design test cases, it is important to first talk about what was assumed while coding the program as the test cases exists, or don't exists, based on what was assumed.

The reason assumptions had to be taken is because the specification was not formal or specific enough on how the interface was meant to work. For example, the specification gave no instructions on program behaviour when the file does not exist. Either an assumption had to be made that the file will always exists, or the potential error had to be dealt with in the code, the later of which was done in this program.

The assumptions used while programming are as follows.

1. All The names and macid of the students are correct and match those in other files such as freeChoice
2. All students have a gender that is either 'male' or 'female' and the gender is spelt correctly.
3. All students have a GPA that is between 1.0 and 12.0.
4. All students have three proper engineering streams that they would like to go into, spelt correctly.

5. There is enough capacity in each department for every student with free choice to be allocated to their first choice
6. There is enough capacity in each department for every student to be allocated to at least one of their top three choices.
7. Every student with free choice passed first year engineering (GPA  $\geq$  4.0).

Based on the assumptions outline above, there were two types of test cases designed.

The first type of test cases checked for correctness of the functions. This type included the second, third, fourth, fifth, sixth, and eighth test cases. These cases were chosen to test the main functionality of each of the functions in CalcModule at least once. After these test cases, it can be confirmed that the implementation of the functions are correct. A description and rationale of each one will be briefly discussed. All these test cases passed.

The second test case checked to see whether the sort function sorted the students in order of GPA correctly. It just compared to the output of the function to a dictionary of sorted students which was known to be correct.

The third, fourth, fifth, and sixth test cases check to see whether a correct average was returned for males and females from two different data sets. The test case returned false when the exact float value was compared with the output so to solve the issue, a float value in a very small range was compared with the output.

The eighth test case confirmed that the allocate properly placed students into their engineering streams first by free choice, then in order of GPA.

The second type of test cases checked for correct behaviour of program when weird inputs, like missing files, or incomplete data was passed to the functions. This type included the first, seventh, and ninth test cases. The number of test cases of this type required to build a modest amount of confidence in the program depends on the amount of assumptions. Since quite a few things were assumed, less test cases of this type were needed. All these test cases passed after modification to the the code. The rationale behind them, problems uncovered while testing, and a brief description of each test case will be discussed.

In the first test case, the functions in ReadAllocationData were tested instead of those in CalcModule. It tested for program response when all the files were empty. The functions responded correctly by returning empty dictionaries or lists.

In the seventh test case, the average function was checked to see behaviour when tried to get the average of all the females, but there are no females in the data. Based on this test case failing for the first time, the code had to be modified to return 'None', as well as correctly deal with the fact that there is no one of that gender in the data.

Finally, the ninth test case checked to see whether the allocation function worked correctly when it was given student data and none of them had free choice. This was tested to ensure that the function still operated correctly when one of the files was empty.

All this list of nine test cases covered quite a bit of program functionality and possible errors, building confidence in the robustness and correctness of it, there is still more testing that could have been done to verify these things. This was what could be done in the timing given.

## 2 Results of Testing Partner's Code

A table outlining the summary of results after running the test script on the partners code is seen below.

Test Case	Result
1	Pass
2	Pass
3	Pass
4	Pass
5	Pass
6	Pass
7	Fail - ZeroDivisionError
8	Pass
9	Pass

Table 1: Table outlining the results of testing partner code

As can be seen from the table all the test cases were passed except for the seventh one. The seventh test case check to see how the program behaved when asked to calculate the average GPA of all the females, yet there were no females in the data.

The error that was gotten was a ZeroDivisionError at line 42 in the partners CalcModule program. This line of code is:

$$aveFemale = sumFemale / numFemale$$

This line of code divides the total sum by the number of females. However, if there are zero females, the program tries to divide by zero, throwing an error, leading to this particular test case to fail.

## **3 Discussion of Test Results**

### **3.1 Problems with Original Code**

### **3.2 Problems with Partner's Code**

## **4 Critique of Design Specification**

## **5 Answers to Questions**

(a) answer

(b) answer

(c) ...

## F Code for ReadAllocationData.py

```
## @file ReadAllocationData.py
# @Joshua Guinness, guinnessj
# @A module to open files, process, then store the data
# @January 14-18, 2019

# For these functions I am making the assumption that the the contents in the file are accurate and
# the formatting is correct.
# I am doing error checking on the opening files, but am assuming the rest is correct

# Import for error raising and exiting
import sys

## @brief A function which reads in student data from a file and stores it in a list of dictionaries
# @param p1 A string corresponding to a filename
# @return Returns a list of dictionaries of student information
def readStdnts(s):

    # Creates a new list which will store student dictionaries
    student_info = []

    # Try-Except statement for opening the file
    try:

        # Opens the file for reading
        # How to open a file taken from:
        # https://docs.python.org/3/tutorial/inputoutput.html#reading-and-writing-files
        f = open(s, 'r')

    except:

        # Exit if the file does not exist or can't be opened.
        # Method seen here: https://python-forum.io/Thread-How-to-exit-after-a-try-exception
        sys.exit("Error opening the file of student data!")

    # Reads in each line, converts to a dictionary, then adds the dictionary to the list
    for line in f:

        # Strips the newline character at the end of the string.
        # Method taken from:
        # https://stackoverflow.com/questions/275018/how-can-i-remove-a-trailing-newline-in-python
        line = line.rstrip()

        # Splits each line at each tab into a list
        # How the split strings taken from here:
        # https://www.pythoncentral.io/cutting-and-slicing-strings-in-python/
        student_string = line.split('\t')

        # Splits the choices at commas and spaces
        choices = student_string[5].split(', ')

        # Transforms the current line student to a dictionary
        student_dictionary = {'macid': student_string[0], 'fname': student_string[1], 'lname':
            student_string[2], 'gender': student_string[3], 'gpa': float(student_string[4]), 'choices':
                choices}

        # Adds the current dictionary to a list of student info
        student_info.append(student_dictionary)

    # Closes the file
    f.close()

    #print(student_info)

    # Return statement
    return student_info

## @brief A function which reads in data about students with free choice from a file and stores it in
# a list
# @param p1 A string corresponding to a filename
# @return Returns a list of macids of students with free choice
def readFreeChoice(s):

    # Creates an empty list
```

```

students_free_choice = []

# Try-Except block for opening the file
try:

    # Opens the file
    f = open(s, 'r')

except:

    sys.exit("Error opening the file of students with free choice!")

# Iterates through the file, stripping the new line character, and appending each macid to the list
for line in f:
    line = line.rstrip()
    students_free_choice.append(line)

# Closes the file
f.close()

#print(students_free_choice)

# Returns the list
return students_free_choice

## @brief A function which reads in data about department capacities from a file and stores it in a
#         dictionary
# @param p1 A string corresponding to a filename
# @return Returns a dictionary of departments and their capacity
def readDeptCapacity(s):

    # Create an empty dictionary
    department_capacity = {}

    # Try-Except for opening the file
    try:

        # Opens the file
        f = open(s, 'r')

    except:

        sys.exit("Error opening the file of department capacities!")

    # Iterates through the file line by line, splitting at spaces, and adding the department and its
    # capacity to a dictionary
    for line in f:
        line = line.rstrip()
        list = line.split(' ')

        # How to add key's and values to a dictionary got from:
        # https://docs.python.org/3/tutorial/datastructures.html#dictionaries
        department_capacity[list[0]] = int(list[1])

    # Closes the file
    f.close()

    #print(department_capacity)

    # Returns a dictionary of the departments and their capacity
    return department_capacity

```

## G Code for CalcModule.py

```

## @file CalcModule.py
# @author Behzad Khamneli
# @brief Sorts the students info based on their GPA, calculates their average and assigns them to a
#       department.
# @date 1/18/2019

## @brief Function sort takes a list of the dictionaries of students from readStdnts in
#       ReadAllocationData.
# @return A list of dictionaries in sorted order.
# Citation: https://www.saltycrane.com/blog/2007/09/how-to-sort-python-dictionary-by-keys/
def sort(S):
    if S == "File Error":
        return "File Error"
    else:
        return sorted(S, key = lambda grade: grade['gpa'], reverse = True)

## @brief This function calculates the average gpa of male or female students.
# @details If param g is 'male', then it returns the average gpa of male students and if g is
# 'female' then it returns the average gpa for female students. If non of them has been entered,
# then it returns an error.
# @param L Is a list of dictionaries of students.
# @param g Can be either male or female.
# @return The average gpa of male or female students, with the choice depending on the param g.
def average(L, g):
    if L == "File Error":
        return "File Error"
    else:
        sumMale = 0
        numofMale = 0
        aveMale = 0

        sumFemale = 0
        numFemale = 0
        aveFemale = 0
        for dicty in L:
            if dicty['gender'] == 'male':
                sumMale = sumMale + dicty['gpa']
                numofMale += 1
            if dicty['gender'] == 'female':
                sumFemale = sumFemale + dicty['gpa']
                numFemale += 1

        if g == 'male':
            aveMale = sumMale / numofMale
            return aveMale
        if g == 'female':
            aveFemale = sumFemale / numFemale
            return aveFemale
        else:
            return "g can be either male or female"

## @brief This function assigns the students to a department depending on their gpa and freechoice.
# @details After each iteration, this function stores the macid of the students who have been
# assigned to a department to a list so that the same student will not be assigned to another
# department.
# @param S Is a list of the dictionaries of students created by readStdnts.
# @param F Is a list of students with free choice.
# @param C Is a dictionary of department capacities.
# @return A dictionary with the following format {'civil': [student, student,...], 'chemical':
# [student, student,...],...}. Student corresponds to the students' information.
def allocate(S, F, C):
    if (S == "File Error") or (F == "File Error") or (C == "File Error"):
        return "File Error"
    else:
        alldic = {}
        numofFree = len(F)
        assigned = []
        civil = []
        chemical = []
        electrical = []
        mechanical = []
        software = []
        materials = []
        engphys = []

        for std in sort(S):
            for i in range (numofFree):
                if std['macid'] == F[i]:

```

```

        if std['choices'][0] == 'civil' and C['civil'] != 0:
            civil.append(std)
            C['civil'] = C['civil'] - 1

        elif std['choices'][0] == 'chemical' and C['chemical'] != 0:
            chemical.append(std)
            C['chemical'] = C['chemical'] - 1

        elif std['choices'][0] == 'electrical' and C['electrical'] != 0:
            electrical.append(std)
            C['electrical'] = C['electrical'] - 1

        elif std['choices'][0] == 'mechanical' and C['mechanical'] != 0:
            mechanical.append(std)
            C['mechanical'] = C['mechanical'] - 1

        elif std['choices'][0] == 'software' and C['software'] != 0:
            software.append(std)
            C['software'] = C['software'] - 1

        elif std['choices'][0] == 'materials' and C['materials'] != 0:
            materials.append(std)
            C['materials'] = C['materials'] - 1

        elif std['choices'][0] == 'engphys' and C['engphys'] != 0:
            engphys.append(std)
            C['engphys'] = C['engphys'] - 1

    for std in sort(S):
        for i in range(3):
            if std['macid'] not in F and std['macid'] not in assigned and std['gpa'] >= 4.0:

                if std['choices'][i] == 'civil':
                    if C['civil'] != 0:
                        civil.append(std)
                        C['civil'] = C['civil'] - 1
                        assigned.append(std['macid'])

                if std['choices'][i] == 'chemical':
                    if C['chemical'] != 0:
                        chemical.append(std)
                        C['chemical'] = C['chemical'] - 1
                        assigned.append(std['macid'])

                if std['choices'][i] == 'electrical':
                    if C['electrical'] != 0:
                        electrical.append(std)
                        C['electrical'] = C['electrical'] - 1
                        assigned.append(std['macid'])

                if std['choices'][i] == 'mechanical':
                    if C['mechanical'] != 0:
                        mechanical.append(std)
                        C['mechanical'] = C['mechanical'] - 1
                        assigned.append(std['macid'])

                if std['choices'][i] == 'software':
                    if C['software'] != 0:
                        software.append(std)
                        C['software'] = C['software'] - 1
                        assigned.append(std['macid'])

                if std['choices'][i] == 'materials':
                    if C['materials'] != 0:
                        materials.append(std)
                        C['materials'] = C['materials'] - 1
                        assigned.append(std['macid'])

                if std['choices'][i] == 'engphys':
                    if C['engphys'] != 0:
                        engphys.append(std)
                        C['engphys'] = C['engphys'] - 1
                        assigned.append(std['macid'])

    alldic['civil'] = civil

```



```
alldic['chemical'] = chemical
alldic['electrical'] = electrical
alldic['mechanical'] = mechanical
alldic['software'] = software
alldic['materials'] = materials
alldic['engphys'] = engphys
return alldic
```

## H Code for testCalc.py

```
## @file testCalc.py
# @Joshua Guinness, guinnesj
# @A module to test CalcModule.py
# @January 14-18, 2019

# Imports
from CalcModule import *
from ReadAllocationData import *
import unittest

# Test Case 1:
# Checks response of functions when the files are empty.

if (readStdnts('TestingData/rawStudentData2') == []
    and readFreeChoice('TestingData/freeChoice2') == []
    and readDeptCapacity('TestingData/rawDepartmentData2') == {}):
    print("Test Case 1: Pass")
else:
    print("Test Case 1: Fail")

# Test Case 2:
# Testing whether sort function sorts students by gpa properly
student_dictionaries = readStdnts('TestingData/rawStudentData')
students_with_free_choice = readFreeChoice('TestingData/freeChoice')
department_capacity = readDeptCapacity('TestingData/rawDepartmentData')

sorted_student_dictionaries = sort(student_dictionaries)

if (sorted_student_dictionaries == [{'gender': 'male', 'gpa': 12.0, 'choices': ['software',
    'electrical', 'mechanical'], 'lname': 'Guinness', 'fname': 'Joshua', 'macid': 'guinnesj'},
    {'gender': 'male', 'gpa': 11.9, 'choices': ['materials',
    'engphys', 'software'], 'lname': 'Guinness', 'fname':
    'Daniel', 'macid': 'danielg'},
    {'gender': 'female', 'gpa': 11.2, 'choices': ['chemical',
    'electrical', 'engphys'], 'lname': 'Khani', 'fname':
    'Sophia', 'macid': 'khanisl'},
    {'gender': 'male', 'gpa': 9.8, 'choices': ['civil', 'mechanical',
    'materials'], 'lname': 'Tara', 'fname': 'Mickey', 'macid':
    'taraml'},
    {'gender': 'female', 'gpa': 8.6, 'choices': ['mechanical',
    'civil', 'materials'], 'lname': 'Brown', 'fname': 'Grace',
    'macid': 'browng'},
    {'gender': 'female', 'gpa': 7.1, 'choices': ['engphys',
    'chemical', 'civil'], 'lname': 'Kass', 'fname': 'Cassie',
    'macid': 'cassyk'},
    {'gender': 'male', 'gpa': 6.4, 'choices': ['software', 'civil',
    'electrical'], 'lname': 'So', 'fname': 'Leon', 'macid':
    'leon2'},
    {'gender': 'female', 'gpa': 6.3, 'choices': ['mechanical',
    'electrical', 'software'], 'lname': 'Smith', 'fname':
    'Roxanne', 'macid': 'smithr'},
    {'gender': 'female', 'gpa': 4.4, 'choices': ['mechanical',
    'electrical', 'chemical'], 'lname': 'Xiao', 'fname': 'Joy',
    'macid': 'joyxiao'},
    {'gender': 'male', 'gpa': 2.2, 'choices': ['software',
    'materials', 'civil'], 'lname': 'Choy', 'fname': 'Timothy',
    'macid': 'choyt2'}]):
    print("Test Case 2: Pass")
else:
    print("Test Case 2: Fail")

# Test Case 3:
# Testing whether average function returns the correct average for males
student_dictionaries = readStdnts('TestingData/rawStudentData')

average_gpa = average(student_dictionaries, 'male')

if (average_gpa > 8.45 and average_gpa < 8.47):
    print("Test Case 3: Pass")
else:
    print("Test Case 3: Fail")

# Test Case 4:
# Testing whether average function returns the correct average for females
student_dictionaries = readStdnts('TestingData/rawStudentData')
```

```

average_gpa = average(student_dictionaries, 'female')

if (average_gpa > 7.51 and average_gpa < 7.53):
    print("Test Case 4: Pass")
else:
    print("Test Case 4: Fail")

# Test Case 5:
# Testing whether average function returns the correct average for males on a different data set
student_dictionaries = readStdnts('TestingData/rawStudentData3')

average_gpa = average(student_dictionaries, 'male')

if (average_gpa > 6.73 and average_gpa < 6.75):
    print("Test Case 5: Pass")
else:
    print("Test Case 5: Fail")

# Test Case 6:
# Testing whether average function returns the correct average for females on a different data set
student_dictionaries = readStdnts('TestingData/rawStudentData3')

average_gpa = average(student_dictionaries, 'female')

if (average_gpa > 9.21 and average_gpa < 9.23):
    print("Test Case 6: Pass")
else:
    print("Test Case 6: Fail")

# Test Case 7:
# Testing whether average function returns the correct average when there are no students of the
# gender called
student_dictionaries = readStdnts('TestingData/rawStudentData4')

average_gpa = average(student_dictionaries, 'female')

if (average_gpa == None):
    print("Test Case 7: Pass")
else:
    print("Test Case 7: Fail")

# Test Case 8:
# Testing whether allocate function allocates the students properly
student_dictionaries = readStdnts('TestingData/rawStudentData')
students_with_free_choice = readFreeChoice('TestingData/freeChoice')
department_capacity = readDeptCapacity('TestingData/rawDepartmentData')

allocation_dictionary = allocate(student_dictionaries, students_with_free_choice, department_capacity)

if (allocation_dictionary == {'engphys': [{'gender': 'female', 'gpa': 7.1, 'choices': ['engphys',
    'chemical', 'civil'], 'lname': 'Kass', 'fname': 'Cassie', 'macid': 'cassyk'}],
    'civil': [{'gender': 'male', 'gpa': 9.8, 'choices': ['civil',
    'mechanical', 'materials'], 'lname': 'Tara', 'fname': 'Mickey',
    'macid': 'taram1'}],
    'chemical': [{'gender': 'female', 'gpa': 11.2, 'choices': ['chemical',
    'electrical', 'engphys'], 'lname': 'Khani', 'fname': 'Sophia',
    'macid': 'khanisl'}],
    'materials': [{'gender': 'male', 'gpa': 11.9, 'choices': ['materials',
    'engphys', 'software'], 'lname': 'Guinness', 'fname': 'Daniel',
    'macid': 'danielg'}],
    'electrical': [{'gender': 'female', 'gpa': 4.4, 'choices':
    ['mechanical', 'electrical', 'chemical'], 'lname': 'Xiao', 'fname':
    'Joy', 'macid': 'joyxiao'}],
    'mechanical': [{'gender': 'female', 'gpa': 8.6, 'choices':
    ['mechanical', 'civil', 'materials'], 'lname': 'Brown', 'fname':
    'Grace', 'macid': 'browng'},
        {'gender': 'female', 'gpa': 6.3, 'choices':
    ['mechanical', 'electrical', 'software'], 'lname':
    'Smith', 'fname': 'Roxanne', 'macid': 'smithr'}],
    'software': [{'gender': 'male', 'gpa': 12.0, 'choices': ['software',
    'electrical', 'mechanical'], 'lname': 'Guinness', 'fname':
    'Joshua', 'macid': 'guinnesj'},
        {'gender': 'male', 'gpa': 6.4, 'choices': ['software',
    'civil', 'electrical'], 'lname': 'So', 'fname':
    'Leon', 'macid': 'leon2'}]}]):
    print("Test Case 8: Pass")
else:
    print("Test Case 8: Fail")

```

```

# Test Case 9:
# Testing whether allocate function allocates the students properly when no one has free choice
student_dictionaries = readStdnts('TestingData/rawStudentData')
students_with_free_choice = readFreeChoice('TestingData/freeChoice2')
department_capacity = readDeptCapacity('TestingData/rawDepartmentData')

allocation_dictionary = allocate(student_dictionaries, students_with_free_choice, department_capacity)

if (allocation_dictionary == {'engphys': [{'gender': 'female', 'gpa': 7.1, 'choices': ['engphys',
'chemical', 'civil'], 'lname': 'Kass', 'fname': 'Cassie', 'macid': 'cassyk'}],
'civil': [{'gender': 'male', 'gpa': 9.8, 'choices': ['civil',
'mechanical', 'materials'], 'lname': 'Tara', 'fname': 'Mickey',
'macid': 'taraml'}],
'chemical': [{'gender': 'female', 'gpa': 11.2, 'choices': ['chemical',
'electrical', 'engphys'], 'lname': 'Khani', 'fname': 'Sophia',
'macid': 'khanisl'}],
'materials': [{'gender': 'male', 'gpa': 11.9, 'choices': ['materials',
'engphys', 'software'], 'lname': 'Guinness', 'fname': 'Daniel',
'macid': 'danielg'}],
'electrical': [{'gender': 'female', 'gpa': 4.4, 'choices':
['mechanical', 'electrical', 'chemical'], 'lname': 'Xiao', 'fname':
'Joy', 'macid': 'joyxiao'}],
'mechanical': [{'gender': 'female', 'gpa': 8.6, 'choices':
['mechanical', 'civil', 'materials'], 'lname': 'Brown', 'fname':
'Grace', 'macid': 'browng'},
{'gender': 'female', 'gpa': 6.3, 'choices':
['mechanical', 'electrical', 'software'], 'lname':
'Smith', 'fname': 'Roxanne', 'macid': 'smithr'}],
'software': [{'gender': 'male', 'gpa': 12.0, 'choices': ['software',
'electrical', 'mechanical'], 'lname': 'Guinness', 'fname':
'Joshua', 'macid': 'guinnesj'},
{'gender': 'male', 'gpa': 6.4, 'choices': ['software',
'civil', 'electrical'], 'lname': 'So', 'fname':
'Leon', 'macid': 'leon2'}]}):

    print("Test Case 9: Pass")
else:
    print("Test Case 9: Fail")

print("All Test Cases Complete")

```

# I Code for Partner's CalcModule.py

```
## @file CalcModule.py
# @author Behzad Khamneli
# @brief Sorts the students info based on their GPA, calculates their average and assigns them to a
#       department.
# @date 1/18/2019

## @brief Function sort takes a list of the dictionaries of students from readStdnts in
#       ReadAllocationData.
# @return A list of dictionaries in sorted order.
# Citation: https://www.saltycrane.com/blog/2007/09/how-to-sort-python-dictionary-by-keys/
def sort(S):
    if S == "File Error":
        return "File Error"
    else:
        return sorted(S, key = lambda grade: grade['gpa'], reverse = True)

## @brief This function calculates the average gpa of male or female students.
# @details If param g is 'male', then it returns the average gpa of male students and if g is
# 'female' then it returns the average gpa for female students. If non of them has been entered,
# then it returns an error.
# @param L Is a list of dictionaries of students.
# @param g Can be either male or female.
# @return The average gpa of male or female students, with the choice depending on the param g.
def average(L, g):
    if L == "File Error":
        return "File Error"
    else:
        sumMale = 0
        numofMale = 0
        aveMale = 0

        sumFemale = 0
        numFemale = 0
        aveFemale = 0
        for dicty in L:
            if dicty['gender'] == 'male':
                sumMale = sumMale + dicty['gpa']
                numofMale += 1
            if dicty['gender'] == 'female':
                sumFemale = sumFemale + dicty['gpa']
                numFemale += 1

        if g == 'male':
            aveMale = sumMale / numofMale
            return aveMale
        if g == 'female':
            aveFemale = sumFemale / numFemale
            return aveFemale
        else:
            return "g can be either male or female"

## @brief This function assigns the students to a department depending on their gpa and freechoice.
# @details After each iteration, this function stores the macid of the students who have been
# assigned to a department to a list so that the same student will not be assigned to another
# department.
# @param S Is a list of the dictionaries of students created by readStdnts.
# @param F Is a list of students with free choice.
# @param C Is a dictionary of department capacities.
# @return A dictionary with the following format {'civil': [student, student,...], 'chemical':
# [student, student,...],...}. Student corresponds to the students' information.
def allocate(S, F, C):
    if (S == "File Error") or (F == "File Error") or (C == "File Error"):
        return "File Error"
    else:
        alldic = {}
        numofFree = len(F)
        assigned = []
        civil = []
        chemical = []
        electrical = []
        mechanical = []
        software = []
        materials = []
        engphys = []

        for std in sort(S):
            for i in range (numofFree):
                if std['macid'] == F[i]:
```

```

        if std['choices'][0] == 'civil' and C['civil'] != 0:
            civil.append(std)
            C['civil'] = C['civil'] - 1

        elif std['choices'][0] == 'chemical' and C['chemical'] != 0:
            chemical.append(std)
            C['chemical'] = C['chemical'] - 1

        elif std['choices'][0] == 'electrical' and C['electrical'] != 0:
            electrical.append(std)
            C['electrical'] = C['electrical'] - 1

        elif std['choices'][0] == 'mechanical' and C['mechanical'] != 0:
            mechanical.append(std)
            C['mechanical'] = C['mechanical'] - 1

        elif std['choices'][0] == 'software' and C['software'] != 0:
            software.append(std)
            C['software'] = C['software'] - 1

        elif std['choices'][0] == 'materials' and C['materials'] != 0:
            materials.append(std)
            C['materials'] = C['materials'] - 1

        elif std['choices'][0] == 'engphys' and C['engphys'] != 0:
            engphys.append(std)
            C['engphys'] = C['engphys'] - 1

    for std in sort(S):
        for i in range(3):
            if std['macid'] not in F and std['macid'] not in assigned and std['gpa'] >= 4.0:

                if std['choices'][i] == 'civil':
                    if C['civil'] != 0:
                        civil.append(std)
                        C['civil'] = C['civil'] - 1
                        assigned.append(std['macid'])

                if std['choices'][i] == 'chemical':
                    if C['chemical'] != 0:
                        chemical.append(std)
                        C['chemical'] = C['chemical'] - 1
                        assigned.append(std['macid'])

                if std['choices'][i] == 'electrical':
                    if C['electrical'] != 0:
                        electrical.append(std)
                        C['electrical'] = C['electrical'] - 1
                        assigned.append(std['macid'])

                if std['choices'][i] == 'mechanical':
                    if C['mechanical'] != 0:
                        mechanical.append(std)
                        C['mechanical'] = C['mechanical'] - 1
                        assigned.append(std['macid'])

                if std['choices'][i] == 'software':
                    if C['software'] != 0:
                        software.append(std)
                        C['software'] = C['software'] - 1
                        assigned.append(std['macid'])

                if std['choices'][i] == 'materials':
                    if C['materials'] != 0:
                        materials.append(std)
                        C['materials'] = C['materials'] - 1
                        assigned.append(std['macid'])

                if std['choices'][i] == 'engphys':
                    if C['engphys'] != 0:
                        engphys.append(std)
                        C['engphys'] = C['engphys'] - 1
                        assigned.append(std['macid'])

    alldic['civil'] = civil

```

```
alldic['chemical'] = chemical
alldic['electrical'] = electrical
alldic['mechanical'] = mechanical
alldic['software'] = software
alldic['materials'] = materials
alldic['engphys'] = engphys
return alldic
```

## J Makefile

```
PY = python
PYFLAGS =
DOC = doxygen
DOCFLAGS =
DOCCONFIG = docConfig

SRC = src/testCalc.py

.PHONY: all test doc clean

test:
    $(PY) $(PYFLAGS) $(SRC)

doc:
    $(DOC) $(DOCFLAGS) $(DOCCONFIG)
    cd latex && $(MAKE)

all: test doc

clean:
    rm -rf html
    rm -rf latex
```