


Lecture 7

Warm up problem: **The Campers' Problem** (Section 3.1 in Ecco)

A counsellor has eight campers with her at a junction in a hiking trail. She knows their camp is twenty minutes down one of four possible paths. It will be dark in one hour and the group must find their camp before dark. Two of the eight campers sometimes lie, and unfortunately the counsellor doesn't know which of the eight they are.



Example 1: How can the counselor find the camp?

The counselor checks one path and sends

- 3 campers down path 1
- 3 _____ 2
- 2 _____ 3

CASE 1: There is a disagreement on two of the paths.

- Listen to the majority on paths 1 & 2.

CASE 2: There is a disagreement on at most one path.

- Listen to two paths that agree.


\therefore in both cases the counselor knows what is down 3 of the paths and can deduce where the camp is.

Example 2: Design a code that will enable the counselor to accurately deduce the location of the camp.

The counselor can check one path, leaving the other three paths for the 8 campers. She should send 3 campers down each of paths #1 and #2 and send 2 campers down path #3.

To show why this works we will make a code containing three codewords. Each codeword will represent the camp being down a particular path. Each bit in a codeword will represent the answer given by a camper. In this code a 1 will represent “yes” and a 0 will represent “no”.

Codeword #1: The camp is down #1 and no one lies:	111	000	00
Codeword #2: The camp is down #2 and no one lies:	000	111	00
Codeword #3: The camp is down #3 and no one lies:	000	000	11




Each pair of codewords in the code has a hamming distance of 5 or more. This means the minimum hamming distance of this code is 5. To find out how many errors the code can correct we solve:

$$\begin{aligned}
 2n + 1 &= \min H(x, y) \\
 \Rightarrow 2n + 1 &= 5 \\
 \Rightarrow n &= 2
 \end{aligned}$$

Therefore the code can correct up to 2 corrupted bits, which represent campers that have lied. This means the counselor can correct the two campers that are lying, and therefore can accurately deduce the location of the camp.


Note: The following figure illustrates this solution. In the figure, circles are drawn around each codeword (representing a path). These circles contain erroneous codewords that have a Hamming distance of at most 2 from the real codeword in the center of each circle. Since the circles do not intersect, this code can correct two errors (lying campers). Notice: for clarity, some erroneous codewords have been omitted.

Path 1




011 011 01



Path 3



Path 2



111 111 11




Example 3: Back at camp, 7 mini marshmallows have gone missing. The Camp Director found out that the 7 marshmallows had been stuck up 5 junior camper's noses. Show that there must be a group of 3 junior campers with a combined total of 3 or less marshmallows up their noses.



Marshmallows



Junior Campers



\therefore a junior camper has $\lceil \frac{7}{5} \rceil = 2$ or more marshmallows in their nose.

\therefore the other four junior campers have a combined total of $7 - \lceil \frac{7}{5} \rceil = 5$ or less marshmallows up their noses :

Marshmallows




Junior Campers



\therefore three junior campers have a combined total of $5 - \lceil \frac{5}{4} \rceil = 3$ or less marshmallows up their noses.

Example 4: Prove the campers' problem cannot be solved with only 7 campers.



\therefore two paths have a combined total of $7 - \lceil \frac{7}{3} \rceil = 4$ or less campers.

Now when the code from example 2 is used we get:

codeword A :	11...1	0...0	0...0
codeword B :	00...0	1...1	0...0
codeword C :	00...0	0...0	1...1

$\underbrace{\hspace{1.5cm}}$
3 or more
 $\underbrace{\hspace{2.5cm}}$
4 or less

$\therefore H(\text{codeword B}, \text{codeword C}) \leq 4$

$\therefore \min H(x, y) \leq 4$

But, to correct 2 corrupted bits we need:

$$\min H(x, y) = 2n + 1 = 2(2) + 1 = 5 \quad (\text{or more})$$

\therefore the counselor can no longer correct the two liars.