

SMT1500RM2UC

APC Smart-UPS, Line Interactive, 1500VA,
Rackmount 2U, 120V, 6x NEMA 5-15R outlets,
SmartConnect Port+SmartSlot, AVR, LCD



Product availability: Non-Stock - Not normally stocked in distribution facility

Overview

Presentation	Intelligent and efficient network power protection from entry level to scalable runtime. Ideal UPS for
--------------	--

Main

Main Input Voltage	120 V AC 1 phase
Other Input Voltages	110 V 125 V
Input Connection Type	NEMA 5-15P
Efficiency at full load	75...154 V adjustable 82...144 V
Input Frequency	50/60 Hz +/- 3 Hz auto-sensing
Output voltage	120 V AC 1 phase
Other Output Voltages	110 V 125 V
Rated power in W	1000 W
Rated power in VA	1440 VA
Output connection type	6 NEMA 5-15R
Harmonic distortion	Less than 5%
Maximum configurable power in VA	1440 VA
Max Configurable Power (Watts)	1000 W
Transfer Time	6ms typical : 10ms maximum
Topology	Line Interactive
Waveform Type	Sine wave
Output Frequency (sync to mains)	50/60 Hz +/- 3 Hz sync to mains

Complementary

Battery Size	Lead-acid internal included
Control panel	Multi-function LCD status and control console
Free slots	1
Alarm	Alarm when on battery : distinctive low battery alarm : configurable delays
UPS connectivity	Serial port USB port SmartConnect port Available expansion slot
Communication port support	SmartConnect Ethernet port: for cloud monitoring feature availability varies by terms of use
Software package	SmartConnect software for remote power monitoring feature availability varies by terms of use
Surge energy rating	680 J
Filtering	Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : m
Number of rack unit	2U
Cable length	8 Ft (2.4 m)
Number of cables	1
Color	Black
Height	3.4 In (86 mm)
Width	17.008 In (432 mm)
Depth	18.8 In (477 mm)
Product Weight	58.4 Lb(US) (26.5 kg)
Mounting Location	Front
Mounting preference	Lower
Mounting Mode	Rack-mounted
Two post mountable	0
USB compatible	Yes
Mounting mode	Rack-mounted with included kit
Provided equipment	Installation guide Rack Mounting support rails USB cable
Number of power module	0
Number of power module filled slots	0
Number of power module free slots	0
Additional specification	Cloud-enabled monitoring
Redundant	No
Range of Product	Smart-UPS
Product or Component Type	Uninterruptible power supply (UPS)

Environment

Product Certifications	cULus[RETURN]ENERGY STAR V2.0 (USA)
Equipment protection policy	Lifetime : \$150000
Ambient Air Temperature for Operation	32...104 °F (0...40 °C)
Ambient Air Temperature for Storage	5...113 °F (-15...45 °C)
Storage altitude	0...50000 Ft (0...15240 m)
Relative Humidity	0...95 %
Storage Relative Humidity	0...95 %
Acoustic level	45 dBA
Online Thermal Dissipation	225 Btu/H
Operating altitude	0...10000 ft

Batteries & Runtime

Battery Type	Lead-Acid battery
Extendable Run Time	0
Included Battery Modules	0
Battery Slots Empty	0
Typical recharge time	3 H
RBC Quantity	1
Battery life	4...6 Year(S)
Battery Charge Power (Watts)	144 W rated

Ordering and shipping details

Category	11309 - APC RESALE PRODUCTS
GTIN	731304322801
Returnability	No
Country of origin	VN

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	9.3 In (23.5 cm)
Package 1 Width	24.02 In (61 cm)
Package 1 Length	23.2 In (59 cm)
Package weight(Lbs)	70.81 Lb(US) (32.12 kg)

Environmental data

Recyclability potential, in %	51
Total lifecycle Carbon footprint	1 113 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	841.9909666596
Carbon footprint of the manufacturing phase [A1 to A3]	842 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	20.1145228632
Carbon footprint of the distribution phase [A4]	20 kg CO2 eq.
Carbon footprint of the installation phase [A5]	5.8474389951
Carbon footprint of the installation phase [A5]	6 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	214.1829515949
Carbon footprint of the use phase [B2, B3, B4, B6]	214 kg CO2 eq.
Mercury free	Yes
Sustainable packaging	No
Carbon footprint of the end-of-life phase [C1 to C4]	30.6710527921
Carbon footprint of the end-of-life phase [C1 to C4]	31 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile
Carbon footprint (kg CO2 eq, Total Life cycle)	1113
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
SCIP Number	B2b22a56-41f2-497e-9ea6-cf093b3b8bd3
REACH Regulation	Reference contains Substances of Very High Concern above the threshold View
EU RoHS Directive	Compliant By Exemption View
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which
POP Directive	Contains POPs View
Optimized Energy Efficiency	Energy efficient product

ENERGY STAR®	ENERGY STAR UPS V2.0 (USA)
Circularity Profile	End Of Life Information
Removable battery	User replaceable
Take-back	Yes
WEEE Label	The product must be disposed on European Union markets following specific waste collection and neve

Contractual warranty

Warranty (in months)	24 Battery 36 UPS
----------------------	-------------------

Product Life Status : **Commercialised**