

```
## Loading required package: carData

## Loading required package: zoo

##
## Attaching package: 'zoo'

## The following objects are masked from 'package:base':
##
##      as.Date, as.Date.numeric

##
## Please cite as:

## Hlavac, Marek (2018). stargazer: Well-Formatted Regression and Summary Statistics Tables.

## R package version 5.2.2. https://CRAN.R-project.org/package=stargazer

##
## Attaching package: 'dplyr'

## The following object is masked from 'package:car':
##
##      recode

## The following objects are masked from 'package:stats':
##
##      filter, lag

## The following objects are masked from 'package:base':
##
##      intersect, setdiff, setequal, union

##
## Attaching package: 'reshape2'

## The following object is masked from 'package:tidyr':
##
##      smiths
```

```
#read in the data
#data <- read.csv(file = 'H:/ROL/MIDS/W203 Stats/lab_3/crime_v2.csv') #Robert

data <- read.csv(file = '~/Desktop/W203/w203_lab3-master/crime_v2.csv') #Praveen
```

## 2. A Model Building Process

### Exploratory Data Analysis

We started by conducting exploratory data analysis. First, we read the original paper to get a better understanding of each variable. We defined the variables in the table below and grouped them into five groups in order to get a better handle on them.

```

crime_count <- c(1:25)
data_variables <- c("county", "year", "crm rte", "prbarr", "prbconv", "prbpris", "avg sen", "polpc", "density", "taxpc", "west", "central", "urban", "pctmin80", "wcon", "wtuc", "wtrd", "wfir", "wser", "wmfg", "wfed", "wsta", "wloc", "mix", "pctymle")
data_description <- c("county identifier", "1987", "crimes committed per person", "'probability' of arrest", "'probability' of conviction", "'probability' of prison sentence", "avg. sentence, days", "police per capita", "people per sq. mile", "tax revenue per capita", "=1 if in western N.C.", "=1 if in central N.C.", "=1 if in SMSA", "perc. minority, 1980", "weekly wage, construction", "wkly wge, trns, util, commun", "wkly wge, whlesle, retail trade", "wkly wge, fin, ins, real est", "wkly wge, service industry", "wkly wge, manufacturing", "wkly wge, fed employees", "wkly wge, state employees", "wkly wge, local gov emps", "offense mix: face-to-face/other", "percent young male")
data_group <- c("Control", "", "", "Deterrent", "Deterrent", "Deterrent", "Deterrent", "Deterrent", "Deterrent", "Demographic", "Demographic", "Region", "Region", "Urban", "Demographic", "Wages", "Wages", "Wages", "Wages", "Wages", "Wages", "Wages", "Wages", "Wages", "Wages", "Demographic", "Demographic")
data_notes <- c("", "", "ratio of FBI index crimes to county population", "ratio of arrests to offenses", "ratio of convictions to arrests", "proportion of total convictions resulting in prison sentences", "average sentence in days", "country population divided by county land area", "dummy", "dummy", "dummy", "proportion of country population that is minority or nonwhite", "average weekly wage in that sector", "average weekly wage in that sector", "average weekly wage in that sector", "average weekly wage in that sector", "average weekly wage in that sector", "average weekly wage in that sector", "average weekly wage in that sector", "average weekly wage in that sector", "average weekly wage in that sector", "ratio of face-to-face crimes (robbery, assault, rape) to non-face-to-face crimes", "proportion of country population that is male between 15 and 24")
data_headers <- c("Variable", "Description", "Group", "Note")
data_table <- data.frame(data_variables, data_description, data_group, data_notes)
kable(data_table, col.names = data_headers, caption = "Descriptions and Groups of Variables")

```

Table 1: Descriptions and Groups of Variables

Variable	Description	Group	Note
county	county identifier	Control	
year	1987		
crm rte	crimes committed per person		ratio of FBI index crimes to county population
prbarr	'probability' of arrest	Deterrent	ratio of arrests to offenses
prbconv	'probability' of conviction	Deterrent	ratio of convictions to arrests
prbpris	'probability' of prison sentence	Deterrent	proportion of total convictions resulting in prison sentences
avg sen	avg. sentence, days	Deterrent	average sentence in days
polpc	police per capita	Deterrent	
density	people per sq. mile	Demographic	country population divided by county land area
taxpc	tax revenue per capita	Demographic	
west	=1 if in western N.C.	Region	dummy
central	=1 if in central N.C.	Region	dummy
urban	=1 if in SMSA	Urban	dummy
pctmin80	perc. minority, 1980	Demographic	proportion of country population that is minority or nonwhite
wcon	weekly wage, construction	Wages	average weekly wage in that sector
wtuc	wkly wge, trns, util, commun	Wages	average weekly wage in that sector
wtrd	wkly wge, whlesle, retail trade	Wages	average weekly wage in that sector
wfir	wkly wge, fin, ins, real est	Wages	average weekly wage in that sector
wser	wkly wge, service industry	Wages	average weekly wage in that sector
wmfg	wkly wge, manufacturing	Wages	average weekly wage in that sector
wfed	wkly wge, fed employees	Wages	average weekly wage in that sector
wsta	wkly wge, state employees	Wages	average weekly wage in that sector
wloc	wkly wge, local gov emps	Wages	average weekly wage in that sector
mix	offense mix: face-to-face/other	Demographic	ratio of face-to-face crimes (robbery, assault, rape) to non-face-to-face crimes
pctymle	percent young male	Demographic	proportion of country population that is male between 15 and 24

To get a better sense of the data set the summary function was run.

```
summary(data)
```

```

##      county      year      crm rte      prbarr
##  Min.   : 1.0    Min.   :87    Min.   :0.005533   Min.   :0.09277
##  1st Qu.: 52.0   1st Qu.:87    1st Qu.:0.020927   1st Qu.:0.20568
##  Median :105.0   Median :87    Median :0.029986   Median :0.27095
##  Mean   :101.6   Mean   :87    Mean   :0.033400   Mean   :0.29492
##  3rd Qu.:152.0   3rd Qu.:87    3rd Qu.:0.039642   3rd Qu.:0.34438
##  Max.   :197.0   Max.   :87    Max.   :0.098966   Max.   :1.09091
##  NA's   :6      NA's   :6      NA's   :6         NA's   :6

```

```

##          prbconv          prbpris          avgsen          polpc
##              : 5      Min.      :0.1500      Min.      : 5.380      Min.      :0.000746
## 0.588859022: 2      1st Qu.:0.3648      1st Qu.: 7.340      1st Qu.:0.001231
## `          : 1      Median :0.4234      Median : 9.100      Median :0.001485
## 0.068376102: 1      Mean     :0.4108      Mean     : 9.647      Mean     :0.001702
## 0.140350997: 1      3rd Qu.:0.4568      3rd Qu.:11.420      3rd Qu.:0.001877
## 0.154451996: 1      Max.      :0.6000      Max.      :20.700      Max.      :0.009054
## (Other)      :86      NA's      :6          NA's      :6          NA's      :6
##          density          taxpc          west          central
## Min.      :0.00002      Min.      : 25.69      Min.      :0.0000      Min.      :0.0000
## 1st Qu.:0.54741      1st Qu.: 30.66      1st Qu.:0.0000      1st Qu.:0.0000
## Median :0.96226      Median : 34.87      Median :0.0000      Median :0.0000
## Mean     :1.42884      Mean     : 38.06      Mean     :0.2527      Mean     :0.3736
## 3rd Qu.:1.56824      3rd Qu.: 40.95      3rd Qu.:0.5000      3rd Qu.:1.0000
## Max.      :8.82765      Max.      :119.76      Max.      :1.0000      Max.      :1.0000
## NA's      :6          NA's      :6          NA's      :6          NA's      :6
##          urban          pctmin80          wcon          wtuc
## Min.      :0.00000      Min.      : 1.284      Min.      :193.6      Min.      :187.6
## 1st Qu.:0.00000      1st Qu.: 9.845      1st Qu.:250.8      1st Qu.:374.6
## Median :0.00000      Median :24.312      Median :281.4      Median :406.5
## Mean     :0.08791      Mean     :25.495      Mean     :285.4      Mean     :411.7
## 3rd Qu.:0.00000      3rd Qu.:38.142      3rd Qu.:314.8      3rd Qu.:443.4
## Max.      :1.00000      Max.      :64.348      Max.      :436.8      Max.      :613.2
## NA's      :6          NA's      :6          NA's      :6          NA's      :6
##          wtrd          wfir          wser          wmfgr
## Min.      :154.2      Min.      :170.9      Min.      : 133.0      Min.      :157.4
## 1st Qu.:190.9      1st Qu.:286.5      1st Qu.: 229.7      1st Qu.:288.9
## Median :203.0      Median :317.3      Median : 253.2      Median :320.2
## Mean     :211.6      Mean     :322.1      Mean     : 275.6      Mean     :335.6
## 3rd Qu.:225.1      3rd Qu.:345.4      3rd Qu.: 280.5      3rd Qu.:359.6
## Max.      :354.7      Max.      :509.5      Max.      :2177.1      Max.      :646.9
## NA's      :6          NA's      :6          NA's      :6          NA's      :6
##          wfed          wsta          wloc          mix
## Min.      :326.1      Min.      :258.3      Min.      :239.2      Min.      :0.01961
## 1st Qu.:400.2      1st Qu.:329.3      1st Qu.:297.3      1st Qu.:0.08074
## Median :449.8      Median :357.7      Median :308.1      Median :0.10186
## Mean     :442.9      Mean     :357.5      Mean     :312.7      Mean     :0.12884
## 3rd Qu.:478.0      3rd Qu.:382.6      3rd Qu.:329.2      3rd Qu.:0.15175
## Max.      :598.0      Max.      :499.6      Max.      :388.1      Max.      :0.46512
## NA's      :6          NA's      :6          NA's      :6          NA's      :6
##          pctymle
## Min.      :0.06216
## 1st Qu.:0.07443
## Median :0.07771
## Mean     :0.08396
## 3rd Qu.:0.08350
## Max.      :0.24871
## NA's      :6

```

This function provides a high level view of each variable. Six rows have missing values for all variables. In addition, there is one duplicate row. Also the variable prbconv is loaded as a factor, so it needs to be converted to numeric. These issues are handled below to create the initial data set.

```

#eliminate N/A's
data_crmrte <- data[!is.na(data$crmrte),]

#remove duplicates
data_crmrte <- data_crmrte %>% distinct()

#make prbconv numeric
data_crmrte$prbconv <- as.numeric(as.character(data_crmrte$prbconv))

```

With 25 original variables in the data set the natural place to start is with the dependent variable, crmrte. To get a better sense of this variable, the distribution is graphed below.


```
quantile(data_crmrte$crmrate, c(0, .01, .05, .10, .25, .50, .75, .90, .95, .99, 1.0))
```

```

##          0%          1%          5%          10%          25%          50%          75%
## 0.00553320 0.01006330 0.01235660 0.01418007 0.02060425 0.03000200 0.04024925
##          90%          95%          99%         100%
## 0.06054659 0.07191830 0.08954881 0.09896590


```

```
hist(data_crmrte$crmrate,breaks=20)
```




```
boxplot(data_crmrte$crmrate, main="Boxplot of crmrte")
```


**Boxplot of cmrte**



```
plot(data_cmrte$cmrte)
```



```
qqnorm(data_crmrte$crmrite)
```



There are several outliers in the variable `crmte` and the distribution is right skewed. We have ninety observations so perhaps we normality is not a top concern but this distribution is not perfectly normal. The largest outliers on the right side of the distribution are examined. Unfortunately, looking at these observations in a dataframe does not show any obvious patterns (e.g. they are all in the same region, they all have similar values of a variable like density, etc.)


```
data_crmte[data_crmte$crmte > 0.065,]
```

##	county	year	crmte	prbarr	prbconv	prbpris	avgsen	polpc	density
## 23	51	87	0.0883849	0.155248	0.259833	0.407628	11.93	0.00190802	3.9345510
## 25	55	87	0.0790163	0.224628	0.207831	0.304348	13.57	0.00400962	0.5115089
## 29	63	87	0.0706599	0.133225	0.459216	0.363636	11.51	0.00237609	5.6744967
## 30	65	87	0.0658801	0.287330	0.154452	0.403922	9.84	0.00185739	1.1679842
## 53	119	87	0.0989659	0.149094	0.347800	0.486183	7.13	0.00223135	8.8276520
## 57	129	87	0.0834982	0.236601	0.393413	0.415158	9.57	0.00255849	6.2864866
## 82	181	87	0.0729479	0.182590	0.343023	0.548023	7.06	0.00172948	1.5702811
##	taxpc	west	central	urban	pctmin80	wcon	wtuc	wtrd	wfir
## 23	35.69936	0	0	1	37.77920	283.6695	412.4720	213.7524	324.8357
## 25	119.76145	0	0	0	6.49622	309.5238	445.2762	189.7436	284.5933
## 29	50.19918	0	1	1	38.22300	349.3267	548.9865	238.9154	435.1107
## 30	30.62824	0	0	0	51.69320	362.1527	540.1061	209.0579	316.2955
## 53	75.67243	0	1	1	28.54600	436.7666	548.3239	354.6761	509.4655
## 57	67.67963	0	0	1	23.04410	315.5760	392.0999	220.4530	363.2880
## 82	27.59179	0	1	0	44.62830	244.8362	365.4716	279.2273	325.0271
##	wser	wmfg	wfed	wsta	wloc	mix	pctymle		
## 23	257.3344	441.72	433.94	367.34	333.71	0.10474319	0.14223780		

```
## 25 221.3903 319.21 338.91 361.68 326.08 0.08437271 0.07613807
## 29 391.3081 646.85 563.77 415.51 362.58 0.07585382 0.09468981
## 30 216.4589 313.71 543.03 348.88 329.16 0.09364294 0.07622346
## 53 354.3007 494.30 568.40 329.22 379.77 0.16869897 0.07916495
## 57 292.7027 464.49 548.49 421.36 319.08 0.07871422 0.08109921
## 82 213.5822 290.69 453.53 317.23 286.45 0.10003893 0.07977433
```

For campaign purposes, we want to predict crime. We want our candidate to be able to say that he or she can reduce crime in order to win votes. What is the most effective way to convey that? Using crime rate as it appears in the data set is using the level of crime rate and would suggest the following statement as a campaign slogan - “I can reduce crime to this rate by doing x, y, and z”. Transforming crime rate into the log of crime rate allows for the statement “I can reduce crime by n% by doing x, y, and z.” We find the latter more powerful and meaningful to voters since voters have no idea about the level of crime rates. In addition, we will show that the transformation of crime rate improves the normality and distribution of the variable, which will often reduce skew in the errors as well.


```
data_crmrte$log_crmrte <- log(data_crmrte$crmrate)
hist(data_crmrte$log_crmrte,breaks=20)
```




```
boxplot(data_crmrte$log_crmrte, main="Boxplot of log of crmrte")
```




**Boxplot of log of crmrte**



```
plot(data_crmrte$log_crmrte)
```



```
qqnorm(data_crmrte$log_crmrte)
```



The histogram of the transformed crime rate is much more symmetrical and shows much less right skew. The box plot shows all of the outliers on the high end have been removed, though one outlier on the low end has been introduced. The scatter plot looks much more normal, and the Q-Q plot is much closer to normal with the data points hugging the 45 degree line much more closely. Given the stronger argument for the political campaign and the benefits to normality we have chosen to model the transformation of crime rate as opposed to crime rate.

### Groupings


In order to digest the data in the data set we decided to group the variables into five groups: deterrent, wages, demographic, region, and urban. We performed exploratory data analysis on all of these variables.

The group is deterrent data. As cited in the original paper, these variables were hypothesized to reduce crime rate through disincentivizing crime. Essentially, as the probability of getting caught increases, criminals' desire to commit crimes decreases.

### Deterrent Data

```
deterrent_data <- data_crmrte[,c('prbarr', 'prbconv', 'prbpris', 'crmrate',
                                'avgsen', 'polpc')]


ggplot(gather(deterrent_data[,c('prbarr', 'prbconv', 'prbpris',
                                'avgsen', 'polpc')]), aes(value)) +
geom_histogram(bins = 10) + facet_wrap(~key, scales = 'free_x')
```



```
my_vars1 <- c("prbarr","prbconv","prbpris")
deterrent_data2 <- deterrent_data[my_vars1]
my_vars2 <- c("polpc")
deterrent_data3 <- deterrent_data[my_vars2]


boxplot(deterrent_data2, main="Boxplot of prbarr, prbconv, prbpris")
```

**Boxplot of prbarr, prbconv, prbpris**




```
boxplot(deterrent_data3, main="Boxplot of polpc")
```

## Boxplot of polpc



```
boxplot(deterrent_data$avgsen, main="Boxplot of avgsen")
```

## Boxplot of avgsen




The first four histograms show right skew while prbpris shows left skew. The biggest outlier is observation 51. This observation has the lowest crime rate in the data set, obviously the highest polpc (police per capita), the highest avg sentence, the third highest prbconv, and the lowest pctmin80. This observation is likely to affect many of the regressions so it will need to be examined further. These variables are candidates to be transformed.

## Wages Data


```
#create a dataframe of just the wage variables
wages_data <- data_crmrte[,c('wcon','wtuc','wtrd','wfir', 'wser',
                             'wmfg','wfed', 'wsta', 'wloc')]

#plot histograms of just the wage variables
ggplot(gather(wages_data), aes(value)) +
  geom_histogram(bins = 10) +
  facet_wrap(~key, scales = 'free_x')
```



```
#generate boxplots of just the wage variables
boxplot(wages_data)
```






There is an obvious outlier in wser. This seems like a typo. The next highest average weekly wage in any sector is 646 versus the value of 2177. If you take the average of all weekly wages it has the highest average but only the 24th highest taxpc (though tax revenue is driven largely by sales and property taxes, many areas have local income tax as well. It is very possible that it is an error but we will revisit this later. For now, we create an additional variable that is the median of all wage variables for each observation. If it conveys as much information, it has the benefit of increasing our degrees of freedom and removing the effect of the outlier.

```
data_crmrte$median_wage <- apply(data_crmrte[c("wcon", "wtuc", "wtrd",
                                                "wfir", "wser", "wmfg",
                                                "wfed", "wsta", "wloc")],
                                1, FUN=median, na.rm=TRUE)
```

Region Data\_\_

```
#create a dataframe of just the wage variables
dummies_data <- data_crmrte[,c('west', 'central')]

#plot histograms of just the dummy variables
ggplot(gather(dummies_data), aes(value)) +
  geom_histogram(bins = 2) +
  facet_wrap(~key)
```




```
#just a quick check that there is no overlap
region_check <- data_crmrte[which(data_crmrte$west == 1 && data_crmrte$central == 1)]
```

The regions are broken up into central, west, and east. East is left out of the data set and its effect as the final level of the indicator variable will move to the intercept.

## Urban Data

```
#plot histograms of just the wage variables
hist(data_crmrte$urban)
```

## Histogram of data\_crmrte\$urban




Urban did not fit into a great grouping so we left this variable on its own. A histogram shows that the state has relatively few urban counties, something to keep in mind when analyzing other variables such as density.


## Demographic Data

```
#create a dataframe of just the demographic variables
demographic_data <- data_crmrte[,c('density', 'taxpc', 'pctmin80',
                                   'mix', 'pctymle')]


#plot histograms of just the demographic variables
ggplot(gather(demographic_data), aes(value)) +
  geom_histogram(bins = 10) +
  facet_wrap(~key, scales = 'free_x')
```




```
#Lots of skewed distributions above, particularly in pctymle and taxpc
#generate boxplots of just the demographic variables
demographic_data2 <- demographic_data[c("taxpc", "pctmin80")]
boxplot(demographic_data2)
```




```
demographic_data3 <- demographic_data[c("pctymle")]  
boxplot(demographic_data3)
```



```
demographic_data4 <- demographic_data[c("density")]  
boxplot(demographic_data4)
```



```
demographic_data5 <- demographic_data[c("mix")]  
boxplot(demographic_data5)
```




Once again we see a lot of right skewed distributions in the histograms and in the box plots.

After exploring all of the variables we decided to transform the other variables that are potentially under a politician's control - the deterrent variables. This gives us our final data set and so we can start running regressions.

```
data_crmrte$prbconv <- as.numeric(as.character(data_crmrte$prbconv))
data_crmrte$log_prbarr <- log(data_crmrte$prbarr)
data_crmrte$log_prbconv <- log(data_crmrte$prbconv)
data_crmrte$log_prbpris <- log(data_crmrte$prbpris)
data_crmrte$log_avgsen <- log(data_crmrte$avgsen)
data_crmrte$log_polpc <- log(data_crmrte$polpc)
data_crmrte$log_taxpc <- log(data_crmrte$taxpc)

#plot histograms of just the demographic variables
ggplot(gather(data_crmrte[,c('log_prbarr', 'log_prbconv', 'log_prbpris', 'log_avgsen', 'log_polpc', 'log_taxpc')],
  geom_histogram(bins = 10) +
  facet_wrap(~key, scales = 'free_x')
```





Though the distribution of the variables still exhibits skew, the skew does seem to be reduced.

### Log Tranformed Dependent Variable Comparison

In order to settle on the final data set we compare an all-in log-log model with an all-in log-linear to see which dependent variables are more suitable.

```
##### Initial Models #####
all_in_model <- lm(crmrte ~ prbarr + prbconv + prbpris
  + avgsen + polpc + density
  + taxpc + west + central + urban + pctmin80 + wcon
  + wtuc + wtrd + wfir + wser + wmfg
  + wfed + wsta + wloc
  + mix + pctymle,
  data = data_crmrte)
se.all_in_model = sqrt(diag(vcovHC(all_in_model)))
coeftest(all_in_model, vcov = vcovHC)
```

```
##
## t test of coefficients:
##
##           Estimate Std. Error t value Pr(>|t|)
## (Intercept) 1.3853e-02 3.0755e-02  0.4504 0.6538622
## prbarr      -5.1466e-02 1.5689e-02 -3.2805 0.0016467 **
## prbconv     -1.8633e-02 6.5853e-03 -2.8295 0.0061464 **
```

```
## prbpris      3.1727e-03  1.3586e-02  0.2335 0.8160642
## avgsen      -3.9858e-04  5.5361e-04 -0.7200 0.4740570
## polpc       6.9679e+00  2.9536e+00  2.3591 0.0212406 *
## density     5.3314e-03  1.4895e-03  3.5793 0.0006464 ***
## taxpc       1.6240e-04  2.8408e-04  0.5717 0.5694537
## west        -2.5652e-03  4.4698e-03 -0.5739 0.5679579
## central     -4.2416e-03  3.7423e-03 -1.1334 0.2610725
## urban       -9.6498e-05  8.2752e-03 -0.0117 0.9907307
## pctmin80    3.2542e-04  1.3849e-04  2.3497 0.0217429 *
## wcon        2.3025e-05  3.2876e-05  0.7004 0.4861334
## wtuc        6.1914e-06  1.9862e-05  0.3117 0.7562178
## wtrd        2.8767e-05  8.7294e-05  0.3295 0.7427756
## wfir        -3.5455e-05  3.5699e-05 -0.9932 0.3242068
## wser        -1.7158e-06  9.9447e-05 -0.0173 0.9862856
## wmfg        -8.9675e-06  1.7469e-05 -0.5133 0.6094087
## wfed        2.9075e-05  3.7780e-05  0.7696 0.4442480
## wsta        -2.2302e-05  3.6828e-05 -0.6056 0.5468431
## wloc        1.4456e-05  8.5367e-05  0.1693 0.8660410
## mix         -1.8693e-02  2.2922e-02 -0.8155 0.4176761
## pctymle     1.0125e-01  4.7826e-02  2.1170 0.0379748 *
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
```

```
AIC(all_in_model, k=2)
```

```
## [1] -585.5858
```

```
all_in_model_log_level <- lm(log_crmrte ~ prbarr + prbconv + prbpris
+ avgsen + polpc + density
+ taxpc + west + central + urban
+ pctmin80 + wcon
+ wtuc + wtrd + wfir + wser + wmfg
+ wfed + wsta + wloc
+ mix + pctymle,
data = data_crmrte)
se.all_in_model_log_level = sqrt(diag(vcovHC(all_in_model_log_level)))
coeftest(all_in_model_log_level, vcov = vcovHC)
```

```
##
## t test of coefficients:
##
##           Estimate Std. Error t value Pr(>|t|)
## (Intercept) -4.0261e+00 8.4822e-01 -4.7466 1.128e-05 ***
## prbarr      -1.8891e+00 3.7955e-01 -4.9773 4.770e-06 ***
## prbconv     -6.5603e-01 1.7443e-01 -3.7611 0.0003579 ***
## prbpris     -9.3077e-02 3.9921e-01 -0.2332 0.8163542
## avgsen      -7.8769e-03 1.6125e-02 -0.4885 0.6267962
## polpc       1.5484e+02 8.6523e+01  1.7895 0.0780510 .
## density     1.1653e-01 5.4037e-02  2.1566 0.0346326 *
## taxpc       3.3224e-03 7.2890e-03  0.4558 0.6500012
## west        -1.1492e-01 1.2509e-01 -0.9187 0.3615403
## central     -1.0078e-01 9.2053e-02 -1.0948 0.2775232
## urban       -1.6923e-01 2.2872e-01 -0.7399 0.4619535
```

```
## pctmin80      9.9770e-03  3.0480e-03  3.2733 0.0016833 **
## wcon          4.6001e-04  8.3564e-04  0.5505 0.5838140
## wtuc          1.0174e-04  6.0187e-04  0.1690 0.8662750
## wtrd          2.5964e-04  1.7638e-03  0.1472 0.8834136
## wfir         -1.1015e-03  1.1960e-03 -0.9210 0.3603557
## wser         -1.3142e-04  1.5060e-03 -0.0873 0.9307193
## wmfg         -2.0528e-04  5.1630e-04 -0.3976 0.6921878
## wfed          2.3405e-03  1.0820e-03  2.1632 0.0340968 *
## wsta         -1.1357e-03  8.9769e-04 -1.2651 0.2102213
## wloc          5.8983e-04  2.4003e-03  0.2457 0.8066400
## mix          -2.3924e-01  6.2632e-01 -0.3820 0.7036869
## pctymle       2.7706e+00  1.4330e+00  1.9334 0.0574191 .
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
```

```
AIC(all_in_model_log_level, k=2)
```

```
## [1] 21.354
```

```
all_in_model_log_log <- lm(log_crmrte ~ log_prbarr + log_prbconv
+ log_prbpris + log_avgsen + log_polpc
+ density+ log_taxpc + west + central
+ urban + pctmin80 + wcon
+ wtuc + wtrd + wfir
+ wser + wmfg + wfed + wsta + wloc
+ mix + pctymle,
data = data_crmrte)
se.all_in_model_log_log = sqrt(diag(vcovHC(all_in_model_log_log)))
coeftest(all_in_model_log_log, vcov = vcovHC)
```

```
##
## t test of coefficients:
##
##              Estimate Std. Error t value Pr(>|t|)
## (Intercept) -3.36882669  2.97497990 -1.1324 0.261508
## log_prbarr   -0.52143620  0.16459898 -3.1679 0.002313 **
## log_prbconv  -0.33101341  0.15365522 -2.1543 0.034820 *
## log_prbpris  -0.06569465  0.19741379 -0.3328 0.740342
## log_avgsen   -0.19652151  0.18205821 -1.0794 0.284261
## log_polpc     0.29132794  0.27176129  1.0720 0.287567
## density       0.12320127  0.06040422  2.0396 0.045335 *
## log_taxpc     0.06158051  0.30979897  0.1988 0.843040
## west         -0.18453792  0.16353910 -1.1284 0.263174
## central       -0.10789292  0.09991865 -1.0798 0.284100
## urban         -0.14767055  0.26670745 -0.5537 0.581641
## pctmin80      0.00956927  0.00358175  2.6717 0.009466 **
## wcon          0.00078953  0.00090745  0.8701 0.387376
## wtuc          0.00010106  0.00075559  0.1337 0.894001
## wtrd          0.00029022  0.00177967  0.1631 0.870952
## wfir         -0.00108230  0.00125937 -0.8594 0.393186
## wser         -0.00042887  0.00096365 -0.4451 0.657718
## wmfg         -0.00014147  0.00061356 -0.2306 0.818343
## wfed          0.00224918  0.00136611  1.6464 0.104363
```

```
## wsta      -0.00102039  0.00106131 -0.9614 0.339787
## wloc       0.00017815  0.00261968  0.0680 0.945986
## mix       -0.44834658  0.77846459 -0.5759 0.566587
## pctymle    2.00755501  2.60186976  0.7716 0.443075
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
```

```
AIC(all_in_model_log_log, k=2)
```

```
## [1] 44.17803
```

```
#Not comparing r-squared, just looking at significant variables
stargazer(all_in_model, all_in_model_log_level,
  all_in_model_log_log,
  type = "text", omit.stat = "f",
  se = list(se.all_in_model, se.all_in_model_log_level,
    se.all_in_model_log_log),
  star.cutoffs = c(0.05, 0.01, 0.001))
```

```
##
## =====
##                               Dependent variable:
##                               -----
##                               crmrte      log_crmrte
##                               (1)         (2)         (3)
## -----
## prbarr      -0.051**  -1.889***
##              (0.016)   (0.380)
##
## prbconv     -0.019**  -0.656***
##              (0.007)   (0.174)
##
## prbpris      0.003    -0.093
##              (0.014)   (0.399)
##
## avgsen      -0.0004   -0.008
##              (0.001)   (0.016)
##
## polpc        6.968*   154.835
##              (2.954)   (86.523)
##
## log_prbarr                                -0.521**
##                                              (0.165)
##
## log_prbconv                                -0.331*
##                                              (0.154)
##
## log_prbpris                                -0.066
##                                              (0.197)
##
## log_avgsen                                -0.197
##                                              (0.182)
##
```

## log_polpc			0.291
##			(0.272)
##			
## density	0.005***	0.117*	0.123*
##	(0.001)	(0.054)	(0.060)
##			
## taxpc	0.0002	0.003	
##	(0.0003)	(0.007)	
##			
## log_taxpc			0.062
##			(0.310)
##			
## west	-0.003	-0.115	-0.185
##	(0.004)	(0.125)	(0.164)
##			
## central	-0.004	-0.101	-0.108
##	(0.004)	(0.092)	(0.100)
##			
## urban	-0.0001	-0.169	-0.148
##	(0.008)	(0.229)	(0.267)
##			
## pctmin80	0.0003*	0.010**	0.010**
##	(0.0001)	(0.003)	(0.004)
##			
## wcon	0.00002	0.0005	0.001
##	(0.00003)	(0.001)	(0.001)
##			
## wtuc	0.00001	0.0001	0.0001
##	(0.00002)	(0.001)	(0.001)
##			
## wtrd	0.00003	0.0003	0.0003
##	(0.0001)	(0.002)	(0.002)
##			
## wfir	-0.00004	-0.001	-0.001
##	(0.00004)	(0.001)	(0.001)
##			
## wser	-0.00000	-0.0001	-0.0004
##	(0.0001)	(0.002)	(0.001)
##			
## wmfg	-0.00001	-0.0002	-0.0001
##	(0.00002)	(0.001)	(0.001)
##			
## wfed	0.00003	0.002*	0.002
##	(0.00004)	(0.001)	(0.001)
##			
## wsta	-0.00002	-0.001	-0.001
##	(0.00004)	(0.001)	(0.001)
##			
## wloc	0.00001	0.001	0.0002
##	(0.0001)	(0.002)	(0.003)
##			
## mix	-0.019	-0.239	-0.448
##	(0.023)	(0.626)	(0.778)
##			

```
## pctymle          0.101*      2.771      2.008
##                (0.048)    (1.433)    (2.602)
##
## Constant         0.014     -4.026***   -3.369
##                (0.031)    (0.848)    (2.975)
##
## -----
## Observations      90        90        90
## R2                0.855      0.854      0.812
## Adjusted R2       0.807      0.806      0.750
## Residual Std. Error (df = 67) 0.008      0.242      0.275
## =====
## Note:              *p<0.05; **p<0.01; ***p<0.001
```

```
# #r-squared comparison of final two models
# yhat_level_level <- predict(all_in_model)
#
# #get the coefficients
# for (b in coef(all_in_model_log_level))
# {
#   beta_log_level <- c(beta_log_level, b)
# }
# #calculate the predictions
# for (b in coef(all_in_model_log_level))
# {
#   beta_log_level <- c(beta_log_level, b)
# }
#
# data_crmrte$log_level_yhat <- exp(--3.36882669
#
#   -0.5214362*data_crmrte$log_prbarr
#
#   -0.33101341*data_crmrte$log_prbconv
#
#   -0.06569465*data_crmrte$log_prbpris
#
#   -0.19652151*data_crmrte$log_avgsen
#
#   +0.29132794*data_crmrte$log_polpc
#
#   +0.12320127*data_crmrte$density
#
#   +0.06158051*data_crmrte$log_taxpc
#
#   -0.18453792*data_crmrte$west
#
#   -0.10789292*data_crmrte$central
#
#   -0.14767055*data_crmrte$urban
#
#   +0.00956927*data_crmrte$pctmin80
#
#   +0.00078953*data_crmrte$wcon
#
#   +0.00010106*data_crmrte$wtuc
#
#   +0.00029022*data_crmrte$wtrd
#
#   -0.0010823*data_crmrte$wfir
#
#   -0.00042887*data_crmrte$user
#
#   -0.00014147*data_crmrte$wumfg
#
#   +0.00224918*data_crmrte$wfed
#
#   -0.00102039*data_crmrte$wsta
#
#   +0.00017815*data_crmrte$wloc
#
#   -0.44834658*data_crmrte$mix
#
#   +2.00755501*data_crmrte$pctymle
# )
# r_squared_level_level <- cor(data_crmrte$crmte, yhat_level_level)
# r_squared_log_level <- cor(data_crmrte$crmte, data_crmrte$log_level_yhat)
```

```
# (r_squared_level_level)
# (r_squared_log_level)
```

## Model 1: Simple Model

In order to create a simple model we decided to build using a bottom up approach. We looked at a correlation matrix

```
#Anyone know how to print this better?
cor(data_crmrte$log_crmrte,data_crmrte)
```

```
## Warning in cor(data_crmrte$log_crmrte, data_crmrte): the standard deviation is
## zero
```

```
##      county year   crmrte   prbarr   prbconv   prbpris   avgsen
## [1,] 0.02376789   NA 0.9415465 -0.4727669 -0.4468136 0.02147024 -0.04936931
##      polpc  density   taxpc      west   central   urban  pctmin80
## [1,] 0.0104058 0.6330234 0.3583234 -0.4143996 0.1847192 0.4914645 0.2329182
##      wcon   wtuc   wtrd   wfir   wser   wmfg   wfed
## [1,] 0.3937149 0.2014649 0.3937924 0.2932426 -0.113128 0.3075373 0.5233058
##      wsta   wloc   mix   pctymle log_crmrte median_wage log_prbarr
## [1,] 0.1697021 0.2885668 -0.1247344 0.2781547      1      0.454422 -0.4357539
##      log_prbconv log_prbpris log_avgsen log_polpc log_taxpc
## [1,] -0.3724961 0.06960729 0.02341717 0.2845396 0.3398432
```

/ In the above correlation matrix, focusing on the correlations between the log\_crmrte and all other variables, density has the highest correlation. This variable makes intuitive sense. As a single variable it might encompass a lot of other factors. Lower income people with more incentive to commit crimes tend to live in more highly populated areas. Below is the simple regression.

```
simple_regression_model <- lm(log_crmrte ~ density, data = data_crmrte)
se.simple_regression_model = sqrt(diag(vcovHC(simple_regression_model)))
coeftest(simple_regression_model, vcov = vcovHC)
```

```
##
## t test of coefficients:
##
##      Estimate Std. Error  t value Pr(>|t|)
## (Intercept) -3.869488    0.068563 -56.4366 < 2e-16 ***
## density      0.228298    0.030439   7.5003 4.8e-11 ***
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
```


```
AIC(simple_regression_model, k=2)
```

```
## [1] 106.2991
```


```
stargazer(simple_regression_model,
  type = "text", omit.stat = "f",
  se = list(se.simple_regression_model),
  star.cutoffs = c(0.05, 0.01, 0.001))
```


```
##
## =====
##                               Dependent variable:
##                               -----
##                               log_crmrte
## -----
## density                      0.228***
##                               (0.030)
##
## Constant                    -3.869***
##                               (0.069)
## -----
## Observations                 90
## R2                          0.401
## Adjusted R2                 0.394
## Residual Std. Error         0.427 (df = 88)
## =====
## Note:                       *p<0.05; **p<0.01; ***p<0.001
```


```
plot(simple_regression_model)
```











The variable density explains 40.1% of the variation in the log of crime rate. As density increases by 1 unit (as the county population divided by the county land area increases by 1%) crime increases by 22%. The residuals vs. fitted plot indicates that the zero conditional mean assumption is violated. The Q-Q plot shows that the residuals are normally distributed, and the residuals vs leverage plot shows that there are no influential outliers.

### Model 3: Kitchen Sink Model

Still, we can do better in predicting the log crime rate than simply using one variable. We now examine a “kitchen sink” model. This model includes all of the variables in the data set except county (which has too many values to be a useful indicator variable) and year, which is a constant (1987). Below are the results.

```
all_in_model_log_level <- lm(log_crmrte ~ prbarr + prbconv + prbpris
+ avgsen + polpc + density
+ taxpc + west + central + urban
+ pctmin80 + wcon
+ wtuc + wtrd + wfir + wser + wmfg
+ wfed + wsta + wloc
+ mix + pctymle,
data = data_crmrte)
se.all_in_model_log_level = sqrt(diag(vcovHC(all_in_model_log_level)))
coeftest(all_in_model_log_level, vcov = vcovHC)
```

```
##
## t test of coefficients:
##
```

```
##           Estimate Std. Error t value Pr(>|t|)
## (Intercept) -4.0261e+00 8.4822e-01 -4.7466 1.128e-05 ***
## prbarr      -1.8891e+00 3.7955e-01 -4.9773 4.770e-06 ***
## prbconv     -6.5603e-01 1.7443e-01 -3.7611 0.0003579 ***
## prbpris     -9.3077e-02 3.9921e-01 -0.2332 0.8163542
## avgssen     -7.8769e-03 1.6125e-02 -0.4885 0.6267962
## polpc       1.5484e+02 8.6523e+01 1.7895 0.0780510 .
## density     1.1653e-01 5.4037e-02 2.1566 0.0346326 *
## taxp       3.3224e-03 7.2890e-03 0.4558 0.6500012
## west        -1.1492e-01 1.2509e-01 -0.9187 0.3615403
## central     -1.0078e-01 9.2053e-02 -1.0948 0.2775232
## urban       -1.6923e-01 2.2872e-01 -0.7399 0.4619535
## pctmin80     9.9770e-03 3.0480e-03 3.2733 0.0016833 **
## wcon        4.6001e-04 8.3564e-04 0.5505 0.5838140
## wtuc        1.0174e-04 6.0187e-04 0.1690 0.8662750
## wtrd        2.5964e-04 1.7638e-03 0.1472 0.8834136
## wfir        -1.1015e-03 1.1960e-03 -0.9210 0.3603557
## wser        -1.3142e-04 1.5060e-03 -0.0873 0.9307193
## wmfg        -2.0528e-04 5.1630e-04 -0.3976 0.6921878
## wfed        2.3405e-03 1.0820e-03 2.1632 0.0340968 *
## wsta        -1.1357e-03 8.9769e-04 -1.2651 0.2102213
## wloc        5.8983e-04 2.4003e-03 0.2457 0.8066400
## mix         -2.3924e-01 6.2632e-01 -0.3820 0.7036869
## pctymle     2.7706e+00 1.4330e+00 1.9334 0.0574191 .
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
```

```
AIC(all_in_model_log_level, k=2)
```

```
## [1] 21.354
```

```
stargazer(simple_regression_model, all_in_model_log_level,
  type = "text", omit.stat = "f",
  se = list(se.simple_regression_model, se.all_in_model_log_level),
  star.cutoffs = c(0.05, 0.01, 0.001))
```

```
##
## =====
##                               Dependent variable:
##                               -----
##                               log_crmrte
##                               (1)         (2)
## -----
## prbarr                               -1.889***
##                               (0.380)
##
## prbconv                              -0.656***
##                               (0.174)
##
## prbpris                              -0.093
##                               (0.399)
##
## avgssen                              -0.008
```

##		(0.016)
##		
## polpc		154.835
##		(86.523)
##		
## density	0.228***	0.117*
##	(0.030)	(0.054)
##		
## taxpc		0.003
##		(0.007)
##		
## west		-0.115
##		(0.125)
##		
## central		-0.101
##		(0.092)
##		
## urban		-0.169
##		(0.229)
##		
## pctmin80		0.010**
##		(0.003)
##		
## wcon		0.0005
##		(0.001)
##		
## wtuc		0.0001
##		(0.001)
##		
## wtrd		0.0003
##		(0.002)
##		
## wfir		-0.001
##		(0.001)
##		
## wser		-0.0001
##		(0.002)
##		
## wmfg		-0.0002
##		(0.001)
##		
## wfed		0.002*
##		(0.001)
##		
## wsta		-0.001
##		(0.001)
##		
## wloc		0.001
##		(0.002)
##		
## mix		-0.239
##		(0.626)
##		
## pctymle		2.771

```
##                                     (1.433)
##
## Constant          -3.869***      -4.026***
##                   (0.069)        (0.848)
##
## -----
## Observations           90          90
## R2                     0.401        0.854
## Adjusted R2            0.394        0.806
## Residual Std. Error 0.427 (df = 88) 0.242 (df = 67)
## =====
## Note:                *p<0.05; **p<0.01; ***p<0.001
```

Unsurprisingly, the r-squared of the “kitchen sink” model is substantially higher (85.4% vs. 40.1%). More importantly, the adjusted r-squared which accounts for the number of variables in the models, is also higher (80.6% vs 39.4%). Interestingly, density is no longer the variable with the highest statistical significance. The coefficients show the effect after all the other variables have been controlled for (partialled out). In the “kitchen sink” model prbarr and prbconv both have the lowest p-values.

## Model 2: Balanced Model

We took two approaches to building the balanced model. We used a bottom up approach that relied on both the correlation matrix and stepwise regression. We also used a top down approach that started with the “kitchen sink” model and excluded variables. Both methods are discussed below. Both approaches relied on our categories of variables to simplify the process.

```
base_forward = lm(log_crmrte ~ density,
                  data = data_crmrte)
forward_step = step(base_forward, scope = formula(all_in_model_log_level), direction = "forward")
```

```
## Start: AIC=-151.11
## log_crmrte ~ density
##
##           Df Sum of Sq  RSS    AIC
## + west      1   2.94477 13.116 -167.34
## + prbconv    1   2.59934 13.461 -165.00
## + prbarr     1   2.33206 13.729 -163.23
## + pctmin80   1   2.11480 13.946 -161.82
## + pctymle    1   1.14375 14.917 -155.76
## + wfed       1   0.92973 15.131 -154.48
## + taxpc      1   0.72379 15.337 -153.26
## + wser       1   0.53323 15.527 -152.15
## + wcon       1   0.38803 15.672 -151.31
## <none>              16.061 -151.11
## + avgse      1   0.24653 15.814 -150.50
## + polpc      1   0.22427 15.836 -150.38
## + wfir       1   0.10688 15.954 -149.71
## + urban      1   0.06260 15.998 -149.46
## + central    1   0.05318 16.007 -149.41
## + mix        1   0.03960 16.021 -149.33
## + wmfgr      1   0.02854 16.032 -149.27
## + wsta       1   0.02520 16.035 -149.25
## + prbpris    1   0.02040 16.040 -149.22
```

```

## + wtrd      1    0.01224 16.048 -149.18
## + wtuc      1    0.00322 16.057 -149.13
## + wloc      1    0.00022 16.060 -149.11
##
## Step:  AIC=-167.34
## log_crmrte ~ density + west
##
##           Df Sum of Sq    RSS    AIC
## + prbconv  1    2.50648 10.609 -184.43
## + prbarr   1    1.68746 11.428 -177.73
## + pctymle  1    1.05265 12.063 -172.87
## + central  1    0.86332 12.252 -171.47
## + wser     1    0.68045 12.435 -170.13
## + wfed     1    0.57636 12.539 -169.38
## + taxpc    1    0.36020 12.756 -167.85
## <none>          13.116 -167.34
## + pctmin80  1    0.19632 12.919 -166.70
## + wcon      1    0.14814 12.968 -166.36
## + avgsgen   1    0.08265 13.033 -165.91
## + wmfg      1    0.07694 13.039 -165.87
## + wfir      1    0.06497 13.051 -165.79
## + mix       1    0.06018 13.056 -165.75
## + prbpris   1    0.04089 13.075 -165.62
## + wtuc      1    0.03304 13.083 -165.57
## + urban     1    0.03096 13.085 -165.55
## + polpc     1    0.02985 13.086 -165.54
## + wloc      1    0.01397 13.102 -165.44
## + wsta      1    0.00583 13.110 -165.38
## + wtrd      1    0.00529 13.111 -165.38
##
## Step:  AIC=-184.43
## log_crmrte ~ density + west + prbconv
##
##           Df Sum of Sq    RSS    AIC
## + prbarr    1    2.34643  8.2629 -204.92
## + wfed      1    0.83512  9.7742 -189.81
## + central   1    0.73021  9.8791 -188.84
## + mix       1    0.71874  9.8906 -188.74
## + pctymle   1    0.65915  9.9502 -188.20
## + pctmin80  1    0.32029 10.2890 -185.19
## + taxpc     1    0.26004 10.3493 -184.66
## + wmfg      1    0.24268 10.3666 -184.51
## <none>          10.6093 -184.43
## + wcon      1    0.13057 10.4787 -183.54
## + wtuc      1    0.08905 10.5203 -183.19
## + urban     1    0.04370 10.5656 -182.80
## + polpc     1    0.03042 10.5789 -182.69
## + wloc      1    0.02897 10.5803 -182.67
## + prbpris   1    0.02395 10.5854 -182.63
## + wser      1    0.00516 10.6042 -182.47
## + wtrd      1    0.00479 10.6045 -182.47
## + wsta      1    0.00284 10.6065 -182.45
## + wfir      1    0.00233 10.6070 -182.45
## + avgsgen   1    0.00006 10.6093 -182.43

```

```

##
## Step: AIC=-204.92
## log_crmrte ~ density + west + prbconv + prbarr
##
##          Df Sum of Sq    RSS    AIC
## + polpc   1   1.41147 6.8514 -219.78
## + wfed    1   0.81108 7.4518 -212.22
## + central 1   0.76023 7.5026 -211.61
## + pctmin80 1  0.70778 7.5551 -210.98
## + pctymle  1  0.30509 7.9578 -206.31
## + wmfg     1  0.22113 8.0418 -205.37
## + taxpc    1  0.21216 8.0507 -205.26
## + wloc     1  0.19827 8.0646 -205.11
## <none>          8.2629 -204.92
## + avgssen  1  0.12246 8.1404 -204.27
## + wtuc     1  0.11422 8.1487 -204.18
## + mix      1  0.08199 8.1809 -203.82
## + wsta     1  0.04978 8.2131 -203.47
## + wcon     1  0.03148 8.2314 -203.27
## + wser     1  0.02647 8.2364 -203.21
## + wtrd     1  0.01465 8.2482 -203.08
## + urban    1  0.01199 8.2509 -203.05
## + wfir     1  0.00439 8.2585 -202.97
## + prbpris  1  0.00072 8.2622 -202.93
##
## Step: AIC=-219.78
## log_crmrte ~ density + west + prbconv + prbarr + polpc
##
##          Df Sum of Sq    RSS    AIC
## + pctmin80 1  1.23128 5.6201 -235.61
## + central   1  0.63049 6.2209 -226.47
## + wfed      1  0.59242 6.2590 -225.92
## <none>          6.8514 -219.78
## + wsta     1  0.13668 6.7147 -219.59
## + pctymle   1  0.10414 6.7473 -219.16
## + wtuc     1  0.05144 6.8000 -218.46
## + wcon     1  0.04219 6.8092 -218.34
## + wmfg     1  0.03521 6.8162 -218.25
## + mix      1  0.03490 6.8165 -218.24
## + avgssen   1  0.01955 6.8319 -218.04
## + wtrd     1  0.01788 6.8335 -218.02
## + urban    1  0.01590 6.8355 -217.99
## + wloc     1  0.00690 6.8445 -217.87
## + wfir     1  0.00240 6.8490 -217.81
## + prbpris   1  0.00027 6.8511 -217.79
## + taxpc    1  0.00020 6.8512 -217.78
## + wser     1  0.00014 6.8513 -217.78
##
## Step: AIC=-235.61
## log_crmrte ~ density + west + prbconv + prbarr + polpc + pctmin80
##
##          Df Sum of Sq    RSS    AIC
## + wfed     1  0.53345 5.0867 -242.59
## + wsta     1  0.31439 5.3057 -238.79

```



```

## + wcon      1    0.22014 5.4000 -237.21
## + mix       1    0.19495 5.4252 -236.79
## + urban     1    0.14253 5.4776 -235.92
## + central   1    0.13315 5.4870 -235.77
## <none>              5.6201 -235.61
## + wtuc      1    0.12224 5.4979 -235.59
## + wtrd      1    0.09692 5.5232 -235.18
## + pctymle   1    0.07319 5.5469 -234.79
## + wloc      1    0.06955 5.5506 -234.73
## + wser      1    0.05762 5.5625 -234.54
## + wmfgr     1    0.04954 5.5706 -234.41
## + prbpris   1    0.01786 5.6023 -233.90
## + taxpc     1    0.00591 5.6142 -233.71
## + avgscn    1    0.00101 5.6191 -233.63
## + wfir      1    0.00073 5.6194 -233.62
##
## Step:  AIC=-242.59
## log_crmrte ~ density + west + prbconv + prbarr + polpc + pctmin80 +
##      wfed
##
##           Df Sum of Sq    RSS    AIC
## + wsta      1   0.36526 4.7214 -247.29
## + central   1   0.26095 4.8257 -245.33
## + pctymle   1   0.17155 4.9151 -243.67
## + wfir      1   0.15143 4.9353 -243.31
## <none>              5.0867 -242.59
## + urban     1   0.08107 5.0056 -242.03
## + taxpc     1   0.06932 5.0174 -241.82
## + wcon      1   0.05252 5.0342 -241.52
## + mix       1   0.05158 5.0351 -241.50
## + wser      1   0.03779 5.0489 -241.26
## + prbpris   1   0.02681 5.0599 -241.06
## + wtuc      1   0.02287 5.0638 -240.99
## + avgscn    1   0.01320 5.0735 -240.82
## + wmfgr     1   0.00108 5.0856 -240.61
## + wtrd      1   0.00084 5.0858 -240.60
## + wloc      1   0.00053 5.0862 -240.60
##
## Step:  AIC=-247.29
## log_crmrte ~ density + west + prbconv + prbarr + polpc + pctmin80 +
##      wfed + wsta
##
##           Df Sum of Sq    RSS    AIC
## + pctymle   1   0.269426 4.4520 -250.58
## + central   1   0.222728 4.4987 -249.64
## <none>              4.7214 -247.29
## + wfir      1   0.088681 4.6327 -247.00
## + mix       1   0.068999 4.6524 -246.62
## + prbpris   1   0.040292 4.6811 -246.06
## + urban     1   0.026383 4.6950 -245.80
## + wser      1   0.025477 4.6960 -245.78
## + taxpc     1   0.024825 4.6966 -245.77
## + wtrd      1   0.019294 4.7021 -245.66
## + wcon      1   0.018232 4.7032 -245.64

```

```

## + wmgf      1  0.008071 4.7134 -245.45
## + wloc      1  0.006051 4.7154 -245.41
## + avgse     1  0.000694 4.7207 -245.31
## + wtuc      1  0.000097 4.7213 -245.29
##
## Step: AIC=-250.58
## log_crmrte ~ density + west + prbconv + prbarr + polpc + pctmin80 +
##      wfed + wsta + pctymle
##
##           Df Sum of Sq    RSS    AIC
## + central  1  0.160121 4.2919 -251.88
## + taxpc    1  0.106562 4.3454 -250.76
## <none>      4.4520 -250.58
## + wfir     1  0.090730 4.3613 -250.43
## + mix      1  0.037862 4.4141 -249.35
## + prbpris  1  0.027609 4.4244 -249.14
## + wser     1  0.026573 4.4254 -249.12
## + wcon     1  0.020851 4.4312 -249.00
## + urban    1  0.016567 4.4354 -248.92
## + wmgf     1  0.009857 4.4421 -248.78
## + wloc     1  0.007999 4.4440 -248.74
## + wtrd     1  0.006269 4.4457 -248.71
## + avgse    1  0.004132 4.4479 -248.66
## + wtuc     1  0.000726 4.4513 -248.60
##
## Step: AIC=-251.88
## log_crmrte ~ density + west + prbconv + prbarr + polpc + pctmin80 +
##      wfed + wsta + pctymle + central
##
##           Df Sum of Sq    RSS    AIC
## <none>      4.2919 -251.88
## + wfir     1  0.074114 4.2178 -251.44
## + taxpc    1  0.065113 4.2268 -251.25
## + urban    1  0.043628 4.2483 -250.80
## + wcon     1  0.039905 4.2520 -250.72
## + avgse    1  0.030713 4.2612 -250.52
## + mix      1  0.024668 4.2672 -250.40
## + wloc     1  0.019087 4.2728 -250.28
## + wmgf     1  0.010493 4.2814 -250.10
## + prbpris  1  0.007598 4.2843 -250.04
## + wtuc     1  0.003155 4.2887 -249.94
## + wtrd     1  0.002043 4.2898 -249.92
## + wser     1  0.001662 4.2902 -249.91

```

With the top down approach, we started with model 3 and looked to exclude variables that weren't as predictive. We ran hypothesis testing on all five groups, one group at a time.

```

#deterrent
linearHypothesis(all_in_model_log_level,
  c("prbarr = 0", "prbconv = 0", "prbpris = 0",
    "avgse = 0", "polpc = 0"),
  vcov = vcovHC)

```

```
## Linear hypothesis test
```

```
##
## Hypothesis:
## prbarr = 0
## prbconv = 0
## prbpris = 0
## avgsgen = 0
## polpc = 0
##
## Model 1: restricted model
## Model 2: log_crmrte ~ prbarr + prbconv + prbpris + avgsgen + polpc + density +
##      taxpc + west + central + urban + pctmin80 + wcon + wtuc +
##      wtrd + wfir + wser + wmfg + wfed + wsta + wloc + mix + pctymle
##
## Note: Coefficient covariance matrix supplied.
##
##   Res.Df Df      F    Pr(>F)
## 1      72
## 2      67  5 6.0582 0.0001101 ***
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
```

```
#wage
linearHypothesis(all_in_model_log_level,
                  c("wcon = 0", "wtuc = 0", "wtrd = 0",
                    "wfir = 0", "wser = 0", "wmfg = 0",
                    "wfed = 0", "wsta = 0", "wloc = 0"),
                  vcov = vcovHC)
```

```
## Linear hypothesis test
##
## Hypothesis:
## wcon = 0
## wtuc = 0
## wtrd = 0
## wfir = 0
## wser = 0
## wmfg = 0
## wfed = 0
## wsta = 0
## wloc = 0
##
## Model 1: restricted model
## Model 2: log_crmrte ~ prbarr + prbconv + prbpris + avgsgen + polpc + density +
##      taxpc + west + central + urban + pctmin80 + wcon + wtuc +
##      wtrd + wfir + wser + wmfg + wfed + wsta + wloc + mix + pctymle
##
## Note: Coefficient covariance matrix supplied.
##
##   Res.Df Df      F Pr(>F)
## 1      76
## 2      67  9 1.372 0.2185
```

```
#region
linearHypothesis(all_in_model_log_level,
                  c("west = 0", "central = 0"),
                  vcov = vcovHC)

## Linear hypothesis test
##
## Hypothesis:
## west = 0
## central = 0
##
## Model 1: restricted model
## Model 2: log_crmrte ~ prbarr + prbconv + prbpris + avgsgen + polpc + density +
##          taxpc + west + central + urban + pctmin80 + wcon + wtuc +
##          wtrd + wfir + wser + wmfg + wfed + wsta + wloc + mix + pctymle
##
## Note: Coefficient covariance matrix supplied.
##
##      Res.Df Df      F Pr(>F)
## 1         69
## 2         67  2 0.623 0.5394
```

```
#urban
linearHypothesis(all_in_model_log_level,
                  c("urban = 0"),
                  vcov = vcovHC)

## Linear hypothesis test
##
## Hypothesis:
## urban = 0
##
## Model 1: restricted model
## Model 2: log_crmrte ~ prbarr + prbconv + prbpris + avgsgen + polpc + density +
##          taxpc + west + central + urban + pctmin80 + wcon + wtuc +
##          wtrd + wfir + wser + wmfg + wfed + wsta + wloc + mix + pctymle
##
## Note: Coefficient covariance matrix supplied.
##
##      Res.Df Df      F Pr(>F)
## 1         68
## 2         67  1 0.5474 0.462
```

```
#demographic
linearHypothesis(all_in_model_log_level,
                  c("density = 0", "taxpc = 0", "pctmin80 = 0",
                    "mix = 0", "pctymle = 0"),
                  vcov = vcovHC)
```

```
## Linear hypothesis test
##
## Hypothesis:
```

```
## density = 0
## taxpc = 0
## pctmin80 = 0
## mix = 0
## pctymle = 0
##
## Model 1: restricted model
## Model 2: log_crmrte ~ prbarr + prbconv + prbpris + avgse + polpc + density +
##      taxpc + west + central + urban + pctmin80 + wcon + wtuc +
##      wtrd + wfir + wser + wmfgr + wfed + wsta + wloc + mix + pctymle
##
## Note: Coefficient covariance matrix supplied.
##
##      Res.Df Df      F    Pr(>F)
## 1      72
## 2      67  5 3.9627 0.003298 **
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
```

/ The hypothesis tests below show that of the five groups the only groups that are jointly significant are the deterrent data and the demographic data. These tests measure whether removing all the variables within a group reduces the r-squared by a statistically significant amount. We will re-run the models and compare.

```
balanced_model_top_1 <- lm(log_crmrte ~ prbarr + prbconv + prbpris
+ avgse + polpc + density
+ taxpc + pctmin80 + mix + pctymle,
data = data_crmrte)
se.balanced_model_top_1 = sqrt(diag(vcovHC(balanced_model_top_1)))
coeftest(balanced_model_top_1, vcov = vcovHC)
```

```
##
## t test of coefficients:
##
##      Estimate Std. Error t value Pr(>|t|)
## (Intercept) -3.3522918  0.3558217 -9.4213 1.467e-14 ***
## prbarr      -1.9627484  0.4014808 -4.8888 5.228e-06 ***
## prbconv     -0.7672158  0.1366862 -5.6130 2.846e-07 ***
## prbpris     -0.0764993  0.4732818 -0.1616 0.872005
## avgse       -0.0044749  0.0140406 -0.3187 0.750789
## polpc       176.1347220 82.5884550  2.1327 0.036056 *
## density      0.1135225  0.0351279  3.2317 0.001796 **
## taxpc        0.0020988  0.0055753  0.3764 0.707593
## pctmin80     0.0125062  0.0016215  7.7128 3.155e-11 ***
## mix         -0.7304967  0.5396416 -1.3537 0.179702
## pctymle      1.3832565  1.6211791  0.8532 0.396105
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
```

```
AIC(balanced_model_top_1, k=2)
```

```
## [1] 27.4514
```

```
stargazer(simple_regression_model, all_in_model_log_level, balanced_model_top_1,
          type = "text", omit.stat = "f",
          se = list(se.simple_regression_model, se.all_in_model_log_level, se.balanced_model_top_1),
          star.cutoffs = c(0.05, 0.01, 0.001))
```

```
##
## =====
##                               Dependent variable:
##                               -----
##                               log_crmrte
##                               (1)          (2)          (3)
## -----
## prbarr                        -1.889***      -1.963***
##                               (0.380)        (0.401)
##
## prbconv                      -0.656***      -0.767***
##                               (0.174)        (0.137)
##
## prbpris                      -0.093         -0.076
##                               (0.399)        (0.473)
##
## avgsen                      -0.008         -0.004
##                               (0.016)        (0.014)
##
## polpc                        154.835        176.135*
##                               (86.523)      (82.588)
##
## density                      0.228***      0.117*      0.114**
##                               (0.030)      (0.054)    (0.035)
##
## taxpc                        0.003         0.002
##                               (0.007)      (0.006)
##
## west                        -0.115
##                               (0.125)
##
## central                     -0.101
##                               (0.092)
##
## urban                       -0.169
##                               (0.229)
##
## pctmin80                    0.010**      0.013***
##                               (0.003)      (0.002)
##
## wcon                        0.0005
##                               (0.001)
##
## wtuc                        0.0001
##                               (0.001)
##
## wtrd                        0.0003
##                               (0.002)
```

```
##
## wfir -0.001
## (0.001)
##
## wser -0.0001
## (0.002)
##
## wmfg -0.0002
## (0.001)
##
## wfed 0.002*
## (0.001)
##
## wsta -0.001
## (0.001)
##
## wloc 0.001
## (0.002)
##
## mix -0.239 -0.730
## (0.626) (0.540)
##
## pctymle 2.771 1.383
## (1.433) (1.621)
##
## Constant -3.869*** -4.026*** -3.352***
## (0.069) (0.848) (0.356)
##
## -----
## Observations 90 90 90
## R2 0.401 0.854 0.796
## Adjusted R2 0.394 0.806 0.770
## Residual Std. Error 0.427 (df = 88) 0.242 (df = 67) 0.263 (df = 79)
## =====
## Note: *p<0.05; **p<0.01; ***p<0.001
```

Our adjusted r-squared has only fallen from 80.6% to 77.6% but we have dropped 12 variables. This is a much more parsimonious model. In order to double check wages, we decided to try to one more model that included just the median wage from all industries. The fundamental concept behind this is that the median could capture all opportunity for potential criminals, and it has the benefit of not being affected by the outlier in wser. Unfortunately, though it was much better, it was still not predictive.

```
balanced_model_top_2 <- lm(log_crmrte ~ prbarr + prbconv + prbpris
+ avgsen + polpc + density
+ taxpc + pctmin80 + mix + pctymle
+ median_wage,
data = data_crmrte)
se.balanced_model_top_2 = sqrt(diag(vcovHC(balanced_model_top_2)))
coeftest(balanced_model_top_2, vcov = vcovHC)
```

```
##
## t test of coefficients:
##
```

```
##           Estimate Std. Error t value Pr(>|t|)
## (Intercept) -3.7018614  0.6241512 -5.9310 7.799e-08 ***
## prbarr      -1.9379154  0.4176289 -4.6403 1.381e-05 ***
## prbconv     -0.7650603  0.1360985 -5.6214 2.826e-07 ***
## prbpris     -0.1114352  0.4509889 -0.2471 0.805487
## avgsen      -0.0046181  0.0137443 -0.3360 0.737770
## polpc       167.9127417  85.2311288  1.9701 0.052378 .
## density      0.0977596  0.0343625  2.8450 0.005671 **
## taxpc        0.0020705  0.0056750  0.3648 0.716214
## pctmin80     0.0123893  0.0016202  7.6467 4.534e-11 ***
## mix         -0.5896970  0.5806401 -1.0156 0.312961
## pctymle      1.5670818  1.9109317  0.8201 0.414680
## median_wage  0.0011536  0.0014133  0.8162 0.416848
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
```

```
AIC(balanced_model_top_2, k=2)
```

```
## [1] 28.07462
```

```
stargazer(simple_regression_model, all_in_model_log_level, balanced_model_top_1, balanced_model_top_2,
  type = "text", omit.stat = "f",
  se = list(se.simple_regression_model, se.all_in_model_log_level,
    se.balanced_model_top_1, se.balanced_model_top_2),
  star.cutoffs = c(0.05, 0.01, 0.001))
```

```
##
## =====
##                               Dependent variable:
##                               -----
##                               log_crmrte
##                               (1)          (2)          (3)          (4)
## -----
## prbarr                               -1.889***      -1.963***      -1.938***
##                               (0.380)      (0.401)      (0.418)
##
## prbconv                             -0.656***      -0.767***      -0.765***
##                               (0.174)      (0.137)      (0.136)
##
## prbpris                             -0.093         -0.076         -0.111
##                               (0.399)      (0.473)      (0.451)
##
## avgsen                              -0.008         -0.004         -0.005
##                               (0.016)      (0.014)      (0.014)
##
## polpc                               154.835        176.135*       167.913*
##                               (86.523)      (82.588)      (85.231)
##
## density                0.228***      0.117*        0.114**       0.098**
##                (0.030)      (0.054)      (0.035)      (0.034)
##
## taxpc                    0.003         0.002         0.002
##                (0.007)      (0.006)      (0.006)
```



##				
## west		-0.115		
##		(0.125)		
##				
## central		-0.101		
##		(0.092)		
##				
## urban		-0.169		
##		(0.229)		
##				
## pctmin80		0.010**	0.013***	0.012***
##		(0.003)	(0.002)	(0.002)
##				
## wcon		0.0005		
##		(0.001)		
##				
## wtuc		0.0001		
##		(0.001)		
##				
## wtrd		0.0003		
##		(0.002)		
##				
## wfir		-0.001		
##		(0.001)		
##				
## wser		-0.0001		
##		(0.002)		
##				
## wmfg		-0.0002		
##		(0.001)		
##				
## wfed		0.002*		
##		(0.001)		
##				
## wsta		-0.001		
##		(0.001)		
##				
## wloc		0.001		
##		(0.002)		
##				
## mix		-0.239	-0.730	-0.590
##		(0.626)	(0.540)	(0.581)
##				
## pctymle		2.771	1.383	1.567
##		(1.433)	(1.621)	(1.911)
##				
## median_wage				0.001
##				(0.001)
##				
## Constant	-3.869***	-4.026***	-3.352***	-3.702***
##	(0.069)	(0.848)	(0.356)	(0.624)
##				
## -----				
## Observations	90	90	90	90

```
## R2                0.401                0.854                0.796                0.799
## Adjusted R2        0.394                0.806                0.770                0.770
## Residual Std. Error 0.427 (df = 88) 0.242 (df = 67) 0.263 (df = 79) 0.263 (df = 78)
## =====
## Note:                                     *p<0.05; **p<0.01; ***p<0.001
```

Three of the five groups have been eliminated, with only the deterrent and demographic groups remaining. We will use step wise regression to evaluate.

```
base_backward = lm(log_crmrte ~ prbarr + prbconv + prbpris
                    + avgsen + polpc + density
                    + taxpc + pctmin80 + mix + pctymle,
                    data = data_crmrte)
backward_step = step(base_backward, scope = formula(base_backward), direction = "backward")
```

```
## Start:  AIC=-229.96
## log_crmrte ~ prbarr + prbconv + prbpris + avgsen + polpc + density +
##      taxpc + pctmin80 + mix + pctymle
##
##           Df Sum of Sq   RSS   AIC
## - prbpris    1    0.0031 5.4786 -231.91
## - avgsen      1    0.0103 5.4858 -231.79
## - taxpc       1    0.0474 5.5229 -231.18
## - pctymle     1    0.0771 5.5526 -230.70
## <none>                5.4755 -229.96
## - mix         1    0.2159 5.6914 -228.48
## - polpc       1    1.1452 6.6207 -214.87
## - density     1    1.8044 7.2799 -206.32
## - prbarr      1    2.9989 8.4744 -192.65
## - pctmin80    1    3.4894 8.9649 -187.59
## - prbconv     1    4.2940 9.7695 -179.85
##
## Step:  AIC=-231.91
## log_crmrte ~ prbarr + prbconv + avgsen + polpc + density + taxpc +
##      pctmin80 + mix + pctymle
##
##           Df Sum of Sq   RSS   AIC
## - avgsen      1    0.0091 5.4877 -233.76
## - taxpc       1    0.0529 5.5316 -233.04
## - pctymle     1    0.0815 5.5601 -232.58
## <none>                5.4786 -231.91
## - mix         1    0.2221 5.7007 -230.33
## - polpc       1    1.1489 6.6275 -216.77
## - density     1    1.8111 7.2897 -208.20
## - prbarr      1    2.9964 8.4750 -194.64
## - pctmin80    1    3.5028 8.9814 -189.42
## - prbconv     1    4.2956 9.7742 -181.81
##
## Step:  AIC=-233.76
## log_crmrte ~ prbarr + prbconv + polpc + density + taxpc + pctmin80 +
##      mix + pctymle
```

```

##
##           Df Sum of Sq    RSS    AIC
## - taxpc    1    0.0545 5.5422 -234.87
## - pctymle   1    0.0789 5.5667 -234.47
## <none>                5.4877 -233.76
## - mix      1    0.2139 5.7016 -232.32
## - polpc    1    1.2273 6.7150 -217.59
## - density  1    1.8088 7.2965 -210.12
## - prbarr   1    3.0183 8.5060 -196.31
## - pctmin80 1    3.5470 9.0348 -190.89
## - prbconv  1    4.3218 9.8095 -183.48
##
## Step: AIC=-234.87
## log_crmrte ~ prbarr + prbconv + polpc + density + pctmin80 +
##      mix + pctymle
##
##           Df Sum of Sq    RSS    AIC
## - pctymle   1    0.0525 5.5947 -236.02
## <none>                5.5422 -234.87
## - mix      1    0.2148 5.7571 -233.44
## - polpc    1    1.7384 7.2806 -212.31
## - density  1    1.8905 7.4328 -210.45
## - prbarr   1    3.5982 9.1404 -191.84
## - pctmin80 1    3.6798 9.2220 -191.04
## - prbconv  1    4.8508 10.3931 -180.28
##
## Step: AIC=-236.02
## log_crmrte ~ prbarr + prbconv + polpc + density + pctmin80 +
##      mix
##
##           Df Sum of Sq    RSS    AIC
## <none>                5.5947 -236.02
## - mix      1    0.2319 5.8267 -234.36
## - density  1    1.8553 7.4500 -212.24
## - polpc    1    1.9402 7.5349 -211.22
## - pctmin80 1    3.7524 9.3471 -191.83
## - prbarr   1    3.9930 9.5877 -189.54
## - prbconv  1    5.3975 10.9922 -177.24

balanced_model_top_3 <- lm(log_crmrte ~ mix + density
                          + polpc + pctmin80
                          + prbarr + prbconv,
                          data = data_crmrte)
se.balanced_model_top_3 = sqrt(diag(vcovHC(balanced_model_top_3)))
coeftest(balanced_model_top_2, vcov = vcovHC)

##
## t test of coefficients:
##
##           Estimate Std. Error t value Pr(>|t|)
## (Intercept) -3.7018614  0.6241512 -5.9310 7.799e-08 ***
## prbarr      -1.9379154  0.4176289 -4.6403 1.381e-05 ***
## prbconv     -0.7650603  0.1360985 -5.6214 2.826e-07 ***
## prbpris     -0.1114352  0.4509889 -0.2471 0.805487

```

```
## avgsen      -0.0046181    0.0137443 -0.3360  0.737770
## polpc       167.9127417   85.2311288  1.9701  0.052378 .
## density     0.0977596    0.0343625  2.8450  0.005671 **
## taxpc       0.0020705    0.0056750  0.3648  0.716214
## pctmin80    0.0123893    0.0016202  7.6467  4.534e-11 ***
## mix        -0.5896970    0.5806401 -1.0156  0.312961
## pctymle     1.5670818    1.9109317  0.8201  0.414680
## median_wage 0.0011536    0.0014133  0.8162  0.416848
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
```

```
AIC(balanced_model_top_2, k=2)
```

```
## [1] 28.07462
```

```
stargazer(simple_regression_model, all_in_model_log_level, balanced_model_top_1, balanced_model_top_3,
  type = "text", omit.stat = "f",
  se = list(se.simple_regression_model, se.all_in_model_log_level,
    se.balanced_model_top_1, se.balanced_model_top_3),
  star.cutoffs = c(0.05, 0.01, 0.001))
```

```
##
## =====
##                               Dependent variable:
##                               -----
##                               log_crmrte
##                               (1)          (2)          (3)          (4)
## -----
## prbarr                               -1.889***      -1.963***      -2.100***
##                               (0.380)      (0.401)      (0.436)
##
## prbconv                             -0.656***      -0.767***      -0.809***
##                               (0.174)      (0.137)      (0.126)
##
## prbpris                             -0.093         -0.076
##                               (0.399)      (0.473)
##
## avgsen                             -0.008         -0.004
##                               (0.016)      (0.014)
##
## polpc                               154.835        176.135*       190.549**
##                               (86.523)      (82.588)      (71.937)
##
## density                0.228***      0.117*       0.114**       0.113***
##                (0.030)      (0.054)      (0.035)      (0.027)
##
## taxpc                               0.003         0.002
##                               (0.007)      (0.006)
##
## west                             -0.115
##                               (0.125)
##
## central                             -0.101
```

```

##                                     (0.092)
##
## urban                             -0.169
##                                     (0.229)
##
## pctmin80                          0.010**      0.013***      0.013***
##                                     (0.003)      (0.002)      (0.001)
##
## wcon                              0.0005
##                                     (0.001)
##
## wtuc                              0.0001
##                                     (0.001)
##
## wtrd                              0.0003
##                                     (0.002)
##
## wfir                              -0.001
##                                     (0.001)
##
## wser                              -0.0001
##                                     (0.002)
##
## wmfg                              -0.0002
##                                     (0.001)
##
## wfed                              0.002*
##                                     (0.001)
##
## wsta                              -0.001
##                                     (0.001)
##
## wloc                              0.001
##                                     (0.002)
##
## mix                               -0.239      -0.730      -0.745
##                                     (0.626)      (0.540)      (0.474)
##
## pctymle                           2.771      1.383
##                                     (1.433)      (1.621)
##
## Constant                         -3.869***    -4.026***    -3.352***    -3.197***
##                                (0.069)      (0.848)      (0.356)      (0.237)
##
## -----
## Observations                      90          90          90          90
## R2                                0.401        0.854        0.796        0.791
## Adjusted R2                       0.394        0.806        0.770        0.776
## Residual Std. Error 0.427 (df = 88) 0.242 (df = 67) 0.263 (df = 79) 0.260 (df = 83)
## =====
## Note:                             *p<0.05; **p<0.01; ***p<0.001

```

The difference between the backward and forward model is that the backward model chooses variables for exclusion based on comparing significance while the forward model looks for significance in inclusion. We

also used the f-tests (hypothesis tests) to give the backward stepwise regression a head start.

The backward stepwise regression yielded a more reasonable model so that is the model we are choosing for our balanced model. This model strikes a nice balance between parsimony and explanatory power. The variables included are `prbarr`, `prbconv`, `polpc`, `density`, `pctmin80`, and `mix`. Six out of the original 24 independent variables are included. The adjust r-squared is only 3% lower (77.6% vs. 80.6%). It includes a blend of actionable items for the campaign in the deterrent data as well as demographic variables that perhaps can focus the campaign's efforts.