
title: Solana QuickStart

description: Get started with Solana RPC on Quicknode. Follow this QuickStart to get up and running with your own Quicknode endpoint and making your first API request to the Solana blockchain.

The quickest way to start building on Solana with Quicknode is by sending a JSON-RPC request to your endpoint. In this quickstart, you'll create an endpoint, copy its provider URL, and make your first request. Code samples are available in ****cURL**** as well as popular SDKs and programming languages.

Get Your Solana Endpoint

> For the complete documentation index, see [llms.txt](/docs/llms.txt)

1

Create a Quicknode account

Sign up [here](https://www.quicknode.com/signup?utm_source=internal&utm_campaign=docs&utm_content=quickstart-Solana) if you haven't already.

2

Go to your dashboard

Go to your Quicknode dashboard, then select [Endpoints] (https://dashboard.quicknode.com/endpoints) from the left sidebar.

3

Create a new endpoint

Click ****Create Endpoint**** in the top-right corner. Select ****Solana**** as the chain, click ****Continue****, then select your preferred network.

4

Copy your provider URLs

Keep the HTTP URL handy. You'll use it in your requests below.

Learn More about the Dashboard

For a detailed walkthrough of the Quicknode dashboard, check out our [guide] (https://www.quicknode.com/guides/quicknode-products/how-to-use-the-quicknode-dashboard)

Send Your First Request

Your endpoint is ready. Now, let's make your first call to the Solana blockchain. We'll use the ``getSlot`` method, which returns the slot number. ****Select your preferred language or SDK and follow the steps below to send your first request****.

****cURL****

1

Get Slot

To run the cURL request, open a terminal window and paste the following code to retrieve the current slot.

```
```bash
curl 'YOUR_QUICKNODE_ENDPOINT_URL/' \
 -X POST \
 -H "Content-Type: application/json" \
 --data '{"jsonrpc":"2.0","id":1, "method":"getSlot"}'
```
```

****Solana Kit (@solana/kit)****

1

Set up your project

Create a new directory and initialize a Node.js project (assumes Node.js is already installed):

```
```bash
mkdir solana-quickstart
cd solana-quickstart
npm init -y
```
```

2

Install Solana Kit

Install the Solana Kit SDK for blockchain interaction:

```
```bash
npm install --save @solana/kit
```
```

3

Create your main file

Create an index.ts file with the following code:

```
```typescript
import { createSolanaRpc } from "@solana/kit";
```

```
(async () => {
 const solanaRpc = createSolanaRpc("YOUR_QUICKNODE_ENDPOINT_URL/");

 try {
 const slot = await solanaRpc.getSlot().send();
 console.log(slot);
 } catch (error) {
 console.error("Error fetching slot:", error);
 }
})();
```

4

### Run your project

Execute your script to see the current slot:

```
```bash
npx tsx index.ts
```
```

**\*\*Solana-Web3.js\*\***

1

### Set up your project

Create a new directory and initialize a Node.js project (assumes Node.js is already installed):

```
```bash
mkdir solana-quickstart
cd solana-quickstart
npm init -y
```
```

2

### Install Solana Web3.js SDK

Install the Solana JavaScript SDK for blockchain interaction:

```
```bash
npm install --save @solana/web3.js
```
```

3

### Create your main file

Create an index.js file with the following code:

```
```bash
const web3 = require("@solana/web3.js");

(async () => {
  const solana = new web3.Connection("YOUR_QUICKNODE_ENDPOINT_URL/");
  const slot = await solana.getSlot();
  console.log('Current slot:', slot);
})();
```
```

4

### Run your project

Execute your script to see the current slot number:

```
```bash
node index.js
```
```

**\*\*Solana.py\*\***

1

### Set up your project

Create a new directory for your Solana Python project:

```
```bash
mkdir solana-python-quickstart

cd solana-python-quickstart
```
```

2

### Install Solana.py (if not already installed)

Check if solana is installed with `\`pip list | grep solana\``. If not found, install it:

```
```bash
pip install solana cachetools
```
```

### Create and run Python script

Create an `app.py` file with the following code, then execute it with `\`python app.py\`` to retrieve the current slot number:

```
```bash
from solana.rpc.api import Client

solana_client = Client("YOUR_QUICKNODE_ENDPOINT_URL/")

slot_response = solana_client.get_slot()

print(f"Current slot: {slot_response.value}")
```

Solana CLI
```

1

### Get current slot

```
```bash
solana slot --url YOUR_QUICKNODE_ENDPOINT_URL/
```
```

If you want to continue learning about making API requests, check out our [guides] (<https://quicknode.com/guides>) and [sample apps] (<https://www.quicknode.com/sample-app-library/welcome>).

- [API Overview](/docs/solana/api-overview): Discover Supported Solana APIs, Networks, Chain Configurations, and compatible Quicknode Products
- [Provider Endpoints](/docs/solana/endpoints): Learn how to set up and configure your Solana RPC endpoints for development and production use
- [Endpoint Security](/docs/solana/endpoint-security): Secure your endpoints with Token Authentication, Rate-limiting, Whitelisting, JWT and best security practices
- [Error Reference](/docs/solana/error-references): Reference document for common Solana RPC error codes and troubleshooting tips
- [Add-ons](/docs/solana/add-ons): Discover endpoint add-ons that extend your Solana development workflow
- [Guides](/guides/tags/solana): Explore comprehensive Solana development guides and best practices to accelerate your blockchain application development