

02/12/2019, 12:08 1 of 4

S-16S (22.2V-74V, Adjustable) 100A max. BMS Battery Management	https://voltaplex.com/22-2v-59-2v-pcb-bms-battery-management-system
--	---

		ш	nperature Sv	
		ш	rmistor	
		_	it-Sink	
		☐ Diod		
		* Required Fields		
		04	•	_
		Qty:	2	▼
		A (22.2 \ion batte		ttery management system (BMS) for use wit
DESCRIPTION				
SPECIFICATIONS				
SPECIFICATIONS	STABLE			
BASIC	Options			Balancer, CANbus, I2C, RS232, RS48 Bus
BASIC	Options  Country of Manufacture			
BASIC				Bus
BASIC	Country of Manufacture			Bus  China  6S, 7S, 8S, 9S, 10S, 11S, 12S, 13S, 14
	Country of Manufacture  Series (compatible with)			Bus  China  6S, 7S, 8S, 9S, 10S, 11S, 12S, 13S, 14 S, 16S
	Country of Manufacture  Series (compatible with)  Length, max.			Bus  China  6S, 7S, 8S, 9S, 10S, 11S, 12S, 13S, 14 S, 16S  134.50 mm
	Country of Manufacture  Series (compatible with)  Length, max.  Width, max.			China  6S, 7S, 8S, 9S, 10S, 11S, 12S, 13S, 14 S, 16S  134.50 mm
SIZE	Country of Manufacture  Series (compatible with)  Length, max.  Width, max.  Height, max.	current		Bus  China  6S, 7S, 8S, 9S, 10S, 11S, 12S, 13S, 14S, 16S  134.50 mm  140.50 mm  5.00 mm

2 of 4 02/12/2019, 12:08