

Assignment Two

Josh Seligman

joshua.seligman1@marist.edu

September 25, 2022

1 SELECTION SORT

1.1 THE ALGORITHM

Selection sort is a sorting algorithm that, for each iteration of the array, selects the smallest (or largest) element of the unsorted part of the array and places the element into its sorted position. As shown in the pseudocode for the sort in Algorithm 1, selection sort works with the subset of the array in the range $[i, n)$ in each iteration because the elements in the indices less than i are already sorted and do not have to be checked. Thus, as more elements get sorted, the quicker each iteration becomes because a smaller portion of the array is compared until $i = n - 2$, which is the final iteration of the algorithm. Selection sort is also very consistent in that it runs in the same amount of time regardless of the order of the elements and has both a best and worst case of n^2 , which will be analyzed in further detail in Section 1.2.

Algorithm 1 Selection Sort Algorithm

```
1: procedure SELECTIONSORT(arr)
2:   for  $i \leftarrow 0, n - 2$  do    // Iterate through the second to last element as an array of size 1 is sorted
3:     smallestIndex  $\leftarrow i$ 
4:     for  $j \leftarrow i + 1, n - 1$  do    // Iterate through the remainder of the array
5:       if  $arr[j] < arr[smallestIndex]$  then
6:         smallestIndex  $\leftarrow j$     // Set the new smallest index if a smaller element is found
7:       end if
8:     end for
9:     swap(arr, i, smallestIndex)    // Place the smallest item in the subarray into its sorted place
10:  end for
11: end procedure
```

1.2 ASYMPTOTIC ANALYSIS AND COMPARISONS

Listing 1 contains the C++ code implementing selection sort on lines 6 - 25. Line 6 defines a loop that iterates $n - 1$ times and contains 2 assignments and a comparison, all of which operate in constant time for each iteration. Thus, line 6 will take $(n - 1) * C_1$ time, where C_1 is the time needed for each of the operations.

Next, line 8 is an assignment, which takes a constant time and executes $n - 1$ times because it is in the outer loop, resulting in a time of $(n - 1) * C_2$, where C_2 is the constant time needed for the assignment. Line 11, similar to line 6, defines a loop with 3 constant time expressions, which can be marked as C_3 . However, since it is nested inside of the loop on line 6, the total number of iterations of the inner loop is more complex. In the first iteration of the outer loop, the inner loop runs $n - 1$ times. From there, each corresponding iteration of the outer loop results in one less iteration of the inner loop with a minimum of 1 pass on the inner loop when $i = n - 2$. Therefore, the total number of times the inner loop on line 11 will be called is $\sum_{k=1}^{n-1} k$, which by the formula for the sum of the first N natural numbers, is equal to $\frac{(n-1)(n-1+1)}{2} = \frac{1}{2}n^2 - \frac{1}{2}n$. Thus, the total time to execute line 11 is $(\frac{1}{2}n^2 - \frac{1}{2}n) * C_3$. Next, line 13 contains a comparison that, since it is nested inside the inner loop, will run in $(\frac{1}{2}n^2 - \frac{1}{2}n) * C_4$ time, where C_4 is the time needed to make the comparison. Line 15 is a simple assignment and, just like line 14, will run in $(\frac{1}{2}n^2 - \frac{1}{2}n) * C_5$, where C_5 is the time to perform the assignment. The assignment on line 18 is purely for collecting data and not part of the algorithm and, therefore, will be excluded from the asymptotic analysis of selection sort. Line 19 is the end of the inner loop, and represents an unconditional branch back to the top of the loop, which means it runs the same number of iterations as the loop, which is $(\frac{1}{2}n^2 - \frac{1}{2}n) * C_6$, where C_6 is the time needed to execute the branch. Next, lines 22-24 are all assignments, which run in constant time, and are located in the outer loop. Thus, they run in $(n - 1) * C_7$ time, where C_7 is the time needed to perform the swap. Lastly, line 25 is the close and unconditional branch for the outer loop, which will run in $(n - 1) * C_8$ time, where C_8 is the time to execute the unconditional branch. Overall, when adding up the runtimes of each line and dropping the constants, the sum is $4 * (n - 1) + 4 * (\frac{1}{2}n^2 - \frac{1}{2}n) = 2n^2 + 2n - 4 \approx n^2 + n$ is $O(n^2)$.

As shown in Table 3.1, selection sort is very consistent with the number of comparisons made as, regardless of the state of the list, it always makes $\frac{1}{2}n^2 - \frac{1}{2}n$ comparisons. This is no coincidence as it is also the number of times the algorithm's inner loop iterates, which means that the selection sort will run very consistently for all lists, no matter the state of the array prior to running the algorithm.

2 INSERTION SORT

2.1 THE ALGORITHM

Insertion sort is a sorting algorithm that places an element in its sorted place by sliding previously sorted elements over until the sorted position is found for the element. Unlike selection sort, insertion sort has a unique property in that its performance varies based on the state of the input array. For instance, if the array is already completely sorted, the while loop on line 5 in Algorithm 2 will never be entered because each element is already sorted and in its proper position. This makes the best case runtime of insertion sort $\Omega(n)$ because the inner loop is never run and the outer loop just iterates through the array once. However, the worst case of insertion sort is when the array is in reverse order. This becomes the worst case because, as shown within the while loop in Algorithm 2, each element will have to be compared with every other element, which will cause j to end at -1 and the element gets inserted at the front of the array. This results in a worst case runtime complexity of $O(n^2)$, which will be analyzed and proved in detail in Section 2.2.

2.2 ASYMPTOTIC ANALYSIS AND COMPARISONS

The code implementation of insertion sort is in Listing 2 on lines 7-34. As mentioned in Section 2.1, the worst case for insertion sort is when the array is in reverse order because every element will have to be compared to every element within the sorted portion of the array. First, the outer loop begins on line 7 and contains 2 assignments and a comparison. Based on the definition of the loop, these statements will run $n - 1$ times, which means the line will run in $(n - 1) * C_1$ time, where C_1 is the time needed to execute these statements. Next, line 9 is a basic assignment and, since it is in the loop, will run in $(n - 1) * C_2$ time, where C_2 is the time to perform the assignment. Line 12 is also an assignment in the outer loop, which will run in $(n - 1) * C_3$ time, where C_3 is the time to execute the assignment. Next, line 16 contains the definition for a while loop, which

Algorithm 2 Insertion Sort Algorithm

```
1: procedure INSERTIONSORT(arr)
2:   for  $i \leftarrow 1, n - 1$  do    // Start at index 1 because the first element is already sorted
3:      $currentVal \leftarrow arr[i]$ 
4:      $j \leftarrow i - 1$ 
5:     while  $j \geq 0$  and  $currentVal < arr[j]$  do    // Find the position to place the element
6:        $arr[j + 1] \leftarrow arr[j]$     // Shift the element over because it is greater than the current value
7:        $j \leftarrow j - 1$ 
8:     end while
9:      $arr[j + 1] \leftarrow currentVal$     // Place the element in its sorted position
10:  end for
11: end procedure
```

has 2 comparisons. Since the worst case requires each element to be compared to all of the other sorted elements, the while loop will terminate when $j = -1$. Thus, when $i = 1$, the while loop will only iterate once, and the number of iterations for the while loop will increment with a max of $n - 1$ for when $i = n - 1$. The total iterations is explained in Section 1.2 as being $\sum_{k=1}^{n-1} k = \frac{(n-1)(n-1+1)}{2} = \frac{1}{2}n^2 - \frac{1}{2}n$, which means the loop on line 16 will run in $(\frac{1}{2}n^2 - \frac{1}{2}n) * C_4$ time, where C_4 is the time to perform the comparisons. Line 18 is just for counting the comparisons and will be excluded from the analysis of the algorithm. Next, the assignment on line 21 runs in constant time and, since it is in the inner loop, will run in $(\frac{1}{2}n^2 - \frac{1}{2}n) * C_5$ time, where C_5 is the time to perform the assignment. Line 22 also contains an assignment and runs in $(\frac{1}{2}n^2 - \frac{1}{2}n) * C_6$ time, where C_6 is the time to perform the assignment. Line 23 is the end of the while loop, which translates to an unconditional branch to the top of the loop, which will run in $(\frac{1}{2}n^2 - \frac{1}{2}n) * C_7$ time, where C_7 is the time to execute the branch. Lines 28-30 are used for counting the comparisons and are excluded from the analysis of insertion sort. Next, line 33 is an assignment to put the element in its sorted place, which will run in $(n - 1) * C_8$ time because it is in the outer loop, where C_8 is the time to perform the assignment. Lastly, line 34 is the end of the for loop, which is an unconditional branch to the top of the loop, which will run in $(n - 1) * C_9$, where C_9 is the time to perform the branch. Overall, when summing up each runtime and dropping the constants, the total is $5 * (n - 1) + 4 * (\frac{1}{2}n^2 - \frac{1}{2}n) = 2n^2 + 3n - 5 \approx n^2 + n$ is $O(n^2)$.

In Table 3.1, insertion sort is shown to have 3 very different outcomes for the lists that were used for testing relative to selection sort. First, insertion sort used about half the number of comparisons as selection sort for a list of 666 shuffled magic items. This is because the inner loop of insertion sort may terminate when $arr[j] < currentVal$ (see line 16 in Listing 2) and in a randomly shuffled list, the probability of $arr[j] < currentVal$ will be around 50%. Therefore, insertion sort will on average be about 50% more efficient than selection sort, but is still classified as $O(n^2)$ because it is still running at a function of n^2 . Next, when the list is already shuffled, insertion sort only makes $n - 1$ comparisons. As mentioned in Section 2.1, the best case for insertion sort is $\Omega(n)$ because the inner loop will never be entered as the second condition for $arr[j] < currentVal$ will always return false. This means there will be only 1 comparison made for each iteration of the outer loop, which equates to $n - 1$ comparisons. Lastly, Section 2.1 mentioned that the worst case for insertion sort is when the list is in reverse order because every element will have to compare itself with all of the elements in the sorted portion of the array. This causes insertion sort to have the same number of comparisons as selection sort for a reversed list at $\frac{1}{2}n^2 - \frac{1}{2}n$, which is also the same number of iterations as the inner loop for insertion sort and makes insertion sort $O(n^2)$.

3 APPENDIX

3.1 COMPARISONS TABLE

Algorithm	List	Comparisons	Time
Selection Sort	666 magic items, shuffled	221445	3625271 ns
	20 Yankees greats, sorted	190	3673 ns
	20 Yankees greats, reversed	190	3636 ns
Insertion Sort	666 magic items, shuffled	104628	2523161 ns
	20 Yankees greats, sorted	19	795 ns
	20 Yankees greats, reversed	190	2966 ns

Table 3.1: A table of the number of comparisons made and time to complete each sort on a variety of lists.

3.2 SELECTION SORT

```
1 int selectionSort(StringArr* data) {
2     // Start comparisons at 0
3     int comparisons = 0;
4
5     // Iterate through the second to last element because the last element will already be
6     // sorted as is
7     for (int i = 0; i < data->length - 1; i++) {
8         // The smallest index is going to start as the start of the subset of the list
9         int smallestIndex = i;
10
11        // Iterate through the rest of the list
12        for (int j = i + 1; j < data->length; j++) {
13            // Compare the current element to the current smallest element in the subset
14            if (data->arr[smallestIndex].compare(data->arr[j]) > 0) {
15                // If the current element comes first, make it the new smallest element
16                smallestIndex = j;
17            }
18            // Increment comparisons
19            comparisons++;
20        }
21
22        // Put the smallest index in its respective place
23        std::string temp = data->arr[i];
24        data->arr[i] = data->arr[smallestIndex];
25        data->arr[smallestIndex] = temp;
26    }
27
28    // Return the number of comparisons
29    return comparisons;
}
```

Listing 1: Selection Sort (C++)

3.3 INSERTION SORT

```
1 int insertionSort(StringArr* data) {
2     // Number of comparisons starts at 0
3     int comparisons = 0;
4
5     // We begin with the second element because an array of size 1 is already sorted
6     // So no need to check on the first element
7     for (int i = 1; i < data->length; i++) {
8         // Save the current element for later use
9         std::string currentVal = data->arr[i];
10    }
```

```

11     // Comparisons are going to start with the previous index
12     int j = i - 1;
13
14     // Continue until j is a valid index (< 0) or until we found an element that is less
15     // than the
16     // current element that is being sorted
17     while (j >= 0 && currentVal.compare(data->arr[j]) < 0) {
18         // We made a comparison so increment it
19         comparisons++;
20
21         // Shift the compared element over 1 to make room for the element being sorted
22         data->arr[j + 1] = data->arr[j];
23         j--;
24     }
25
26     // After the loop, we want to increment comparisons only if j >= 0 because
27     // if j < 0, then the boolean expression would have immediately returned false
28     // without making
29     // a comparison
30     if (j >= 0) {
31         comparisons++;
32     }
33
34     // Place the value in its proper place
35     data->arr[j + 1] = currentVal;
36 }
37
38 // Return the number of comparisons
39 return comparisons;
40 }

```

Listing 2: Insertion Sort (C++)