

stop using native HTML5

Kyle Simpson

http://getify.me

@getify

http://yj9.geti.fi/slides/strangeloop


native HTML5 (JavaScript) considered harmful!!!!



O'REILLY®

Christopher Schmitt & Kyle Simpson

O'Reilly discount code: "AUTHD"




Browser Versions Must Die



HTML5 & Friends

We Puzzle It!





```
23
            var sid = sessionStorage.getItem("session_id");
            if (sid) return sid;
24
            return null;
25
26
27
28
      function saveSessionId(sid) {
29
            sessionStorage.setItem("session_id",sid);
30
31
32
       function forgetSessionId() {
            sessionStorage.removeItem("session_id");
33
34
35
36
       function saveUserInfo(uinfo) {
            localStorage.setItem("user_info", JSON.stringify(uinfo));
37
38
39
40
      function retrieveUserInfo() {
            var uinfo = localStorage.getItem("user_info");
41
42
               (uinfo) return JSON.parse(uinfo);
            return {};
43
44
45
```

```
433
             $canvas.attr({width:tiled_width,height:tiled_height});
436
             context = $canvas.get(0).getContext("2d");
437
             context.drawImage($orig_preview_img.get(0),
438
                 img_x, img_y, tiled_width/img_ratio, tiled_height/img_ratio,
439
                 0, 0, tiled_width, tiled_height
440
441
             );
             new_img_data = $canvas.get(0).toDataURL(preview_img_type);
442
443
444
             // update the preview image with the new image data
445
             $preview_img
             .bind("load", function(evt){
446
                 $(this).unbind("load");
447
448
449
                 $preview_grid = buildPreviewGrid($preview_img,tiled_width,tile
450
451
                 // save grid meta-data (used later during game upload)
452
                 $preview_grid.attr({
453
                     "data-rows": rows,
454
                     "data-cols": cols,
455
                     "data-tile-size": tile_size
                 });
456
457
458
                 $preview_container
```

```
345
             context.save():
346
             // first, draw the grid to use a mask for the preview image
             context.beginPath();
347
348
            drawGrid();
             context.clip(); // turns the drawing into a mask
349
350
351
             // next, draw the preview image onto the canvas using the mask
352
             context.drawImage(spreview_img.get(0),0,0);
             context.restore();
353
354
             // set composite mode for redrawing the grid on top of the preview
355
             context.globalCompositeOperation = "lighter";
356
357
             context.globalAlpha = 0.7;
358
             // now, redraw the grid clipped preview image again, using the com
359
360
             context.save();
361
             context.beginPath();
            drawGrid();
362
363
             context.clip(); // turns the drawing into a mask
364
             // redraw the preview image (masked by the grid) onto the canvas
365
             context.drawImage(spreview_img.get(0),0,0);
366
             context.restore();
367
```

```
function readFile(file) {
510
511
             // render the initial image preview with the dataURI
             function preview(dataURI) {
512
                 $preview_container.empty();
513
                 renderPreview(dataURI, file.type);
514
             }
515
516
517
             var $preview_container = $("#preview_container");
518
             $preview_container.html("Please wait...processing.");
519
520
521
             // is the local file access FileReader API defined?
522
                (FILEREADER_DEFINED) {
523
                 var reader = new FileReader();
                 // listen for when file read has finished
524
                 reader.onload = function(evt) {
525
526
                     reader.onload = null;
                     preview(evt.target.result);
527
                 };
528
529
530
                 // read the file, format read data as data-URL
                 reader.readAsDataURL(file);
531
532
```

aslicknet (a) slicknet

http://guf.geti.fi/html5/js/zakas

Specs

"The best thing about standards is that there's so many to choose from."

tous 5

"behavior is as intended" (crocky)

prefixes

what-about-vendor-postfixes-webkit

progress

71,510,162 seconds left

verbosity

overly repetitive and redundant

facades

"i'll write yet-another-anotheranother-another-anotheranother framework"

-- every dev, constantly

"framework" design

"Perfection is achieved, not when there is nothing more to add, but when there is nothing left to take away."

-- Antoine de Saint-Exupery

modular

Gimme everything on the buffet

facade design

light sugar

Where's my super sized soft drink?

not shims/ not shims/ polyfills

The 80's are definitely coming back

80%

Good enough is usually good enough

facade design

fix* bugs

Don't let the bed bugs bite

smoothe* quirks

"Iced Orange Banango" smoothie flavor

facade design

conceptuals

"disconceptualizations"

ready yet?

code for today

http://h5ive.com

G storage

```
• save(1
        prefs: { /* ... */ }
   });
10
11
12
   session
13
   .save({
        session_id: 123456,
        foo: "bar baz"
16 })
    .discard(["foo"]);
18
19
   temp.save({
        active login: session get("session
```

G storage

```
35
36
37
                return publicAPI;
38
39
            function get(keys) {
40
                var i, val, ret = [], now = (new Date()).getTime();
41
42
43
                if (Object.prototype.toString.call(keys) !== "[object
44
                for (i=0; i<keys.length; i++) {</pre>
45
                     val = ret[keys[i]] = store.getItem(keys[i]);
46
                     try {
47
                         val = JSON.parse(val);
48
                         if ("h5ive:data" in val) {
49
                             if ("h5ive:expires" in val && now >= val
50
                                  delete ret[keys[i]];
51
52
                                  continue;
53
                             ret[keys[i]] = val["h5ive:data"].
```



```
.connect("http://example.com")
   .send(data)
   .error(function(status, statusText){
        console.error("XHR Error: " + status
   })
   .progress(function(info){
        console.log("Progress: " +
            Math.round(info.bytesLoaded / info.byte
13
   })
14
   success(function(res){
        console.log(res);
```



```
8
            var XHR, publicAPI, used = false;
10
            function connect(url) {
                if (used) reset();
11
12
                used = true;
13
                for (var header in opts.headers) {
                     XHR.setRequestHeader(header,opts.heade
15
16
                XHR.open(opts.method,url,false,opts.user,d
                return publicAPI;
17
18
19
20
            function send(data) {
21
                XHR.send(data);
22
                return publicAPI;
23
```

<anvas>

```
35
        ł,
36
        fill: {
37
            color: "red"
38
   })
39
40
    .rect({
41
        fill: [40,40,25,25]
42
   })
43
    .rect({
        stroke: [400,400,50,50]
44
45
   })
46
   .popState()
47
    .startPath(275,275)
48
    .defineSegments([
49
        { arc: [275,275,100,Math.PI/2,3*Math.PI/2,true] }
    1)
50
    .endPath({
51
```



```
in_path = true;
81
82
83
                 return publicAPI;
            }
84
85
            function defineSegments(segments) {
86
87
                 var segment, type;
88
89
                 if (!in_path) throw new Error("Segments need a
90
91
                segments = segments || [];
92
93
                 for (var i=0; i<segments.length; i++) {</pre>
94
                     segment = segments[i];
                     type = Object.keys(segment)[0];
95
                     if (type in segmentTypes) {
96
                         CONTEXT[type].apply(CONTEXT, segment[typ
97
98
99
```

getUserMedia

```
ท๖
   .userMedia({
       video: true
   .stream(function(src){
       var video = document.getElementById("mycam"
       video.src = src;
       video.play();
   })
10
   .failed(function(){
       alert("Access to the media failed.");
11
   })
13
```

getUserMedia

```
failed_cb.apply(h5.userMedia,argument
43
45
                 else {
46
                     failed_cb = true;
                     failed_args = [].slice.call(arguments
47
48
49
50
51
            success_cb = successCB;
            failed_cb = failedCB;
52
53
54
            if (gUM) {
55
                for (idx in opts) { if (opts.has0wnProper
                     opts_str += (opts_str != "" ?
56
                 }}
57
58
                 try {
59
                     gUM.call(navigator, opts, handleSuccess
```

History

Web Workers

Web Socket

Geolocation

<audio> / <video>

File / FileSystem

PeerConnection/WebRTC

Web DBs

BlobBuilder

Blob URL

FormData

Device APIs

Server-Sent Events

appCache

• • •

what's left?

Thanks!!

Questions?

Kyle Simpson http://getify.me @getify