

Assignment 5: REST API

1. General

- ◆ All ID's (like "5" in the endpoint examples below) are assigned by the back-end and are implementation specific. Therefore, it's OK if your IDs are different than appear here, in the curl/Postman queries, or the sample output. The UI will work with whatever IDs you pass it.
- ◆ All commands return HTTP 200 (OK) unless otherwise stated.
- ◆ Any endpoint which accepts an ID (be it in the path, query string, or in the body) must return an HTTP 404 error with a meaningful message if the ID does not exist.
- ◆ Most arrays must be in sorted order so that the UI displays values in correct order.
- ◆ See website for provided data transfer objects (DTOs) for REST API to exchange with frontend.

GET /api/about

- ◆ Return a simple structure of some description of your app (you choose!) and your name.

GET /api/dump-model

- ◆ Trigger the model dump to the server's console. If you are running the server via IntelliJ, then you'll see the output inside the IntelliJ console.
- ◆ No content is returned to the client; this just outputs the debug information to the terminal.

2. Access Departments, Courses, Offerings, and Sections

GET /api/departments

- ◆ List of all departments.
- ◆ Each department has an ID (deptId) and a name (name).

GET /api/departments/5/courses

- ◆ Lists all courses for department with deptId 5.
- ◆ Each course has an ID (courseId) and a number (catalogNumber).
 - Note that the course number can be more than just an integer (such as 105W, or 2XX)

GET /api/departments/5/courses/123/offerings

- ◆ Lists the offerings of the course with courseId 123 inside department with deptId 5.
- ◆ Each course offering has:
 - courseOfferingId: The ID of this offering; assigned by the back-end.
 - location: String describing where the course is offered, such as "SURREY"
 - instructors: String representing the names of the instructors who teach the offering.
 - year: Integer value for the year, such as 2018.
 - semesterCode: Integer value for the SFU semester code, such as 1187
 - term: String describing the semester of the year, such as "Fall".

GET /api/departments/5/courses/123/offerings/4321

- ◆ Return the list of sections for the offering with courseOfferingId 4321, in the course with courseId 123, in the department with deptId 5.
 - For example, an offering in Surrey of CMPT 130 may have lecture and tutorial "sections".
- ◆ Each section expected to have:
 - type: String describing the section type (comes from data file).
 - enrollmentTotal: Integer holding the total number of students enrolled in this section.
 - enrollmentCap: Integer holding the capacity of the section.

department
-> list of courses

need to return total students in 1 department in 1 semester

each course
-> list of offerings

each course offering

3. Graph Data - Bonus

-> list of sections (has type LEC)

-> semester

GET `/api/stats/students-per-semester?deptId=5`

- ◆ Returns a list of data points showing how many spaces in courses were filled by students during each semester for the selected department.
 - Return one data point for each semester between the start and end of your data (see below).
 - Each returned data point is for a single semester and stores the total number of seats taken by students in lecture (“LEC”) sections for courses in the given department during that semester.
 - Calculate this value for a given semester by:
 - ▶ Find the set of course offerings in the selected department for each semester of interest.
 - ▶ Then sum up the `enrollmentTotal` values for all “LEC” type sections of those offerings.
- ◆ Returned data expected to be an array of objects:
 - `semesterCode`: The SFU semester code.
 - `totalCoursesTaken`: The total number of filled seats in all courses offered by the selected department during that semester.
- ◆ The `semesterCode` must start at the first semester for which your system is given data, and must go up to the last semester for which you have data.
 - Use only the semesters 1 (Spring), 4 (Summer), and 7 (Fall).
 - Do not skip over a semester if there is no data for that semester: include it in the data set.
 - Array must be sorted by `semesterCode` (i.e., in chronological order).

4. Add New Offering / Section

POST `/api/addoffering`

- ◆ Add a new section to the data stored by the system.
 - This mimics the behaviour of dynamically adding data that could have been found as a row in the input data file.
- ◆ Returns HTTP 201: Created.
- ◆ POST message has the following fields:
 - `semester`: The SFU semester code, such as 1181.
 - `subjectName`: The department name, such as “CMPT”
 - `catalogNumber`: The course number, such as 213 for CMPT 213.
 - `location`: String representing the location, such as “SURREY”.
 - `enrollmentCap`: Total number of filled seats in the class (number of students).
 - `component`: The component or section code, such as “LEC” or “TUT”.
 - `enrollmentTotal`: Total number of seats in the class.
 - `instructor`: String for the instructor’s name.
- ◆ Note that when data is added to the model the Web UI will not automatically refresh; user must manually reload the current page to have the data update.
- ◆ Adding a new section via this endpoint can add new offerings, courses, and even departments to the system.
- ◆ TIP: Do not repeat yourself! You already have code to do this task when you read data from the CSV file; reuse that same code.

5. Course Change Watchers

GET /api/watchers

- ◆ Lists all change-watchers.
 - A course change watcher (“watcher”) is stored on the server and allows the user to “watch” a specific course for sections being added.
 - When created the change-watcher registers as an observer with the desired course.
 - When the course knows that it is changed (in response to reading a new row from the CSV file, or from data dynamically added via the API) it notifies the watcher.
 - The watcher maintains a list of descriptions of sections (i.e. components) being added to a course.
- ◆ Each watcher object returned by this endpoint has:
 - `id`: Watcher’s ID, as assigned by the back-end.
 - `department`: JSON object for the department of the course being watched. Expected sub-fields are `deptId` and `name`.
 - `course`: JSON object for the course being watched. Expected sub-fields are `courseId` and `catalogNumber`.
 - `events`: Array of strings, showing the history of events it has observed.
 - ▶ Expected format of each event should be similar to the template:
[date]: Added section [type] with enrollment ([total]/[cap]) to offering [term] [year]
 - ▶ For example:
Sun Mar 25 21:41:35 PDT 2018: Added section LEC with enrollment (89 / 90) to offering Spring 2019
 - ▶ [total] and [cap] should be the new amount added by this change, rather than the total number. i.e., if you are adding an extra tutorial holding 23 students with a cap of 30 to an existing set of tutorials for a course offering, the event should show (23/30), not the much greater total of all tutorials for this section.

POST /api/watchers

- ◆ Create a new watcher.
- ◆ Returns HTTP 201: Created.
- ◆ Request body contents:
 - `deptId`: ID of the department in which the course is found.
 - `courseId`: ID of the course which is to be watched.

GET /api/watchers/42

- ◆ Get the list of events recorded by the watcher with ID 42.
- ◆ See GET /api/watchers section above for fields.
(This is returning just one watched, /api/watchers returns an array of all watchers).

DELETE /api/watchers/42

- ◆ Delete the watcher with ID 42.
- ◆ Returns HTTP 204: No content.