

Class 09: Halloween Mini-Project

Josie (A11433761)

1: Import data

```
candy_file<-"candy-data.csv"
candy<-read.csv(candy_file, row.names = 1)
head(candy)
```

	chocolate	fruity	caramel	peanutyalmondy	nougat	crispedricewafer
100 Grand	1	0	1	0	0	1
3 Musketeers	1	0	0	0	1	0
One dime	0	0	0	0	0	0
One quarter	0	0	0	0	0	0
Air Heads	0	1	0	0	0	0
Almond Joy	1	0	0	1	0	0

	hard	bar	pluribus	sugarpercent	pricepercent	winpercent
100 Grand	0	1	0	0.732	0.860	66.97173
3 Musketeers	0	1	0	0.604	0.511	67.60294
One dime	0	0	0	0.011	0.116	32.26109
One quarter	0	0	0	0.011	0.511	46.11650
Air Heads	0	0	0	0.906	0.511	52.34146
Almond Joy	0	1	0	0.465	0.767	50.34755

```
nrow(candy)
```

```
[1] 85
```

```
sum(candy$fruity)
```

```
[1] 38
```

```
dim(candy)
```

```
[1] 85 12
```

2: Favorite Candy

```
candy["Dum Dums",]$winpercent
```

```
[1] 39.46056
```

```
library(dplyr)
```

Attaching package: 'dplyr'

The following objects are masked from 'package:stats':

filter, lag

The following objects are masked from 'package:base':

intersect, setdiff, setequal, union

```
candy|>
filter( rownames(candy)=="Dum Dums")|>
  select(winpercent)
```

```
      winpercent
Dum Dums  39.46056
```

```
candy|>
filter( rownames(candy)=="Kit Kat")|>
  select(winpercent)
```

```
      winpercent
Kit Kat   76.7686
```

```
candy|>
  filter(rownames(candy)%in% c("Kit Kat", "Tootsie Roll Snack Bars"))|>
  select(winpercent)
```

	winpercent
Kit Kat	76.7686
Tootsie Roll Snack Bars	49.6535

%in% operator useful for checking the intersection

Install “skimr” in console

```
library("skimr")
skim(candy)
```

Table 1: Data summary

Name	candy
Number of rows	85
Number of columns	12
Column type frequency:	
numeric	12
Group variables	None


Variable type: numeric

skim_variable	n_missing	complete_rate	mean	sd	p0	p25	p50	p75	p100	hist
chocolate	0	1	0.44	0.50	0.00	0.00	0.00	1.00	1.00	
fruity	0	1	0.45	0.50	0.00	0.00	0.00	1.00	1.00	
caramel	0	1	0.16	0.37	0.00	0.00	0.00	0.00	1.00	
peanutyalmondy	0	1	0.16	0.37	0.00	0.00	0.00	0.00	1.00	
nougat	0	1	0.08	0.28	0.00	0.00	0.00	0.00	1.00	
crispedricewafer	0	1	0.08	0.28	0.00	0.00	0.00	0.00	1.00	
hard	0	1	0.18	0.38	0.00	0.00	0.00	0.00	1.00	
bar	0	1	0.25	0.43	0.00	0.00	0.00	0.00	1.00	
pluribus	0	1	0.52	0.50	0.00	0.00	1.00	1.00	1.00	
sugarpercent	0	1	0.48	0.28	0.01	0.22	0.47	0.73	0.99	
pricepercent	0	1	0.47	0.29	0.01	0.26	0.47	0.65	0.98	

skim_variable	n_missing	complete_rate	mean	sd	p0	p25	p50	p75	p100	hist
winpercent	0	1	50.32	14.71	22.45	39.14	47.83	59.86	84.18	


Q6:winpercent column is on a very different scale than the rest of the data. It will need to be scaled.

```
hist(candy$winpercent)
```



```
library(ggplot2)

ggplot(candy)+ aes(winpercent)+
  geom_histogram(bins=10)+
  theme_bw()
```



```
summary(candy$winpercent)
```

Min.	1st Qu.	Median	Mean	3rd Qu.	Max.
22.45	39.14	47.83	50.32	59.86	84.18

Q11: Chocolate ranks higher than fruity candy

```
inds<-candy$chocolate==1
candy[inds,]$winpercent
```

```
[1] 66.97173 67.60294 50.34755 56.91455 38.97504 55.37545 62.28448 56.49050
[9] 59.23612 57.21925 76.76860 71.46505 66.57458 55.06407 73.09956 60.80070
[17] 64.35334 47.82975 54.52645 70.73564 66.47068 69.48379 81.86626 84.18029
[25] 73.43499 72.88790 65.71629 34.72200 37.88719 76.67378 59.52925 48.98265
[33] 43.06890 45.73675 49.65350 81.64291 49.52411
```

```
chocolate.win<-candy|>
  filter(chocolate==1)|>
  select(winpercent)
```

```
fruit.win<-candy|>
  filter(fruity==1)|>
  select(winpercent)
```

```
t.test(fruit.win,chocolate.win)
```

Welch Two Sample t-test

```
data: fruit.win and chocolate.win
t = -6.2582, df = 68.882, p-value = 2.871e-08
alternative hypothesis: true difference in means is not equal to 0
95 percent confidence interval:
 -22.15795 -11.44563
sample estimates:
mean of x mean of y
 44.11974  60.92153
```

3: Candy Rankings

Lowest ranking candies: Nik L Nip,Boston Baked Beans,Chiclets,Super Bubble,Jawbusters
 Highest ranking candies: Reese's Peanut Butter cup,Reese's Miniatures,Twix,Kit Kat,Snickers

```
head(candy[order(candy$winpercent),], n=5)
```

	chocolate	fruity	caramel	peanut	almondy	nougat
Nik L Nip	0	1	0		0	0
Boston Baked Beans	0	0	0		1	0
Chiclets	0	1	0		0	0
Super Bubble	0	1	0		0	0
Jawbusters	0	1	0		0	0

	crispedrice	wafer	hard bar	pluribus	sugarpercent	pricepercent
Nik L Nip	0	0	0	1	0.197	0.976
Boston Baked Beans	0	0	0	1	0.313	0.511
Chiclets	0	0	0	1	0.046	0.325
Super Bubble	0	0	0	0	0.162	0.116
Jawbusters	0	1	0	1	0.093	0.511

	winpercent
Nik L Nip	22.44534

```
Boston Baked Beans    23.41782
Chiclets              24.52499
Super Bubble         27.30386
Jawbusters           28.12744
```

```
sort(candy$winpercent)
```

```
[1] 22.44534 23.41782 24.52499 27.30386 28.12744 29.70369 32.23100 32.26109
[9] 33.43755 34.15896 34.51768 34.57899 34.72200 35.29076 36.01763 37.34852
[17] 37.72234 37.88719 38.01096 38.97504 39.01190 39.14106 39.18550 39.44680
[25] 39.46056 41.26551 41.38956 41.90431 42.17877 42.27208 42.84914 43.06890
[33] 43.08892 44.37552 45.46628 45.73675 45.99583 46.11650 46.29660 46.41172
[41] 46.78335 47.17323 47.82975 48.98265 49.52411 49.65350 50.34755 51.41243
[49] 52.34146 52.82595 52.91139 54.52645 54.86111 55.06407 55.10370 55.35405
[57] 55.37545 56.49050 56.91455 57.11974 57.21925 59.23612 59.52925 59.86400
[65] 60.80070 62.28448 63.08514 64.35334 65.71629 66.47068 66.57458 66.97173
[73] 67.03763 67.60294 69.48379 70.73564 71.46505 72.88790 73.09956 73.43499
[81] 76.67378 76.76860 81.64291 81.86626 84.18029
```

```
inds<-order(candy$winpercent)
head(candy[inds,])
```

	chocolate	fruity	caramel	peanut	almond	nougat
Nik L Nip	0	1	0		0	0
Boston Baked Beans	0	0	0		1	0
Chiclets	0	1	0		0	0
Super Bubble	0	1	0		0	0
Jawbusters	0	1	0		0	0
Root Beer Barrels	0	0	0		0	0

	crisped	rice	wafer	hard	bar	pluribus	sugar	percent	price	percent
Nik L Nip				0	0	0	1	0.197	0.976	
Boston Baked Beans				0	0	0	1	0.313	0.511	
Chiclets				0	0	0	1	0.046	0.325	
Super Bubble				0	0	0	0	0.162	0.116	
Jawbusters				0	1	0	1	0.093	0.511	
Root Beer Barrels				0	1	0	1	0.732	0.069	

	winpercent
Nik L Nip	22.44534
Boston Baked Beans	23.41782
Chiclets	24.52499
Super Bubble	27.30386

Jawbusters	28.12744
Root Beer Barrels	29.70369


```
inds<-order(candy$winpercent,decreasing=T)
head(candy[inds,],5)
```

	chocolate	fruity	caramel	peanut	almond	nougat
Reese's Peanut Butter cup	1	0	0		1	0
Reese's Miniatures	1	0	0		1	0
Twix	1	0	1		0	0
Kit Kat	1	0	0		0	0
Snickers	1	0	1		1	1


	crisped	rice	wafer	hard	bar	pluribus	sugar
Reese's Peanut Butter cup		0	0	0		0	0.720
Reese's Miniatures		0	0	0		0	0.034
Twix		1	0	1		0	0.546
Kit Kat		1	0	1		0	0.313
Snickers		0	0	1		0	0.546

	price	percent	winpercent
Reese's Peanut Butter cup	0.651	84.18029	
Reese's Miniatures	0.279	81.86626	
Twix	0.906	81.64291	
Kit Kat	0.511	76.76860	
Snickers	0.651	76.67378	

```
ggplot(candy)+
  aes(x=winpercent, y=reorder(rownames(candy),winpercent))+
  geom_col()
```


```
my_cols=rep("black", nrow(candy))
my_cols[as.logical(candy$chocolate)] = "chocolate"
my_cols[as.logical(candy$bar)] = "brown"
my_cols[as.logical(candy$fruity)] = "pink"
ggplot(candy)+
  aes(x=winpercent, y=reorder(rownames(candy),winpercent))+
  geom_col(fill=my_cols)
```



Worst chocolate ranked: Sixlets Best fruity candy ranked: Starbursts

```
#Finding Sour Patch Kids and coloring the bar

my_cols=rep("black", nrow(candy))
my_cols[as.logical(candy$chocolate)] = "chocolate"
my_cols[as.logical(candy$bar)] = "brown"
my_cols[as.logical(candy$fruity)] = "pink"
my_cols[rownames(candy)=="Sour Patch Kids"] = "blue"
ggplot(candy)+
  aes(x=winpercent, y=reorder(rownames(candy),winpercent))+
  geom_col(fill=my_cols)
```



```
ord <- order(candy$pricepercent, decreasing = TRUE)
head( candy[ord,c(11,12)], n=5 )
```


	pricepercent	winpercent
Nik L Nip	0.976	22.44534
Nestle Smarties	0.976	37.88719
Ring pop	0.965	35.29076
Hershey's Krackel	0.918	62.28448
Hershey's Milk Chocolate	0.918	56.49050

4: Taking a look at pricepercent

```
library(ggrepel)

ggplot(candy) +
  aes(winpercent, pricepercent, label=rownames(candy)) +
  geom_point(col=my_cols) +
  geom_text_repel(col=my_cols, size=3.3, max.overlaps = 8)
```

Warning: ggrepel: 52 unlabeled data points (too many overlaps). Consider increasing max.overlaps




5: Exploring the correlation structure

```
library(corrplot)
```

```
corrplot 0.95 loaded
```

```
cij <- cor(candy)
corrplot(cij)
```



6: Principal Component Analysis


```
pca <- prcomp(candy,scale=TRUE )
summary(pca)
```

Importance of components:

	PC1	PC2	PC3	PC4	PC5	PC6	PC7
Standard deviation	2.0788	1.1378	1.1092	1.07533	0.9518	0.81923	0.81530
Proportion of Variance	0.3601	0.1079	0.1025	0.09636	0.0755	0.05593	0.05539
Cumulative Proportion	0.3601	0.4680	0.5705	0.66688	0.7424	0.79830	0.85369


	PC8	PC9	PC10	PC11	PC12
Standard deviation	0.74530	0.67824	0.62349	0.43974	0.39760
Proportion of Variance	0.04629	0.03833	0.03239	0.01611	0.01317
Cumulative Proportion	0.89998	0.93832	0.97071	0.98683	1.00000

```
plot(pca$x[,2],col=my_cols,pch=16)
```



ggplot version

```
my_data <- cbind(candy, pca$x[,1:3])
p<-ggplot(my_data)+
  aes(x=PC1, y=PC2,
      size=winpercent/100,
      text=rownames(my_data),
      label=rownames(my_data)) +
  geom_point(col=my_cols)
p
```




```
p + geom_text_repel(size=3.3, col=my_cols, max.overlaps = 20) +
  theme(legend.position = "none") +
  labs(title="Halloween Candy PCA Space",
        subtitle="Colored by type: chocolate bar (dark brown), chocolate other (light brown),
        caption="Data from 538")
```

Warning: ggrepel: 20 unlabeled data points (too many overlaps). Consider increasing max.overlaps


Halloween Candy PCA Space

Colored by type: chocolate bar (dark brown), chocolate other (light brown),



Data from 538

```
par(mar=c(8,4,2,2))
barplot(pca$rotation[,1], las=2, ylab="PC1 Contribution")
```



Q24: Fruity,hard and pluribus make sense to be correlated with each other because that is how that type of candy is usually seen. The PC1 reflects that.