https://joskapotin.github.io/joskapotin_14_27052022/jquery-version/employee-list.html

100
Performance

92
Best Practices

There were issues affecting this run of Lighthouse:

- **There may be stored data affecting loading performance in this location: IndexedDB. Audit this page in an incognito window to prevent those resources from affecting your scores.**

100

Performance

Values are estimated and may vary. The performance score is calculated directly from these metrics. See calculator.

▲ 0–49   50–89   90–100

METRICS

Expand view

First Contentful Paint	Time to Interactive
0.6 s	**0.6 s**

Speed Index	Total Blocking Time
0.6 s	**0 ms**

Largest Contentful Paint	Cumulative Layout Shift
0.6 s	**0.001**

[View Original Trace]   [View Treemap]

Show audits relevant to: All   FCP   TBT   LCP   CLS

OPPORTUNITIES

Opportunity	Estimated Savings
Eliminate render-blocking resources	0.34 s ∧

Resources are blocking the first paint of your page. Consider delivering critical JS/CSS inline and deferring all non-critical JS/styles. Learn more. `FCP` `LCP`

URL	Transfer Size	Potential Savings
…css/jquery.dataTables.min.css (cdn.datatables.net)	2.2 KiB	260 ms
…3.5.1/jquery.min.js (ajax.googleapis.com)	30.4 KiB	280 ms
…js/jquery.dataTables.min.js (cdn.datatables.net)	28.5 KiB	80 ms

These suggestions can help your page load faster. They don't directly affect the Performance score.

DIAGNOSTICS

▲ Does not have a `<meta name="viewport">` tag with `width` or `initial-scale` No `<meta name="viewport">` tag found   ∧

A `<meta name="viewport">` not only optimizes your app for mobile screen sizes, but also prevents a 300 millisecond delay to user input. Learn more. `TBT`

○ Avoid chaining critical requests — 5 chains found   ∧

The Critical Request Chains below show you what resources are loaded with a high priority. Consider reducing the length of chains, reducing the download size of resources, or deferring the download of unnecessary resources to improve page load. Learn more. `FCP` `LCP`

Maximum critical path latency: **130 ms**

Initial Navigation

  …jquery-version/employee-list.html (joskapotin.github.io)

    …3.5.1/jquery.min.js (ajax.googleapis.com) **- 80 ms, 30.37 KiB**

    …js/jquery.dataTables.min.js (cdn.datatables.net) **- 70 ms, 28.47 KiB**

    …css/jquery.dataTables.min.css (cdn.datatables.net) **- 70 ms, 2.18 KiB**

    …jquery-version/employee-list.js (joskapotin.github.io) **- 60 ms, 0.46 KiB**

    …jquery-version/app.css (joskapotin.github.io) **- 50 ms, 0.34 KiB**

○ Keep request counts low and transfer sizes small — 8 requests • 63 KiB   ∧

To set budgets for the quantity and size of page resources, add a budget.json file. [Learn more](#).

Resource Type	Requests	Transfer Size
Total	8	63.0 KiB
Script	3	59.3 KiB
Stylesheet	2	2.5 KiB
Document	1	0.6 KiB
Image	2	0.5 KiB
Media	0	0.0 KiB
Font	0	0.0 KiB
Other	0	0.0 KiB
Third-party	5	61.5 KiB

○ Largest Contentful Paint element — 1 element found ⌃

This is the largest contentful element painted within the viewport. [Learn More](#) (LCP)

Element	
	h1

○ Avoid large layout shifts — 1 element found ⌃

These DOM elements contribute most to the CLS of the page. (CLS)

Element	CLS Contribution

Element	CLS Contribution
a	0.001

○ Avoid long main-thread tasks — 1 long task found   ⌃

Lists the longest tasks on the main thread, useful for identifying worst contributors to input delay. Learn more TBT

URL	Start Time	Duration
chrome-extension://bnjjngeaknajbdcgpfkgnonkmififhfo/build/content-script.js	254 ms	63 ms

More information about the performance of your application. These numbers don't directly affect the Performance score.

PASSED AUDITS (33)   Hide

Properly size images   ⌃

Serve images that are appropriately-sized to save cellular data and improve load time. Learn more.

Defer offscreen images   ⌃

Consider lazy-loading offscreen and hidden images after all critical resources have finished loading to lower time to interactive. Learn more.

Minify CSS   ⌃

Minifying CSS files can reduce network payload sizes. Learn more. FCP LCP

Minify JavaScript   ⌃

Minifying JavaScript files can reduce payload sizes and script parse time. Learn more. FCP LCP

Reduce unused CSS   ⌃

Reduce unused rules from stylesheets and defer CSS not used for above-the-fold content to decrease bytes consumed by network activity. Learn more. FCP LCP

Reduce unused JavaScript ⌃

Reduce unused JavaScript and defer loading scripts until they are required to decrease bytes consumed by network activity. [Learn more](#). LCP

Efficiently encode images ⌃

Optimized images load faster and consume less cellular data. [Learn more](#).

Serve images in next-gen formats ⌃

Image formats like WebP and AVIF often provide better compression than PNG or JPEG, which means faster downloads and less data consumption. [Learn more](#).

Enable text compression ⌃

Text-based resources should be served with compression (gzip, deflate or brotli) to minimize total network bytes. [Learn more](#). FCP LCP

Preconnect to required origins ⌃

Consider adding `preconnect` or `dns-prefetch` resource hints to establish early connections to important third-party origins. [Learn more](#). FCP LCP

Initial server response time was short — Root document took 40 ms ⌃

Keep the server response time for the main document short because all other requests depend on it. [Learn more](#). FCP LCP

URL	Time Spent
…jquery-version/employee-list.html (joskapotin.github.io)	40 ms

Avoid multiple page redirects ⌃

Redirects introduce additional delays before the page can be loaded. [Learn more](#). FCP LCP

○ Preload key requests ⌃

Consider using `<link rel=preload>` to prioritize fetching resources that are currently requested later in page load. [Learn more](#). FCP LCP

Use HTTP/2 ⌃

HTTP/2 offers many benefits over HTTP/1.1, including binary headers and multiplexing. Learn more.

Use video formats for animated content	⌃

Large GIFs are inefficient for delivering animated content. Consider using MPEG4/WebM videos for animations and PNG/WebP for static images instead of GIF to save network bytes. Learn more LCP

Remove duplicate modules in JavaScript bundles	⌃

Remove large, duplicate JavaScript modules from bundles to reduce unnecessary bytes consumed by network activity. TBT

Avoid serving legacy JavaScript to modern browsers	⌃

Polyfills and transforms enable legacy browsers to use new JavaScript features. However, many aren't necessary for modern browsers. For your bundled JavaScript, adopt a modern script deployment strategy using module/nomodule feature detection to reduce the amount of code shipped to modern browsers, while retaining support for legacy browsers. Learn More TBT

Preload Largest Contentful Paint image	⌃

Preload the image used by the LCP element in order to improve your LCP time. Learn more. LCP

Avoids enormous network payloads — Total size was 63 KiB	⌃

Large network payloads cost users real money and are highly correlated with long load times. Learn more. LCP

☑ Show 3rd-party resources (5)

URL	Transfer Size
…3.5.1/jquery.min.js (ajax.googleapis.com)	30.4 KiB
…js/jquery.dataTables.min.js (cdn.datatables.net)	28.5 KiB
…css/jquery.dataTables.min.css (cdn.datatables.net)	2.2 KiB
…jquery-version/employee-list.html (joskapotin.github.io)	0.6 KiB
…jquery-version/employee-list.js (joskapotin.github.io)	0.5 KiB
…jquery-version/app.css (joskapotin.github.io)	0.3 KiB
…images/sort_both.png (cdn.datatables.net)	0.3 KiB

URL	Transfer Size
…images/sort_asc.png (cdn.datatables.net)	0.2 KiB

Uses efficient cache policy on static assets — 2 resources found ⌃

A long cache lifetime can speed up repeat visits to your page. Learn more.

URL	Cache TTL	Transfer Size
…jquery-version/employee-list.js (joskapotin.github.io)	10 m	0 KiB
…jquery-version/app.css (joskapotin.github.io)	10 m	0 KiB

Avoids an excessive DOM size — 135 elements ⌃

A large DOM will increase memory usage, cause longer style calculations, and produce costly layout reflows. Learn more. TBT

Statistic	Element	Value
Total DOM Elements		135
Maximum DOM Depth	option	7
Maximum Child Elements	tbody	10

○ User Timing marks and measures ⌃

Consider instrumenting your app with the User Timing API to measure your app's real-world performance during key user experiences. Learn more.

JavaScript execution time — 0.1 s ⌃

Consider reducing the time spent parsing, compiling, and executing JS. You may find delivering smaller JS payloads helps with this. Learn more. TBT

☑ Show 3rd-party resources (1)

URL	Total CPU Time	Script Evaluation	Script Parse
…3.5.1/jquery.min.js (ajax.googleapis.com)	86 ms	44 ms	2 ms
chrome-extension://bnjjngeaknajbdcgpfkgnonkmififhfo/build/content-script.js	73 ms	41 ms	29 ms

Minimizes main-thread work — 0.2 s   ⌃

Consider reducing the time spent parsing, compiling and executing JS. You may find delivering smaller JS payloads helps with this. Learn more TBT

Category	Time Spent
Script Evaluation	96 ms
Other	40 ms
Style & Layout	38 ms
Script Parsing & Compilation	34 ms
Parse HTML & CSS	14 ms
Rendering	10 ms

All text remains visible during webfont loads   ⌃

Leverage the font-display CSS feature to ensure text is user-visible while webfonts are loading. Learn more. FCP LCP

Minimize third-party usage — Third-party code blocked the main thread for 0 ms   ⌃

Third-party code can significantly impact load performance. Limit the number of redundant third-party providers and try to load third-party code after your page has primarily finished loading. Learn more. TBT

Third-Party	Transfer Size	Main-Thread Blocking Time
Google CDN	30 KiB	0 ms
…3.5.1/jquery.min.js (ajax.googleapis.com)	30 KiB	0 ms

◯   Lazy load third-party resources with facades   ⌃

Some third-party embeds can be lazy loaded. Consider replacing them with a facade until they are required. [Learn more](#). TBT

○ Largest Contentful Paint image was not lazily loaded ⌃

Above-the-fold images that are lazily loaded render later in the page lifecycle, which can delay the largest contentful paint. [Learn more](#).

Uses passive listeners to improve scrolling performance ⌃

Consider marking your touch and wheel event listeners as `passive` to improve your page's scroll performance. [Learn more](#).

Avoids `document.write()` ⌃

For users on slow connections, external scripts dynamically injected via `document.write()` can delay page load by tens of seconds. [Learn more](#).

○ Avoid non-composited animations ⌃

Animations which are not composited can be janky and increase CLS. [Learn more](#) CLS

○ Image elements have explicit `width` and `height` ⌃

Set an explicit width and height on image elements to reduce layout shifts and improve CLS. [Learn more](#) CLS

Avoids `unload` event listeners ⌃

The `unload` event does not fire reliably and listening for it can prevent browser optimizations like the Back-Forward Cache. Use `pagehide` or `visibilitychange` events instead. [Learn more](#)

92

Best Practices

BROWSER COMPATIBILITY

⚠ Page lacks the HTML doctype, thus triggering quirks-mode Document must contain a doctype ⌃

Specifying a doctype prevents the browser from switching to quirks-mode. [Learn more](#).

TRUST AND SAFETY

○ Ensure CSP is effective against XSS attacks ⌃

A strong Content Security Policy (CSP) significantly reduces the risk of cross-site scripting (XSS) attacks. Learn more

Description	Directive	Severity
No CSP found in enforcement mode		High

GENERAL

○ Detected JavaScript libraries ⌃

All front-end JavaScript libraries detected on the page. Learn more.

Name	Version
jQuery	3.5.1

PASSED AUDITS (12)   Hide

Uses HTTPS ⌃

All sites should be protected with HTTPS, even ones that don't handle sensitive data. This includes avoiding mixed content, where some resources are loaded over HTTP despite the initial request being served over HTTPS. HTTPS prevents intruders from tampering with or passively listening in on the communications between your app and your users, and is a prerequisite for HTTP/2 and many new web platform APIs. Learn more.

Avoids requesting the geolocation permission on page load ⌃

Users are mistrustful of or confused by sites that request their location without context. Consider tying the request to a user action instead. Learn more.

Avoids requesting the notification permission on page load ⌃

Users are mistrustful of or confused by sites that request to send notifications without context. Consider tying the request to user gestures instead. Learn more.

Avoids front-end JavaScript libraries with known security vulnerabilities ⌃

Some third-party scripts may contain known security vulnerabilities that are easily identified and exploited by attackers. [Learn more](#).

Allows users to paste into password fields ⌃

Preventing password pasting undermines good security policy. [Learn more](#).

Displays images with correct aspect ratio ⌃

Image display dimensions should match natural aspect ratio. [Learn more](#).

Serves images with appropriate resolution ⌃

Image natural dimensions should be proportional to the display size and the pixel ratio to maximize image clarity. [Learn more](#).

Properly defines charset ⌃

A character encoding declaration is required. It can be done with a `<meta>` tag in the first 1024 bytes of the HTML or in the Content-Type HTTP response header. [Learn more](#).

Avoids deprecated APIs ⌃

Deprecated APIs will eventually be removed from the browser. [Learn more](#).

No browser errors logged to the console ⌃

Errors logged to the console indicate unresolved problems. They can come from network request failures and other browser concerns. [Learn more](#)

No issues in the `Issues` panel in Chrome Devtools ⌃

Issues logged to the `Issues` panel in Chrome Devtools indicate unresolved problems. They can come from network request failures, insufficient security controls, and other browser concerns. Open up the Issues panel in Chrome DevTools for more details on each issue.

Page has valid source maps ⌃

Source maps translate minified code to the original source code. This helps developers debug in production. In addition, Lighthouse is able to provide further insights. Consider deploying source maps to take advantage of these benefits. [Learn more](#).

NOT APPLICABLE (1)   Hide

○ Fonts with `font-display: optional` are preloaded ⌃

Preload `optional` fonts so first-time visitors may use them. [Learn more](#)

Captured at Aug 3, 2022, 4:49 PM GMT+2

Initial page load

Emulated Desktop with Lighthouse 9.6.1

Custom throttling

Single page load

Using Chromium 103.0.0.0 with devtools

Generated by **Lighthouse** 9.6.1 | File an issue