


Easy and Intelligent Pivot Tables with DuckDB



After exploring the various capabilities of DuckDB <u>in my earlier articles</u>, I want to focus more on its powerful data analytical functionality. In this article, I will delve into the PIVOT command, an amazing powerful tool for creating pivot tables, even from complex datasets.

Pivot tables are a staple for data analysis, but they can be tedious to set up in some systems. DuckDB makes this process both simple and efficient. Let me demonstrate it with a classic "sales" example, inspired by a testing scenario I explored using ChatGPT.

The Example Data

I will use a sales table that tracks sales figures for various products, salespeople, and years. Here's the table structure and some sample data:

```
CREATE TABLE sales (
    id SERIAL PRIMARY KEY,
    salesperson VARCHAR(50),
    product VARCHAR(50),
    year INT,
    sales_amount NUMERIC
);
INSERT INTO sales (salesperson, product, year, sales_amount) VALUES
('Alice', 'Laptop', 2022, 1200),
('Alice', 'Phone', 2022, 800),
('Alice', 'Tablet', 2022, 300),
('Alice', 'Laptop', 2023, 1400),
('Alice', 'Phone', 2023, 900),
('Alice', 'Tablet', 2023, 400),
('Bob', 'Laptop', 2022, 1000),
('Bob', 'Phone', 2022, 600),
('Bob', 'Laptop', 2023, 1100),
('Charlie', 'Tablet', 2022, 500),
('Charlie', 'Laptop', 2022, 1100),
('Charlie', 'Phone', 2022, 700),
('Charlie', 'Tablet', 2023, 600),
('Charlie', 'Laptop', 2023, 1200),
('Charlie', 'Phone', 2023, 800);
```

Pivoting in PostgreSQL: The Hard Way

Creating a pivot table in standard PostgreSQL is of course perfectly possible but involves a fair amount of manual work. For example, let's pivot the sales table to display sales amounts for each salesperson by product and year. Here's the query:

```
SELECT
salesperson,
SUM(sales_amount) FILTER (WHERE product = 'Laptop' AND year = 2022) AS Lapto
SUM(sales_amount) FILTER (WHERE product = 'Phone' AND year = 2022) AS Phone_
SUM(sales_amount) FILTER (WHERE product = 'Tablet' AND year = 2022) AS Table
SUM(sales_amount) FILTER (WHERE product = 'Laptop' AND year = 2023) AS Lapto
SUM(sales_amount) FILTER (WHERE product = 'Phone' AND year = 2023) AS Phone_
SUM(sales_amount) FILTER (WHERE product = 'Tablet' AND year = 2023) AS Table
```

```
sales
GROUP BY
salesperson
ORDER BY
salesperson;
```

This works but requires explicitly specifying every product and year combination in the query. If people later add new products or years, we must rewrite the query to account for those changes. Clearly, this approach doesn't scale well and involves too much manual effort.

Pivoting in DuckDB: Let's Make Pivot Fun Again

DuckDB offers a simpler and more flexible solution with its internal **PIVOT** command. By attaching a remote PostgreSQL database, we can process the same data in a far more elegant way. Adjusting pivot criteria is effortless, making it an incredibly user-friendly tool for dynamic data exploration.

D pivot pg.sales on product using sum(sales_amount) group by salesperson order by salesperson;

salesperson varchar	Laptop double	Phone double	Tablet double
Alice	2600.0	1700.0	700.0
Bob	2100.0	600.0	AL 8/4/1/A 0.0
Charlie	2300.0	1500.0	1100.0

D pivot pg.sales on (product, year) using sum(sales_amount) group by salesperson order by salesperson;

salesperson varchar	(Laptop, 2022) double	(Laptop, 2023) double	(Phone, 2022) double	(Phone, 2023) double	(Tablet, 2022) double	(Tablet, 2023) double
Alice	1200.0	1400.0	800.0	900.0	300.0	400.0
Bob	1000.0	1100.0	600.0			
Charlie	1100.0	1200.0	700.0	800.0	500.0	600.0

D pivot pg.sales on (year,product) using sum(sales_amount) group by salesperson order by salesperson;

salesperson varchar	(2022, Laptop) double	(2022, Phone) double	(2022, Tablet) double	(2023, Laptop) double	(2023, Phone) double	(2023, Tablet) double
Alice	1200.0	800.0	300.0	1400.0	900.0	400.0
Bob	1000.0	600.0	1.00.000	1100.0	VIII CONTRACTOR	
Charlie	1100.0	700.0	500.0	1200.0	800.0	600.0

D pivot pg.sales on (year) using sum(sales_amount) group by salesperson order by salesperson;

salesperson varchar	2022 double	2023 double
Alice	2300.0	2700.0
Bob	1600.0	1100.0
Charlie	2300.0	2600.0

Conclusion

DuckDB transforms the process of creating pivot tables into a seamless experience, saving us both time and effort. As shown in these examples, its built-in capabilities outperform traditional SQL methods for pivoting. Whether we are dealing with a simple dataset or a complex one, DuckDB makes data analysis not just easier but also more enjoyable.

Duckdb Pivot Tables Pivoting Postgresql



Written by Josef Machytka

Edit profile

16 Followers - 3 Following

I work as Professional Service Consultant - PostgreSQL specialist in NetApp Deutschland GmbH, Open Source Services division.

More from Josef Machytka







How DuckDB handles data not fitting into memory?

In my previous article about DuckDB I described how to use this database as an...





Josef Machytka

Extending DuckDB ETL Capabilities with Python

DuckDB has recently become my go-to solution for small ETL tasks. It is an...

Nov 24 👋 12





har:	apprex_unique int64	avg varcher	std varchar	q25 varchar	ve
t	368	200512.6231617008	928.6562707338801	199729	20
	2	1.3918669432239588	0.488167229676373	1	1
	260	193.20352292962244	121.02486459889657	106	12
	146	313.31866609794747	179.77396070679418	104	34
1000	17334				
10000000	924549	47876.754848697165	29145919.848440725	8	0
19678	1767602	127166.98737165982	4571867.453589752	98	71
1402	1394313	32408.302375721876	376988.2117641157	720	24

u.use u.ema	rname,						
	er_date,						
	al_amount,						
p.pro	duct_name,						
od . qu	antity,						
p.pri	ce,						
	uantity * p.price) AS	total_price					
FROM							
pg13.	users u						
JOIN							
ne16	orders o ON u.user_id	= o.user_id					
pgro.							
JOIN PG15.							
NIOL	order_details od ON o	.order_id = od	order_id				
NIOL	order_details od ON o	order_id = od	order_id				
JOIN pg15.	order_details od ON o						
JOIN pg15.							
JOIN pg15. JOIN pg14. ORDER BY							
JOIN pg15. JOIN pg14. ORDER BY u.use	products p ON od.produ			product name	quantity	price	total price
JOIN pg15. JOIN pg14. ORDER BY	products p ON od.produrname, o.order_date;	uct_id = p.prod	duct_id	product_name	quantity int32	price decimal(10,2)	
JOIN pg15. JOIN pg14. ORDER BY u.use	products p ON od.produrname, o.order_date;	order_date	duct_id total_amount				total_price decimal(18,2



Josef Machytka

Using DuckDB as an Intelligent ETL tool for PostgreSQL

There is a lot of hype around DuckDB these days. At one PostgreSQL conference, I even...

DuckDBDuckDB was created with simplicity and ease

of use in mind. In my previous article, I...

Easy Cross-Database Selects with

Nov 2	W 6		•

Nov 26 👋 2

See all from Josef Machytka

Recommended from Medium





In T3CH by Jesus L. Monroy

Supercharge Your SQL Analysis with Python and DuckDB

Rethinking Data Analysis: A New Paradigm

5d ago









In Code Like A Girl by Chris Ng

I Removed VS Code, and My **Productivity Improved...**

A Journey from Clunky to Efficient: How The New IDE Transformed My Workflow

Nov 26 **3** 553





Lists



Staff picks

780 stories • 1488 saves



Self-Improvement 101

20 stories - 3114 saves




Stories to Help You Level-Up at Work

19 stories - 888 saves



Productivity 101

20 stories - 2623 saves



datadice



In Towards Data Science by Eirik Berge, PhD

Introducing BigQuery Workflows

A New Era of Data Orchestration. By Fassil S. Yehuala

Nov 27 **W** 108



Use Tablib to Handle Simple Tabular Data in Python

Sometimes a Shallow Abstraction is more Valuable than Performance



Nov 27













In Level Up Coding by Md Arman Hossen



Data Cleaning Tools in 2024

Data cleaning tools: Code-based (pandas,



Thibaut Gourdel

The Lazy Developer's Guide to **Python Automation (and Why...**

It was another late night at the office. The soft glow of my monitor illuminated the scattere...









Nov 26 **3** 25





dbt), Open-source (Amphi, OpenRefine), and...

See more recommendations