

The UUposter class*

Joseph Scott
`joseph.scott@it.uu.se`

November 1, 2011

1 Introduction

Making a scientific poster in L^AT_EX is a non-trivial task, as anyone who has made the attempt is aware. This class makes use of the `a0poster` base class and the `flowfram` package for the layout of posters in the style of Uppsala University. It was initially designed for personal use, and the resulting design reflects the aesthetic sensibilities of the author; however, an attempt has been made to make the class as flexible as (reasonably) possible.

2 Usage

The default layout is an a0 poster in portrait orientation, with a light grey sidebar on the left, and a title in red at the top. The university logo will appear in the top left corner (inside the sidebar), followed by author information. The main body of the poster consists of several columns of flowing content. These columns are called *flow frames* in the `flowfram` package, while the sidebar and title bar are in *static frames*.

No special measures need to be taken to get the contents of your document into the flow frames. Sectioning commands should work normally.

2.1 Floats

You can use floats inside the flow frames, although your results may vary. Wrapping text around floats is not straightforward, as the `wrapfig` package does not seem to function correctly inside a flow frame. The best option seems to be using the `multicol` package to make a small section with side-by-side figure and text. Alternately, you can use `sidecap` to place captions alongside figures, and `caption` to adjust the formatting.

*This document corresponds to UUposter v0.8, dated 2011/11/01.

2.2 Author and Title

`\title` The title of the poster is set using `\title {{title}}`, just as you would expect.

`\uuposterAuthor` The author block is less straightforward, unfortunately. You will need to redefine the `\uuposterAuthor` macro in your document preface, like so:

```
\renewcommand\uuposterAuthor{
  Joseph~Scott\uuposterInst{Dept. of Information Technology,\\University of Uppsala}\\
  Someone~Else\uuposterInst{Another Division,\\ Another School}
}
```

`\uuposterInst` The contents of the author block are typeset in a minipage environment, and the `\uuposterInst` macros create footnotes at the bottom of this minipage. The

`\uuposterAuthorContent` spacing is optimized for the **sidebar** layout; if you are using the **top** layout, you may need to renew the `\uuposterAuthorContent` macro to get an author format that works for you. The default author block is generated like this:

```
\newcommand\uuposterAuthorContent{%
\begin{minipage}{0.9\logoboxwidth}
\renewcommand{\thempfootnote}{\textcolor{uuposter@fg}{\Large{\arabic{mpfootnote}}}}
\uuposterAuthorTextColor\uuposterAuthorTextStyle\uuposterAuthor
\uuposterAuthorFootSkip
\end{minipage}%
}
```

If you rewrite `\uuposterAuthorContent`, make sure to call `\uuposterAuthor` inside it, to make the author content appear.

2.3 Style

`\uuposterTitle` Inspired by the memoir package, most of the text styling in the class is handled through user-modifiable hooks. For example, the title is typeset by the `\uuposterTitle` macro, defined like this:

```
\newcommand\uuposterTitle{%
\uuposterBeforeTitle%
\uuposterTitleContent%
\uuposterAfterTitle}
```

`\uuposterBeforeTitle` By default, `\uuposterBeforeTitle` and `\uuposterAfterTitle` are empty commands, while `\uuposterTitleContent` just calls `\maketitle`. The user can renew any of these commands in order to get a fine-grained control over the typesetting of the title, though; the author information is typeset in a similar fashion. See the implementation section below for more on what you should be able to modify easily.

`\uuposterTitleTextStyle` Similarly, most font settings are accomplished using macros such as `\uuposterTitleTextStyle` and `\uuposterTitleTextColor`. These macros should be changed if you want a different style. For example, to set the title in italics, and reduce the size to huge, you would add this to your preamble:

```
\renewcommand\uuposterTitleTextStyle{\sffamily\itshape\huge}
```

`\uuposterBodyTextColor` The same approach can be used to change the body text, using `\uuposterBodyTextColor` and `\uuposterBodyTextStyle`.

2.4 Changing the Layout

If you want a completely different layout, you should just use `a0poster` and `flowfram` from scratch, as this will almost certainly involve less work than modifying the relatively fixed layout of this class *post hoc*. That having been said, it is perfectly possible to shift the positions of frames, or create new ones, in your document's preamble. Unfortunately, this involves some calculations to get things to look good. If you're interested in adding a non-overlapping frame to a `UUposter`, I suggest that you read the `flowfram` manual.¹

2.5 Bibliography

Support for including a bibliography is limited, but you shouldn't need a fancy bibliography on a poster anyway... Anyway, including the `bib` option will create a static frame (`bibframe`) at the bottom of the poster. By default, it is `3\baselineskip` in height, and is offset from the bottom of the text frames by `1\baselineskip`, but both of those values are adjustable. This will, of course, make the text frames shorter.

`\uuposterBibliography` `\uuposterBibliography [<style>] {<bib file>}` will fill `bibframe`. The mandatory argument is the name of your bibliography file (without the `.bib` extension). The optional argument is the name of the bibtex style you would like to use; the default is to use `UUposter.bst`, included with this package, to give quite short bibliography entries, but any style should work. If you want to use the included style, you'll need to copy it somewhere that your \TeX can find it (try `~/Library/texmf/bibtex/bst/` if you're using MacTex).

`\uuposterBibTextStyle` The bibliography will be typeset in `\footnotesize` text of `\uuposterBodyTextColor`; you can redefine `\uuposterBibTextStyle` or `\uuposterBibTextColor` if you'd like to customize this behaviour.

3 Options

Any unrecognized options are assumed to be intended for the `a0poster` class.

xetex Load the `UUxetex` package (included with this distribution) in order to utilize the Uppsala University standard fonts: Berling (serif) and Gill Sans Alt One (sans). Note that both of these fonts must be installed on your system if you wish to use them. They are not distributed with this package, but are licensed by the University for official use, and are available to employees from the Office of Graphics and Printing website. Passing this option ensures that `fontspec`, etc., are loaded before `flowfram`; loading XeTeX font handling packages after `flowfram` will break the layout of the poster.

¹Or at the very least, read Nicola Talbot's web page at <http://theoval.cmp.uea.ac.uk/~nlct/latex/posters/>

notimes, nohelvet When not using `fontspec` to load the University fonts, the class will normally use the approved fallbacks (namely, Times and Helvetica). These options allow you to prevent the loading of one or both of these fonts.

nomathtools By default, the incredibly useful `mathtools` package is loaded, which in turn loads the AMS math packages. Rude, I know, but `mathtools` works best if loaded before `unicode-math`, which gets loaded by this class if you are using the `xetex` option, because *that* needs to get loaded before `flowfram`. . . I think you see where this is going. If `mathtools` bugs you, you can switch it off.

mathtools={*<options>*} On the other hand, this option allows you to pass options along to `mathtools`, and by extension on to the `amsmath` package. See the `mathtools` documentation for details.

red, grey, gray Choose the background color of the info bar. These options in turn imply a contrasting font color for the info bar (black text on a grey background, white text on a red background) and make an initial logo selection (four color on the grey background, white on the red background). You can override either of these choices by passing the appropriate options, just make sure to pass those options *after* choosing the info bar color; otherwise your custom choice will be overridden. Note that the only difference between **gray** and **grey** lies in the conscience of the user.

top By default, an information bar with contrasting background color is placed on the (left) side of the poster. If you would prefer to have a contrasting bar at the top, this is the option for you. This will result in several alterations to the layout of the poster. The title remains at the top of the poster in either case, although its color will change (red by default if the contrasting bar is at the side; whatever the foreground color of the bar is if the bar is at the top). The author prefers a sidebar, so unfortunately **top** may be less well supported. You may need to tweak a couple of macros to get it looking just the way you want it (especially `\uuposterAuthorContent`)...

landscape, portrait Orientation of the poster. The default is **portrait**, and that is the better supported option; nevertheless, effort has been made to adjust measurements appropriately when **landscape** is selected.

columns=*<num>* The number of columns in the main body (that is, exclusive of the sidebar). Default is 2 columns for portrait and 3 for landscape; make sure to specify the **column** option *after* choosing the orientation if you want to override these defaults.

ruled Places a vertical rule between each pair of columns in the main body. This is intended as a convenience method, but since the placement of these rules is determined at class load, no document specific alterations to the layout of the flow frames can be taken into account here. If you are manually changing any part of the poster layout (such as adding a static text

box at the footer), you should also add the rules yourself, either by calling `\uuposterInsertVerticalRules` in the document preface after you’ve made any layout changes, or by using the `\insertvrule` macro of the `flowfram` package.

logo= $\langle type \rangle$ Select the logo icon, where $\langle type \rangle$ is one of **4f** (four color), **2f** (two color), **sv** (black), or **vit** (white). The default depends on the background color of the info bar (see above).

sigil= $\langle type \rangle$ Select a sigil to be used in the background. The default is to have no sigil. $\langle type \rangle$ may be one of:

NW, NE, SW, SE A roughly quarter-circle sigil in 10% grey will be placed in the corresponding corner (i.e., northwest, northeast, etc.).

NOTE: southeast (SE) is currently the only supported option here, and the image file used for that logo is quite large. Using this option will result in both larger file sizes and slower typesetting. Will fix in a future version as time permits.

margin Place a 5% grey partial sigil in the colored info bar (at the bottom of the sidebar, or at the right of a top bar—although at the moment only the sidebar is supported).

sigilwidth= $\langle num \rangle$ Width of the sigil, in terms of `\textwidth`. In other words, the default value of 0.5 corresponds to a sigil that is `0.5\textwidth` wide. This applies only to corner sigils; marginal sigils are always the width of the info bar.

sidebarwidth= $\langle num \rangle$ Width of the sidebar, as a proportion of `\textwidth`. This option is ignored when **top** is selected.

titleheight= $\langle num \rangle$ The height of the title bar (default is 6em). Also the height of the info bar when **top** is active.

math,noxits,serif,sans These option are passed directly to `UUxetex`, and are meaningless if that package is not loaded. See package documentation for details.

bib Include a static frame at the bottom of the page for the bibliography. The frame will be named **bibframe**, and will be the width of the combined text columns (although you can change that yourself, using something like `\setstaticframe*{bibframe}{width=\dots}`).

biblines= $\langle num \rangle$ Height of bibliography, as a product of `\baselineskip`

biboffset= $\langle num \rangle$ Distance between bottom of text columns and top of bibliography, as a product of `\baselineskip`.

4 Implementation

4.1 Options

Using xkeyval for key, value pair processing.

```
1 \RequirePackage{xkeyval}
2 \RequirePackage{xparse}
3 \newif\if@uuposter@xetex
4 \newif\if@uuposter@times
5 \@uuposter@timetrue
6 \newif\if@uuposter@helvet
7 \@uuposter@helvettrue
8 \newif\if@uuposter@mathtools
9 \@uuposter@mathtoolstrue
10 \newif\if@uuposter@red
11 \newif\if@uuposter@grey
12 \newif\if@uuposter@top
13 \newif\if@uuposter@landscape
14 \newif\if@uuposter@ruled
15 \newif\if@uuposter@sigil@corner
16 \newif\if@uuposter@sigil@margin
17 \newif\if@uuposter@sigil@left
18 \newif\if@uuposter@sigil@right
19 \newif\if@uuposter@sigil@top
20 \newif\if@uuposter@sigil@bottom
21 \newlength\logoboxwidth
22 \newlength\uuposter@TitleHeight
23 \newif\if@uuposter@TitleHeightSet
24 \DeclareOptionX{xetex}{\@uuposter@xetextrue}
25 \DeclareOptionX{notimes}{\@uuposter@timefalse}
26 \DeclareOptionX{nohelvet}{\@uuposter@helvetfalse}
27 \DeclareOptionX{nomathtools}{\@uuposter@mathtoolsfalse}
28 \DeclareOptionX{mathtools}[]{\PassOptionsToPackage{mathtools}{#1}}
29 \DeclareOptionX{red}{
30 \@uuposter@redtrue
31 \@uuposter@greyfalse
32 \ExecuteOptionsX{logo=vit}
33 }
34 \DeclareOptionX{grey}{
35 \@uuposter@redfalse
36 \@uuposter@greytrue
37 \ExecuteOptionsX{logo=4f}
38 }
39 \DeclareOptionX{gray}{
40 \@uuposter@redfalse
41 \@uuposter@greytrue
42 \ExecuteOptionsX{logo=4f}
43 }
44 \DeclareOptionX{top}{\@uuposter@toptrue}
45 \DeclareOptionX{landscape}{
```

```

46 \ExecuteOptionsX{sidebarwidth=0.1,columns=3}
47 \@uuposter@landscape>true
48 }
49 \DeclareOptionX{portrait}{
50 \ExecuteOptionsX{sidebarwidth=0.20,columns=2}
51 \@uuposter@landscape=false
52 }
53 \DeclareOptionX{columns}[2]{\def \uuposter@columns {#1}}
54 \DeclareOptionX{ruled}{\@uuposter@ruled=true}
55 \DeclareOptionX{logo}[4f]{\def \uuposter@LogoInclude{\includegraphics[width=\logoboxwidth]{UU_lo

uuposterSigil Insert an appropriate version of the University sigil. Not all options are fully
implemented.
56 \NewDocumentCommand \uuposterSigil {} {}
57 \define@choicekey+{UUposter.cls}{sigil}{\val\nr}{NW,NE,SW,SE,margin}[SE]{
58 \ifcase\nr\relax
59 \RenewDocumentCommand \uuposterSigil {} {\includegraphics[width=\sigilwidth]{UU_sigill_S0_10Sva
60 \@uuposter@sigil@corner=true
61 \@uuposter@sigil@margin=false
62 \@uuposter@sigil@top=true
63 \@uuposter@sigil@left=true
64 \@uuposter@sigil@bottom=false
65 \@uuposter@sigil@right=false
66 \or
67 \RenewDocumentCommand \uuposterSigil {} {\includegraphics[width=\sigilwidth]{img/UU_sigill_SV_1
68 \@uuposter@sigil@corner=true
69 \@uuposter@sigil@margin=false
70 \@uuposter@sigil@top=true
71 \@uuposter@sigil@right=true
72 \@uuposter@sigil@bottom=false
73 \@uuposter@sigil@left=false
74 \or
75 \RenewDocumentCommand \uuposterSigil {} {\includegraphics[width=\sigilwidth]{img/UU_sigill_NO_1
76 \@uuposter@sigil@corner=true
77 \@uuposter@sigil@margin=false
78 \@uuposter@sigil@bottom=true
79 \@uuposter@sigil@left=true
80 \@uuposter@sigil@top=false
81 \@uuposter@sigil@right=false
82 \or
83 \RenewDocumentCommand \uuposterSigil {} {\includegraphics[width=\sigilwidth]{img/UU_sigill_NV_1
84 \@uuposter@sigil@corner=true
85 \@uuposter@sigil@margin=false
86 \@uuposter@sigil@bottom=true
87 \@uuposter@sigil@right=true
88 \@uuposter@sigil@top=false
89 \@uuposter@sigil@left=false
90 \or
91 \@uuposter@sigil@margin=true
92 \@uuposter@sigil@corner=false

```

```

93 \RenewDocumentCommand \uuposterSigil {} {\includegraphics[width=\sigilwidth]{img/UU_marginalsig
94 \fi
95 }\ClassWarning{UUposter}{Ignoring unrecognized value for option 'sigil' (valid options: NW,NE,

96 \DeclareOptionX{sigilwidth}[0.5]{\def\sigilproportion{#1}}
97 \DeclareOptionX{sidebarwidth}[0.2]{\def\sidebarproportion{#1}}
98 \DeclareOptionX{titleheight}[6em]{
99 \@uuposter@TitleHeightSettrue
100 \setlength\uuposter@TitleHeight{#1}
101 }
102 \DeclareOptionX{math}{\PassOptionsToPackage{\CurrentOption}{UUxetex}}
103 \DeclareOptionX{noxits}{\PassOptionsToPackage{\CurrentOption}{UUxetex}}
104 \DeclareOptionX{serif}{\PassOptionsToPackage{\CurrentOption}{UUxetex}}
105 \DeclareOptionX{sanserif}{\PassOptionsToPackage{\CurrentOption}{UUxetex}}
106 \newif\if@uuposter@hasbib
107 \DeclareOptionX{bib}{\@uuposter@hasbibtrue}
108 \DeclareOptionX{biblines}[3]{\def\uuposter@biblines{#1}}
109 \DeclareOptionX{biboffset}[1]{\def\uuposter@biboffset{#1}}
110 \DeclareOptionX*{\PassOptionsToClass{\CurrentOption}{a0poster}}
111 \ExecuteOptionsX{grey,sigilwidth,portrait,biblines,biboffset}
112 \ProcessOptionsX\relax

```

4.2 Base Class

```

113 \if@uuposter@landscape
114 \PassOptionsToClass{landscape}{a0poster}
115 \else
116 \PassOptionsToClass{portrait}{a0poster}
117 \fi
118 \LoadClass{a0poster}

```

4.3 Misc. packages

```

119 \if@uuposter@mathtools
120 \RequirePackage{mathtools}
121 \fi
122 \if@uuposter@xetex
123 \RequirePackage{UUxetex}
124 \else
125 \if@uuposter@times
126 \RequirePackage{times}
127 \fi
128 \if@uuposter@helvet
129 \RequirePackage{helvet}
130 \fi
131 \fi

```

`xcolor` At the moment only red and light grey are actually used. I copied these values from the uu beamer theme, incidentally.

```

132 \RequirePackage{xcolor}
133 \definecolor{uuposterred}{RGB}{153,0,0}

```



```

134 \definecolor{uuposterlightgrey}{RGB}{230,230,230}
135 \definecolor{uupostermidgrey}{RGB}{190,190,190}
136 \definecolor{uuposterdarkgrey}{RGB}{130,130,130}
137 \if@uuposter@red
138 \definecolor{uuposter@bg}{named}{uuposterred}
139 \definecolor{uuposter@fg}{named}{white}
140 \else
141 \if@uuposter@grey
142 \definecolor{uuposter@bg}{named}{uuposterlightgrey}
143 \definecolor{uuposter@fg}{named}{black}
144 \fi
145 \fi

```

footmisc The footmisc package is used to fix footnotes in the sidebar minipage:

```

146 \RequirePackage[hang,norule,multiple]{footmisc}
147 \setlength{\footnotemargin}{2em}

148 \RequirePackage{graphicx}

```

forloop Using the forloop package just for this seems ridiculous, so I don't:

```

149 \RequirePackage{ifthen}
150 \newcommand{\forloop}[5][1]{%
151 \setcounter{#4}{#2} %
152 \ifthenelse{ \value{#4}<#3 }{%
153 {%
154 #5 %
155 \addtocounter{#4}{#1} %
156 \forloop[#1]{\value{#4}}{#3}{#4}{#5} %
157 }{%
158 #5 %
159 }}%

```

4.4 Flow frame layout

The flowfram package is used to control the poster layout:

```

160 \RequirePackage{flowfram}

\vcolumnsep is the space between two vertical columns. For consistency, this
value is used several other places in the layout, so changing it may move more
things than you expect. Still, any small value should work out OK. \columnsep
defaults to the same value, but doesn't get used nearly as often.

```

```

161 \setlength{\vcolumnsep}{2\baselineskip}
162 \setlength{\columnsep}{2\baselineskip}

```

These lengths are mostly dependent on a combination of orientation (portrait vs. landscape) and layout (top vs. side). You should be able to control them pretty well with the class options, but in a pinch you can modify them directly.

```

163 \newlength\sidebarwidth
164 \newlength\sidebaroffset
165 \setlength{\sidebarwidth}{\sidebarproportion\textwidth}

```

```

166 \setlength{\logoboxwidth}{\sidebarwidth}
167 \addtolength{\logoboxwidth}{-\columnsep}
168 \newlength\logoboxoffset
169 \setlength{\logoboxoffset}{\columnsep}
170 \if@uuposter@TitleHeightSet
171 \if@uuposter@top
172 \setlength{\logoboxwidth}{\uuposter@TitleHeight}
173 \addtolength{\logoboxwidth}{-\vcolumnsep}
174 \fi
175 \else
176 \setlength\uuposter@TitleHeight{\logoboxwidth}
177 \addtolength{\uuposter@TitleHeight}{-2\logoboxoffset}
178 \@uuposter@TitleHeightSettrue
179 \fi
180 \if@uuposter@top
181 \setlength{\sidebarwidth}{0pt}
182 \setlength{\sidebaroffset}{0pt}
183 \else
184 \setlength{\sidebaroffset}{\sidebarwidth}
185 \addtolength{\sidebaroffset}{\vcolumnsep}
186 \fi
187
188 \newlength\sigilwidth
189 \if@uuposter@sigil@margin
190 \if@uuposter@top
191 \setlength{\sigilwidth}{\uuposter@TitleHeight}
192 \else
193 \setlength{\sigilwidth}{\sidebarwidth}
194 \fi
195 \fi
196 \if@uuposter@sigil@corner
197 \setlength{\sigilwidth}{\sigilproportion\textwidth}
198 \newlength\sigiloffsetx
199 \newlength\sigiloffsety
200 \if@uuposter@sigil@right
201 \setlength{\sigiloffsetx}{\textwidth}
202 \addtolength{\sigiloffsetx}{-\sigilwidth}
203 \else \if@uuposter@sigil@left
204 \setlength{\sigiloffsetx}{\sidebarwidth}
205 \fi \fi
206 \if@uuposter@sigil@bottom
207 \setlength{\sigiloffsety}{0pt}
208 \else \if@uuposter@sigil@top
209 \setlength{\sigiloffsety}{\textheight}
210 \addtolength{\sigiloffsety}{-\sigilwidth}
211 \fi \fi
212 \newstaticframe{\sigilwidth}{\sigilwidth}{\sigiloffsetx}{\sigiloffsety}[background]
213 \setstaticframe*{background}{valign=b}
214 \fi
215 \newlength\mainwidth

```

```

216 \setlength{\mainwidth}{\textwidth}
217 \addtolength{\mainwidth}{-\sidebaroffset}
218 \Ncolumntopinarea{static}{\uuposter@columns}{\uuposter@TitleHeight}{\mainwidth}{\textheight}{\s
219 \if@uuposter@sigil@corner
220 \setstaticframe{2}{label={title}}
221 \else
222 \setstaticframe{1}{label={title}}
223 \fi
224 \newlength\uupostercolwidth
225 \getflowbounds{1}
226 \setlength{\uupostercolwidth}{\ffareaawidth}
227
228 \newstaticframe{\sidebarwidth}{\textheight}{0pt}{0pt}[sidebar]
229 \newlength\authoroffset
230 \if@uuposter@top
231 \setstaticframe*{title}{backcolor=uuposter@bg}
232 \getstaticbounds*{title}
233 \newstaticframe{\logoboxwidth}{\ffareaaheight}{0pt}{\ffareay}[logobox]
234 \setlength{\authoroffset}{\textwidth}
235 \addtolength{\authoroffset}{-\logoboxwidth}
236 \newstaticframe{\logoboxwidth}{\ffareaaheight}{\authoroffset}{\ffareay}[authorbox]
237 \addtolength{\authoroffset}{-\logoboxwidth}
238 \newstaticframe{\authoroffset}{\ffareaaheight}{\logoboxwidth}{\ffareay}[titlebox]
239 \else
240 \setstaticframe*{sidebar}{backcolor=uuposter@bg}
241 \if@uuposter@landscape
242 \setlength{\authoroffset}{3em}
243 \else
244 \setlength{\authoroffset}{6em}
245 \fi
246 \fi
247

```

4.5 Bibliography

Create a bibliography frame at the bottom of the page if requested. There is an assumption here that the height of all the flow frames are equal, so using the height of just the first frame makes sense for all of them.

```

248 \if@uuposter@hasbib
249 \newlength{\bibframeheight}
250 \setlength{\bibframeheight}{\uuposter@biblines\baselineskip}
251 \newlength{\biboffset}
252 \setlength{\biboffset}{\bibframeheight}
253 \addtolength{\biboffset}{\uuposter@biboffset\baselineskip}
254 \compute flowframearea{1,\uuposter@columns}
255 \addtolength{\ffareaaheight}{-\biboffset}
256 \newcounter{maincol}
257 \setcounter{maincol}{1}
258 \forloop{1}{\uuposter@columns}{maincol}{%

```

```

259 \setflowframe{\themaincol}{y=\biboffset,height=\ffareaheight}
260 }
261 \newlength{\bibframewidth}
262 \setlength{\bibframewidth}{\ffareawidth}
263 \newstaticframe{\bibframewidth}{\bibframeheight}{\ffareaax}{0in}[bibframe]
264 %\setstaticframe*{bibframe}{border=plain}

```

By default the bibliography gets a section level heading, which is far too distracting in this context. Would like to have the option to include a smaller header, but haven't been able to make it work yet. For now, just set the name of the section to be empty, and it goes away.

```

265 \renewcommand{\refname}{}
266 \fi
267 \newcommand{\uuposterBibTextColor}{\uuposterBodyTextColor}
268 \newcommand{\uuposterBibTextStyle}{\footnotesize}

```

`\uuposterBibliography` Fill the bibliography frame.

```

269 \NewDocumentCommand \uuposterBibliography { 0{UUposter} m }{%
270 \begin{staticcontents*}{bibframe}\uuposterBibTextColor\uuposterBibTextStyle
271 \vskip-\baselineskip
272 \bibliographystyle{#1}
273 \bibliography{#2}
274 \end{staticcontents*}%
275 }

```

4.6 Vertical Rules

`\uuposterInsertVerticalRules` Insert a vertical rule between every pair of flow frames:

```

276 \NewDocumentCommand \uuposterInsertVerticalRules {} {%
277 \newcounter{firstcol}%
278 \setcounter{firstcol}{1}%
279 \newcounter{secondcol}%
280 \forloop{2}{\uuposter@columns}{secondcol}{%
281 \insertvrule{flow}{\thefirstcol}{flow}{\thesecondcol}%
282 \addtocounter{firstcol}{1}%
283 }%
284 }%

285 \if@uuposter@ruled
286 \uuposterInsertVerticalRules
287 \fi
288 \setallstaticframes{valign=t}

```

4.7 Title

`\uuposterTitleTextColor` Color and style of title text. Default color is UU red unless the top bar is colored, in which case the default foreground color is used instead.

```

289 \newcommand\uuposterTitleTextColor{%
290 \if@uuposter@top

```

```

291 \color{uuposter@fg}%
292 \else
293 \color{uuposterred}%
294 \fi%
295 }
296 \newcommand\uuposterTitleTextStyle{%
297 \sffamily\bfseries\veryHuge%
298 }

```

`\maketitle` This is called by `\uuposterTitleContent`. You probably don't need to modify this directly, but feel free.

```

299 \renewcommand\@maketitle{%
300   \raggedright%
301   \let \footnote \thanks
302   {%
303     \uuposterTitleTextColor%
304     \uuposterTitleTextStyle%
305     \@title \par}%
306   \par
307   }
308

```

Modify these macros to control the placement of the title:

`\uuposterBeforeTitle`

```

309 \newcommand\uuposterBeforeTitle{}
310

```

`\uuposterTitleContent`

```

311 \newcommand\uuposterTitleContent{\maketitle}
312

```

`\uuposterAfterTitle`

```

313 \newcommand\uuposterAfterTitle{}
314

```

`\uuposterTitle`

```

315 \newcommand\uuposterTitle{%
316 \uuposterBeforeTitle%
317 \uuposterTitleContent%
318 \uuposterAfterTitle}

```

4.8 Author

`\uuposterAuthor` Override this to set the author content in the document:

```

319 \newcommand\uuposterAuthor{}

```

`\uuposterAuthorBlock`

```

320 \newcommand{\uuposterAuthorBlock}{%
321 \uuposterBeforeAuthor%
322 \uuposterAuthorContent%
323 \uuposterAfterAuthor%
324 }

```

`\uuposterAuthorFootSkip` The space between the list of authors and the list of institutions:

```

325 \newcommand\uuposterAuthorFootSkip{%
326 \if@uuposter@top
327 \vspace{0.5\baselineskip}
328 \else
329 \vspace{\baselineskip}
330 \fi%
331 }

```

`\uuposterAuthorOffset` The space above the author list.

```

332 \newlength\uuposterAuthorOffset
333 \if@uuposter@top
334 \setlength{\uuposterAuthorOffset}{0pt}
335 \else
336 \if@uuposter@landscape
337 \setlength{\uuposterAuthorOffset}{3em}
338 \else
339 \setlength{\uuposterAuthorOffset}{6em}
340 \fi
341 \fi

```

`\uuposterBeforeAuthor` Create a little space above the author list. Alternately, if a sigil is in the sidebar, let the authors float between the bottom of the logo and the top of the sigil.

```

342 \newcommand\uuposterBeforeAuthor{%
343 \if@uuposter@sigil@margin
344 \vfill
345 \else
346 \vskip \uuposterAuthorOffset
347 \fi%
348 }

```

`\uuposterAuthorTextColor` Color of the author text.

```

349 \newcommand\uuposterAuthorTextColor{\color{uuposter@fg}}

```

`\uuposterAuthorTextStyle` Style of the author text. You may need to make this smaller if you shrink the sidebar.

```

350 \newcommand\uuposterAuthorTextStyle{\sffamily\Large}

```

`\uuposterAuthorContent` This works well for the sidebar, even with a large number of authors. Squeezing several authors into the top bar may require a bit of creativity, though.

```

351 \newcommand\uuposterAuthorContent{%

```

```

352 \begin{minipage}{0.9\logoboxwidth}
353 \renewcommand{\thempfootnote}{\textcolor{uuposter@fg}{\Large{\arabic{mpfootnote}}}}}
354 \uuposterAuthorTextColor\uuposterAuthorTextStyle\uuposterAuthor
355 \uuposterAuthorFootSkip
356 \end{minipage}%
357 }

```

\uuposterAfterAuthor

```

358 \newcommand\uuposterAfterAuthor{}

```

\uuposterInstTextStyle

```

359 \newcommand\uuposterInstTextStyle{\large\sffamily}

```

\uuposterInstTextColor

```

360 \newcommand\uuposterInstTextColor{\uuposterAuthorTextColor}

```

\uuposterInst

```

361 \NewDocumentCommand \uuposterInst { m } {%
362 \footnote{\uuposterInstTextColor\uuposterInstTextStyle{#1}}%
363 }

```

4.9 Logo

\uuposterBeforeLogo

```

364 \newcommand\uuposterBeforeLogo{%
365 \vspace{\logoboxoffset}
366 }

```

\uuposterLogoContent

```

367 \newcommand\uuposterLogoContent{\uuposter@LogoInclude}

```

\uuposterAfterLogo

```

368 \newcommand\uuposterAfterLogo{}

```

\uuposterLogo

```

369 \newcommand\uuposterLogo{%
370 \uuposterBeforeLogo%
371 \uuposterLogoContent%
372 \uuposterAfterLogo%
373 }

```

4.10 Sectioning Commands

\uuposterSectionTextColor

```

\uuposterSectionTextStyle 374 \newcommand\uuposterSectionTextColor{\color{black}}

```

```

\uuposterSubSectionTextColor 375 \newcommand\uuposterSectionTextStyle{\sffamily\Huge}

```

```

\uuposterSubSectionTextStyle 376 \newcommand\uuposterSubSectionTextColor{\uuposterSectionTextColor}

```

```

\section 377 \newcommand\uuposterSubSectionTextStyle{\sffamily\huge}

```

\subSection

```

378 \renewcommand\section{%
379 \@startsection{section}{1}{\z@}%
380         {-3ex \@plus -1ex \@minus -.2ex}%
381         {2.3ex \@plus.2ex}%
382         {\uuposterSectionTextColor\uuposterSectionTextStyle}}
383 \renewcommand\subsection{%
384 \@startsection{subsection}{2}{\z@}%
385         {-2.25ex\@plus -1ex \@minus -.2ex}%
386         {1ex \@plus .2ex}%
387         {\uuposterSubSectionTextColor\uuposterSubSectionTextStyle}}

\uuposterBodyTextStyle
\uuposterBodyTextColor 388 \NewDocumentCommand \uuposterBodyTextStyle {} {\normalsize}
389 \NewDocumentCommand \uuposterBodyTextColor {} {\color{black}}

390 \hyphenpenalty 10000
391 \tolerance 5000

```

4.11 Document Contents

None of this gets generated until the document begins, so any changes you make in the preamble should take effect here:

```

392 \AtBeginDocument{%
393 \if@uuposter@sigil@corner
394 \begin{staticcontents*}{background}
395 \raggedleft
396 \uuposterSigil
397 \end{staticcontents*}
398 \fi
399 \if@uuposter@top
400 \begin{staticcontents*}{titlebox}%
401 \uuposterTitle%
402 \end{staticcontents*}
403 \begin{staticcontents*}{logobox}
404 \uuposterLogo
405 \end{staticcontents*}
406 \begin{staticcontents*}{authorbox}
407 \uuposterAuthorBlock
408 \end{staticcontents*}
409 \else
410 \begin{staticcontents*}{title}%
411 \uuposterTitle%
412 \end{staticcontents*}
413 \begin{staticcontents*}{sidebar}
414 \begin{center}
415 \uuposterLogo
416 \uuposterAuthorBlock
417 \end{center}
418 \if@uuposter@sigil@margin

```



```

419 \vfill
420 \uuposterSigil
421 \fi
422 \end{staticcontents*}
423 \fi
424 \uuposterBodyTextColor\uuposterBodyTextStyle%
425 }

```

Change History

0.5	General: Added the option for a bibliography frame at the bottom. 11	ports variable number of columns 1
	\uuposterInsertVerticalRules: Made the insert rules macro user accessible 12	v0.4b General: fixed header height calculation in landscape mode 1
0.6	uuposterSigil: Moved image files to img subdir 7	v0.5 General: Moved to .dtx .ins structure, documented source file ... 1
v0.1b	General: Initial Version 1	v0.6 General: Simpler bibliography insertion 1
v0.2b	General: xetex driver optional, changed image files 1	v0.7 General: Completed switch to docstrip format 1
v0.3b	General: Ruled option now sup-	v0.8 General: Using xparse for macro definitions 1

Index

Numbers written in *italic* refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; numbers in *roman* refer to the code lines where the entry is used.

Symbols	\@uuposter@hasbibtrue	\@uuposter@mathtoolstrue
\@maketitle 299 107 9
\@minus 380, 385	\@uuposter@helvetfalse 26	\@uuposter@redfalse 35, 40
\@plus 380, 381, 385, 386	\@uuposter@helvettrue 7	\@uuposter@redtrue . 30
\@startsection 379, 384	\@uuposter@landscapefalse	\@uuposter@ruledtrue 54
\@title 305	\@uuposter@landscapetrue 51	\@uuposter@sigil@bottomfalse 64, 72
\@uuposter@TitleHeightSettrue 99, 178	\@uuposter@landscapetrue 47	\@uuposter@sigil@bottomtrue 78, 86
\@uuposter@greyfalse 31	\@uuposter@mathtoolfalse 27	\@uuposter@sigil@cornerfalse 92
\@uuposter@greytrue 36, 41		

<code>\@uuposter@sigil@cornertrue</code>	<code>\computeeflowframearea</code>	<code>\if@uuposter@mathtools</code>
.... 60, 68, 76, 84 254 8, 119
<code>\@uuposter@sigil@leftfalse</code>		<code>\if@uuposter@red</code> 10, 137
..... 73, 89	D	<code>\if@uuposter@ruled</code> .
<code>\@uuposter@sigil@lefttrue</code>	<code>\define@choicekey</code> . 57 14, 285
..... 63, 79	E	<code>\if@uuposter@sigil@bottom</code>
<code>\@uuposter@sigil@marginfalse</code>	<code>\end</code> 274, 356, 20, 206
.... 61, 69, 77, 85	397, 402, 405,	<code>\if@uuposter@sigil@corner</code>
<code>\@uuposter@sigil@margintrue</code>	408, 412, 417, 422	. 15, 196, 219, 393
..... 91		<code>\if@uuposter@sigil@left</code>
<code>\@uuposter@sigil@rightfalse</code>	F 17, 203
..... 65, 81	<code>\ffareaheight</code> . 233,	<code>\if@uuposter@sigil@margin</code>
<code>\@uuposter@sigil@righttrue</code>	236, 238, 255, 259	. 16, 189, 343, 418
..... 71, 87	<code>\ffareawidth</code> .. 226, 262	<code>\if@uuposter@sigil@right</code>
<code>\@uuposter@sigil@topfalse</code>	<code>\ffareax</code> 263 18, 200
..... 80, 88	<code>\ffareay</code> .. 233, 236, 238	<code>\if@uuposter@sigil@top</code>
<code>\@uuposter@sigil@toptrue</code>	<code>\fi</code> 94, 117, 121, 127, 19, 208
..... 62, 70	130, 131, 144,	<code>\if@uuposter@times</code> .
<code>\@uuposter@timefalse</code> 25	145, 174, 179, 4, 125
<code>\@uuposter@timetrue</code> 5	186, 194, 195,	<code>\if@uuposter@TitleHeightSet</code>
<code>\@uuposter@toptrue</code> . 44	205, 211, 214, 23, 170
<code>\@uuposter@xetextrue</code> 24	223, 245, 246,	<code>\if@uuposter@top</code> ..
	266, 287, 294, 12, 171,
A	330, 340, 341,	180, 190, 230,
<code>\AtBeginDocument</code> .. 392	347, 398, 421, 423	290, 326, 333, 399
<code>\authoroffset</code> . 229,	<code>\footmisc</code> 146	<code>\if@uuposter@xetex</code> .
234–238, 242, 244	<code>\footnote</code> 301, 362 3, 122
	<code>\footnotemargin</code> ... 147	<code>\includegraphics</code> 55,
B	<code>\footnotesize</code> 268	59, 67, 75, 83, 93
<code>\baselineskip</code>	<code>\forloop</code> 149,	<code>\insertvrule</code> 281
. 161, 162, 250,	150, 156, 258, 280	
253, 271, 327, 329	G	L
<code>\begin</code> 270, 352,	<code>\getflowbounds</code> 225	<code>\Large</code> 350, 353
394, 400, 403,	<code>\getstaticbounds</code> .. 232	<code>\large</code> 359
406, 410, 413, 414		<code>\let</code> 301
<code>\bfseries</code> 297	H	<code>\LoadClass</code> 118
<code>\bibframeheight</code> ...	<code>\Huge</code> 375	<code>\logoboxoffset</code>
. 249, 250, 252, 263	<code>\huge</code> 377	. 168, 169, 177, 365
<code>\bibframewidth</code> 261–263	<code>\hyphenpenalty</code> 390	<code>\logoboxwidth</code>
<code>\bibliography</code> 273		21, 55, 166, 167,
<code>\bibliographystyle</code> . 272	I	172, 173, 176,
<code>\biboffset</code>	<code>\if@uuposter@grey</code> .	233, 235–238, 352
. 251–253, 255, 259 11, 141	M
C	<code>\if@uuposter@hasbib</code>	<code>\mainwidth</code> ... 215–218
<code>\ClassWarning</code> 95 106, 248	<code>\maketitle</code> ... 299, 311
<code>\color</code> 291,	<code>\if@uuposter@helvet</code>	
293, 349, 374, 389 6, 128	N
<code>\columnsep</code> 162, 167, 169	<code>\if@uuposter@landscape</code>	<code>\Ncolumntopinarea</code> . 218
	. 13, 113, 241, 336	<code>\newcounter</code> 256, 277, 279

<code>\NewDocumentCommand</code>	<code>\sidebaroffset</code>	<code>\uuposterAuthor</code> 319 , 354
. 56 , 269 , 164 , 182 ,	<code>\uuposterAuthorBlock</code>
276 , 361 , 388 , 389	184 , 185 , 217 , 218 320 , 407 , 416
<code>\newif</code> 3 , 4 ,	<code>\sidebarproportion</code> .	<code>\uuposterAuthorContent</code>
6 , 8 , 10–20 , 23 , 106 97 , 165 322 , 351
<code>\newlength</code> . . 21 , 22 ,	<code>\sidebarwidth</code> . 163 ,	<code>\uuposterAuthorFootSkip</code>
163 , 164 , 168 ,	165 , 166 , 181 , 325 , 355
188 , 198 , 199 ,	184 , 193 , 204 , 228	<code>\uuposterAuthorOffset</code>
215 , 224 , 229 ,	<code>\sigiloffsetx</code> . 198 , 332 , 346
249 , 251 , 261 , 332	201 , 202 , 204 , 212	<code>\uuposterAuthorTextColor</code>
<code>\newstaticframe</code> . .	<code>\sigiloffsety</code> . 199 , 349 , 354 , 360
. 212 , 228 ,	207 , 209 , 210 , 212	<code>\uuposterAuthorTextStyle</code>
233 , 236 , 238 , 263	<code>\sigilproportion</code> 96 , 197 350 , 354
<code>\normalsize</code> 388	<code>\sigilwidth</code> 59 ,	<code>\uuposterBeforeAuthor</code>
<code>\nr</code> 57 , 58	67 , 75 , 83 , 93 , 321 , 342
	188 , 191 , 193 ,	<code>\uuposterBeforeLogo</code>
	197 , 202 , 210 , 212 364 , 370
O	<code>\subSection</code> 374	<code>\uuposterBeforeTitle</code>
<code>\or</code> 66 , 74 , 82 , 90	<code>\subsection</code> 383 309 , 316
P		<code>\uuposterBibliography</code>
<code>\par</code> 305 , 306	T 269
<code>\PassOptionsToClass</code>	<code>\textcolor</code> 353	<code>\uuposterBibTextColor</code>
. 110 , 114 , 116	<code>\textheight</code> 209 , 218 , 228 267 , 270
<code>\PassOptionsToPackage</code>	<code>\textwidth</code> . . . 165 ,	<code>\uuposterBibTextStyle</code>
. 28 , 102–105	197 , 201 , 216 , 234 268 , 270
<code>\ProcessOptionsX</code> . . 112	<code>\thanks</code> 301	<code>\uuposterBodyTextColor</code>
	<code>\thefirstcol</code> 281 267 , 388 , 424
R	<code>\themaincol</code> 259	<code>\uuposterBodyTextStyle</code>
<code>\raggedleft</code> 395	<code>\thempfootnote</code> 353 388 , 424
<code>\raggedright</code> 300	<code>\thesecondcol</code> 281	<code>\uupostercolwidth</code> .
<code>\refname</code> 265	<code>\tolerance</code> 391 224 , 226
<code>\relax</code> 58 , 112	U	<code>\uuposterInsertVerticalRules</code>
<code>\renewcommand</code> . 265 ,	<code>\uuposter@biblines</code> 276 , 286
299 , 353 , 378 , 383 108 , 250	<code>\uuposterInst</code> 361
<code>\RenewDocumentCommand</code>	<code>\uuposter@biboffset</code>	<code>\uuposterInstTextColor</code>
. 59 , 67 , 75 , 83 , 93 109 , 253 360 , 362
<code>\RequirePackage</code> . .	<code>\uuposter@columns</code> 53 ,	<code>\uuposterInstTextStyle</code>
. 1 , 2 , 120 , 123 ,	218 , 254 , 258 , 280 359 , 362
126 , 129 , 132 ,	<code>\uuposter@LogoInclude</code>	<code>\uuposterLogo</code>
146 , 148 , 149 , 160 55 , 367 369 , 404 , 415
S	<code>\uuposter@TitleHeight</code>	<code>\uuposterLogoContent</code>
<code>\section</code> 374	. . 22 , 100 , 172 , 367 , 371
<code>\setallstaticframes</code> 288	176 , 177 , 191 , 218	<code>\uuposterSectionTextColor</code>
<code>\setflowframe</code> 259	<code>\uuposterAfterAuthor</code> 374
<code>\setstaticframe</code> 323 , 358	<code>\uuposterSectionTextStyle</code>
. 213 , 220 ,	<code>\uuposterAfterLogo</code> 374
222 , 231 , 240 , 264 368 , 372	<code>\uuposterSigil</code>
<code>\sffamily</code> 297 ,	<code>\uuposterAfterTitle</code>	. 56 , 56 , 59 , 67 ,
350 , 359 , 375 , 377 313 , 318	75 , 83 , 93 , 396 , 420

<code>\uuposterSubSectionTextColor</code> 289 , 303	<code>\vfill</code> 344, 419
..... 374	<code>\uuposterTitleTextStyle</code>	<code>\vskip</code> 271, 346
<code>\uuposterSubSectionTextStyle</code> 289 , 304	<code>\vspace</code>	... 327, 329, 365
..... 374			
<code>\uuposterTitle</code>	V	X
.... 315 , 401, 411	<code>\val</code> 57	<code>\xcolor</code>
<code>\uuposterTitleContent</code>	<code>\value</code> 152, 156 132
..... 311 , 317	<code>\vcolumnsep</code>	161, 173, 185	Z
<code>\uuposterTitleTextColor</code>	<code>\veryHuge</code> 297	<code>\z0</code>
		 379, 384