```
mysql> SELECT * FROM student WHERE marks > (SELECT AVG(marks) FROM student);
+-------+------+----------+-------+-------------+-------------+
| regno | name | courseno | marks | FacultyDOJ | asessments |
+-------+------+----------+-------+-------------+-------------+
|  1234 | nani | co01     |    50 |        2001 |           5 |
|  1254 | ramu | co01     |    50 |        2002 |           4 |
+-------+------+----------+-------+-------------+-------------+
2 rows in set (0.00 sec)
```

```
mysql> SELECT name FROM student WHERE asessments>1;
+-------+
| name |
+------+
| nani |
| ramu |
| ravi |
+------+
3 rows in set (0.00 sec)
```

```
mysql> SELECT * FROM faculty ORDER BY Doj limit 1;
+-------+-------------+--------+------------+------------+------------+--------+
| FacNo | FacultyName | gender | Dob        | Doj        | Mobileno   | DeptNo |
+-------+-------------+--------+------------+------------+------------+--------+
| f01   | chaithu     | M      | 2000-01-01 | 2020-01-01 | 9876543210 | cse    |
+-------+-------------+--------+------------+------------+------------+--------+
1 row in set (0.00 sec)
```

```
mysql> SELECT courseno,marks FROM student WHERE marks>(SELECT avg(marks) FROM student) ORDER BY courseno;
+----------+-------+
| courseno | marks |
+----------+-------+
| co01     |    50 |
| co01     |    50 |
+----------+-------+
2 rows in set (0.00 sec)

mysql>
```