

NotesTeX

An All-In-One Notes Package For Students

Aditya Dhumuntarao¹

*DAMTP, University of Cambridge
Perimeter Institute of Theoretical Physics
University of Minnesota*

E-mail: adhumunt@gmail.com

¹ *[My Personal Website](#)*

Contents

I	Introduction	1
1	Motivation	1
2	Required Packages	1
3	License	1
II	Modifications	2
4	Features	2
5	Included Packages	2
6	Margins	3
6.1	Why use both <code>marginnotes</code> and <code>sidenotes</code> ?	3
7	<code>T_EX</code> Shortcuts	4
7.1	Available Shortcuts	4
8	<code>amsthm</code> Environments	5
8.1	<code>tcolorbox</code> Environment and Known Issues	7
9	The Part Environment	7
10	Fullpage Environment	8
10.1	Known Issues with Fullpage	8
III	Advanced Page Formatting	9
11	Page Dimensions	9
12	Fancyhdr Layout	9
13	Alternative Language Integration: Persian	10

Introduction

1 Motivation

During my year as a Part III student at Cambridge, I realized that my theoretical physics professors, namely David Tong and David Skinner, would use the `jhep` format to typeset the notes for their classes. As the year went on, I started typesetting my personal notes during class and realized that the `jhep` format, while great for publications and lecture notes in general, was lacking a few small but useful features.

I came across James P. Sethna's wonderful text on statistical mechanics, published by the Oxford University Press, and loved the formatting of the OUP. Sadly the OUP does not have a publicly released LaTeX `.sty` file for their content, and while the `Memoir` class and the `Tufte` style packages provide extensive functionality, I needed something slightly different and a package that was more readily modifiable. Enter *NotesTeX*.

The result of this year long work, from 2016-2017, is the package now known as *NotesTeX*. The purpose of this package was to consolidate all these changes that I slowly incorporated into the original `jhep` format, and to provide stable support for commonly used physics and mathematics environments. I sincerely hope that you enjoy the package!

Section 1. Motivation
Section 2. Required Packages
Section 3. Margins

2 Required Packages

For *NotesTeX*, the following packages are required

`marginnote`, `sidenotes`, `fancyhdr`, `titlesec`, `geometry`, and `tcolorbox`.

The roles of each of these packages will be discussed in Part II. However, for a brief summary, the `marginnote`, `sidenote`, `titlesec`, and `tcolorbox` packages are used in creating the `\part` environment, the package `geometry` is used globally to set the page width, page height, and margin width, and finally, `fancyhdr`, which is overridden on the title page, the contents page, and the `\part` page, sets the header for the body.

3 License

Aditya Dhumuntarao does not own the copyright to the original package, `jheppub.sty`. All modification have been approved by the Jhep Editorial committee, and permission has been attributed to Aditya to distribute freely the modified version of `jheppub.sty`, known as *NotesTeX.sty*.

This work may be distributed and/or modified under the conditions of the LaTeX Project Public License, either version 1.3 of this license or (at your option) any later version. The latest version of this license is found [here](#), and version 1.3 or later is part of all distributions of LaTeX version 2005/12/01 or later. The current maintainer of this work is Aditya Dhumuntarao.¹

¹Please contact me at my email if you have any questions or comments.

Modifications

4 Features

While *NotesTeX*² inherits most of the **jhep** formatting for sections, subsections, subsubsections, title page, contents page, and bibliography presets, there are significant departures from the original format and underlying features. The central focus of this package was to expand the use of the margin in order to include; simple marginnotes, numbered side-notes, marginfigures, and margintables. The secondary motivation was to include a list of preloaded packages that any physics or mathematics students would require while typesetting notes. Lastly, there are a few stylistic improvements that allow for better readability.

NotesTeX includes the following:

1. Several mathematics and physics packages.
2. Margins and margin environments for tables, figures, and asides.
3. \TeX shortcuts for various math scripts namely vector bold math, **mathbb**, **mathfrak**, and **mathcal**.
4. **amsthm** integrations and special environments for theorems, lemmas, proofs, definitions, examples, and remarks.
5. Stylized support for the **part** environment.
6. A fullpage environment that spans across the text width and the margin for longer equations and horizontal figures.

Each of these will be discussed in the following subsections.

5 Included Packages

Additional package are listed right under the required packages in **NotesTeX.sty**. These are divided into font styling packages and mathematical and physics related packages. The list of packages are also reiterated here and their links are in the sidenotes.

<code>\usepackage[T1]{fontenc}</code>	% Font Styling
<code>\usepackage{lmodern,mathrsfs}</code>	
<code>\usepackage[shortlabels]{enumitem}</code>	% Enumitem Options
<code>\usepackage{mathtools,amssymb,amsfonts,amsthm,bm}</code>	% Math Presets
<code>\usepackage{array,tabularx,booktabs}</code>	% Table Presets
<code>\usepackage{graphicx,wrapfig,float,caption}</code>	% Figure Presets
<code>\usepackage{setspace,multicol}</code>	% Text Presets
<code>\usepackage{tikz,physics,cancel}</code>	% Physics Presets

Section 4. Features
 Section 5. Included Packages
 Section 6. Margins
 Section 7. Shortcuts
 Section 8. **amsthm** Environments
 Section 9. Part Environment
 Section 10. Fullpage Environment

Table 1. Contents for PART II

[fontenc](#)
[mathrsfs](#)
[enumitem](#)
[mathtools](#)
[amsfonts](#)
[amsthm](#)
[bm](#)
[array](#)
[tabularx](#)
[booktabs](#)
[graphicx](#)
[float](#)
[caption](#)
[setspace](#)
[multicol](#)
[tikz](#)
[physics](#)
[cancel](#)

Table 2. Links

²Affectionately called *NoTeX*.

6 Margins

NotesTeX inherits all the margin commands that are used by `sidenote` and `marginnote`, and two additional pre-configured commands known as `\mn` and `\sn`. The relevant commands, and the packages they belong to, are

`\marginfigure [sidenote]`
`\sidenote [sidenote]`
`\marginnote [marginnote]`

`\margintable [sidenote]`
`\sn [NotesTeX]`
`\mn [NotesTeX]`

The implementation of each of these is as follows.

1. **Marginnote:** This is how a `\marginnote{...}` behaves.

2. **Mn:** This is how a `\mn{...}` behaves.¹

3. **Sidenote:** This is how a `\sidenote{...}` behaves.²

4. **Sn:** This is how a `\sn{...}` behaves.³

5. **Marginfigure:** This environment requires the `\begin{marginfigure} ... \end{marginfigure}` enclosings. The `caption` package is needed to caption the figure.

6. **Margintable:** This environment requires the `\begin{margintable} ... \end{margintable}` enclosings. A table package, such as `tabular`, `tabulary`, `tabu`, or `tabularx` is required. The `caption` package is needed to caption the table.

Not numbered, 10pt.

¹ *Numbered, footnotesize.*

² *Numbered, 10pt.*

³ *Numbered, footnotesize.*




Figure 1. Marginfigure: Tikz

<i>NotesTeX</i>	rocks!
-----------------	---------------

Table 3. Margintable

6.1 Why use both marginnotes and sidenotes?

Quite simply, `marginnotes` overlap each other if they are too close. This means that figures, and tables can overlap by just using `marginnotes`. This is why `sidenotes` is so useful as it not only numbers all side notes, but also dynamically aligns all side notes, figures, and tables.

So clearly, `sidenotes` must be better right? There are a few places where `sidenotes` fails too however. For instance, `sidenotes` cannot be used in equations, `multicols`, and with the `tcolorbox`⁴ environment. As the majority of the special environments from `amsthm` are modified to use `tcolorbox`, `marginnotes` becomes an essential part of *NotesTeX*.

⁴ See 8 and 10 for more details.

7 TEX Shortcuts

NotesTeX comes built in with a minimal set of keyboard shortcuts for a few special characters. All of these shortcuts can be found in `NotesTeX.sty` just under

```
% -----
%           User Created Commands
% -----
...
```

If one has their own macros,⁵ then simply add it under this area.

7.1 Available Shortcuts

To keep things light, *NotesTeX* offers the following simplifications/shortcuts to the mathematics dictionary.

1. **Vector Bold Math:** The shortcut `{\bf ·} → \bf·` creates boldface text. For example, `{\bf a}` becomes `\bfa` producing the output **a**. This works for both upper and lower case alphabet.
2. **Mathfrak:** The `\mathfrak` environment is quite similar to the Vector Bold Math in the shortcut argument, `\mathfrak{·} → \mf·`. This works for both upper and lower case producing

a b c d e f g h i j k l m n o p q r s t u v w x y z
A B C D E F G H I J K L M N O P Q R S T U V W X Y Z

3. **Mathbb:** All `\mathbb{·}` objects are turned into `\bb{·}`. This only works for uppercase alphabet.

A B C D E F G H I J K L M N O P Q R S T U V W X Y Z

4. **Mathcal:** All `\mathcal{·}` objects are turned into `\mc{·}`. This only works for uppercase alphabet.

A B C D E F G H I J K L M N O P Q R S T U V W X Y Z

⁵ Most people have their own shortcuts for commonly used mathematics, such as derivatives or integrals. For those looking for physics shortcuts, the excellent `physics` package (automatically included in *NotesTeX*) has possible everything that one can imagine.

8 amsthm Environments

`amsthm` environments are defined as usual being enclosed by `\begin{environment}`...`\end{environment}` and most have been modified ostensibly from the original `amsthm` presets. Primarily, most environments, with the exception of the exercise environment, are now integrated with the wonderful `tcolorbox` package. Note that the counting for theorems and lemmas is distinct from the counting for definitions. Also note that the `breakable` for `tcolorbox` allows these environments to span multiple pages.

Definition 8.1. The definition environment and the associated `tcolorbox` are provided by the following code in `NotesTeX.sty`:

```
\tcolorboxenvironment{definition}{
  boxrule=0pt,
  boxsep=0pt,
  colback={White!90!Cerulean},
  enhanced jigsaw,
  borderline west={2pt}{0pt}{Cerulean},
  sharp corners,
  before skip=10pt,
  after skip=10pt,
  breakable,
}
```

Theorem 8.1. The theorem environment and the associated `tcolorbox` are provided by the following code in `NotesTeX.sty`:

```
\tcolorboxenvironment{theorem}{
  boxrule=0pt,
  boxsep=0pt,
  colback={White!90!Dandelion},
  enhanced jigsaw,
  borderline west={2pt}{0pt}{Dandelion},
  sharp corners,
  before skip=10pt,
  after skip=10pt,
  breakable,
}
```

Lemma 8.2. The lemma environment and the associated `tcolorbox` are provided by the following code in `NotesTeX.sty`:

```
\tcolorboxenvironment{lemma}{
  boxrule=0pt,
  boxsep=0pt,
  blanker,
  borderline west={2pt}{0pt}{Red},
  before skip=10pt,
  after skip=10pt,
  sharp corners,
  left=12pt,
```

```

    right=12pt,
    breakable,
}

```

Proof. The `proof` environment and the associated `tcolorbox` are provided by the following code in `NotesTeX.sty`:

```

\tcolorboxenvironment{proof}{
  boxrule=0pt,
  boxsep=0pt,
  blanker,
  borderline west={2pt}{0pt}{NavyBlue!80!white},
  before skip=10pt,
  after skip=10pt,
  left=12pt,
  right=12pt,
  breakable,
}

```

□

Example. The `example` environment and the associated `tcolorbox` are provided by the following code in `NotesTeX.sty`:

```

\tcolorboxenvironment{example}{
  boxrule=0pt,
  boxsep=0pt,
  blanker,
  borderline west={2pt}{0pt}{Black},
  sharp corners,
  before skip=10pt,
  after skip=10pt,
  left=12pt,
  right=12pt,
  breakable,
}

```

Remark. The `remark` environment and the associated `tcolorbox` are provided by the following code in `NotesTeX.sty`:

```

\tcolorboxenvironment{remark}{
  boxrule=0pt,
  boxsep=0pt,
  blanker,
  borderline west={2pt}{0pt}{Green},
  before skip=10pt,
  after skip=10pt,
  left=12pt,
  right=12pt,
  breakable,
}

```

Exercise. The `exercise` environment remains unchanged from the `amsthm` presets.

8.1 tcolorbox Environment and Known Issues

There is one issue with this however. Since we are using a `tcolorbox`, this proof environment is incompatible with `\sn` and `\sidenote`, as it results in a **Float(s) Error**. However, this environment is compatible with `\mn` and `\marginnote` thankfully.⁶


The `breakable` should allow the `proof` environment to span multiple pages. If one wishes to change the color, simply modify the line which states `borderline west={1pt}{0pt}{blue}`. The first numeric value dictates the width of the line, the second dictates how close it is away from the *left* margin, while the last argument obviously dictates the color. This code could also be used to change any of the other `amsthm` environments.

Not a major one but frustrating nonetheless.

⁶ As one can see right here.

9 The Part Environment

In the original Jhep format, the `\part` environment is not special and is set to the default given by the article class. In *NotesTeX*, the `part` environment produces the following image. Furthermore the code responsible is noted below.



```
\titleformat{\part}[hang]{\thispagestyle{plain}}\Huge\bfseries{\marginnote{
\begin{tcolorbox}
[width=\marginparwidth,height=\marginparwidth/2,colback=black!75!white,
colframe=black!75!white,center title,fonttitle=\bfseries\normalsize,title=PART,
text fill]

\begin{center}
{\color{white}\thepart}
\end{center}

\end{tcolorbox}
}[-1.25in]{0pt}{\Huge\bfseries}
```

This combines the `titlesec` and the `tcolorbox` packages, placing the title of the `\part` on the left hand side, and the `\part` number in the margin. It is recommended that one do not mess with this, other than changing the colors given by `colback` and `colframe`.

10 Fullpage Environment

The `fullpage` environment is defined by

```
\begin{fullpage}
...
\end{fullpage}
```

with the width of the `fullpage` environment given by `\textwidth+\marginparsep+\marginparwidth`.

There are some clear benefits of having use of the full page at times. Suppose that one wants to place a figure that cannot fit into the margins, or if an equation is quite long and it bleeds into the margin, then the `fullpage` environment can both clearly separate these from the surrounding text and allot for the dimensions without hassle. The code in `NotesTeX.sty` that is responsible for the `fullpage` environment is given by⁷

⁷ *This is also an example of why the `fullpage` environment is nice.*

```
\newenvironment{fullpage}{
\smallskip\noindent
\begin{minipage}{\textwidth+\marginparwidth+\marginparsep}\hrule\smallskip\smallskip}
{\smallskip\smallskip\hrule\end{minipage}\vspace{.1in}}
}
```

Remark. If one do not like the lines at the beginning and end of the `fullpage` environment, simply remove all the `\hrule` that is in the code. Similarly, it is possible to change the vertical spacing after the `fullpage` is over, by modifying the `\vspace{}` argument.

A major benefit of having a `fullpage` is the ability to use `multicols` to its fullest extent. For example, these empty sentences are an example of how effective the `multicols` package can be inside of the `fullpage` environment.

This would be especially useful for formatting exercises in multiple columns and it makes the text distinct from the rest of the `fullpage` environment. The author has run out of things to say.

10.1 Known Issues with Fullpage

There are a few issues with the `fullpage` however.

Remark. Since the `fullpage` environment uses a `minipage`, and minipages do not work over multiple pages, one will need a new `fullpage` per page.

Remark. Also, please note `marginnote`, or `sidenotes` cannot be used in this environment. Footnotes, on the other hand, can be used but are really ugly.

Remark. If the `twoside` option is enabled in the `documentclass` header, then the `fullpage` is known to bleed out beyond the margin.

Advanced Page Formatting

For those wanting to adjust the margin sizes, or the `fancyhdr` layout, there are a few comments that could be made here.

11 Page Dimensions

Notes *TeX* relies on the `geometry` package to set its dimensions. The associated code is the deceptively simple chunk of code given by

```
\geometry{paperheight=845pt,paperwidth=597pt,
  marginparsep=.02\paperwidth,marginparwidth=.23\paperwidth,
  inner=.05\paperwidth,voffset=-1in,headheight=.02\paperheight,
  headsep=.03\paperheight,footskip=20pt,
  textheight=.84\paperheight,textwidth=.64\paperwidth}
```

Ignoring most of the arguments, the `\paperheight` and `\paperwidth` are set to be the standard 8×11 inches but in `pt` format instead. All other options, with the exception of `\voffset`, inherit fractions of `\paperheight` and `\paperwidth`, the most important being `\marginparwidth`. Increasing `\marginparwidth` causes the margin to bleed off of the right side of the page. In order to increase, one **must** decrease the `\textwidth` accordingly.

12 Fancyhdr Layout

As mentioned before, `fancyhdr` is overridden on the title page, the contents page, and the `\part` page, and sets the header for all other pages through the code

```
\pagestyle{fancy}%
\newlength{\offset}%
\setlength{\offset}{\marginparwidth + \marginparsep}%
\renewcommand{\sectionmark}[1]{\markboth{#1}{}}%
\renewcommand{\subsectionmark}[1]{\markright{#1}{}}%

\fancypagestyle{fancynotes}{%
  \fancyhf{}%
  \fancyheadoffset[rh]{\offset}%
  \renewcommand{\headrulewidth}{0pt}%
  \fancyhead[L]{\textsc{\leftmark}}%
  \fancyhead[R]{\footnotesize \textit{\rightmark}~~~~ \thepage}%
}%
```

The header style is set so that it spans the width of the entire page as opposed to just the `\textwidth` through the line `\fancyheadoffset[rh]{\myoddoffset}`. The `\sectionmark` and `\subsectionmark` are set up so that the `section` appears on the left and `subsections` appear on the right along with the page number, and this is given in the last two lines of code.

13 Alternative Language Integration: Persian

For languages which flow from right to left, such as Persian, we have developed a way⁸ to use *NotesTeX* and `xePersian`. A complied example can be found in the Persian folder.

⁸ *We are still exploring issues with integration of Persian.*

Remark. This only works with the XeLaTeX engine.

Remark. We have only tested the [XB Niloofar](#) font. In principle, any Persian font could work.

Remark. One must load the `xePersian` package just before `\begin{document}`.

The `twoside` option must be enabled in the `documentclass`. A minimal working example is given below.

```
\documentclass[10pt,twoside]{article}
```

```
\usepackage{lipsum}
```

```
\usepackage{NoTeX_Persian}
```

```
\usepackage{xepersian}
```

```
\settextfont{XB Niloofar}
```

```
\setlatintextfont{Times New Roman}
```

```
\begin{document}
```

```
...
```

As we have noted before, the `fullpage` environment will fail here since it is incompatible with the `twoside` option. Also the title page is shifted by the `twoside` option, see [here](#) for a workaround. However, the `sidenote` and `marginnote` packages work well with the `twoside` option.