

ANDROID STATIC ANALYSIS REPORT



\Pi Lightning (5.1.0)

File Name:	web1.apk		
Package Name:	acr.browser.lightning		
Scan Date:	May 23, 2022, 5:04 p.m.		
App Security Score:	42/100 (MEDIUM RISK		
Grade:			

FINDINGS SEVERITY

派 HIGH	▲ MEDIUM	i INFO	✓ SECURE	ℚ HOTSPOT
6	12	2	2	1

FILE INFORMATION

File Name: web1.apk
Size: 3.27MB

MD5: 53fe67fa520915c26175e3b94fcf7da2

SHA1: 33138fd5bc32e2a841a734b8a410162f370e7758

SHA256: 820f4f9977a20b060b4091db2b35cff8cd360e060f94aa742255c845747a2d7f

i APP INFORMATION

App Name: Lightning

Package Name: acr.browser.lightning

Main Activity: acr.browser.lightning.MainActivity

Target SDK: 29 Min SDK: 19 Max SDK:

Android Version Name: 5.1.0
Android Version Code: 101

B APP COMPONENTS

Activities: 4 Services: 0 Receivers: 0 Providers: 1

Exported Activities: 3 Exported Services: 0 Exported Receivers: 0 Exported Providers: 0

***** CERTIFICATE INFORMATION

APK is signed v1 signature: True v2 signature: False v3 signature: False

Found 1 unique certificates

Subject: C=UK, ST=ORG, L=ORG, O=fdroid.org, OU=FDroid, CN=FDroid

Signature Algorithm: rsassa_pkcs1v15 Valid From: 2014-06-25 10:14:27+00:00 Valid To: 2041-11-10 10:14:27+00:00

Issuer: C=UK, ST=ORG, L=ORG, O=fdroid.org, OU=FDroid, CN=FDroid

Serial Number: 0x7d3e0ae1 Hash Algorithm: sha256

md5: d56c4e05c5007ad77d2071fd78381f17

sha1: 7f57aa7e1d20bd64ccd07a01778e2a484a9fc93f

sha256: fe63eb794a51ef486d2ab633ed87628c8f7df656fca2d97cb2182610a38aca3b

sha512: b3bc2e2d2058e3b9c41328d7d3f67fdaec61b6577e9884f88575d83b709df13862bf6f6a0fa9aea95ab93cf1e57911129569bf1289416ba6b5f420118fb1afc76ab6b2f4

TITLE	SEVERITY	DESCRIPTION
Signed Application	info	Application is signed with a code signing certificate

TITLE	SEVERITY	DESCRIPTION
Application vulnerable to Janus Vulnerability	high	Application is signed with v1 signature scheme, making it vulnerable to Janus vulnerability on Android 5.0-8.0, if signed only with v1 signature scheme. Applications running on Android 5.0-7.0 signed with v1, and v2/v3 scheme is also vulnerable.

⋮ APPLICATION PERMISSIONS

PERMISSION	STATUS	INFO	DESCRIPTION
android.permission.INTERNET	normal	full Internet access	Allows an application to create network sockets.
android.permission.WRITE_EXTERNAL_STORAGE	dangerous	read/modify/delete external storage contents	Allows an application to write to external storage.
android.permission.READ_EXTERNAL_STORAGE	dangerous	read external storage contents	Allows an application to read from external storage.
android.permission.ACCESS_FINE_LOCATION	dangerous	fine (GPS) location	Access fine location sources, such as the Global Positioning System on the phone, where available. Malicious applications can use this to determine where you are and may consume additional battery power.
android.permission.ACCESS_NETWORK_STATE	normal	view network status	Allows an application to view the status of all networks.
com.android.launcher.permission.lNSTALL_SHORTCUT	unknown	Unknown permission	Unknown permission from android reference
android.permission.RECORD_AUDIO	dangerous	record audio	Allows application to access the audio record path.

PERMISSION	STATUS	INFO	DESCRIPTION
android.permission.CAMERA	dangerous	take pictures and videos	Allows application to take pictures and videos with the camera. This allows the application to collect images that the camera is seeing at any time.
android.permission.MODIFY_AUDIO_SETTINGS	normal	change your audio settings	Allows application to modify global audio settings, such as volume and routing.

命 APKID ANALYSIS

FILE	DETAILS		
classes.dex	FINDINGS DETAILS		
clusses.dex	Compiler	r8	

BROWSABLE ACTIVITIES

ACTIVITY	INTENT
acr.browser.lightning.MainActivity	Schemes: file://, http://, https://, about://, javascript://, inline://, Mime Types: text/html, text/plain, application/xhtml+xml, application/vnd.wap.xhtml+xml, application/x-webarchive-xml,



NO	SCOPE	SEVERITY	DESCRIPTION	

Q MANIFEST ANALYSIS

NO	ISSUE	SEVERITY	DESCRIPTION
1	Clear text traffic is Enabled For App [android:usesCleartextTraffic=true]	high	The app intends to use cleartext network traffic, such as cleartext HTTP, FTP stacks, DownloadManager, and MediaPlayer. The default value for apps that target API level 27 or lower is "true". Apps that target API level 28 or higher default to "false". The key reason for avoiding cleartext traffic is the lack of confidentiality, authenticity, and protections against tampering; a network attacker can eavesdrop on transmitted data and also modify it without being detected.
2	Application Data can be Backed up [android:allowBackup=true]	warning	This flag allows anyone to backup your application data via adb. It allows users who have enabled USB debugging to copy application data off of the device.
3	Launch Mode of Activity (acr.browser.lightning.MainActivity) is not standard.	high	An Activity should not be having the launch mode attribute set to "singleTask/singleInstance" as it becomes root Activity and it is possible for other applications to read the contents of the calling Intent. So it is required to use the "standard" launch mode attribute when sensitive information is included in an Intent.
4	Launch Mode of Activity (acr.browser.lightning.lncognitoActivity) is not standard.	high	An Activity should not be having the launch mode attribute set to "singleTask/singleInstance" as it becomes root Activity and it is possible for other applications to read the contents of the calling Intent. So it is required to use the "standard" launch mode attribute when sensitive information is included in an Intent.
5	Activity (acr.browser.lightning.lncognitoActivity) is not Protected. An intent-filter exists.	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device. The presence of intent-filter indicates that the Activity is explicitly exported.

NO	ISSUE	SEVERITY	DESCRIPTION
6	Activity (acr.browser.lightning.settings.activity.SettingsActivity) is not Protected. An intent-filter exists.	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device. The presence of intent-filter indicates that the Activity is explicitly exported.
7	Activity (acr.browser.lightning.reading.activity.ReadingActivity) is not Protected. An intent-filter exists.	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device. The presence of intent-filter indicates that the Activity is explicitly exported.

</> CODE ANALYSIS

NO	ISSUE	SEVERITY	STANDARDS	FILES
1	This App copies data to clipboard. Sensitive data should not be copied to clipboard as other applications can access it.	info	OWASP MASVS: MSTG-STORAGE-10	acr/browser/lightning/j.java
2	App can read/write to External Storage. Any App can read data written to External Storage.	warning	CWE: CWE-276: Incorrect Default Permissions OWASP Top 10: M2: Insecure Data Storage OWASP MASVS: MSTG-STORAGE-2	acr/browser/lightning/a0/e.java acr/browser/lightning/n0/g.java acr/browser/lightning/settings/fragme nt/a0.java acr/browser/lightning/settings/fragme nt/q.java acr/browser/lightning/settings/fragme nt/BookmarkSettingsFragment.java acr/browser/lightning/n0/r.java

NO	ISSUE	SEVERITY	STANDARDS	FILES
3	The App logs information. Sensitive information should never be logged.	info	CWE: CWE-532: Insertion of Sensitive Information into Log File OWASP MASVS: MSTG-STORAGE-3	c/m/a/e.java d/c/a/a/a.java d/b/a/b.java net/i2p/android/router/service/State.ja va acr/browser/lightning/c0/b.java c/h/b/k.java acr/browser/lightning/reading/activity/ ReadingActivity.java acr/browser/lightning/r/v/e/a.java c/o/a/a/u.java acr/browser/lightning/view/o0.java acr/browser/lightning/l0/b0/b.java acr/browser/lightning/n0/g.java c/j/a/l.java acr/browser/lightning/g.java c/j/a/l.java acr/browser/lightning/reading/Convert er.java c/h/h/m.java acr/browser/lightning/reading/Convert er.java c/h/b/g.java c/h/b/b.java acr/browser/lightning/reading/ArticleT extExtractor.java acr/browser/lightning/n0/n.java c/b/b/a/b.java acr/browser/lightning/mo/n.java c/b/b/a/b.java acr/browser/lightning/mo/n.java c/h/h/h.java acr/browser/lightning/ho/a.java c/h/b/f.java f/a/a/b/a.java acr/browser/lightning/ho/r.java c/h/b/a.java acr/browser/lightning/no/r.java c/h/b/a.java acr/browser/lightning/no/r.java c/h/b/a.java acr/browser/lightning/no/r.java

NO	ISSUE	SEVERITY	STANDARDS	FILES
4	This App uses SSL certificate pinning to detect or prevent MITM attacks in secure communication channel.	secure	OWASP MASVS: MSTG-NETWORK-4	k/s0.java org/jsoup/helper/HttpConnection.java
5	IP Address disclosure	warning	CWE: CWE-200: Information Exposure OWASP MASVS: MSTG-CODE-2	acr/browser/lightning/r/t/b.java
6	App uses SQLite Database and execute raw SQL query. Untrusted user input in raw SQL queries can cause SQL Injection. Also sensitive information should be encrypted and written to the database.	warning	CWE: CWE-89: Improper Neutralization of Special Elements used in an SQL Command ('SQL Injection') OWASP Top 10: M7: Client Code Quality	acr/browser/lightning/w/m/j.java acr/browser/lightning/w/n/e.java acr/browser/lightning/w/l/d.java acr/browser/lightning/w/o/f.java acr/browser/lightning/w/k/d.java
7	The App uses an insecure Random Number Generator.	warning	CWE: CWE-330: Use of Insufficiently Random Values OWASP Top 10: M5: Insufficient Cryptography OWASP MASVS: MSTG-CRYPTO-6	org/jsoup/helper/DataUtil.java
8	Insecure WebView Implementation. WebView ignores SSL Certificate errors and accept any SSL Certificate. This application is vulnerable to MITM attacks	high	CWE: CWE-295: Improper Certificate Validation OWASP Top 10: M3: Insecure Communication OWASP MASVS: MSTG-NETWORK-3	acr/browser/lightning/view/o0.java
9	MD5 is a weak hash known to have hash collisions.	warning	CWE: CWE-327: Use of a Broken or Risky Cryptographic Algorithm OWASP Top 10: M5: Insufficient Cryptography OWASP MASVS: MSTG-CRYPTO-4	acr/browser/lightning/r/u/d.java
10	Remote WebView debugging is enabled.	high	CWE: CWE-919: Weaknesses in Mobile Applications OWASP Top 10: M1: Improper Platform Usage OWASP MASVS: MSTG-RESILIENCE-2	acr/browser/lightning/BrowserApp.jav a

NO	ISSUE	SEVERITY	STANDARDS	FILES
11	App creates temp file. Sensitive information should never be written into a temp file.	warning	CWE: CWE-276: Incorrect Default Permissions OWASP Top 10: M2: Insecure Data Storage OWASP MASVS: MSTG-STORAGE-2	acr/browser/lightning/n0/r.java
12	Files may contain hardcoded sensitive information like usernames, passwords, keys etc.	warning	CWE: CWE-312: Cleartext Storage of Sensitive Information OWASP Top 10: M9: Reverse Engineering OWASP MASVS: MSTG-STORAGE-14	org/jsoup/nodes/DocumentType.java

SHARED LIBRARY BINARY ANALYSIS

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
----	---------------	----	-----------------	-------	-------	---------	---------	---------------------

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
1	lib/mips/libjbigi.so	True info The shared object has NX bit set. This marks a memory page non- executable making attacker injected shellcode non- executable.	False high This shared object does not have a stack canary value added to the stack. Stack canaries are used to detect and prevent exploits from overwriting return address. Use the option - fstack- protector-all to enable stack canaries.	Partial RELRO warning This shared object has partial RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In partial RELRO, the non-PLT part of the GOT section is read only but .got.plt is still writeable. Use the option - z,relro,-z,now to enable full RELRO.	None info The shared object does not have run-time search path or RPATH set.	None info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option - D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
2	lib/armeabi-v7a/libjbigi.so	True info The shared object has NX bit set. This marks a memory page non- executable making attacker injected shellcode non- executable.	False high This shared object does not have a stack canary value added to the stack. Stack canaries are used to detect and prevent exploits from overwriting return address. Use the option - fstack- protector-all to enable stack canaries.	Partial RELRO warning This shared object has partial RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In partial RELRO, the non-PLT part of the GOT section is read only but .got.plt is still writeable. Use the option - z,relro,-z,now to enable full RELRO.	None info The shared object does not have run-time search path or RPATH set.	None info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option - D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
3	lib/arm64-v8a/libjbigi.so	True info The shared object has NX bit set. This marks a memory page non- executable making attacker injected shellcode non- executable.	False high This shared object does not have a stack canary value added to the stack. Stack canaries are used to detect and prevent exploits from overwriting return address. Use the option - fstack- protector-all to enable stack canaries.	Partial RELRO warning This shared object has partial RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In partial RELRO, the non-PLT part of the GOT section is read only but .got.plt is still writeable. Use the option - z,relro,-z,now to enable full RELRO.	None info The shared object does not have run-time search path or RPATH set.	None info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option - D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
4	lib/armeabi/libjbigi.so	True info The shared object has NX bit set. This marks a memory page non- executable making attacker injected shellcode non- executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The shared object does not have run-time search path or RPATH set.	None info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option - D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.

■ NIAP ANALYSIS v1.3

NO	IDENTIFIER	REQUIREMENT	FEATURE	DESCRIPTION

NO	IDENTIFIER	REQUIREMENT	FEATURE	DESCRIPTION
1	FCS_RBG_EXT.1.1	Security Functional Requirements	Random Bit Generation Services	The application invoke platform-provided DRBG functionality for its cryptographic operations.
2	FCS_STO_EXT.1.1	Security Functional Requirements	Storage of Credentials	The application does not store any credentials to non-volatile memory.
3	FCS_CKM_EXT.1.1	Security Functional Requirements	Cryptographic Key Generation Services	The application generate no asymmetric cryptographic keys.
4	FDP_DEC_EXT.1.1	Security Functional Requirements	Access to Platform Resources	The application has access to ['location', 'microphone', 'camera', 'network connectivity'].
5	FDP_DEC_EXT.1.2	Security Functional Requirements	Access to Platform Resources	The application has access to no sensitive information repositories.
6	FDP_NET_EXT.1.1	Security Functional Requirements	Network Communications	The application has user/application initiated network communications.
7	FDP_DAR_EXT.1.1	Security Functional Requirements	Encryption Of Sensitive Application Data	The application does not encrypt files in non-volatile memory.
8	FMT_MEC_EXT.1.1	Security Functional Requirements	Supported Configuration Mechanism	The application invoke the mechanisms recommended by the platform vendor for storing and setting configuration options.
9	FTP_DIT_EXT.1.1	Security Functional Requirements	Protection of Data in Transit	The application does encrypt some transmitted data with HTTPS/TLS/SSH between itself and another trusted IT product.

NO	IDENTIFIER	REQUIREMENT	FEATURE	DESCRIPTION
10	FCS_RBG_EXT.2.1,FCS_RBG_EXT.2.2	Selection-Based Security Functional Requirements	Random Bit Generation from Application	The application perform all deterministic random bit generation (DRBG) services in accordance with NIST Special Publication 800-90A using Hash_DRBG. The deterministic RBG is seeded by an entropy source that accumulates entropy from a platform-based DRBG and a software-based noise source, with a minimum of 256 bits of entropy at least equal to the greatest security strength (according to NIST SP 800-57) of the keys and hashes that it will generate.
11	FCS_COP.1.1(2)	Selection-Based Security Functional Requirements	Cryptographic Operation - Hashing	The application perform cryptographic hashing services not in accordance with FCS_COP.1.1(2) and uses the cryptographic algorithm RC2/RC4/MD4/MD5.
12	FCS_HTTPS_EXT.1.1	Selection-Based Security Functional Requirements	HTTPS Protocol	The application implement the HTTPS protocol that complies with RFC 2818.
13	FCS_HTTPS_EXT.1.2	Selection-Based Security Functional Requirements	HTTPS Protocol	The application implement HTTPS using TLS.
14	FCS_HTTPS_EXT.1.3	Selection-Based Security Functional Requirements	HTTPS Protocol	The application notify the user and not establish the connection or request application authorization to establish the connection if the peer certificate is deemed invalid.
15	FIA_X509_EXT.1.1	Selection-Based Security Functional Requirements	X.509 Certificate Validation	The application invoked platform-provided functionality to validate certificates in accordance with the following rules: ['The certificate path must terminate with a trusted CA certificate'].
16	FIA_X509_EXT.2.1	Selection-Based Security Functional Requirements	X.509 Certificate Authentication	The application use X.509v3 certificates as defined by RFC 5280 to support authentication for HTTPS , TLS.

Q DOMAIN MALWARE CHECK

DOMAIN	STATUS	GEOLOCATION
www.facebook.com	ok	IP: 31.13.64.35 Country: Netherlands Region: Noord-Holland City: Amsterdam Latitude: 52.374031 Longitude: 4.889690 View: Google Map
jetsli.de	ok	IP: 185.53.177.33 Country: Germany Region: Bayern City: Munich Latitude: 48.137428 Longitude: 11.575490 View: Google Map
duckduckgo.com	ok	IP: 52.142.124.215 Country: Ireland Region: Dublin City: Dublin Latitude: 53.343990 Longitude: -6.267190 View: Google Map

DOMAIN	STATUS	GEOLOCATION
www.google.com	ok	IP: 142.250.179.164 Country: United States of America Region: California City: Mountain View Latitude: 37.405991 Longitude: -122.078514 View: Google Map
startpage.com	ok	IP: 145.131.132.74 Country: Netherlands Region: Utrecht City: Utrecht Latitude: 52.090832 Longitude: 5.122220 View: Google Map
search.yahoo.com	ok	IP: 212.82.100.137 Country: Ireland Region: Dublin City: Dublin Latitude: 53.343990 Longitude: -6.267190 View: Google Map
www.baidu.com	ok	IP: 104.193.88.77 Country: United States of America Region: California City: Cupertino Latitude: 37.316605 Longitude: -122.046486 View: Google Map

Т

DOMAIN	STATUS	GEOLOCATION
github.com	ok	IP: 140.82.121.4 Country: United States of America Region: California City: San Francisco Latitude: 37.775700 Longitude: -122.395203 View: Google Map
search.naver.com	ok	IP: 223.130.192.148 Country: Korea (Republic of) Region: Gyeonggi-do City: Seongnam Latitude: 37.438610 Longitude: 127.137779 View: Google Map
www.bing.com	ok	IP: 204.79.197.200 Country: United States of America Region: Washington City: Redmond Latitude: 47.682899 Longitude: -122.120903 View: Google Map
yandex.ru	ok	IP: 77.88.55.88 Country: Russian Federation Region: Moskva City: Moscow Latitude: 55.752220 Longitude: 37.615559 View: Google Map

DOMAIN	STATUS	GEOLOCATION
www.w3.org	ok	IP: 128.30.52.100 Country: United States of America Region: Massachusetts City: Cambridge Latitude: 42.365078 Longitude: -71.104523 View: Google Map
www.ask.com	ok	IP: 151.101.38.114 Country: United States of America Region: California City: San Francisco Latitude: 37.775700 Longitude: -122.395203 View: Google Map

▶ HARDCODED SECRETS

POSSIBLE SECRETS "password": "パスワードを記憶する" "password": "保存密码" "password": "儲存密碼"

Report Generated by - MobSF v3.5.2 Beta

Mobile Security Framework (MobSF) is an automated, all-in-one mobile application (Android/iOS/Windows) pen-testing, malware analysis and security assessment

framework capable of performing static and dynamic analysis.

© 2022 Mobile Security Framework - MobSF | <u>Ajin Abraham</u> | <u>OpenSecurity</u>.