

ANDROID STATIC ANALYSIS REPORT



Missed Notifications Reminder (1.3.2.0.10)

File Name:	installer235.apk
Package Name:	com.app.missednotificationsreminder
Scan Date:	May 31, 2022, 4:28 p.m.
App Security Score:	46/100 (MEDIUM RISK)
Grade:	

FINDINGS SEVERITY

派 HIGH	▲ MEDIUM	i INFO	✓ SECURE	♠ HOTSPOT
2	6	1	1	1

FILE INFORMATION

File Name: installer235.apk

Size: 3.87MB

MD5: 923f2f123bb7b2423770d237f1b639cf

SHA1: 6fe237cccddfb3f67bbb38720c62508fc02e660e

SHA256: 21afb493255c956bdf224d6bb0362df1a01f3306cf6ec7212b17eb0434cb848d

i APP INFORMATION

App Name: Missed Notifications Reminder

Package Name: com.app.missednotificationsreminder

Main Activity: com.app.missednotificationsreminder.ui.activity.SettingsActivity

Target SDK: 27 Min SDK: 14 Max SDK:

Android Version Name: 1.3.2.0.10
Android Version Code: 2010302010

EE APP COMPONENTS

Activities: 3 Services: 6 Receivers: 2 Providers: 2

Exported Activities: O Exported Services: 2 Exported Receivers: O Exported Providers: O

***** CERTIFICATE INFORMATION

APK is signed v1 signature: True v2 signature: False v3 signature: False

Found 1 unique certificates

Subject: C=UK, ST=ORG, L=ORG, O=fdroid.org, OU=FDroid, CN=FDroid

Signature Algorithm: rsassa_pkcs1v15 Valid From: 2016-08-10 17:30:03+00:00 Valid To: 2043-12-27 17:30:03+00:00

Issuer: C=UK, ST=ORG, L=ORG, O=fdroid.org, OU=FDroid, CN=FDroid

Serial Number: 0x2ea993b5 Hash Algorithm: sha256

md5: 81f9f5665c5c5599df56eca470ccfb20

sha1: 302e94ddc77fe96666e3056917468623ab750ed4

sha256: e37b940e25515999af1cc3ce198c90bac958e0b12f092b24328f2c6188cbab61

TITLE	SEVERITY	DESCRIPTION
Signed Application	info	Application is signed with a code signing certificate

TITLE	SEVERITY	DESCRIPTION
Application vulnerable to Janus Vulnerability	high	Application is signed with v1 signature scheme, making it vulnerable to Janus vulnerability on Android 5.0-8.0, if signed only with v1 signature scheme. Applications running on Android 5.0-7.0 signed with v1, and v2/v3 scheme is also vulnerable.

⋮ APPLICATION PERMISSIONS

PERMISSION	STATUS	INFO	DESCRIPTION
android.permission.BIND_ACCESSIBILITY_SERVICE	signature		Must be required by an AccessibilityService, to ensure that only the system can bind to it.
android.permission.WAKE_LOCK	normal	prevent phone from sleeping	Allows an application to prevent the phone from going to sleep.
android.permission.READ_EXTERNAL_STORAGE	dangerous	read external storage contents	Allows an application to read from external storage.
android.permission.VIBRATE	normal	control vibrator	Allows the application to control the vibrator.
android.permission.ACCESS_NETWORK_STATE	normal	view network status	Allows an application to view the status of all networks.
android.permission.RECEIVE_BOOT_COMPLETED	normal	automatically start at boot	Allows an application to start itself as soon as the system has finished booting. This can make it take longer to start the phone and allow the application to slow down the overall phone by always running.

命 APKID ANALYSIS

FILE	DETAILS			
classes.dex	FINDINGS DETAILS			
	Compiler	r8		

△ NETWORK SECURITY

	NO	SCOPE	SEVERITY	DESCRIPTION
--	----	-------	----------	-------------

Q MANIFEST ANALYSIS

NO	ISSUE	SEVERITY	DESCRIPTION
1	Application Data can be Backed up [android:allowBackup=true]	warning	This flag allows anyone to backup your application data via adb. It allows users who have enabled USB debugging to copy application data off of the device.

NO	ISSUE	SEVERITY	DESCRIPTION
2	Service (com.app.missednotificationsreminder.service.ReminderNotificationListenerService) is Protected by a permission, but the protection level of the permission should be checked. Permission: android.permission.BIND_ACCESSIBILITY_SERVICE [android:exported=true]	warning	A Service is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device. It is protected by a permission which is not defined in the analysed application. As a result, the protection level of the permission should be checked where it is defined. If it is set to normal or dangerous, a malicious application can request and obtain the permission and interact with the component. If it is set to signature, only applications signed with the same certificate can obtain the permission.
3	Launch Mode of Activity (com.app.missednotificationsreminder.ui.activity.SettingsActivity) is not standard.	high	An Activity should not be having the launch mode attribute set to "singleTask/singleInstance" as it becomes root Activity and it is possible for other applications to read the contents of the calling Intent. So it is required to use the "standard" launch mode attribute when sensitive information is included in an Intent.
4	Service (com.evernote.android.job.gcm.PlatformGcmService) is Protected by a permission, but the protection level of the permission should be checked. Permission: com.google.android.gms.permission.BIND_NETWORK_TASK_SERVICE [android:exported=true]	warning	A Service is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device. It is protected by a permission which is not defined in the analysed application. As a result, the protection level of the permission should be checked where it is defined. If it is set to normal or dangerous, a malicious application can request and obtain the permission and interact with the component. If it is set to signature, only applications signed with the same certificate can obtain the permission.



NO	ISSUE	SEVERITY	STANDARDS	FILES
1	App uses SQLite Database and execute raw SQL query. Untrusted user input in raw SQL queries can cause SQL Injection. Also sensitive information should be encrypted and written to the database.	CWE: CWE-89: Improper Neutralization of Special Elements used in an SQL Command ('SQL Injection') OWASP Top 10: M7: Client Code Quality		com/evernote/android/job/JobStorage.java
2	The App logs information. Sensitive information should never be logged.	info	CWE: CWE-532: Insertion of Sensitive Information into Log File OWASP MASVS: MSTG-STORAGE-3	com/wdullaer/materialdatetimepicker/time/TimePickerDialog.java com/wdullaer/materialdatetimepicker/time/RadialPickerLayout.java com/app/missednotificationsreminder/ui/activity/common/AppCompatActivityWithNestedFragmentFix.java com/tbruyelle/rxpermissions/RxPermissions.java com/wdullaer/materialdatetimepicker/time/RadialTextsView.java timber/log/Timber.java com/wdullaer/materialdatetimepicker/date/DayPickerView.java com/wdullaer/materialdatetimepicker/time/RadialSelectorView.java com/wdullaer/materialdatetimepicker/time/CircleView.java com/wdullaer/materialdatetimepicker/time/CircleView.java com/wdullaer/materialdatetimepicker/time/AmPmCirclesView.java com/appyvet/rangebar/RangeBar.java com/appymissednotificationsreminder/service/ReminderNotificationListenerService.java
3	Files may contain hardcoded sensitive information like usernames, passwords, keys etc.	warning	CWE: CWE-312: Cleartext Storage of Sensitive Information OWASP Top 10: M9: Reverse Engineering OWASP MASVS: MSTG-STORAGE-14	rx/internal/schedulers/NewThreadWorker.java dagger/internal/Linker.java dagger/internal/ProvidesBinding.java

NO	ISSUE	SEVERITY STANDARDS		FILES
4	App can read/write to External Storage. Any App can read data written to External Storage.	warning	CWE: CWE-276: Incorrect Default Permissions OWASP Top 10: M2: Insecure Data Storage OWASP MASVS: MSTG-STORAGE-2	com/jakewharton/u2020/data/LumberYard.java

■ NIAP ANALYSIS v1.3

NO	IDENTIFIER	REQUIREMENT	FEATURE	DESCRIPTION
1	FCS_RBG_EXT.1.1	Security Functional Requirements	Random Bit Generation Services	The application use no DRBG functionality for its cryptographic operations.
2	FCS_STO_EXT.1.1	Security Functional Requirements	Storage of Credentials	The application does not store any credentials to non-volatile memory.
3	FCS_CKM_EXT.1.1	Security Functional Requirements	Cryptographic Key Generation Services	The application generate no asymmetric cryptographic keys.
4	FDP_DEC_EXT.1.1	Security Functional Requirements	Access to Platform Resources	The application has access to ['network connectivity'].
5	FDP_DEC_EXT.1.2	Security Functional Requirements	Access to Platform Resources	The application has access to no sensitive information repositories.
6	FDP_NET_EXT.1.1	Security Functional Requirements	Network Communications	The application has no network communications.

NO	IDENTIFIER	REQUIREMENT	FEATURE	DESCRIPTION
7	FDP_DAR_EXT.1.1	Security Functional Requirements	Encryption Of Sensitive Application Data	The application implement functionality to encrypt sensitive data in non-volatile memory.
8	FMT_MEC_EXT.1.1	Security Functional Requirements	Supported Configuration Mechanism	The application invoke the mechanisms recommended by the platform vendor for storing and setting configuration options.
9	FTP_DIT_EXT.1.1	Security Functional Requirements	Protection of Data in Transit	The application does encrypt some transmitted data with HTTPS/TLS/SSH between itself and another trusted IT product.
10	FCS_HTTPS_EXT.1.2	Selection-Based Security Functional Requirements	HTTPS Protocol	The application implement HTTPS using TLS.
11	FCS_HTTPS_EXT.1.3	Selection-Based Security Functional Requirements	HTTPS Protocol	The application notify the user and not establish the connection or request application authorization to establish the connection if the peer certificate is deemed invalid.
12	FIA_X509_EXT.2.1	Selection-Based Security Functional Requirements	X.509 Certificate Authentication	The application use X.509v3 certificates as defined by RFC 5280 to support authentication for HTTPS , TLS.

Q DOMAIN MALWARE CHECK

DOMAIN	STATUS	GEOLOCATION

DOMAIN	STATUS	GEOLOCATION
github.com	ok	IP: 140.82.121.3 Country: United States of America Region: California City: San Francisco Latitude: 37,775700 Longitude: -122.395203 View: Google Map
xmlpull.org	ok	IP: 74.50.61.58 Country: United States of America Region: Texas City: Dallas Latitude: 32.814899 Longitude: -96.879204 View: Google Map

HARDCODED SECRETS

POSSIBLE SECRETS

"mdtp_deleted_key": "%1\$sを削除しました"

Report Generated by - MobSF v3.5.2 Beta

Mobile Security Framework (MobSF) is an automated, all-in-one mobile application (Android/iOS/Windows) pen-testing, malware analysis and security assessment framework capable of performing static and dynamic analysis.

© 2022 Mobile Security Framework - MobSF | Ajin Abraham | OpenSecurity.