

ANDROID STATIC ANALYSIS REPORT



• OpenMW (0.46.0)

File Name:	installer3857.apk
Package Name:	com.libopenmw.openmw
Scan Date:	May 31, 2022, 6:50 p.m.
App Security Score:	54/100 (MEDIUM RISK)
Grade:	

FINDINGS SEVERITY

☆ HIGH	▲ MEDIUM	i INFO	✓ SECURE	्र HOTSPOT
1	3	2	1	1

FILE INFORMATION

File Name: installer3857.apk

Size: 75.37MB

MD5: 01e5ca9b60da2d573b2087fa09d22822

SHA1: c8dfbc113c65dcd3da9ae5824d75bcda8b4f7900

SHA256: 99c17339bfeaac139f2ccc65d618b2663b7bfe18bdac72d287870fe9aede1f7e

1 APP INFORMATION

App Name: OpenMW

Package Name: com.libopenmw.openmw Main Activity: ui.activity.MainActivity

Target SDK: 28 Min SDK: 21 Max SDK:

Android Version Name: 0.46.0 Android Version Code: 8



Activities: 4 Services: 0 Receivers: 0 Providers: 0

Exported Activities: 1 Exported Services: 0 Exported Receivers: 0 Exported Providers: 0

***** CERTIFICATE INFORMATION

APK is signed v1 signature: True v2 signature: False v3 signature: False

Found 1 unique certificates

Subject: C=UK, ST=ORG, L=ORG, O=fdroid.org, OU=FDroid, CN=FDroid

Signature Algorithm: rsassa_pkcs1v15 Valid From: 2019-06-10 09:17:53+00:00 Valid To: 2046-10-26 09:17:53+00:00

Issuer: C=UK, ST=ORG, L=ORG, O=fdroid.org, OU=FDroid, CN=FDroid

Serial Number: 0x3f6d9155 Hash Algorithm: sha256

md5: 1751ac602dfd6c9a6c65b1ba873b8a38

sha1: 2a65fe4248d787ab3d3e1bd0f00a022f7411085a

sha256: f1a449f598e66ee693a0868e6e6093a7d112116be1ebbe48dfe84a1f61d765bf

sha512: 1c9306a34b17af49a8090b175879e7aee514ef1c0c34904de50eb4603b3c938654731250afd5781b54d9c43b9b717c139c4f8b20ff2ecc634fc0e1afe203bbdf

TITLE	SEVERITY	DESCRIPTION
Signed Application	info	Application is signed with a code signing certificate
Application vulnerable to Janus Vulnerability	high	Application is signed with v1 signature scheme, making it vulnerable to Janus vulnerability on Android 5.0-8.0, if signed only with v1 signature scheme. Applications running on Android 5.0-7.0 signed with v1, and v2/v3 scheme is also vulnerable.

⋮ APPLICATION PERMISSIONS

PERMISSION	STATUS	INFO	DESCRIPTION
android.permission.WRITE_EXTERNAL_STORAGE	dangerous	read/modify/delete external storage contents	Allows an application to write to external storage.
android.permission.READ_EXTERNAL_STORAGE	dangerous	read external storage contents	Allows an application to read from external storage.
android.permission.INTERNET	normal	full Internet access	Allows an application to create network sockets.

ক্ল APKID ANALYSIS

FILE	DETAILS				
classes.dex	FINDINGS	DETAILS			
Classes.dex	Compiler	r8			

△ NETWORK SECURITY

NO	SCOPE	SEVERITY	DESCRIPTION
----	-------	----------	-------------

Q MANIFEST ANALYSIS

٨	10	ISSUE	SEVERITY	DESCRIPTION
1		Application Data can be Backed up [android:allowBackup=true]	warning	This flag allows anyone to backup your application data via adb. It allows users who have enabled USB debugging to copy application data off of the device.
2		Activity (com.libopenmw.openmw.FileChooser) is not Protected. An intent-filter exists.	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device. The presence of intent-filter indicates that the Activity is explicitly exported.

</> CODE ANALYSIS

NO	ISSUE	SEVERITY	STANDARDS	FILES
1	The App logs information. Sensitive information should never be logged.	info	CWE: CWE-532: Insertion of Sensitive Information into Log File OWASP MASVS: MSTG-STORAGE-3	org/libsdl/app/SDLMain.java org/libsdl/app/SDLActivity.java org/libsdl/app/SDLSurface.java org/libsdl/app/SDLAudioManager.java ui/activity/GameActivity.java ui/activity/MainActivity.java
2	App can read/write to External Storage. Any App can read data written to External Storage.	warning	CWE: CWE-276: Incorrect Default Permissions OWASP Top 10: M2: Insecure Data Storage OWASP MASVS: MSTG-STORAGE-2	file/ConfigsFileStorageHelper.java
3	This app listens to Clipboard changes. Some malware also listen to Clipboard changes.	info	OWASP MASVS: MSTG-PLATFORM-4	org/libsdl/app/SDLClipboardHandler_API1 1.java



NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
1	lib/armeabi-v7a/libopenal.so	True info The shared object has NX bit set. This marks a memory page non- executable making attacker injected shellcode non- executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The shared object does not have run-time search path or RPATH set.	None info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option - D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
2	lib/armeabi-v7a/libSDL2.so	True info The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Partial RELRO warning This shared object has partial RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In partial RELRO, the non-PLT part of the GOT section is read only but .got.plt is still writeable. Use the option - z,relro,- z,now to enable full RELRO.	None info The shared object does not have run-time search path or RPATH set.	None info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option - D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
3	lib/armeabi-v7a/libc++_shared.so	True info The shared object has NX bit set. This marks a memory page non- executable making attacker injected shellcode non- executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The shared object does not have run-time search path or RPATH set.	None info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option - D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
4	lib/armeabi-v7a/libGL.so	True info The shared object has NX bit set. This marks a memory page non- executable making attacker injected shellcode non- executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Partial RELRO warning This shared object has partial RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In partial RELRO, the non-PLT part of the GOT section is read only but .got.plt is still writeable. Use the option - z,relro,- z,now to enable full RELRO.	None info The shared object does not have run-time search path or RPATH set.	None info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option - D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
5	lib/armeabi- v7a/libopenmw_osg_mainline.so	True info The shared object has NX bit set. This marks a memory page non- executable making attacker injected shellcode non- executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The shared object does not have run-time search path or RPATH set.	None info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option - D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
6	lib/armeabi- v7a/libopenmw_osg_fork.so	True info The shared object has NX bit set. This marks a memory page non- executable making attacker injected shellcode non- executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The shared object does not have run-time search path or RPATH set.	None info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option - D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
7	lib/x86/libopenal.so	True info The shared object has NX bit set. This marks a memory page non- executable making attacker injected shellcode non- executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The shared object does not have run-time search path or RPATH set.	None info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option - D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
8	lib/x86/libSDL2.so	True info The shared object has NX bit set. This marks a memory page non- executable making attacker injected shellcode non- executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Partial RELRO Warning This shared object has partial RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In partial RELRO, the non-PLT part of the GOT section is read only but .got.plt is still writeable. Use the option - z,relro,- z,now to enable full RELRO.	None info The shared object does not have run-time search path or RPATH set.	None info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option - D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
9	lib/x86/libc++_shared.so	True info The shared object has NX bit set. This marks a memory page non- executable making attacker injected shellcode non- executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The shared object does not have run-time search path or RPATH set.	None info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option - D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
10	lib/x86/libGL.so	True info The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Partial RELRO warning This shared object has partial RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In partial RELRO, the non-PLT part of the GOT section is read only but .got.plt is still writeable. Use the option - z,relro,- z,now to enable full RELRO.	None info The shared object does not have run-time search path or RPATH set.	None info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option - D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
11	lib/x86/libopenmw_osg_mainline.so	True info The shared object has NX bit set. This marks a memory page non- executable making attacker injected shellcode non- executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The shared object does not have run-time search path or RPATH set.	None info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option - D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
12	lib/x86/libopenmw_osg_fork.so	True info The shared object has NX bit set. This marks a memory page non- executable making attacker injected shellcode non- executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The shared object does not have run-time search path or RPATH set.	None info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option - D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
13	lib/arm64-v8a/libopenal.so	True info The shared object has NX bit set. This marks a memory page non- executable making attacker injected shellcode non- executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The shared object does not have run-time search path or RPATH set.	None info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option - D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
14	lib/arm64-v8a/libSDL2.so	True info The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	No RELRO high This shared object does not have RELRO enabled. The entire GOT (.got and .got.plt both) are writable. Without this compiler flag, buffer overflows on a global variable can overwrite GOT entries. Use the option - z,relro,- z,now to enable full RELRO and only - z,relro to enable partial RELRO.	None info The shared object does not have run-time search path or RPATH set.	None info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option - D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
15	lib/arm64-v8a/libc++_shared.so	True info The shared object has NX bit set. This marks a memory page non- executable making attacker injected shellcode non- executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The shared object does not have run-time search path or RPATH set.	None info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option - D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
16	lib/arm64-v8a/libGL.so	True info The shared object has NX bit set. This marks a memory page non- executable making attacker injected shellcode non- executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	No RELRO high This shared object does not have RELRO enabled. The entire GOT (.got and .got.plt both) are writable. Without this compiler flag, buffer overflows on a global variable can overwrite GOT entries. Use the option - z,relro,- z,now to enable full RELRO and only - z,relro to enable partial RELRO.	None info The shared object does not have run-time search path or RPATH set.	None info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option - D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
17	lib/arm64- v8a/libopenmw_osg_mainline.so	True info The shared object has NX bit set. This marks a memory page non- executable making attacker injected shellcode non- executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The shared object does not have run-time search path or RPATH set.	None info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option - D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
18	lib/arm64-v8a/libopenmw_osg_fork.so	True info The shared object has NX bit set. This marks a memory page non- executable making attacker injected shellcode non- executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The shared object does not have run-time search path or RPATH set.	None info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option - D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
19	lib/x86_64/libopenal.so	True info The shared object has NX bit set. This marks a memory page non- executable making attacker injected shellcode non- executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The shared object does not have run-time search path or RPATH set.	None info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option - D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
20	lib/x86_64/libSDL2.so	True info The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Partial RELRO warning This shared object has partial RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In partial RELRO, the non-PLT part of the GOT section is read only but .got.plt is still writeable. Use the option - z,relro,- z,now to enable full RELRO.	None info The shared object does not have run-time search path or RPATH set.	None info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option - D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
21	lib/x86_64/libc++_shared.so	True info The shared object has NX bit set. This marks a memory page non- executable making attacker injected shellcode non- executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The shared object does not have run-time search path or RPATH set.	None info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option - D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
22	lib/x86_64/libGL.so	True info The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Partial RELRO warning This shared object has partial RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In partial RELRO, the non-PLT part of the GOT section is read only but .got.plt is still writeable. Use the option - z,relro,- z,now to enable full RELRO.	None info The shared object does not have run-time search path or RPATH set.	None info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option - D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
23	lib/x86_64/libopenmw_osg_mainline.so	True info The shared object has NX bit set. This marks a memory page non- executable making attacker injected shellcode non- executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The shared object does not have run-time search path or RPATH set.	None info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option - D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
24	lib/x86_64/libopenmw_osg_fork.so	True info The shared object has NX bit set. This marks a memory page non- executable making attacker injected shellcode non- executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The shared object does not have run-time search path or RPATH set.	None info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option - D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.

NO	IDENTIFIER	REQUIREMENT	FEATURE	DESCRIPTION
1	FCS_RBG_EXT.1.1	Security Functional Requirements	Random Bit Generation Services	The application use no DRBG functionality for its cryptographic operations.
2	FCS_STO_EXT.1.1	Security Functional Requirements	Storage of Credentials	The application does not store any credentials to non-volatile memory.
3	FCS_CKM_EXT.1.1	Security Functional Requirements	Cryptographic Key Generation Services	The application generate no asymmetric cryptographic keys.
4	FDP_DEC_EXT.1.1	Security Functional Requirements	Access to Platform Resources	The application has access to ['network connectivity'].
5	FDP_DEC_EXT.1.2	Security Functional Requirements	Access to Platform Resources	The application has access to no sensitive information repositories.
6	FDP_NET_EXT.1.1	Security Functional Requirements	Network Communications	The application has user/application initiated network communications.
7	FDP_DAR_EXT.1.1	Security Functional Requirements	Encryption Of Sensitive Application Data	The application implement functionality to encrypt sensitive data in non-volatile memory.
8	FMT_MEC_EXT.1.1	Security Functional Requirements	Supported Configuration Mechanism	The application invoke the mechanisms recommended by the platform vendor for storing and setting configuration options.
9	FTP_DIT_EXT.1.1	Security Functional Requirements	Protection of Data in Transit	The application does encrypt some transmitted data with HTTPS/TLS/SSH between itself and another trusted IT product.

Q DOMAIN MALWARE CHECK

DOMAIN	STATUS	GEOLOCATION
openmw.readthedocs.io	ok	IP: 104.17.32.82 Country: United States of America Region: California City: San Francisco Latitude: 37.775700 Longitude: -122.395203 View: Google Map

Report Generated by - MobSF v3.5.2 Beta

Mobile Security Framework (MobSF) is an automated, all-in-one mobile application (Android/iOS/Windows) pen-testing, malware analysis and security assessment framework capable of performing static and dynamic analysis.

© 2022 Mobile Security Framework - MobSF | Ajin Abraham | OpenSecurity.