MOBSF

ANDROID STATIC ANALYSIS REPORT

Controlloid (1.2.0)

File Name:	installer3845.apk
Package Name:	com.controlloid
Scan Date:	May 31, 2022, 7:02 p.m.
App Security Score:	44/100 (MEDIUM RISK)
Grade:	B

FINDINGS SEVERITY

HIGH	MEDIUM	INFO	SECURE	HOTSPOT
2	2	1	1	0

FILE INFORMATION

File Name: installer3845.apk
Size: 12.81MB
MD5: 8923c6f8b4a34ab55a3b148ccc99c78d
SHA1: 5926903efbcc9586a41b22e3562e61573aeab4bd
SHA256: 919c4501a73515d31cb8c4a0c372746d2608c469d748c65c9f6f4dafc9f23e1c

APP INFORMATION

App Name: Controlloid
Package Name: com.controlloid
Main Activity: com.controlloid.MainActivity
Target SDK: 28
Min SDK: 16
Max SDK:
Android Version Name: 1.2.0
Android Version Code: 11

APP COMPONENTS

Activities: 2
Services: 0
Receivers: 0
Providers: 0
Exported Activities: 0
Exported Services: 0
Exported Receivers: 0
Exported Providers: 0

CERTIFICATE INFORMATION

APK is signed
v1 signature: True
v2 signature: False
v3 signature: False
Found 1 unique certificates
Subject: C=UK, ST=ORG, L=ORG, O=fdroid.org, OU=FDroid, CN=FDroid
Signature Algorithm: rsassa_pkcs1v15
Valid From: 2019-04-17 17:59:56+00:00
Valid To: 2046-09-02 17:59:56+00:00
Issuer: C=UK, ST=ORG, L=ORG, O=fdroid.org, OU=FDroid, CN=FDroid
Serial Number: 0x7dd0b827
Hash Algorithm: sha256
md5: 2f26c4e034ab2cb13e046ebd4d7ee8bb
sha1: f4497dcf26628e84ede3cda637f03b79a95f2a4e
sha256: 7c1dcfa63b58c8a818352079e901c7513d3cf3c0aed319bdecd5bb9eb817ea86
sha512: 83e404d81130ce61296cff0d4d92060e855ce4a45b8cd54937243f22624d8236991c7dadd0934c62ba5f11c5adbab7807792fa01726f6e511044341d330d85eb

TITLE	SEVERITY	DESCRIPTION
Signed Application	info	Application is signed with a code signing certificate

TITLE	SEVERITY	DESCRIPTION
Application vulnerable to Janus Vulnerability	high	Application is signed with v1 signature scheme, making it vulnerable to Janus vulnerability on Android 5.0-8.0, if signed only with v1 signature scheme. Applications running on Android 5.0-7.0 signed with v1, and v2/v3 scheme is also vulnerable.

APPLICATION PERMISSIONS

PERMISSION	STATUS	INFO	DESCRIPTION
android.permission.INTERNET	normal	full Internet access	Allows an application to create network sockets.
android.permission.ACCESS_NETWORK_STATE	normal	view network status	Allows an application to view the status of all networks.
android.permission.ACCESS_WIFI_STATE	normal	view Wi-Fi status	Allows an application to view the information about the status of Wi-Fi.

APKID ANALYSIS

FILE	DETAILS
classes.dex	FINDINGS: Anti-VM Code — DETAILS: Build.FINGERPRINT check possible Build.SERIAL check FINDINGS: Compiler — DETAILS: r8

NETWORK SECURITY

NO	SCOPE	SEVERITY	DESCRIPTION

MANIFEST ANALYSIS

NO	ISSUE	SEVERITY	DESCRIPTION
1	Clear text traffic is Enabled For App [android:usesCleartextTraffic=true]	high	The app intends to use cleartext network traffic, such as cleartext HTTP, FTP stacks, DownloadManager, and MediaPlayer. The default value for apps that target API level 27 or lower is "true". Apps that target API level 28 or higher default to "false". The key reason for avoiding cleartext traffic is the lack of confidentiality, authenticity, and protections against tampering; a network attacker can eavesdrop on transmitted data and also modify it without being detected.

CODE ANALYSIS

NO	ISSUE	SEVERITY	STANDARDS	FILES

NO	ISSUE	SEVERITY	STANDARDS	FILES
1	The App logs information. Sensitive information should never be logged.	info	CWE: CWE-532: Insertion of Sensitive Information into Log File OWASP MASVS: MSTG-STORAGE-3	com/horcrux/svg/RadialGradientView.java com/reactnativecommunity/asyncstorage/ReactDatabaseSupplier.java com/horcrux/svg/LinearGradientView.java com/reactnativecommunity/asyncstorage/AsyncStorageModule.java org/wonday/orientation/OrientationModule.java com/horcrux/svg/ClipPathView.java com/horcrux/svg/MaskView.java com/horcrux/svg/UseView.java com/pusherman/networkinfo/RNNetworkInfo.java com/horcrux/svg/PatternView.java com/horcrux/svg/VirtualView.java com/swmansion/gesturehandler/react/RNGestureHandlerRootHelper.java com/horcrux/svg/Brush.java com/horcrux/svg/ImageView.java com/swmansion/reanimated/nodes/DebugNode.java
2	App uses SQLite Database and execute raw SQL query. Untrusted user input in raw SQL queries can cause SQL Injection. Also sensitive information should be encrypted and written to the database.	warning	CWE: CWE-89: Improper Neutralization of Special Elements used in an SQL Command ('SQL Injection') OWASP Top 10: M7: Client Code Quality	com/reactnativecommunity/asyncstorage/ReactDatabaseSupplier.java
3	IP Address disclosure	warning	CWE: CWE-200: Information Exposure OWASP MASVS: MSTG-CODE-2	com/pusherman/networkinfo/RNNetworkInfo.java

SHARED LIBRARY BINARY ANALYSIS

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
1	lib/armeabi-v7a/libnative-filters.so	True info The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The shared object does not have run-time search path or RPATH set.	None info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
2	lib/armeabi-v7a/libreactnativeblob.so	True info The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The shared object does not have run-time search path or RPATH set.	None info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
3	lib/armeabi-v7a/libnative-imagetranscoder.so	True info The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The shared object does not have run-time search path or RPATH set.	None info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
4	lib/armeabi-v7a/libjsijniprofiler.so	True info The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The shared object does not have run-time search path or RPATH set.	None info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
5	lib/armeabi-v7a/libjsinspector.so	True info The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The shared object does not have run-time search path or RPATH set.	None info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
6	lib/armeabi-v7a/libfolly_json.so	True info The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The shared object does not have run-time search path or RPATH set.	None info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
7	lib/armeabi-v7a/libglog.so	True info The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The shared object does not have run-time search path or RPATH set.	None info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
8	lib/armeabi-v7a/libimagepipeline.so	True info The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The shared object does not have run-time search path or RPATH set.	None info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
9	lib/armeabi-v7a/libglog_init.so	True info The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The shared object does not have run-time search path or RPATH set.	None info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
10	lib/armeabi-v7a/libfolly_futures.so	True info The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The shared object does not have run-time search path or RPATH set.	None info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
11	lib/armeabi-v7a/libhermes.so	True info The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The shared object does not have run-time search path or RPATH set.	None info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
12	lib/armeabi-v7a/libc++_shared.so	True info The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The shared object does not have run-time search path or RPATH set.	None info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
13	lib/armeabi-v7a/libhermes-executor-release.so	True info The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The shared object does not have run-time search path or RPATH set.	None info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
14	lib/armeabi-v7a/libfb.so	True info The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The shared object does not have run-time search path or RPATH set.	None info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
15	lib/armeabi-v7a/libreactnativejni.so	True info The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The shared object does not have run-time search path or RPATH set.	None info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
16	lib/armeabi-v7a/libyoga.so	True info The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The shared object does not have run-time search path or RPATH set.	None info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
17	lib/x86/libnative-filters.so	True info The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The shared object does not have run-time search path or RPATH set.	None info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
18	lib/x86/libreactnativeblob.so	True info The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The shared object does not have run-time search path or RPATH set.	None info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
19	lib/x86/libnative-imagetranscoder.so	True info The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The shared object does not have run-time search path or RPATH set.	None info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
20	lib/x86/libjsijniprofiler.so	True info The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The shared object does not have run-time search path or RPATH set.	None info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
21	lib/x86/libjsinspector.so	True info The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The shared object does not have run-time search path or RPATH set.	None info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
22	lib/x86/libfolly_json.so	True info The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The shared object does not have run-time search path or RPATH set.	None info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
23	lib/x86/libglog.so	True info The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The shared object does not have run-time search path or RPATH set.	None info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
24	lib/x86/libimagepipeline.so	True info The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The shared object does not have run-time search path or RPATH set.	None info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
25	lib/x86/libglog_init.so	True info The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The shared object does not have run-time search path or RPATH set.	None info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
26	lib/x86/libfolly_futures.so	True info The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The shared object does not have run-time search path or RPATH set.	None info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
27	lib/x86/libhermes.so	True info The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The shared object does not have run-time search path or RPATH set.	None info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
28	lib/x86/libc++_shared.so	True info The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The shared object does not have run-time search path or RPATH set.	None info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
29	lib/x86/libhermes-executor-release.so	True info The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The shared object does not have run-time search path or RPATH set.	None info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
30	lib/x86/libfb.so	True info The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The shared object does not have run-time search path or RPATH set.	None info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
31	lib/x86/libreactnativejni.so	True info The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The shared object does not have run-time search path or RPATH set.	None info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
32	lib/x86/libyoga.so	True info The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The shared object does not have run-time search path or RPATH set.	None info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
33	lib/arm64-v8a/libnative-filters.so	True info The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Partial RELRO warning This shared object has partial RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In partial RELRO, the non-PLT part of the GOT section is read only but .got.plt is still writeable. Use the option -z,relro,-z,now to enable full RELRO.	None info The shared object does not have run-time search path or RPATH set.	None info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
34	lib/arm64-v8a/libreactnativeblob.so	True info The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The shared object does not have run-time search path or RPATH set.	None info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
35	lib/arm64-v8a/libnative-imagetranscoder.so	True info The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Partial RELRO warning This shared object has partial RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In partial RELRO, the non-PLT part of the GOT section is read only but .got.plt is still writeable. Use the option -z,relro,-z,now to enable full RELRO.	None info The shared object does not have run-time search path or RPATH set.	None info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
36	lib/arm64-v8a/libjsijniprofiler.so	True info The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The shared object does not have run-time search path or RPATH set.	None info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
37	lib/arm64-v8a/libjsinspector.so	True info The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The shared object does not have run-time search path or RPATH set.	None info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
38	lib/arm64-v8a/libfolly_json.so	True info The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The shared object does not have run-time search path or RPATH set.	None info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
39	lib/arm64-v8a/libglog.so	True info The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The shared object does not have run-time search path or RPATH set.	None info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
40	lib/arm64-v8a/libimagepipeline.so	True info The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Partial RELRO warning This shared object has partial RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In partial RELRO, the non-PLT part of the GOT section is read only but .got.plt is still writeable. Use the option -z,relro,-z,now to enable full RELRO.	None info The shared object does not have run-time search path or RPATH set.	None info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
41	lib/arm64-v8a/libglog_init.so	True info The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The shared object does not have run-time search path or RPATH set.	None info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
42	lib/arm64-v8a/libfolly_futures.so	True info The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The shared object does not have run-time search path or RPATH set.	None info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
43	lib/arm64-v8a/libhermes.so	True info The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The shared object does not have run-time search path or RPATH set.	None info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
44	lib/arm64-v8a/libc++_shared.so	True info The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The shared object does not have run-time search path or RPATH set.	None info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
45	lib/arm64-v8a/libhermes-executor-release.so	True info The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The shared object does not have run-time search path or RPATH set.	None info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
46	lib/arm64-v8a/libfb.so	True info The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The shared object does not have run-time search path or RPATH set.	None info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
47	lib/arm64-v8a/libreactnativejni.so	True info The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The shared object does not have run-time search path or RPATH set.	None info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
48	lib/arm64-v8a/libyoga.so	True info The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The shared object does not have run-time search path or RPATH set.	None info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
49	lib/x86_64/libnative-filters.so	True info The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The shared object does not have run-time search path or RPATH set.	None info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
50	lib/x86_64/libreactnativeblob.so	True info The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The shared object does not have run-time search path or RPATH set.	None info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
51	lib/x86_64/libnative-imagetranscoder.so	True info The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The shared object does not have run-time search path or RPATH set.	None info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
52	lib/x86_64/libjsijniprofiler.so	True info The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The shared object does not have run-time search path or RPATH set.	None info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
53	lib/x86_64/libjsinspector.so	True info The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The shared object does not have run-time search path or RPATH set.	None info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
54	lib/x86_64/libfolly_json.so	True info The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The shared object does not have run-time search path or RPATH set.	None info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
55	lib/x86_64/libglog.so	True info The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The shared object does not have run-time search path or RPATH set.	None info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
56	lib/x86_64/libimagepipeline.so	True info The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The shared object does not have run-time search path or RPATH set.	None info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
57	lib/x86_64/libglog_init.so	True info The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The shared object does not have run-time search path or RPATH set.	None info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
58	lib/x86_64/libfolly_futures.so	True info The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The shared object does not have run-time search path or RPATH set.	None info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
59	lib/x86_64/libhermes.so	True info The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The shared object does not have run-time search path or RPATH set.	None info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
60	lib/x86_64/libc++_shared.so	True info The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The shared object does not have run-time search path or RPATH set.	None info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
61	lib/x86_64/libhermes-executor-release.so	True info The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The shared object does not have run-time search path or RPATH set.	None info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
62	lib/x86_64/libfb.so	True info The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The shared object does not have run-time search path or RPATH set.	None info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
63	lib/x86_64/libreactnativejni.so	True info The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The shared object does not have run-time search path or RPATH set.	None info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
64	lib/x86_64/libyoga.so	True info The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The shared object does not have run-time search path or RPATH set.	None info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.

NIAP ANALYSIS v1.3

NO	IDENTIFIER	REQUIREMENT	FEATURE	DESCRIPTION
1	FCS_RBG_EXT.1.1	Security Functional Requirements	Random Bit Generation Services	The application use no DRBG functionality for its cryptographic operations.
2	FCS_STO_EXT.1.1	Security Functional Requirements	Storage of Credentials	The application does not store any credentials to non-volatile memory.
3	FCS_CKM_EXT.1.1	Security Functional Requirements	Cryptographic Key Generation Services	The application generate no asymmetric cryptographic keys.
4	FDP_DEC_EXT.1.1	Security Functional Requirements	Access to Platform Resources	The application has access to ['network connectivity'].
5	FDP_DEC_EXT.1.2	Security Functional Requirements	Access to Platform Resources	The application has access to no sensitive information repositories.
6	FDP_NET_EXT.1.1	Security Functional Requirements	Network Communications	The application has user/application initiated network communications.
7	FDP_DAR_EXT.1.1	Security Functional Requirements	Encryption Of Sensitive Application Data	The application implement functionality to encrypt sensitive data in non-volatile memory.
8	FMT_MEC_EXT.1.1	Security Functional Requirements	Supported Configuration Mechanism	The application invoke the mechanisms recommended by the platform vendor for storing and setting configuration options.
9	FTP_DIT_EXT.1.1	Security Functional Requirements	Protection of Data in Transit	The application does encrypt some transmitted data with HTTPS/TLS/SSH between itself and another trusted IT product.

NO	IDENTIFIER	REQUIREMENT	FEATURE	DESCRIPTION
10	FCS_COP.1.1(2)	Selection-Based Security Functional Requirements	Cryptographic Operation - Hashing	The application perform cryptographic hashing services not in accordance with FCS_COP.1.1(2) and uses the cryptographic algorithm RC2/RC4/MD4/MD5.
11	FCS_HTTPS_EXT.1.1	Selection-Based Security Functional Requirements	HTTPS Protocol	The application implement the HTTPS protocol that complies with RFC 2818.
12	FCS_HTTPS_EXT.1.2	Selection-Based Security Functional Requirements	HTTPS Protocol	The application implement HTTPS using TLS.
13	FCS_HTTPS_EXT.1.3	Selection-Based Security Functional Requirements	HTTPS Protocol	The application notify the user and not establish the connection or request application authorization to establish the connection if the peer certificate is deemed invalid.
14	FIA_X509_EXT.2.1	Selection-Based Security Functional Requirements	X.509 Certificate Authentication	The application use X.509v3 certificates as defined by RFC 5280 to support authentication for HTTPS , TLS.

Report Generated by - MobSF v3.5.2 Beta

Mobile Security Framework (MobSF) is an automated, all-in-one mobile application (Android/iOS/Windows) pen-testing, malware analysis and security assessment framework capable of performing static and dynamic analysis.

© 2022 Mobile Security Framework - MobSF | Ajin Abraham | OpenSecurity.