

ANDROID STATIC ANALYSIS REPORT



• Chiaki (1.3.0)

| File Name: | installer320.apk | | | | |
|---------------------|-------------------------|--|--|--|--|
| Package Name: | com.metallic.chiaki | | | | |
| Scan Date: | May 31, 2022, 1:47 p.m. | | | | |
| App Security Score: | 54/100 (MEDIUM RISK | | | | |
| Grade: | | | | | |
| | | | | | |

FINDINGS SEVERITY

| 派 HIGH | ▲ MEDIUM | i INFO | ✓ SECURE | ≪ HOTSPOT |
|-------------------|----------|---------------|----------|-----------|
| 1 | 3 | 1 | 1 | 0 |

FILE INFORMATION

File Name: installer320.apk

Size: 8.06MB

MD5: b62e25d5a74c20cb5e5997bee4a0f673

SHA1: 0ba84e720bbcdfb5768516bef43131383d005171

SHA256: 4264f2e32fb499a34fd08ee30a67fea639a1ea0bb7754fa945a88906250b8c0e

i APP INFORMATION

App Name: Chiaki

Package Name: com.metallic.chiaki

Main Activity: com.metallic.chiaki.main.MainActivity

Target SDK: 29 Min SDK: 21 Max SDK:

Android Version Name: 1.3.0 Android Version Code: 7

B APP COMPONENTS

Activities: 6 Services: 1 Receivers: 0 Providers: 2

Exported Activities: O Exported Services: O Exported Receivers: O Exported Providers: O



APK is signed v1 signature: True v2 signature: False v3 signature: False

Found 1 unique certificates

Subject: C=UK, ST=ORG, L=ORG, O=fdroid.org, OU=FDroid, CN=FDroid

Signature Algorithm: rsassa_pkcs1v15 Valid From: 2020-08-22 08:26:14+00:00 Valid To: 2048-01-08 08:26:14+00:00

Issuer: C=UK, ST=ORG, L=ORG, O=fdroid.org, OU=FDroid, CN=FDroid

Serial Number: 0x62c60e5c Hash Algorithm: sha256

md5: 9e63d8fe9205099b094f5d78aa6e05a3

sha1: 7020aec867cda595109f24f4f201f7b87c90e894

sha 256: a 440 f 9 f 5 d 7 9 0 3 6 9 4 7 d 35 c a 3 a 6 d d e d 5 b f e 6 f 5 9 1 d 9 a a b d 6 2 4 a e f e d a e 6 7 4 2 5 a 8 8 9 8 e d e d 6 7 d 2 5 a 8 8 9 8 e d e d 6 7 d 2 5 a 8 8 9 8 e d e d 6 7 d 2 5 a 8 8 9 8 e d 6 7 d 2 5 a 8 8 9 8 e d 6 7 d 2 5 a 8 8 9 8 e d 6 7 d 2 5 a 8 8 9 8 e d 6 7 d 2 5 a 8 8 9 8 e d 6 7 d 2 5 a 8 6 d 2 6

sha512: baa72dc83304e3b31b09a5e72d9ff2937ec2299f063cc1dc7f8fe2773e70555fff1f2bc51eb9be373921a26fc2d8803d0120c34cb382cf51bff346e33e3babdd

| TITLE | SEVERITY | DESCRIPTION |
|--------------------|----------|---|
| Signed Application | info | Application is signed with a code signing certificate |

| TITLE | SEVERITY | DESCRIPTION |
|---|----------|---|
| Application vulnerable to Janus Vulnerability | high | Application is signed with v1 signature scheme, making it vulnerable to Janus vulnerability on Android 5.0-8.0, if signed only with v1 signature scheme. Applications running on Android 5.0-7.0 signed with v1, and v2/v3 scheme is also vulnerable. |

⋮ APPLICATION PERMISSIONS

| PERMISSION | STATUS INFO | | DESCRIPTION | | |
|---|-------------|----------------------|---|--|--|
| android.permission.INTERNET | normal | full Internet access | Allows an application to create network sockets. | | |
| android.permission.ACCESS_NETWORK_STATE | normal | view network status | Allows an application to view the status of all networks. | | |

M APKID ANALYSIS

| FILE | DETAILS | | | | |
|-------------|--------------|--------------------------|--|--|--|
| | FINDINGS | DETAILS | | | |
| classes.dex | Anti-VM Code | Build.MANUFACTURER check | | | |
| | Compiler | r8 | | | |
| | | | | | |

△ NETWORK SECURITY

| NO SCOPE SEVERITY DESCRIPTION | NO | SCOPE | SEVERITY | DESCRIPTION |
|-------------------------------|----|-------|----------|-------------|
|-------------------------------|----|-------|----------|-------------|

Q MANIFEST ANALYSIS

| NO | ISSUE | SEVERITY | DESCRIPTION |
|----|--|----------|---|
| 1 | Application Data can be Backed up [android:allowBackup=true] | warning | This flag allows anyone to backup your application data via adb. It allows users who have enabled USB debugging to copy application data off of the device. |

</> CODE ANALYSIS

| NO | ISSUE | SEVERITY | STANDARDS | FILES |
|----|---|--|--|--|
| 1 | IP Address disclosure | re CWE: CWE-200: Information Exposure OWASP MASVS: MSTG-CODE-2 | | com/metallic/chiaki/discovery/DiscoveryManager.java com/metallic/chiaki/regist/RegistActivity.java |
| 2 | The App logs information. Sensitive information should never be logged. | info | CWE: CWE-532: Insertion of Sensitive Information into Log File OWASP MASVS: MSTG-STORAGE-3 | com/metallic/chiaki/discovery/DiscoveryManager.java com/metallic/chiaki/common/SerializedSettingsKt.java com/metallic/chiaki/lib/DiscoveryService.java com/metallic/chiaki/regist/RegistExecuteViewModel.jav a com/metallic/chiaki/manualconsole/EditManualConsol eViewModel\$existingHost\$1.java |



| NO | SHARED OBJECT | NX | STACK CANARY | RELRO | RPATH | RUNPATH | FORTIFY | SYMBOLS STRIPPED |
|----|--------------------------------------|--|--|--|--|--|---|---------------------------------|
| 1 | lib/armeabi-v7a/libchiaki- jni.so | True info The shared object has NX bit set. This marks a memory page non- executable making attacker injected shellcode non- executable. | True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return. | Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only. | None info The shared object does not have run-time search path or RPATH set. | None info The shared object does not have RUNPATH set. | True info The shared object has the following fortified functions: ['FD_ISSET_chk', 'FD_SET_chk'] | True info Symbols are stripped. |

| NO | SHARED OBJECT | NX | STACK CANARY | RELRO | RPATH | RUNPATH | FORTIFY | SYMBOLS STRIPPED |
|----|--------------------------|--|--|--|--|--|---|---------------------------------|
| 2 | lib/x86/libchiaki-jni.so | True info The shared object has NX bit set. This marks a memory page non- executable making attacker injected shellcode non- executable. | True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return. | Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only. | None info The shared object does not have run-time search path or RPATH set. | None info The shared object does not have RUNPATH set. | True info The shared object has the following fortified functions: ['FD_ISSET_chk', 'FD_SET_chk'] | True info Symbols are stripped. |

| NO | SHARED OBJECT | NX | STACK CANARY | RELRO | RPATH | RUNPATH | FORTIFY | SYMBOLS STRIPPED |
|----|--------------------------------|--|--|--|--|--|---|---------------------------------|
| 3 | lib/arm64-v8a/libchiaki-jni.so | True info The shared object has NX bit set. This marks a memory page non- executable making attacker injected shellcode non- executable. | True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return. | Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only. | None info The shared object does not have run-time search path or RPATH set. | None info The shared object does not have RUNPATH set. | True info The shared object has the following fortified functions: ['FD_ISSET_chk', 'FD_SET_chk'] | True info Symbols are stripped. |

| NO | SHARED OBJECT | NX | STACK CANARY | RELRO | RPATH | RUNPATH | FORTIFY | SYMBOLS STRIPPED |
|----|-----------------------------|--|--|--|--|--|---|---------------------------------|
| 4 | lib/x86_64/libchiaki-jni.so | True info The shared object has NX bit set. This marks a memory page non- executable making attacker injected shellcode non- executable. | True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return. | Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only. | None info The shared object does not have run-time search path or RPATH set. | None info The shared object does not have RUNPATH set. | True info The shared object has the following fortified functions: ['FD_ISSET_chk', 'FD_SET_chk'] | True info Symbols are stripped. |

■ NIAP ANALYSIS v1.3

| NO | IDENTIFIER | REQUIREMENT | FEATURE | DESCRIPTION |
|----|-----------------|-------------------------------------|-----------------------------------|---|
| 1 | FCS_RBG_EXT.1.1 | Security Functional Requirements | Random Bit Generation Services | The application use no DRBG functionality for its cryptographic operations. |
| 2 | FCS_STO_EXT.1.1 | Security Functional Requirements | Storage of Credentials | The application does not store any credentials to non-volatile memory. |

| NO | IDENTIFIER | REQUIREMENT | FEATURE | DESCRIPTION |
|----|-----------------|-------------------------------------|---|---|
| 3 | FCS_CKM_EXT.1.1 | Security Functional Requirements | Cryptographic Key Generation Services | The application generate no asymmetric cryptographic keys. |
| 4 | FDP_DEC_EXT.1.1 | Security Functional Requirements | Access to Platform Resources | The application has access to ['network connectivity']. |
| 5 | FDP_DEC_EXT.1.2 | Security Functional Requirements | Access to Platform Resources | The application has access to no sensitive information repositories. |
| 6 | FDP_NET_EXT.1.1 | Security Functional Requirements | Network Communications | The application has user/application initiated network communications. |
| 7 | FDP_DAR_EXT.1.1 | Security Functional Requirements | Encryption Of Sensitive Application Data | The application does not encrypt files in non-volatile memory. |
| 8 | FMT_MEC_EXT.1.1 | Security Functional Requirements | Supported Configuration Mechanism | The application invoke the mechanisms recommended by the platform vendor for storing and setting configuration options. |
| 9 | FTP_DIT_EXT.1.1 | Security Functional Requirements | Protection of Data in Transit | The application does encrypt some transmitted data with HTTPS/TLS/SSH between itself and another trusted IT product. |

Q DOMAIN MALWARE CHECK

| DOMAIN | STATUS | GEOLOCATION |
|--------|--------|-------------|
| | | |

| DOMAIN | STATUS | GEOLOCATION |
|------------|--------|---|
| github.com | ok | IP: 140.82.121.3 Country: United States of America Region: California City: San Francisco Latitude: 37.775700 Longitude: -122.395203 View: Google Map |

HARDCODED SECRETS

| POSSIBLE SECRETS |
|---|
| "preferences_bitrate_key" : "stream_bitrate" |
| "preferences_discovery_enabled_key" : "discovery_enabled" |
| "preferences_export_settings_key" : "export_settings" |
| "preferences_fps_key" : "stream_fps" |
| "preferences_import_settings_key" : "import_settings" |
| "preferences_log_verbose_key" : "log_verbose" |
| "preferences_on_screen_controls_enabled_key" : "on_screen_controls_enabled" |
| "preferences_resolution_key" : "stream_resolution" |

POSSIBLE SECRETS

"preferences_swap_cross_moon_key": "swap_cross_moon"

"preferences_touchpad_only_key": "touchpad_only_enabled"

Report Generated by - MobSF v3.5.2 Beta

Mobile Security Framework (MobSF) is an automated, all-in-one mobile application (Android/iOS/Windows) pen-testing, malware analysis and security assessment framework capable of performing static and dynamic analysis.

© 2022 Mobile Security Framework - MobSF | Ajin Abraham | OpenSecurity.