


ANDROID STATIC ANALYSIS REPORT



Vector Pinball (1.7.1)

File Name:	installer172.apk
Package Name:	com.dozingcatsoftware.bouncy
Scan Date:	May 30, 2022, 4:09 p.m.
App Security Score:	46/100 (MEDIUM RISK)
Grade:	

FINDINGS SEVERITY

派 HIGH	▲ MEDIUM	i INFO	✓ SECURE	≪ HOTSPOT
2	5	1	1	0

FILE INFORMATION

File Name: installer172.apk

Size: 2.69MB

MD5: d05eb91db7c40742b967ff3cc807e832

SHA1: 61e69cbfc8c5930ac656aea9ce917195627d8e33

SHA256: cdf0962df543dba8f60ce351f7869f7146328f98e16210e6be8cf915ac0cce76

i APP INFORMATION

App Name: Vector Pinball

Package Name: com.dozingcatsoftware.bouncy

 $\textbf{\textit{Main Activity}}: com. dozing cats of tware. bouncy. Bouncy Activity$

Target SDK: 29 Min SDK: 4 Max SDK:

Android Version Name: 1.7.1
Android Version Code: 25

EE APP COMPONENTS

Activities: 3 Services: 0 Receivers: 0 Providers: 0

Exported Activities: O Exported Services: O Exported Receivers: O Exported Providers: O



APK is signed v1 signature: True v2 signature: False v3 signature: False

Found 1 unique certificates

Subject: C=UK, ST=ORG, L=ORG, O=fdroid.org, OU=FDroid, CN=FDroid

Signature Algorithm: rsassa_pkcs1v15 Valid From: 2011-03-10 18:03:00+00:00 Valid To: 2038-07-26 18:03:00+00:00

Issuer: C=UK, ST=ORG, L=ORG, O=fdroid.org, OU=FDroid, CN=FDroid

Serial Number: 0x4d791254 Hash Algorithm: sha1

md5: b7085b53a29a4b71c8166ea6ab2e14bf

sha1: 239587a3f6b8f0e70296d9b1076241afef68caf3

sha256: 0e7b403c101bc1f619ba55382931eef8cf0b694eb3c419db3db17c7f72e8dfa3

sha512: d0cd3e0561b477fb136d7b5270bcdd912c576409fd6bdef37ace5a309f9933e6a31c15d8d9f18c940aadbae7f1a74694ef6622ce8b0952857948b326e33ae81c

TITLE	SEVERITY	DESCRIPTION
Signed Application	info	Application is signed with a code signing certificate

TITLE	SEVERITY	DESCRIPTION
Application vulnerable to Janus Vulnerability	high	Application is signed with v1 signature scheme, making it vulnerable to Janus vulnerability on Android 5.0-8.0, if signed only with v1 signature scheme. Applications running on Android 5.0-7.0 signed with v1, and v2/v3 scheme is also vulnerable.
Certificate algorithm might be vulnerable to hash collision	high	Application is signed with SHA1withRSA. SHA1 hash algorithm is known to have collision issues.

M APKID ANALYSIS

FILE	DETAILS			
classes.dex	FINDINGS	DETAILS		
Classes.dex	Compiler	r8		

△ NETWORK SECURITY

NO SCOPE SEVERITY	DESCRIPTION
-------------------	-------------

Q MANIFEST ANALYSIS

NO	ISSUE	SEVERITY	DESCRIPTION
1	Application Data can be Backed up [android:allowBackup=true]	warning	This flag allows anyone to backup your application data via adb. It allows users who have enabled USB debugging to copy application data off of the device.

</> CODE ANALYSIS

NO	ISSUE	SEVERITY	STANDARDS	FILES
1	The App logs information. Sensitive information should never be logged.	info	CWE: CWE-532: Insertion of Sensitive Information into Log File OWASP MASVS: MSTG-STORAGE-3	com/badlogic/gdx/input/RemoteInput.java com/dozingcatsoftware/bouncy/VPSoundpoo l.java com/badlogic/gdx/graphics/glutils/ETC1.java com/dozingcatsoftware/bouncy/FieldLayout.j ava com/dozingcatsoftware/bouncy/BouncyActivi ty.java
2	The App uses an insecure Random Number Generator.	warning	CWE: CWE-330: Use of Insufficiently Random Values OWASP Top 10: M5: Insufficient Cryptography OWASP MASVS: MSTG-CRYPTO-6	com/badlogic/gdx/math/RandomXS128.java com/dozingcatsoftware/bouncy/VPSoundpoo l.java com/dozingcatsoftware/bouncy/fields/Field3 Delegate.java com/dozingcatsoftware/bouncy/Field.java com/dozingcatsoftware/bouncy/fields/Field6 Delegate.java com/badlogic/gdx/math/MathUtils.java com/dozingcatsoftware/bouncy/FieldLayout.j ava

NO	ISSUE	SEVERITY	STANDARDS	FILES
3	App creates temp file. Sensitive information should never be written into a temp file.	warning	CWE: CWE-276: Incorrect Default Permissions OWASP Top 10: M2: Insecure Data Storage OWASP MASVS: MSTG-STORAGE-2	com/badlogic/gdx/utils/SharedLibraryLoader .java com/badlogic/gdx/files/FileHandle.java
4	App can read/write to External Storage. Any App can read data written to External Storage.	warning	CWE: CWE-276: Incorrect Default Permissions OWASP Top 10: M2: Insecure Data Storage OWASP MASVS: MSTG-STORAGE-2	com/badlogic/gdx/files/FileHandle.java
5	Files may contain hardcoded sensitive information like usernames, passwords, keys etc.	warning	CWE: CWE-312: Cleartext Storage of Sensitive Information OWASP Top 10: M9: Reverse Engineering OWASP MASVS: MSTG-STORAGE-14	com/dozingcatsoftware/bouncy/BouncyActivi ty.java

SHARED LIBRARY BINARY ANALYSIS

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED	
----	---------------	----	-----------------	-------	-------	---------	---------	---------------------	--

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
1	lib/armeabi-v7a/libgdx- box2d.so	True info The shared object has NX bit set. This marks a memory page non- executable making attacker injected shellcode non- executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The shared object does not have run-time search path or RPATH set.	None info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option - D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
2	lib/x86/libgdx-box2d.so	True info The shared object has NX bit set. This marks a memory page non- executable making attacker injected shellcode non- executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The shared object does not have run-time search path or RPATH set.	None info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option - D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
3	lib/arm64-v8a/libgdx- box2d.so	True info The shared object has NX bit set. This marks a memory page non- executable making attacker injected shellcode non- executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Partial RELRO warning This shared object has partial RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In partial RELRO, the non-PLT part of the GOT section is read only but .got.plt is still writeable. Use the option - z,relro,-z,now to enable full RELRO.	None info The shared object does not have run-time search path or RPATH set.	None info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option - D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
4	lib/x86_64/libgdx-box2d.so	True info The shared object has NX bit set. This marks a memory page non- executable making attacker injected shellcode non- executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The shared object does not have run-time search path or RPATH set.	None info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option - D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.

■ NIAP ANALYSIS v1.3

ОИ	IDENTIFIER	REQUIREMENT	FEATURE	DESCRIPTION

NO	IDENTIFIER	REQUIREMENT	FEATURE	DESCRIPTION		
1	FCS_RBG_EXT.1.1	Security Functional Requirements	Random Bit Generation Services	The application use no DRBG functionality for its cryptographic operations.		
2	FCS_STO_EXT.1.1	Security Functional Requirements	Storage of Credentials	The application does not store any credentials to non-volatile memory.		
3	FCS_CKM_EXT.1.1	Security Functional Requirements	Cryptographic Key Generation Services	The application generate no asymmetric cryptographic keys.		
4	FDP_DEC_EXT.1.1	Security Functional Requirements	Access to Platform Resources	The application has access to no hardware resources.		
5	FDP_DEC_EXT.1.2	Security Functional Requirements	Access to Platform Resources	The application has access to no sensitive information repositories.		
6	FDP_NET_EXT.1.1	Security Functional Requirements	Network Communications	The application has no network communications.		
7	FDP_DAR_EXT.1.1	Security Functional Requirements	Encryption Of Sensitive Application Data	The application does not encrypt files in non-volatile memory.		
8	FMT_MEC_EXT.1.1	Security Functional Requirements	Supported Configuration Mechanism	The application invoke the mechanisms recommended by the platform vendor for storing and setting configuration options.		
9	FTP_DIT_EXT.1.1	Security Functional Requirements	Protection of Data in Transit	The application does not encrypt any data in traffic or does not transmit any data between itself and another trusted IT product.		

Q DOMAIN MALWARE CHECK

DOMAIN	STATUS	GEOLOCATION
github.com	ok	IP: 140.82.121.3 Country: United States of America Region: California City: San Francisco Latitude: 37.775700 Longitude: -122.395203 View: Google Map
www.badlogicgames.com	ok	IP: 95.216.8.184 Country: Finland Region: Uusimaa City: Helsinki Latitude: 60.169521 Longitude: 24.935450 View: Google Map
www.twittering.com	ok	IP: 173.254.30.182 Country: United States of America Region: Utah City: Provo Latitude: 40.213909 Longitude: -111.634071 View: Google Map

EMAILS

EMAIL	FILE
bnenning@gmail.com	Android String Resource

Report Generated by - MobSF v3.5.2 Beta

Mobile Security Framework (MobSF) is an automated, all-in-one mobile application (Android/iOS/Windows) pen-testing, malware analysis and security assessment framework capable of performing static and dynamic analysis.

© 2022 Mobile Security Framework - MobSF | Ajin Abraham | OpenSecurity.