

ANDROID STATIC ANALYSIS REPORT



• Chiaki (1.3.0)

File Name:	installer73.apk
Package Name:	com.metallic.chiaki
Scan Date:	May 31, 2022, 9:22 a.m.
App Security Score:	64/100 (LOW RISK)
Grade:	A

FINDINGS SEVERITY

派 HIGH	▲ MEDIUM	i INFO	✓ SECURE	≪ HOTSPOT
0	4	1	1	0

FILE INFORMATION

File Name: installer73.apk

Size: 8.02MB

MD5: 4a30ac42a0a27aa0d93e843d3b6cf724

SHA1: 9fa40e46bbc7f9f24b7964dc7cd6f641c671d580

SHA256: 12dd9e2dfe61050c5e02d7311498852263b18ece34dcff8cbc5f4592bbf25c6f

i APP INFORMATION

App Name: Chiaki

Package Name: com.metallic.chiaki

Main Activity: com.metallic.chiaki.main.MainActivity

Target SDK: 29 Min SDK: 21 Max SDK:

Android Version Name: 1.3.0 Android Version Code: 7

B APP COMPONENTS

Activities: 6 Services: 1 Receivers: 0 Providers: 2

Exported Activities: O Exported Services: O Exported Receivers: O Exported Providers: O

***** CERTIFICATE INFORMATION

APK is signed v1 signature: True v2 signature: True v3 signature: False

Found 1 unique certificates Subject: C=DE, CN=Florian Märkl Signature Algorithm: rsassa_pkcs1v15 Valid From: 2019-11-01 16:51:41+00:00 Valid To: 2044-10-25 16:51:41+00:00 Issuer: C=DE, CN=Florian Märkl

Serial Number: 0xe6c2cb1 Hash Algorithm: sha256

md5: 97db35e4218ef20f474e0436a05f4f0b

sha1: 6a3623112522b287fca2e11d1eeeedc2e45dbd54

sha256: 3108372edcfe425169cc72f4481e76a724f5d5e4c953250411e134a9e48dcbbb

sha512: f5fd455f4df50b1782d05aeb82d9d62f15cc805711a1c0949715299a53b3ad0ef9c1638066b231aa52a3e1715d3a3b905f08ae80865bbb68e8021890b0eccdf2

PublicKey Algorithm: rsa

Bit Size: 2048

Fingerprint: 52ab2f3bce61b5370ee8b70fbcd03cc7f4e37f39bd80371bf17e0c5505f64433

TITLE	SEVERITY	DESCRIPTION
Signed Application	info	Application is signed with a code signing certificate
Application vulnerable to Janus Vulnerability	warning	Application is signed with v1 signature scheme, making it vulnerable to Janus vulnerability on Android 5.0-8.0, if signed only with v1 signature scheme. Applications running on Android 5.0-7.0 signed with v1, and v2/v3 scheme is also vulnerable.

⋮ APPLICATION PERMISSIONS

PERMISSION	STATUS INFO		DESCRIPTION	
android.permission.INTERNET	normal	full Internet access	Allows an application to create network sockets.	
android.permission.ACCESS_NETWORK_STATE	normal	view network status	Allows an application to view the status of all networks.	

命 APKID ANALYSIS

FILE	DETAILS					
	FINDINGS	DETAILS				
classes.dex	Anti-VM Code	Build.MANUFACTURER check				
	Compiler	r8				

△ NETWORK SECURITY

NO SCOPE SEVERITY DESCRIPTION

Q MANIFEST ANALYSIS

NO	ISSUE	SEVERITY	DESCRIPTION
1	Application Data can be Backed up [android:allowBackup=true]	warning	This flag allows anyone to backup your application data via adb. It allows users who have enabled USB debugging to copy application data off of the device.

</> CODE ANALYSIS

NO	ISSUE	SEVERITY	STANDARDS	FILES
1	IP Address disclosure	warning	CWE: CWE-200: Information Exposure OWASP MASVS: MSTG-CODE-2	com/metallic/chiaki/regist/RegistActivity.java com/metallic/chiaki/discovery/DiscoveryManager.java
2	The App logs information. Sensitive information should never be logged.	info	CWE: CWE-532: Insertion of Sensitive Information into Log File OWASP MASVS: MSTG-STORAGE-3	com/metallic/chiaki/manualconsole/EditManualConsol eViewModel\$existingHost\$1.java com/metallic/chiaki/regist/RegistExecuteViewModel.jav a com/metallic/chiaki/discovery/DiscoveryManager.java com/metallic/chiaki/lib/DiscoveryService.java com/metallic/chiaki/common/SerializedSettingsKt.java



NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
1	lib/armeabi-v7a/libchiaki- jni.so	True info The shared object has NX bit set. This marks a memory page non- executable making attacker injected shellcode non- executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The shared object does not have run-time search path or RPATH set.	None info The shared object does not have RUNPATH set.	True info The shared object has the following fortified functions: ['strlen_chk', 'memset_chk', 'vsnprintf_chk', 'memcpy_chk', 'FD_ISSET_chk', 'FD_SET_chk', 'vsprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
2	lib/x86/libchiaki-jni.so	True info The shared object has NX bit set. This marks a memory page non- executable making attacker injected shellcode non- executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The shared object does not have run-time search path or RPATH set.	None info The shared object does not have RUNPATH set.	True info The shared object has the following fortified functions: ['strlen_chk', 'memset_chk', 'vsnprintf_chk', 'memcpy_chk', 'FD_ISSET_chk', 'FD_SET_chk', 'vsprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
3	lib/arm64-v8a/libchiaki-jni.so	True info The shared object has NX bit set. This marks a memory page non- executable making attacker injected shellcode non- executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The shared object does not have run-time search path or RPATH set.	None info The shared object does not have RUNPATH set.	True info The shared object has the following fortified functions: ['FD_ISSET_chk', 'vsprintf_chk', 'memmove_chk', 'memcpy_chk', 'memcpy_chk', 'FD_SET_chk', 'vsnprintf_chk', 'read_chk', 'strlen_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
4	lib/x86_64/libchiaki-jni.so	True info The shared object has NX bit set. This marks a memory page non- executable making attacker injected shellcode non- executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The shared object does not have run-time search path or RPATH set.	None info The shared object does not have RUNPATH set.	True info The shared object has the following fortified functions: ['strlen_chk', 'memset_chk', 'wsnprintf_chk', 'memcpy_chk', 'FD_ISSET_chk', 'FD_SET_chk', 'vsprintf_chk', 'read_chk', 'memmove_chk']	True info Symbols are stripped.

■ NIAP ANALYSIS v1.3

NO	IDENTIFIER	REQUIREMENT	FEATURE	DESCRIPTION
1	FCS_RBG_EXT.1.1	Security Functional Requirements	Random Bit Generation Services	The application use no DRBG functionality for its cryptographic operations.

NO	IDENTIFIER	REQUIREMENT	FEATURE	DESCRIPTION
2	FCS_STO_EXT.1.1	Security Functional Requirements	Storage of Credentials	The application does not store any credentials to non-volatile memory.
3	FCS_CKM_EXT.1.1	Security Functional Requirements	Cryptographic Key Generation Services	The application generate no asymmetric cryptographic keys.
4	FDP_DEC_EXT.1.1	Security Functional Requirements	Access to Platform Resources	The application has access to ['network connectivity'].
5	FDP_DEC_EXT.1.2	Security Functional Requirements	Access to Platform Resources	The application has access to no sensitive information repositories.
6	FDP_NET_EXT.1.1	Security Functional Requirements	Network Communications	The application has user/application initiated network communications.
7	FDP_DAR_EXT.1.1	Security Functional Requirements	Encryption Of Sensitive Application Data	The application does not encrypt files in non-volatile memory.
8	FMT_MEC_EXT.1.1	Security Functional Requirements	Supported Configuration Mechanism	The application invoke the mechanisms recommended by the platform vendor for storing and setting configuration options.
9	FTP_DIT_EXT.1.1	Security Functional Requirements	Protection of Data in Transit	The application does encrypt some transmitted data with HTTPS/TLS/SSH between itself and another trusted IT product.

Q DOMAIN MALWARE CHECK

DOMAIN	STATUS	GEOLOCATION
github.com	ok	IP: 140.82.121.4 Country: United States of America Region: California City: San Francisco Latitude: 37.775700 Longitude: -122.395203 View: Google Map

HARDCODED SECRETS

POSSIBLE SECRETS		
preferences_bitrate_key" : "stream_bitrate"		
"preferences_discovery_enabled_key" : "discovery_enabled"		
"preferences_export_settings_key" : "export_settings"		
"preferences_fps_key" : "stream_fps"		
"preferences_import_settings_key" : "import_settings"		
"preferences_log_verbose_key" : "log_verbose"		
"preferences_on_screen_controls_enabled_key" : "on_screen_controls_enabled"		
"preferences_resolution_key" : "stream_resolution"		

POSSIBLE SECRETS

"preferences_swap_cross_moon_key": "swap_cross_moon"

"preferences_touchpad_only_key": "touchpad_only_enabled"

Report Generated by - MobSF v3.5.2 Beta

Mobile Security Framework (MobSF) is an automated, all-in-one mobile application (Android/iOS/Windows) pen-testing, malware analysis and security assessment framework capable of performing static and dynamic analysis.

© 2022 Mobile Security Framework - MobSF | Ajin Abraham | OpenSecurity.