


#### ANDROID STATIC ANALYSIS REPORT



Puzzles (2019-03-26-0844-68363231)

File Name:	installer3819.apk
Package Name:	name.boyle.chris.sgtpuzzles
Scan Date:	May 31, 2022, 7:42 p.m.
App Security Score:	24/100 (CRITICAL RISK)
Grade:	F

#### FINDINGS SEVERITY

<b>☆</b> HIGH	▲ MEDIUM	<b>i</b> INFO	✓ SECURE	<b>ℚ</b> HOTSPOT
6	2	1	1	1

#### FILE INFORMATION

File Name: installer3819.apk

Size: 4.79MB

MD5: 9db48bfaa8e6899254af4e7543f07e92

SHA1: 24eb43562b60dcd35927ea7f04c9a3041aa7b461

SHA256: 15a837e470eb8526927c206f5b513aedb2de245b510bd8ab754c0d37bfda077b

#### **i** APP INFORMATION

App Name: Puzzles

Package Name: name.boyle.chris.sgtpuzzles

Main Activity: name.boyle.chris.sgtpuzzles.SGTPuzzles

Target SDK: 28 Min SDK: 16 Max SDK:

Android Version Name: 2019-03-26-0844-68363231

Android Version Code: 120

#### **APP COMPONENTS**

Activities: 7 Services: 0 Receivers: 0 Providers: 1

Exported Activities: 1 Exported Services: 0 Exported Receivers: 0 Exported Providers: 0



APK is signed v1 signature: True v2 signature: False v3 signature: False

Found 1 unique certificates

Subject: C=UK, ST=ORG, L=ORG, O=fdroid.org, OU=FDroid, CN=FDroid

Signature Algorithm: rsassa\_pkcs1v15 Valid From: 2014-01-08 07:01:11+00:00 Valid To: 2041-05-26 07:01:11+00:00

Issuer: C=UK, ST=ORG, L=ORG, O=fdroid.org, OU=FDroid, CN=FDroid

Serial Number: 0x25de8d81 Hash Algorithm: sha256

md5: e70ef9d469aa18a04b7c2c874f2c6bd8

sha1: 383f871bbecced227e62a81db709cd822c614f2b

sha256: 9e8a696693c6cd0873455f80d406f84dc15951fdb23e5f2499c596909c2fd44f

sha512: 3a5d8e35cb523ed2c76093ca42c615e617dbf770b071042c1147cce8433f4c21a9daef55ef9ebbdbfebf5c8e07b2d4d083cb6e5a64a54f13f8572d6736696e28

TITLE	SEVERITY	DESCRIPTION
Signed Application	info	Application is signed with a code signing certificate

TITLE	SEVERITY	DESCRIPTION
Application vulnerable to Janus Vulnerability	high	Application is signed with v1 signature scheme, making it vulnerable to Janus vulnerability on Android 5.0-8.0, if signed only with v1 signature scheme. Applications running on Android 5.0-7.0 signed with v1, and v2/v3 scheme is also vulnerable.

#### **⋮** APPLICATION PERMISSIONS

PERMISSION	STATUS	INFO	DESCRIPTION
android.permission.WRITE_EXTERNAL_STORAGE dangerous		read/modify/delete external storage contents	Allows an application to write to external storage.
android.permission.READ_EXTERNAL_STORAGE dangerous		read external storage contents	Allows an application to read from external storage.
android.permission.NFC	normal	control Near-Field Communication	Allows an application to communicate with Near-Field Communication (NFC) tags, cards and readers.

# **M** APKID ANALYSIS

FILE	DETAILS
------	---------

FILE	DETAILS		
classes.dex	FINDINGS	DETAILS	
	Anti-VM Code	Build.FINGERPRINT check	
	Compiler	r8	

# **■** BROWSABLE ACTIVITIES

ACTIVITY	INTENT
----------	--------

ACTIVITY	INTENT
name.boyle.chris.sgtpuzzles.SGTPuzzles	Schemes: sgtpuzzles://, file://, content://, Hosts: *, Mime Types: text/prs.sgtatham.puzzles, */*, Path Patterns: /.*\\.sgtp, /.*\\*\\*\\*\\*\\*\\*\\*\

## **△** NETWORK SECURITY

NO	SCOPE	SEVERITY	DESCRIPTION	

# **Q** MANIFEST ANALYSIS

NO	ISSUE	SEVERITY	DESCRIPTION
1	Application Data can be Backed up [android:allowBackup=true]	warning	This flag allows anyone to backup your application data via adb. It allows users who have enabled USB debugging to copy application data off of the device.

NO	ISSUE	SEVERITY	DESCRIPTION
2	Launch Mode of Activity (name.boyle.chris.sgtpuzzles.GamePlay) is not standard.	high	An Activity should not be having the launch mode attribute set to "singleTask/singleInstance" as it becomes root Activity and it is possible for other applications to read the contents of the calling Intent. So it is required to use the "standard" launch mode attribute when sensitive information is included in an Intent.
3	Launch Mode of Activity (name.boyle.chris.sgtpuzzles.GameChooser) is not standard.	high	An Activity should not be having the launch mode attribute set to "singleTask/singleInstance" as it becomes root Activity and it is possible for other applications to read the contents of the calling Intent. So it is required to use the "standard" launch mode attribute when sensitive information is included in an Intent.
4	Activity (name.boyle.chris.sgtpuzzles.GameChooser) is not Protected. [android:exported=true]	high	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
5	Launch Mode of Activity (name.boyle.chris.sgtpuzzles.PrefsActivity) is not standard.	high	An Activity should not be having the launch mode attribute set to "singleTask/singleInstance" as it becomes root Activity and it is possible for other applications to read the contents of the calling Intent. So it is required to use the "standard" launch mode attribute when sensitive information is included in an Intent.
6	Launch Mode of Activity (name.boyle.chris.sgtpuzzles.HelpActivity) is not standard.	high	An Activity should not be having the launch mode attribute set to "singleTask/singleInstance" as it becomes root Activity and it is possible for other applications to read the contents of the calling Intent. So it is required to use the "standard" launch mode attribute when sensitive information is included in an Intent.

# </> CODE ANALYSIS

NO   ISSUE   SEVERITY   STANDARDS   FILES
---

NO	ISSUE	SEVERITY	STANDARDS	FILES
1	The App logs information. Sensitive information should never be logged.	info	CWE: CWE-532: Insertion of Sensitive Information into Log File OWASP MASVS: MSTG-STORAGE-3	name/boyle/chris/sgtpuzzles/GamePlay.ja va name/boyle/chris/sgtpuzzles/NightModeH elper.java name/boyle/chris/sgtpuzzles/GameView.ja va name/boyle/chris/sgtpuzzles/SmallKeyboa rd.java name/boyle/chris/sgtpuzzles/FilePicker.jav a
2	App can read/write to External Storage. Any App can read data written to External Storage.	warning	CWE: CWE-276: Incorrect Default Permissions OWASP Top 10: M2: Insecure Data Storage OWASP MASVS: MSTG-STORAGE-2	name/boyle/chris/sgtpuzzles/GamePlay.ja va name/boyle/chris/sgtpuzzles/GameChoos er.java name/boyle/chris/sgtpuzzles/FilePicker.jav a

## SHARED LIBRARY BINARY ANALYSIS

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
----	---------------	----	-----------------	-------	-------	---------	---------	---------------------

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
1	lib/armeabi- v7a/libpuzzlesgen.so	True info The shared object has NX bit set. This marks a memory page non- executable making attacker injected shellcode non- executable.	False high This shared object does not have a stack canary value added to the stack. Stack canaries are used to detect and prevent exploits from overwriting return address. Use the option - fstack- protector-all to enable stack canaries.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The shared object does not have run-time search path or RPATH set.	None info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option - D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
2	lib/armeabi-v7a/libpuzzles.so	True info The shared object has NX bit set. This marks a memory page non- executable making attacker injected shellcode non- executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The shared object does not have run-time search path or RPATH set.	None info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option - D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
3	lib/x86/libpuzzlesgen.so	True info The shared object has NX bit set. This marks a memory page non- executable making attacker injected shellcode non- executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The shared object does not have run-time search path or RPATH set.	None info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option - D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
4	lib/x86/libpuzzles.so	True info The shared object has NX bit set. This marks a memory page non- executable making attacker injected shellcode non- executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The shared object does not have run-time search path or RPATH set.	None info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option - D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
5	lib/arm64- v8a/libpuzzlesgen.so	True info The shared object has NX bit set. This marks a memory page non- executable making attacker injected shellcode non- executable.	False high This shared object does not have a stack canary value added to the stack. Stack canaries are used to detect and prevent exploits from overwriting return address. Use the option - fstack- protector-all to enable stack canaries.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The shared object does not have run-time search path or RPATH set.	None info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option - D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
6	lib/arm64-v8a/libpuzzles.so	True info The shared object has NX bit set. This marks a memory page non- executable making attacker injected shellcode non- executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The shared object does not have run-time search path or RPATH set.	None info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option - D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
7	lib/x86_64/libpuzzlesgen.so	True info The shared object has NX bit set. This marks a memory page non- executable making attacker injected shellcode non- executable.	False high This shared object does not have a stack canary value added to the stack. Stack canaries are used to detect and prevent exploits from overwriting return address. Use the option - fstack- protector-all to enable stack canaries.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The shared object does not have run-time search path or RPATH set.	None info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option - D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
8	lib/x86_64/libpuzzles.so	True info The shared object has NX bit set. This marks a memory page non- executable making attacker injected shellcode non- executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The shared object does not have run-time search path or RPATH set.	None info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option - D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.

# ■ NIAP ANALYSIS v1.3

ОИ	IDENTIFIER	REQUIREMENT	FEATURE	DESCRIPTION

NO	IDENTIFIER	REQUIREMENT	FEATURE	DESCRIPTION
1	FCS_STO_EXT.1.1	Security Functional Requirements	Storage of Credentials	The application does not store any credentials to non-volatile memory.
2	FCS_CKM_EXT.1.1	Security Functional Requirements	Cryptographic Key Generation Services	The application generate no asymmetric cryptographic keys.
3	FDP_DEC_EXT.1.1	Security Functional Requirements	Access to Platform Resources	The application has access to ['NFC'].
4	FDP_DEC_EXT.1.2	Security Functional Requirements	Access to Platform Resources	The application has access to no sensitive information repositories.
5	FDP_NET_EXT.1.1	Security Functional Requirements	Network Communications	The application has no network communications.
6	FDP_DAR_EXT.1.1	Security Functional Requirements	Encryption Of Sensitive Application Data	The application does not encrypt files in non-volatile memory.
7	FMT_MEC_EXT.1.1	Security Functional Requirements	Supported Configuration Mechanism	The application invoke the mechanisms recommended by the platform vendor for storing and setting configuration options.
8	FTP_DIT_EXT.1.1	Security Functional Requirements	Protection of Data in Transit	The application does not encrypt any data in traffic or does not transmit any data between itself and another trusted IT product.

# **Q DOMAIN MALWARE CHECK**

DOMAIN	STATUS	GEOLOCATION
code.google.com	ok	IP: 142.250.179.174  Country: United States of America Region: California City: Mountain View Latitude: 37.405991 Longitude: -122.078514 View: Google Map
chris.boyle.name	ok	IP: 217.70.191.130 Country: France Region: Ile-de-France City: Paris Latitude: 48.853409 Longitude: 2.348800 View: Google Map

### **EMAILS**

EMAIL	FILE
chris@boyle.name	Android String Resource



#### POSSIBLE SECRETS

"backup\_api\_key" : ""

#### Report Generated by - MobSF v3.5.2 Beta

Mobile Security Framework (MobSF) is an automated, all-in-one mobile application (Android/iOS/Windows) pen-testing, malware analysis and security assessment framework capable of performing static and dynamic analysis.

© 2022 Mobile Security Framework - MobSF | Ajin Abraham | OpenSecurity.