



ANDROID STATIC ANALYSIS REPORT



 2050 (1.0.5)


File Name: installer25.apk

Package Name: org.mattvchandler.a2050






Scan Date: May 31, 2022, 3:28 p.m.

App Security Score: 56/100 (MEDIUM RISK)

Grade:



FINDINGS SEVERITY

 HIGH	 MEDIUM	 INFO	 SECURE	 HOTSPOT
1	1	1	1	1

FILE INFORMATION

File Name: installer25.apk

Size: 4.2MB

MD5: 8927041556b255bb29cdcb1aaa4b2164

SHA1: dba2b04fd541f85823302d64ad8f7ff9651cedba

SHA256: 0c9fc92cd68d83620c6da0fa2a55457bdf56919c5860415eecb4580ab997c27d

APP INFORMATION

App Name: 2050

Package Name: org.mattvchandler.a2050

Main Activity: org.mattvchandler.a2050.MainActivity

Target SDK: 28

Min SDK: 19

Max SDK:

Android Version Name: 1.0.5

Android Version Code: 190010005

APP COMPONENTS

Activities: 2

Services: 0

Receivers: 0

Providers: 0

Exported Activities: 0

Exported Services: 0

Exported Receivers: 0

Exported Providers: 0

CERTIFICATE INFORMATION

APK is signed

v1 signature: True

v2 signature: False

v3 signature: False

Found 1 unique certificates

Subject: C=UK, ST=ORG, L=ORG, O=fdroid.org, OU=FDroid, CN=FDroid

Signature Algorithm: rsassa_pkcs1v15

Valid From: 2019-05-16 21:00:47+00:00

Valid To: 2046-10-01 21:00:47+00:00

Issuer: C=UK, ST=ORG, L=ORG, O=fdroid.org, OU=FDroid, CN=FDroid

Serial Number: 0x579cff9b

Hash Algorithm: sha256

md5: 2321fb295f54b9ea482c8a821aab48c8

sha1: eee15133beb109f11fc17eeef075f185ded46caf

sha256: b5b82827a3823eff1e86b683977d4a61171941d7a2a9c8632839ad8a45f28759

sha512: f1f11553ee88afc05a1825d01969cf7a95dc1d40c960d2a53ee894a5d87f851c0df054a368b95b93c6b59de2c0b20090791909a2cd2aedb995a6583414000a72

TITLE	SEVERITY	DESCRIPTION
Signed Application	info	Application is signed with a code signing certificate

TITLE	SEVERITY	DESCRIPTION
Application vulnerable to Janus Vulnerability	high	Application is signed with v1 signature scheme, making it vulnerable to Janus vulnerability on Android 5.0-8.0, if signed only with v1 signature scheme. Applications running on Android 5.0-7.0 signed with v1, and v2/v3 scheme is also vulnerable.

APPLICATION PERMISSIONS

PERMISSION	STATUS	INFO	DESCRIPTION
android.permission.ACCESS_FINE_LOCATION	dangerous	fine (GPS) location	Access fine location sources, such as the Global Positioning System on the phone, where available. Malicious applications can use this to determine where you are and may consume additional battery power.

APKID ANALYSIS

FILE	DETAILS	
classes.dex	FINDINGS	DETAILS
	Compiler	unknown (please file detection issue!)

NETWORK SECURITY

NO	SCOPE	SEVERITY	DESCRIPTION
----	-------	----------	-------------

MANIFEST ANALYSIS

NO	ISSUE	SEVERITY	DESCRIPTION
1	Application Data can be Backed up [android:allowBackup=true]	warning	This flag allows anyone to backup your application data via adb. It allows users who have enabled USB debugging to copy application data off of the device.

CODE ANALYSIS

NO	ISSUE	SEVERITY	STANDARDS	FILES
1	The App logs information. Sensitive information should never be logged.	info	CWE: CWE-532: Insertion of Sensitive Information into Log File OWASP MASVS: MSTG-STORAGE-3	org/mattvchandler/a2050/MainActivit y.java

SHARED LIBRARY BINARY ANALYSIS

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
----	---------------	----	-----------------	-------	-------	---------	---------	---------------------

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
1	lib/armeabi-v7a/lib2050.so	<p>True info</p> <p>The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>True info</p> <p>This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>None info</p> <p>The shared object does not have run-time search path or RPATH set.</p>	<p>None info</p> <p>The shared object does not have RUNPATH set.</p>	<p>False warning</p> <p>The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
2	lib/x86/lib2050.so	<p>True info</p> <p>The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>True info</p> <p>This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>None info</p> <p>The shared object does not have run-time search path or RPATH set.</p>	<p>None info</p> <p>The shared object does not have RUNPATH set.</p>	<p>False warning</p> <p>The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option - D_FORTIFY_SOURCE=2 to fortify functions.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
3	lib/arm64-v8a/lib2050.so	<p>True info</p> <p>The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>True info</p> <p>This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>None info</p> <p>The shared object does not have run-time search path or RPATH set.</p>	<p>None info</p> <p>The shared object does not have RUNPATH set.</p>	<p>False warning</p> <p>The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option - D_FORTIFY_SOURCE=2 to fortify functions.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
4	lib/x86_64/lib2050.so	<p>True info</p> <p>The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>True info</p> <p>This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>None info</p> <p>The shared object does not have run-time search path or RPATH set.</p>	<p>None info</p> <p>The shared object does not have RUNPATH set.</p>	<p>False warning</p> <p>The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option - D_FORTIFY_SOURCE=2 to fortify functions.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NIAP ANALYSIS v1.3

NO	IDENTIFIER	REQUIREMENT	FEATURE	DESCRIPTION
----	------------	-------------	---------	-------------

NO	IDENTIFIER	REQUIREMENT	FEATURE	DESCRIPTION
1	FCS_STO_EXT.1.1	Security Functional Requirements	Storage of Credentials	The application does not store any credentials to non-volatile memory.
2	FCS_CKM_EXT.1.1	Security Functional Requirements	Cryptographic Key Generation Services	The application generate no asymmetric cryptographic keys.
3	FDP_DEC_EXT.1.1	Security Functional Requirements	Access to Platform Resources	The application has access to ['location'].
4	FDP_DEC_EXT.1.2	Security Functional Requirements	Access to Platform Resources	The application has access to no sensitive information repositories.
5	FDP_NET_EXT.1.1	Security Functional Requirements	Network Communications	The application has no network communications.
6	FDP_DAR_EXT.1.1	Security Functional Requirements	Encryption Of Sensitive Application Data	The application does not encrypt files in non-volatile memory.
7	FMT_MEC_EXT.1.1	Security Functional Requirements	Supported Configuration Mechanism	The application invoke the mechanisms recommended by the platform vendor for storing and setting configuration options.
8	FTP_DIT_EXT.1.1	Security Functional Requirements	Protection of Data in Transit	The application does not encrypt any data in traffic or does not transmit any data between itself and another trusted IT product.

Report Generated by - MobSF v3.5.2 Beta

Mobile Security Framework (MobSF) is an automated, all-in-one mobile application (Android/iOS/Windows) pen-testing, malware analysis and security assessment framework capable of performing static and dynamic analysis.