

## ANDROID STATIC ANALYSIS REPORT



Badge Magic (1.6.0)

File Name:	installer143.apk	
Package Name:	org.fossasia.badgemagic	
Scan Date:	May 31, 2022, 4:22 p.m.	
App Security Score:	45/100 (MEDIUM RISK)	
Grade:		

#### FINDINGS SEVERITY

<b>ૠ</b> HIGH	<b>▲</b> MEDIUM	<b>i</b> INFO	✓ SECURE	<b>ू</b> HOTSPOT
2	3	1	1	1

#### FILE INFORMATION

File Name: installer143.apk

Size: 3.08MB

MD5: b610b2df684820d47bc615f27e9e3f2b

SHA1: a23386d24c951f7e3b9129223445041a1851f8ae

SHA256: b8821903e3e9ff1605499e979355f8a6039f30f6bbf2b09986b8ba70a12a4fa6

#### **i** APP INFORMATION

App Name: Badge Magic

Package Name: org.fossasia.badgemagic

 ${\it Main\ Activity}: org. fossasia. badge magic.ui. Drawer Activity$ 

Target SDK: 29 Min SDK: 21 Max SDK:

Android Version Name: 1.6.0 Android Version Code: 8



Activities: 3
Services: 1
Receivers: 1
Providers: 1

Exported Activities: O Exported Services: O Exported Receivers: 1 Exported Providers: O

#### **\*** CERTIFICATE INFORMATION

APK is signed v1 signature: True v2 signature: False v3 signature: False

Found 1 unique certificates

Subject: C=UK, ST=ORG, L=ORG, O=fdroid.org, OU=FDroid, CN=FDroid

Signature Algorithm: rsassa\_pkcs1v15 Valid From: 2019-06-03 10:02:14+00:00 Valid To: 2046-10-19 10:02:14+00:00

Issuer: C=UK, ST=ORG, L=ORG, O=fdroid.org, OU=FDroid, CN=FDroid

Serial Number: 0x1f22ed28 Hash Algorithm: sha256

md5: 71c76c3a1d81332d15b1d27614378d06

sha1: 3a46fac4d325c501403e10cf3e15fa386d348f47

sha256: d98471a7bf66f6b48b4d21940a863039dec9c6d3003fcdb847bf66c536edd844

sha512: 1b08e715b850849be86d242630188660acf9fa3643d87377678f02d84ccfed75f9739ebbcf9c9e4664927e0373c7d9f46792eeaad71df1bfb3a5a5d2ce20c6bd

TITLE	SEVERITY	DESCRIPTION
Signed Application	info	Application is signed with a code signing certificate
Application vulnerable to Janus Vulnerability	high	Application is signed with v1 signature scheme, making it vulnerable to Janus vulnerability on Android 5.0-8.0, if signed only with v1 signature scheme. Applications running on Android 5.0-7.0 signed with v1, and v2/v3 scheme is also vulnerable.

## **⋮** APPLICATION PERMISSIONS

PERMISSION	STATUS	INFO	DESCRIPTION
android.permission.BLUETOOTH	normal	create Bluetooth connections	Allows applications to connect to paired bluetooth devices.
android.permission.BLUETOOTH_ADMIN	normal	bluetooth administration	Allows applications to discover and pair bluetooth devices.
android.permission.ACCESS_FINE_LOCATION	dangerous	fine (GPS) location	Access fine location sources, such as the Global Positioning System on the phone, where available. Malicious applications can use this to determine where you are and may consume additional battery power.
android.permission.WRITE_EXTERNAL_STORAGE	dangerous	read/modify/delete external storage contents	Allows an application to write to external storage.
android.permission.READ_EXTERNAL_STORAGE	dangerous	read external storage contents	Allows an application to read from external storage.

## ক্ল APKID ANALYSIS

FILE
------

FILE	DETAILS				
	FINDINGS	DETAILS			
	Anti-VM Code	Build.MANUFACTURER check			
classes.dex	Compiler	unknown (please file detection issue!)			

## **△** NETWORK SECURITY

NO	SCOPE	SEVERITY	DESCRIPTION

# **Q** MANIFEST ANALYSIS

NO	ISSUE	SEVERITY	DESCRIPTION
1	Application Data can be Backed up [android:allowBackup=true]	warning	This flag allows anyone to backup your application data via adb. It allows users who have enabled USB debugging to copy application data off of the device.

NO	ISSUE	SEVERITY	DESCRIPTION
2	Broadcast Receiver (no.nordicsemi.android.support.v18.scanner.PendingIntentReceiver) is not Protected. [android:exported=true]	high	A Broadcast Receiver is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.

# </> CODE ANALYSIS

NO	ISSUE	SEVERITY	STANDARDS	FILES
----	-------	----------	-----------	-------

NO	ISSUE	SEVERITY	STANDARDS	FILES
1	The App logs information. Sensitive information should never be logged.	info	CWE: CWE-532: Insertion of Sensitive Information into Log File OWASP MASVS: MSTG-STORAGE-3	b/f/k/e.java b/j/a/b.java b/f/k/y.java b/f/k/y.java b/a/n/g.java b/a/n/g.java b/l/e0.java b/l/e0.java b/n/a/b.java c/a/a/a/m/h.java b/f/k/g.java b/f/d/h.java b/h/b/c.java b/l/g0.java b/l/d0.java b/l/d0.java b/f/k/b.java b/f/k/b.java b/f/d/d.java c/a/a/a/y/d.java c/a/a/a/z/b.java b/l/z.java b/f/j/b.java
2	App can read/write to External Storage. Any App can read data written to External Storage.	warning	CWE: CWE-276: Incorrect Default Permissions OWASP Top 10: M2: Insecure Data Storage OWASP MASVS: MSTG-STORAGE-2	org/fossasia/badgemagic/m/h.jav a

NO	ISSUE	SEVERITY	STANDARDS	FILES
3	App creates temp file. Sensitive information should never be written into a temp file.	warning	CWE: CWE-276: Incorrect Default Permissions OWASP Top 10: M2: Insecure Data Storage OWASP MASVS: MSTG-STORAGE-2	org/fossasia/badgemagic/m/h.jav a

## SHARED LIBRARY BINARY ANALYSIS

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
----	---------------	----	-----------------	-------	-------	---------	---------	---------------------

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
1	lib/armeabi- v7a/libpl_droidsonroids_gif.so	True info The shared object has NX bit set. This marks a memory page non- executable making attacker injected shellcode non- executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The shared object does not have run-time search path or RPATH set.	None info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option - D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
2	lib/x86/libpl_droidsonroids_gif.so	True info The shared object has NX bit set. This marks a memory page non- executable making attacker injected shellcode non- executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The shared object does not have run-time search path or RPATH set.	None info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option - D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
3	lib/arm64- v8a/libpl_droidsonroids_gif.so	True info The shared object has NX bit set. This marks a memory page non- executable making attacker injected shellcode non- executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The shared object does not have run-time search path or RPATH set.	None info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option - D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
4	lib/x86_64/libpl_droidsonroids_gif.so	True info The shared object has NX bit set. This marks a memory page non- executable making attacker injected shellcode non- executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The shared object does not have run-time search path or RPATH set.	None info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option - D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.

■ NIAP ANALYSIS v1.3

NO	IDENTIFIER	REQUIREMENT	FEATURE	DESCRIPTION
1	FCS_RBG_EXT.1.1	Security Functional Requirements	Random Bit Generation Services	The application use no DRBG functionality for its cryptographic operations.
2	FCS_STO_EXT.1.1	Security Functional Requirements	Storage of Credentials	The application does not store any credentials to non-volatile memory.
3	FCS_CKM_EXT.1.1	Security Functional Requirements	Cryptographic Key Generation Services	The application generate no asymmetric cryptographic keys.
4	FDP_DEC_EXT.1.1	Security Functional Requirements	Access to Platform Resources	The application has access to ['bluetooth', 'location'].
5	FDP_DEC_EXT.1.2	Security Functional Requirements	Access to Platform Resources	The application has access to no sensitive information repositories.
6	FDP_NET_EXT.1.1	Security Functional Requirements	Network Communications	The application has no network communications.
7	FDP_DAR_EXT.1.1	Security Functional Requirements	Encryption Of Sensitive Application Data	The application does not encrypt files in non-volatile memory.
8	FMT_MEC_EXT.1.1	Security Functional Requirements	Supported Configuration Mechanism	The application invoke the mechanisms recommended by the platform vendor for storing and setting configuration options.
9	FTP_DIT_EXT.1.1	Security Functional Requirements	Protection of Data in Transit	The application does encrypt some transmitted data with HTTPS/TLS/SSH between itself and another trusted IT product.

# **Q DOMAIN MALWARE CHECK**

DOMAIN	STATUS	GEOLOCATION
play.google.com	ok	IP: 142.251.36.46  Country: United States of America Region: California City: Mountain View Latitude: 37.405991 Longitude: -122.078514 View: Google Map
psdev.de	ok	IP: 49.12.32.214 Country: Germany Region: Sachsen City: Falkenstein Latitude: 50.477879 Longitude: 12.371290 View: Google Map
xmlpull.org	ok	IP: 74.50.61.58  Country: United States of America Region: Texas City: Dallas Latitude: 32.814899 Longitude: -96.879204 View: Google Map
schemas.android.com	ok	No Geolocation information available.
github.com	ok	IP: 140.82.121.3  Country: United States of America Region: California City: San Francisco Latitude: 37.775700 Longitude: -122.395203 View: Google Map

DOMAIN	STATUS	GEOLOCATION
sg.pslab.io	ok	No Geolocation information available.



#### **POSSIBLE SECRETS**

"file\_provider\_authority": "org.fossasia.badgemagic.fileprovider"

#### Report Generated by - MobSF v3.5.2 Beta

Mobile Security Framework (MobSF) is an automated, all-in-one mobile application (Android/iOS/Windows) pen-testing, malware analysis and security assessment framework capable of performing static and dynamic analysis.

© 2022 Mobile Security Framework - MobSF | Ajin Abraham | OpenSecurity.