

ANDROID STATIC ANALYSIS REPORT



Freebloks (1.2.5)

File Name:	installer107.apk
Package Name:	de.saschahlusiak.freebloks
Scan Date:	May 31, 2022, 9:02 a.m.
App Security Score:	55/100 (MEDIUM RISK)
Grade:	

FINDINGS SEVERITY

派 HIGH	▲ MEDIUM	i INFO	✓ SECURE	♥ HOTSPOT
1	2	1	1	0

FILE INFORMATION

File Name: installer107.apk

Size: 4.56MB

MD5: be0850e28bfb931b15b83239b928ad54

SHA1: 7c0ca0d5b57337e1d0b5e1c9c364db8f0b5ff5c5

SHA256: 1bfa3a745fed454e1fd0d7be5728d4a7726f683cfe7597eb1cbe489e7a29daad

i APP INFORMATION

App Name: Freebloks

 $\begin{picture}{ll} \textbf{Package Name:} de.saschahlusiak.freebloks \\ \end{picture}$

Main Activity: de.saschahlusiak.freebloks.game.FreebloksActivity

Target SDK: 29 Min SDK: 21 Max SDK:

Android Version Name: 1.2.5
Android Version Code: 105

APP COMPONENTS

Activities: 5 Services: 0 Receivers: 0 Providers: 1

Exported Activities: O Exported Services: O Exported Receivers: O Exported Providers: O



APK is signed v1 signature: True v2 signature: False v3 signature: False

Found 1 unique certificates

Subject: C=UK, ST=ORG, L=ORG, O=fdroid.org, OU=FDroid, CN=FDroid

Signature Algorithm: rsassa_pkcs1v15 Valid From: 2016-06-18 08:11:03+00:00 Valid To: 2043-11-04 08:11:03+00:00

Issuer: C=UK, ST=ORG, L=ORG, O=fdroid.org, OU=FDroid, CN=FDroid

Serial Number: 0x4f81de6 Hash Algorithm: sha256

md5: 2cb6d515dc157a743d99829eae0f76aa

sha1: 275e6ae63109add001bb38a138d1567e22f399d6

sha256: b84ad1afd452a019934fbe6a6b8417d8a278373917b738a6776f4db30214d470

sha512: 1d3615 fa5c566 a ea50 e 9 cd9860556 b 63 b 733 b b 95 e 66 b d557 dff 397598 fc 93703 f76 f5d0 a 44 b d6 e ec 226772272 e b 715 f5a f649 a 7 b f165 fd6 e b c 98 f427 e b 0 a b b 1 a 64 b c 98 f427 e b 0 a b 1 a 64 b c 98 f427 e b 0 a b 1 a 64 b c 98 f427 e b 0 a b 1 a 64 b c 98 f427 e b 0 a b 1 a 64 b c 98 f427 e b 0 a b 1 a 64 b c 98 f427 e b 0 a b 1 a 64 b c 98 f427 e b 0 a b 1 a 64 b c 98 f427 e b 0 a b 1 a 64 b c 98 f427 e b 0 a b 1 a 64 b c 98 f427 e b 0 a b 1 a 64 b c 98 f427 e b 0 a b 1 a 64 b c 98 f427 e b 0 a b 1 a 64 b c 98 f427 e b 0 a 64 b c 98 f427 e b 0 a 64 b c 98 f427 e b 0 a 64 b c 98 f427 e b 0 a 64 b c 98 f427 e b 0 a 64 b c 98 f427 e b 0 a 64 b c 98 f427 e b 0 a 64 b c 98 f427 e b 0 a 64 b c 98 f427 e b 0 a 64 b c 98 f427 e b 0 a 64 b c 98 f427 e b 0 a 64 b c 98 f427 e b 0 a 64 b c 98 f427 e b 0 a 64 b c 98 f427 e b 0 a 64 b c

TITLE	SEVERITY	DESCRIPTION
Signed Application	info	Application is signed with a code signing certificate

TITLE	SEVERITY	DESCRIPTION
Application vulnerable to Janus Vulnerability	high	Application is signed with v1 signature scheme, making it vulnerable to Janus vulnerability on Android 5.0-8.0, if signed only with v1 signature scheme. Applications running on Android 5.0-7.0 signed with v1, and v2/v3 scheme is also vulnerable.

⋮ APPLICATION PERMISSIONS

PERMISSION	STATUS	INFO	DESCRIPTION
android.permission.VIBRATE	normal	control vibrator	Allows the application to control the vibrator.
android.permission.INTERNET	normal	full Internet access	Allows an application to create network sockets.
android.permission.BLUETOOTH	normal	create Bluetooth connections	Allows applications to connect to paired bluetooth devices.
android.permission.BLUETOOTH_ADMIN	normal	bluetooth administration	Allows applications to discover and pair bluetooth devices.

M APKID ANALYSIS

FILE DETAILS

FILE	DETAILS	
	FINDINGS	DETAILS
classes.dex	Anti-VM Code	Build.MANUFACTURER check possible VM check
	Compiler	r8

△ NETWORK SECURITY

|--|

Q MANIFEST ANALYSIS

NO	ISSUE	SEVERITY	DESCRIPTION
1	Application Data can be Backed up [android:allowBackup=true]	warning	This flag allows anyone to backup your application data via adb. It allows users who have enabled USB debugging to copy application data off of the device.



|--|

NO	ISSUE	SEVERITY	STANDARDS	FILES
1	The App logs information. Sensitive information should never be logged.	info	CWE: CWE-532: Insertion of Sensitive Information in Sensitive OWASP MASVS: MSTG-STORAGE-3	de/saschahlusiak/freebloks/game/Freebloks Activity.java de/saschahlusiak/freebloks/game/dialogs/ MultiplayerDialog.java de/saschahlusiak/freebloks/view/AnimateTh read.java de/saschahlusiak/freebloks/game/dialogs/R ateAppDialog.java de/saschahlusiak/freebloks/network/messa ge/MessageChat\$Companion\$from\$1.java de/saschahlusiak/freebloks/network/Messa ge.java de/saschahlusiak/freebloks/view/GLConfigC hooser.java de/saschahlusiak/freebloks/view/Freebloks Renderer.java de/saschahlusiak/freebloks/game/Freebloks ActivityViewModel\$connectToBluetooth\$1.j ava de/saschahlusiak/freebloks/game/Freebloks ActivityViewModel.java de/saschahlusiak/freebloks/client/JNIServer. java de/saschahlusiak/freebloks/client/GameClie ntMessageHandler.java de/saschahlusiak/freebloks/network/Messa geWriter.java de/saschahlusiak/freebloks/network/Messa geWriter.java de/saschahlusiak/freebloks/network/blueto oth/BluetoothServerThread.java de/saschahlusiak/freebloks/hetwork/blueto oth/BluetoothServerThread.java de/saschahlusiak/freebloks/theme/BaseSou nds.java

NO	ISSUE	SEVERITY	STANDARDS	FILES
2	App uses SQLite Database and execute raw SQL query. Untrusted user input in raw SQL queries can cause SQL Injection. Also sensitive information should be encrypted and written to the database.	warning	CWE: CWE-89: Improper Neutralization of Special Elements used in an SQL Command ('SQL Injection') OWASP Top 10: M7: Client Code Quality	de/saschahlusiak/freebloks/database/Freebl oksDBOpenHandler.java de/saschahlusiak/freebloks/database/HighS coreDB.java

SHARED LIBRARY BINARY ANALYSIS

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
----	---------------	----	-----------------	-------	-------	---------	---------	---------------------

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
1	lib/armeabi-v7a/libktx.so	True info The shared object has NX bit set. This marks a memory page non- executable making attacker injected shellcode non- executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The shared object does not have run-time search path or RPATH set.	None info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option - D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
2	lib/armeabi-v7a/libserver.so	True info The shared object has NX bit set. This marks a memory page non- executable making attacker injected shellcode non- executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The shared object does not have run-time search path or RPATH set.	None info The shared object does not have RUNPATH set.	True info The shared object has the following fortified functions: ['FD_ISSET_chk', 'FD_SET_chk', 'strcpy_chk', 'vsprintf_chk', 'strlen_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
3	lib/x86/libktx.so	True info The shared object has NX bit set. This marks a memory page non- executable making attacker injected shellcode non- executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The shared object does not have run-time search path or RPATH set.	None info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option - D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
4	lib/x86/libserver.so	True info The shared object has NX bit set. This marks a memory page non- executable making attacker injected shellcode non- executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The shared object does not have run-time search path or RPATH set.	None info The shared object does not have RUNPATH set.	True info The shared object has the following fortified functions: ['strlen_chk', 'FD_ISSET_chk', 'FD_SET_chk', 'strcpy_chk', 'vsprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
5	lib/arm64-v8a/libktx.so	True info The shared object has NX bit set. This marks a memory page non- executable making attacker injected shellcode non- executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The shared object does not have run-time search path or RPATH set.	None info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option - D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
6	lib/arm64-v8a/libserver.so	True info The shared object has NX bit set. This marks a memory page non- executable making attacker injected shellcode non- executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The shared object does not have run-time search path or RPATH set.	None info The shared object does not have RUNPATH set.	True info The shared object has the following fortified functions: ['FD_ISSET_chk', 'strlen_chk', 'FD_SET_chk', 'vsprintf_chk', 'strcpy_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
7	lib/x86_64/libktx.so	True info The shared object has NX bit set. This marks a memory page non- executable making attacker injected shellcode non- executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The shared object does not have run-time search path or RPATH set.	None info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option - D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
8	lib/x86_64/libserver.so	True info The shared object has NX bit set. This marks a memory page non- executable making attacker injected shellcode non- executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The shared object does not have run-time search path or RPATH set.	None info The shared object does not have RUNPATH set.	True info The shared object has the following fortified functions: ['strlen_chk', 'FD_ISSET_chk', 'FD_SET_chk', 'strcpy_chk', 'vsprintf_chk']	True info Symbols are stripped.

■ NIAP ANALYSIS v1.3

NO	IDENTIFIER	REQUIREMENT	FEATURE	DESCRIPTION

NO	IDENTIFIER	REQUIREMENT	FEATURE	DESCRIPTION
1	FCS_RBG_EXT.1.1	Security Functional Requirements	Random Bit Generation Services	The application use no DRBG functionality for its cryptographic operations.
2	FCS_STO_EXT.1.1	Security Functional Requirements	Storage of Credentials	The application does not store any credentials to non-volatile memory.
3	FCS_CKM_EXT.1.1	Security Functional Requirements	Cryptographic Key Generation Services	The application generate no asymmetric cryptographic keys.
4	FDP_DEC_EXT.1.1	Security Functional Requirements	Access to Platform Resources	The application has access to ['network connectivity', 'bluetooth'].
5	FDP_DEC_EXT.1.2	Security Functional Requirements	Access to Platform Resources	The application has access to no sensitive information repositories.
6	FDP_NET_EXT.1.1	Security Functional Requirements	Network Communications	The application has user/application initiated network communications.
7	FDP_DAR_EXT.1.1	Security Functional Requirements	Encryption Of Sensitive Application Data	The application does not encrypt files in non-volatile memory.
8	FMT_MEC_EXT.1.1	Security Functional Requirements	Supported Configuration Mechanism	The application invoke the mechanisms recommended by the platform vendor for storing and setting configuration options.
9	FTP_DIT_EXT.1.1	Security Functional Requirements	Protection of Data in Transit	The application does encrypt some transmitted data with HTTPS/TLS/SSH between itself and another trusted IT product.

Q DOMAIN MALWARE CHECK

DOMAIN	STATUS	GEOLOCATION			
github.com	ok	IP: 140.82.121.4 Country: United States of America Region: California City: San Francisco Latitude: 37.775700 Longitude: -122.395203 View: Google Map			
paypal.me	ok	IP: 64.4.250.36 Country: United States of America Region: Washington City: Seattle Latitude: 47.606209 Longitude: -122.332069 View: Google Map			
www.youtube.com	ok	IP: 216.58.208.110 Country: United States of America Region: California City: Mountain View Latitude: 37.405991 Longitude: -122.078514 View: Google Map			
f-droid.org	ok	IP: 148.251.140.42 Country: Germany Region: Bayern City: Nuremberg Latitude: 49.447781 Longitude: 11.068330 View: Google Map			

Mobile Security Framework (MobSF) is an automated, all-in-one mobile application (Android/iOS/Windows) pen-testing, malware analysis and security assessment framework capable of performing static and dynamic analysis.

© 2022 Mobile Security Framework - MobSF | Ajin Abraham | OpenSecurity.