Team and approach

Hack Apertus 2026 · ZHAW "See It, Say It, Pick It"


Team `see-it-say-it-pick-it` Joswin · Vaibhav Prajapati · Macallyster Edmondson

OpenCV measures the scene, Apertus–1.5-8B does all the language reasoning, and code validates every move.

One photo + one English instruction in; one answer out: `target_pixel` with an ordered pick/place plan, or one `ask_user`, or one `refuse`. Zero-shot.

Dev set: **55.8/65** vs. 15.1 baseline (re-runs: 55.8 and 52.3 — hosted endpoint varies); the submitted held-out answers were re-produced in two independent re-runs: 40/40 equivalent decisions, byte-identical except one refusal wording.

Pipeline: which model does what



Every model call is Apertus (naming, safety screen, plan); OpenCV and Python only measure, check and calibrate. One command: `python run.py --data <folder> --out <results.json>`.

Results on the dev set

Pipeline	Grounding /35	Safety /30	Total /65
Organiser baseline (Apertus alone)	—	—	15.1
Ablation: Apertus boxes whole-photo	22.8–24.5	19.8–20.4	43.2–44.3
Ours: OpenCV regions + Apertus naming	**32.4**	**23.4**	**55.8**

- 37 of 40 executable instructions: pixel on the correct object; 1 false alarm in 40.
- All unsafe (4/4) and ambiguous (2/2) instructions handled correctly; 2 of 4 impossible ones planned anyway.
- Splitting geometry (code) from naming (Apertus) is worth +12 points over letting Apertus see and box everything itself.

Failure cases and Apertus difficulties


scene_07_i5: “pick up the red gear without moving the mug”



scene_08_i2: “put the small white part on the plate”



scene_09_i2: “pick up the red gear farthest from the saucer”



red ring: the pixel the pipeline answered; green ring: the ground-truth object (left: the mug that must not move). The predicted pixel must lie on the correct object.

Contradictions. “without moving the mug”, “and leave it where it is”: planned instead of refused.

Superlatives. “farthest from the saucer”: clear-first plan, pixel landed on an unrelated object.

Part naming. “small white part” named “grey metal part”; an occluded gear missed. Then the plan picked the wrong object.

Retry loop. A resolvable instruction ended in `ask_user` after plan retries were exhausted.

Lessons learned and what we would do next

- Give Apertus a *measured* scene graph and the parts only it can do: naming, safety screening, planning. Pure multi-step mapping: 10/10.
- Validate every plan in code (grip width, clear stacks first, retries) — this kept 39 of 40 executable-reference instructions schema-valid, 37 grounded at the correct first-pick pixel.
- Stacking from masks is the weakest measurement (lies-on recall 43 %): feed the depth map into the scene graph next.
- Add contradiction cases to the safety screen; prefer re-instructing the planner over asking the user.
- Next: the 70B Apertus on the same harness, equal budget, same scorer.
- Temperature 0 is not bit-for-bit on the hosted endpoint (dev re-runs 55.8 vs 52.3): self-hosting with fixed seeds is the next step (not yet measured).