




Ulf Skutnabba, twitter: @skutis77

Konami GX945

Sheet: /CPU Master/
File: cpu_master.kicad_sch**Title: Gradius 3**Size: A3 Date: 2024-04-11
KiCad E.D.A. 8.0.9

Rev: Id: 2/12



Ulf Skutnabba, twitter: @skutis77

Konami GX945

Sheet: /CPU Slave/


File: cpu_slave.kicad_sch

Title: Gradius 3

Size: A3 Date: 2024-04-11

KiCad E.D.A. 8.0.9

Rev: 3/12



Ulf Skutnabba, twitter: @skutis77

Konami GX945

Sheet: /Shared RAM/

File: shram.kicad_sch

Title: Gradius 3

Size: A3 Date: 2024-04-11

KiCad E.D.A. 8.0.9

Rev:

Id: 4/12

1 2 3 4 5 6 7 8


A



B



C




D

E

F

Tile Layers – Shared Data Bus



Ulf Skutnabba, twitter: @skutis77

Konami GX945

Sheet: /Tile Logic/

File: tile_logic.kicad_sch

Title: Gradius 3


Size: A3 Date: 2024-04-11


KiCad E.D.A. 8.0.9


Rev:


Id: 5/12

1 2 3 4 5 6 7 8









Ulf Skutnabba, twitter: @skutis77

Konami GX945

Sheet: /Sound/

File: sound.kicad_sch


Title: Gradius 3

Size: A3 Date: 2024-04-11

KiCad E.D.A. 8.0.9

Rev: 9/12

B15 and B18 do not follow the standard Mask ROM behaviour. The BYTE mode select must be selected from factory and pin 31 is probably not connected.



The values to the right are the capacitors on the PCB. C10X are not visible on the PCB. They are values set to ease debugging.

Ulf Skutnabba, twitter: @skutis77
Konami GX945

Sheet: /PCM/
File: pcm.kicad_sch


Title: pmn.riccardo_sen

Size: A3

KiCad E.D.A. 8.0.9

7

3






Horizontal and vertical synch timing diagrams

The pixel clock is derived from the 24MHz oscillator.
Pixel clock OVCK: $f = 24\text{MHz} / 4 = 6\text{MHz}$

The numbers in the HSYNC and HBL diagram are pixel clock cycles.
All edges are synchronised to the rising edge of the pixel clock.


The signals have been measured at the output of the
graphic chips.

If horizontal blanking is measured at the RGB DACs, the blanking
is delayed 2 pixel clocks relative to composite sync. This
gives BP = 14 and FP = 18.



HSYNC and HBL
Frequency $f = 6\text{MHz} / 384 = 15.625\text{kHz}$.
Period $T = 1/f = 64\text{us}$.

The numbers in the VSYNC and VBL diagram are HSYNC cycles.
All edges are synchronised to the falling edge of HSYNC.



VSYNC and VBL:
Frequency $f = 15.625\text{kHz} / 264 = 59.1856\text{Hz}$
Period $T = 1/f = 1 / 59.1856\text{Hz} = 16.896\text{ms}$

Ulf Skutnabba, twitter: @skutis77

Konami GX945

Sheet: /Misc/

File: misc.kicad_sch

Title: Gradius 3

Size: A3 Date: 2024-04-11

KiCad E.D.A. 8.0.9

Rev:

Id: 12/12