

Base Design

Schematic Capture

INSTRUMENTS

- OSCILLOSCOPE
- LOGIC ANALYSER
- COUNTER TIMER
- VIRTUAL TERMINAL
- SPI DEBUGGER
- I2C DEBUGGER
- SIGNAL GENERATOR
- PATTERN GENERATOR
- DC VOLTMETER
- DC AMMETER
- AC VOLTMETER
- AC AMMETER
- WATTMETER

ARD1

ARDUINO UNO R3

Reset BTN

NO

AREF

PB5/SCK

PB4/MISO

~ PB3/MOSI/OC2A

~ PB2/OC1B

~ PB1/OC1A

PB0/CP1/CLKO

PD7/AIN1

~ PD7/AIN1

~ PD5/T1/OC0B

PD4/T0/XCK

~ PD3/INT1/OC2B

PD2/INT0

PD1/TXD

PD0/RXD

RESET

ANALOG IN

A0=

A1=

A2=

A3=

A4=

A5=

PC0/ADC0

PC1/ADC1

PC2/ADC2

PC3/ADC3

PC4/ADC4/SDA

PC5/ADC5/SCL

1111

www.TheEngineeringProjects.com

RXD

TXD

RTS

CTS

Virtual Terminal

```
Number is 66
Number is 67
Number is 68
Number is 69
Number is 70
Number is 71
Number is 72
Number is 73
Number is 74
Number is 75
Number is 76
Number is 77
Number is 78
Number is 79
Number is 80
Number is 81
Number is 82
Number is 83
Number is 84
Number is 85
Number is 86
Number is 87
Number is 88
Number is 89
Number is 90
Number is 91
Number is 92
Number is 93
Number is 94
Number is 95
Number is 96
```

5 Message(s) ANIMATING: 00:00:48.450000 (CPU load 63%) x: +500.0 y: +3100.0



sketch_aug04a

```
void setup()
{
  Serial.begin(9600); // send and receive at 9600 baud
}

int number = 0;

void loop()
{
  Serial.print("Number is ");
  Serial.println(number); // print the number
  delay(500); // delay half second between numbers
  number++; // to the next number
}
```

Done compiling.

Sketch uses 1902 bytes (5%) of program storage space. Maximum is 32256 bytes.

Global variables use 200 bytes (9%) of dynamic memory, leaving 1848 bytes for local variables. Maximum is 2048 bytes.