

Norlux -the nordic lighting supplier

Maximum 10% is allowed

to fail in fulfilling this level

of performance.

L80

Guaranteed performance, minimum 80% of initial light quality and - quantity after 50.000 hours in use.

Tired of downlights giving obtrusive annoying stray light? Our Trimo range of downlights guarantees a minimum of stray light, this is accomplished by using a recessed LED light source. The Trimo range has a EPCOM18i3 connector and can be supplied with a variety of connector solutions. Please check the table below for an overview of available colors and connectors.

Downligh COB LED







Connection options on request

Ø170mm	9119mm	Ø170mm	
--------	--------	--------	--

Ø155 mm

Dimensions

Cut Size

Life expectancy(L80/B10): 50 000 hours

Product no.	Product name	System (W)	Lumen	Color temp.	CRI	Reflector	Color
18045-5-20-1	Trimo	31W	3385 lm	3000K	80	20°	Grey
18045-5-20-2	Trimo	31W	3385 lm	3000K	80	20°	Black
18045-5-20-3	Trimo	31W	3385 lm	3000K	80	20°	White
18046-5-20-1	Trimo	31W	3700 lm	4000K	80	20°	Grey
18046-5-20-2	Trimo	31W	3700 lm	4000K	80	20°	Black
18046-5-20-3	Trimo	31W	3700 lm	4000K	80	20°	White

831-01-5

Reinforcement base Ø140/155/170/190 mm

Brown

* Also available with reflectors 30°/60°











