

Copana Webservice API Documentation

Overview

The Copana Webservice provides endpoints for system health checks, token authentication, and flight search operations. This API uses XML for request and response formats, adhering to webservice standards.

Base URL

<https://copana.flylang.jobsityapps.com>

Endpoints

1. System Ping

Endpoint: `/webservices/copana/version27_8_5/system/ping.wsd`

Method: `POST`

Description: Checks the health of the system.

Response Example:

```
<response>
  <response>pong</response>
  <time>2025-04-12 14:30:00</time>
</response>
```

2. Token Authentication

Endpoint: `/webservices/copana/version27_8_5/authentication/token.wsd`

Method: `POST`

Description: Generates a token for authentication. Tokens are valid for 2 minutes.

Response Example:

```
<Token>
  <value>abc123xyz456</value>
  <expires_in>120 seconds</expires_in>
</Token>
```

3. Flight Search

Endpoint: `/webservices/copana/version27_8_5/flight/search.wsd`

Method: `POST`

Description: Searches for flights available.

Request Parameters:

Parameter	Type	Required	Description	Example
<code>iata:departure_code</code>	String	Yes	IATA code of the departure airport	<code>MIA</code>
<code>iata:arrival_code</code>	String	Yes	IATA code of the arrival airport	<code>SCL</code>
<code>date:departure</code>	String	Yes	Departure date in <code>DD/MM/YY</code> format	<code>12/04/25</code>
<code>token</code>	String	Yes	Authentication token	<code>abc123xyz456</code>

Response Example (Success):

```
<Flights>
  <Flight>
    <flight:code>CP001</flight:code>
    <date:departure>12/04/25 14:30</date:departure>
    <date:arrival>12/04/25 18:45</date:arrival>
    <amount:pricing>200.00</amount:pricing>
    <flight:route>MIA-SCL</flight:route>
  </Flight>
</Flights>
```

Response Example (Invalid Token):

```
<Error>
  <code>7</code>
  <message>Invalid or expired token</message>
</Error>
```

Response Example (Missing Fields):

```
<Error>
  <code>9</code>
  <message>Missing required fields: iata:from, iata:to, or date:departure</message>
</Error>
```

Response Example (Invalid Date Format):

```
<Error>
  <code>15</code>
  <message>Invalid date format. Use DD/MM/YY (e.g., 12/04/91).</message>
</Error>
```

Error Codes

Code	Message	Description
7	Invalid or expired token	The provided token is invalid or expired.
9	Missing required fields	One or more required fields are missing.
15	Invalid date format	The provided date format is incorrect.

Token Management

- Tokens are valid for **2 minutes**.
- A new token can be generated using the `/authentication/token.wsd` endpoint.

Notes

- All responses are in XML format.
 - Ensure that the token is valid before making requests to the `/flight/search.wsd` endpoint.
 - Use the correct date format (`DD/MM/YY`) for the `date:departure` parameter.
-

Contact

For support or inquiries, contact the Webservices core team.