

Assignment for Chapter 6:

Frequency Domain Analysis

6-1 Using the straight-line approximations, plot the Bode Diagram (Log-magnitude diagram and Log-phase diagram) of the systems described by the following open-loop transfer functions. Determine the Gain crossover frequency ω_c and Phase crossover frequency ω_g .

$$(1) \quad G(s) = \frac{20}{s(s+10)(s+20)}$$

$$(2) \quad G(s) = \frac{5}{s(0.01s^2 + 0.1s + 1)}$$

$$(3) \quad G(s) = \frac{40}{s(s-10)(s+20)}$$

6-2 Please sketch the Nyquist Diagram of the systems described by the following open-loop transfer functions.

$$(1) \quad G(s) = \frac{100}{s(s+10)(s+20)}$$


$$(2) \quad G(s) = \frac{10}{s^3(s+1)(s+2)}$$

$$(3) \quad G(s) = \frac{10(s-1)}{s(s+2)}$$

6-3 Consider the unity-feedback control system described by the open-loop transfer function

$$G(s) = \frac{K(s+8)(as+1)}{s(0.1s+1)(0.25s+1)(bs+1)}.$$

Its Bode diagram is shown in the following figure. Determine the values of K , a and b .



6-4 By using Bode Diagram based stability analysis, please judge if the systems (1)-(3) in 6-1 are stable. If they are stable, please determine the phase margin γ and gain margin GM .

6-5 Please use Nyquist criterion to judge if the systems in 6-2 are stable. Please determine Phase Margin γ and Gain Margin GM .

6-6 Consider the unity-feedback control system described by the open-loop transfer function

$$G(s) = \frac{K_r}{s(s+10)}.$$

If the overshoot of the closed-loop system satisfies $M_p \leq 5\%$, please determine

- (1) open-loop gain (Evan's gain);
- (2) resonant peak $M_{p\omega}$ of the closed-loop system;
- (3) resonant frequency ω_r of the closed-loop system;
- (4) band-width ω_b ;
- (5) unit step response of the closed-loop system.


6-7 Sketch the Nyquist diagram of the systems described by the following open-loop transfer functions. From the obtained Nyquist diagrams, find the range of K for which the systems are stable.

$$(1) \quad G(s) = \frac{K}{s(s^2 + 2s + 4)}$$


$$(2) \quad G(s) = \frac{K(s+1)(s-2)}{s^2(s+4)(-s+1)}$$

6-8 A control system is shown in the block diagram (a), and $G(s)$ and $G_c(s)$ are both of minimum phase. The Log-magnitude diagrams of $G(s)$ and $G_c(s)G(s)$ are given in Figure (b). Please determine

- (1) the transfer function of $G_c(s)$;
- (2) steady-state error constants K_p , K_v and K_a of $G(s)$ and $G_c(s)G(s)$, respectively;
- (3) phase margin of $G(s)$ and $G_c(s)G(s)$;
- (4) the system overshoots with and without $G_c(s)$, respectively.



(a)



(b)