Nodus « demo » project

Bart Jourquin
2017 - 2026
(Last revision: October 13, 2026)

Center for Operations Research and Econometrics (CORE)
Louvain-la-Neuve and Mons, Belgium
e-mail: bart.jourquin@uclouvain.be

This document presents the basic usage of Nodus (since version 7.0) and the structure of the different files and database tables that are used or created by the software. It is followed by a presentation of different scenarios that can be run using the provided sample Nodus project.

Nodus 7.1 is functionally identical to Nodus 7.0, but embeds the Groovy 2.5.x scripting language instead of Groovy 2.4.x. This can potentially (but very unlikely) break some scripts written by end users. The use of Groovy 2.5.x also introduces a change in the directory structure of Nodus, affecting the Java classpath. This change should, however, remain transparent for end users.

Nodus 7.2 embeds Groovy 3.xx.

Nodus 8.0 adds the possibility of defining "transit time" functions along with "cost" functions. This version also improves the "exclusions" mechanism that allows defining the types of operations that can be performed or not at the node level. Nodus 8.0 also introduces a simplified API for "user-defined" modal choice plugins. This is a breaking change, as old plugins are not anymore compatible with this version of Nodus.

Nodus 8.1 introduces the possibility of developing Python and R scripts in addition to Groovy scripts. It also runs on Java 16.

Nodus 8.2 runs on Java 17, but now needs Java 11 or above to run. It embeds Groovy 4.0 and runs the embedded HSQLDB and H2 database engines in server mode, allowing for multiple connections. H2 has also been upgraded to version 2. Existing H2 databases need a migration. See https://www.h2database.com/html/migration-to-v2.html.

Nodus 8.3 runs on Java 25 and embeds Groovy 5.x. The version change is justified by the fact that, although unlikely, some scripts written for previous versions of Nodus in this language may need to be slightly adapted.

Nodus 8.4 reintroduces the Frank-Wolfe based assignment algorithms, which were removed since 8.0 because they were buggy. It should primarily be seen as a stability and robustness update: several sensitive parts of the code were reviewed and strengthened, in particular the project open/close workflows, SQL console execution, time-dependent result display, and resource release.

Nodus 8.5 reintroduces lines and services through a completely revamped workflow. The GUI is also enriched with tooltips for almost all the GUI elements. The "demo" project is somewhat revised and includes a basic example implementing lines and services.

Nodus 9.0 adds embedded modal-choice parameter estimation for univariate logit, probit and proportional methods and modal choice performance measurement indicators. It is also a performance-focused release, highlighting faster assignments (at least four times faster on a set of selected projects), more responsive map navigation and faster database operations. The release also moves the modal-choice API into its own package, which is a breaking change,[1] as custom modal-choice plugins need updated imports and recompilation. From the developers' perspective, a series of unit tests have been added with an automatic continuous integration workflow.

[1] At least at the source level, because Nodus can automatically "upgrade" existent jar files.

Table of contents

1 Needed Inputs....5
1.1 The Project File....5
1.2 The Origin-Destination Matrices....7
1.3 The Cost Files....7
2 The Basics of the Interface....8
2.1 Project Menu....9
2.1.1 Preferences....9
2.1.2 Edit Cost Files....10
2.1.3 Edit Services....10
2.1.4 Modal Choice Estimation....10
2.1.5 Assignment....12
2.1.6 Display Results....14
2.1.7 Scenarios....14
2.1.8 SQL Console....15
2.2 Control Menu....16
2.3 Projection Menu....16
2.4 Tools Menu....17
2.4.1 Look & Feel....17
2.4.2 Language....17
2.4.3 Console....17
2.4.4 Groovy Scripts....17
2.4.5 Resource Monitor....17
3 The “demo” Project....18
3.1 Load the Project....18
3.1.1 Node layers....19
3.1.2 Link layers....19
3.2 Scenario 1: Road assignment....21
3.3 Scenario 2: Multi-Route road assignment....23
3.4 Scenario 3: Inland waterways, with two types of barges....25
3.5 Scenario 4: Rail transport....27
3.6 Scenario 5: Multimodal assignment....28
3.7 Scenario 6: Simple estimation of a multimodal assignment....31
3.8 Validation of a model....32
3.9 Calibration of the model using “pivots”....33
3.10 Scenario 7: User-defined modal-choice plugin’s....34
3.11 Scenario 8: Comparison Between Scenarios....35
3.12 Scenario 9: Intermodal model....37
3.13 Scenario 10: More Complex Intermodal Model....38
3.14 Lines and Services Basics....40
3.14.1 Scenario 11: Example of a service stop....41
3.14.2 Scenario 12: Example of a service switch....41
4 Conclusion....43
5 Appendix – More on cost Functions....44

5.1 Modes, means, groups, classes and Scenarios.....44
5.2 Embedded variables.....45
5.3 Cost Functions for Equilibrium Assignments.....46
5.4 Other capacity constraints.....48

1 Needed Inputs

1.1 The Project File

The information needed to open a Nodus project must be stored in a text file with the ".nodus" extension. The format of the file is similar to a standard Java properties file. Only two mandatory entries must be present: "network.nodes" and "network.links". Both are a space separated list of layers, each one being a standard Esri shapefile, i.e. a ".shp", a ".shx" and a ".dbf" file.

Note that .dbf files are standard dBase files. Numerous software tools can be used to browse or edit these files. Among the open source tools, you can use LibreOffice (http://www.libreoffice.org) to edit .dbf files or QGis (http://www.qgis.org) to manipulate the shapefiles, including the content of the associated ".dbf" files.

Example:

```
network.nodes= centroids road_points iww_points rail_points
network.links= road_polylines iww_polylines rail_polylines \
               road_con iww_con rail_con
```

A Nodus compatible network needs a set of nodes (vertices) and links (edges). In order to be useable by Nodus, the .dbf files of each layer must contain some mandatory fields:

For Nodes:

- NUM,N,10,0 : The unique ID of the node
- STYLE,N,2,0 : The rendering style of the node
- TRANSHIP,N,1,0 : The type of operations that can be performed at the node

For Links:

- NUM,N,10,0 : The unique ID of the link
- STYLE,N,2,0 : The rendering style of the link
- ENABLED,N,1,0 : If 0, the link will not be used in the model
- NODE1,N,10,0 : The ID of the node at the origin of the link
- NODE2,N,10,0 : The ID of the node at the end of the link
- MODE,N,2,0 : The transportation mode used in the link
- MEANS,N,2,0 : The # of means (types of vehicles) that can be used on the link
- CAPACITY,N,10,0 : The capacity of the link
- SPEED,N,7,2 : The (free flow) speed on the link

After these mandatory fields, the user can add additional numeric or character fields. It is wise to use UTF8 encoding for the DBF file. The (uppercase) name of all the numeric fields can be used as variables in the cost functions.

Before the project can be used, Nodus checks if the set of layers is suitable for a project. In particular, the following conditions must be met:

- The ID of a node must be unique across all node layers
- The ID of a link must be unique across all link layers
- NODE1 must be an existent ID in one of the node layers
- NODE1 must be an existent ID in one of the node layers
- NODE1 and NODE2 must be different

This ensures that the set of layers can be seen as a graph to which assignment algorithms can be applied.

Nodus imports all the ".dbf" files into an SQL database. By default, it uses HSQLDB; H2 is also bundled. The embedded DBMS can be selected in Global preferences. Nodus can also use other DBMSs, such as MySQL or PostgreSQL. In that case, the project's ".nodus" file needs "jdbc.driver", "jdbc.user", "jdbc.password" and "jdbc.url" entries.

Example:

```
jdbc.driver=org.mariadb.jdbc.Driver
jdbc.user=nodus
jdbc.password=nodus
jdbc.url=jdbc:mysql://localhost/demo
```

In this example, Nodus will connect to a MySQL database (schema) called "demo", using "nodus" as a user name and password. The MariaDB (an open source MySQL fork) JDBC connector is used. Nodus is shipped with a few JDBC drivers, located in the "jdbcDrivers" directory. The content of this directory is added to the Java CLASSPATH. You can try other DBMS/JDBC solutions, but only those provided with Nodus were tested.

Other, non-mandatory, entries can be found in the .nodus file:

- "xxx.prettyName" : The name used in Nodus to describe the xxx layer. If not given, the file name of the layer will be used.
- "import.tables": a space separated list of .dbf tables that will be imported into the database, along with the network layers. This can be the case for origin-destination tables, for instance. Note that Nodus proposes some "SQL extensions" that can be used in the SQL console. It is, for instance, the case of the "importdbf tableName" command that imports a .dbf file.
- "openmap.layers" : the name of a ".openmap" file that contains a list of background layers. Please refer to the OpenMap documentation (http://openmap-java.org) for a description of the content of ".openmap" files.
- Since Nodus 7.3, colours can be associated with transport modes (used in the statistics pie charts). Use a "color.mode.x" ("x" being a mode ID) entry for each mode. The value can be a named colour ("red" for instance") or an ARGB hex string.

If the files of an OpenMap layer (a shapefile for instance) are stored in the same directory as the node and link layer files, one can just prepend the name of the files with "./", representing the current directory. Nodus will automatically replace "./" with the full path to these files. This makes it easy to move a project directory to another place without having to modify the content of the ".openmap" file.

1.2 The Origin-Destination Matrices

The transport demand is stored in origin-destination (OD) tables. An OD table must at least contain the following fields:

- GRP,N,2,0 : The group of commodities (for instance an NST-R chapter)
- ORG,N,10,0 : The ID of the origin node (often a centroid)
- DST,N,10,0 : The ID of the destination node (also often a centroid)
- QTY,N,10,0 : The quantity to transport from ORG to DST

ORG and DST must be present in one of the node layers. Moreover, loading and/or unloading operations must be allowed at these nodes.

1.3 The Cost Files

Computing (a set of) routes between an origin and a destination needs weights being associated with each link of the networks. Nodus doesn't assign directly to the real networks but generates "virtual networks" that are further used for assignments. Please refer to the provided documentation/help for further details on this concept.

Five types of cost functions must be defined: loading ("ld"), unloading ("ul"), transit ("tr"), transshipment ("tp") and moving ("mv"). They must also be defined for each mode-means combination. The cost functions are written in text files with the ".costs" extension.

The provided ".costs" files are rather well documented and can be used to understand the basics of the Nodus cost functions. Much more is possible, but goes beyond the scope of the demo project.

It is important to note that if a type of cost function is not defined for a given mode/means, a path cannot be computed for it. It is therefore important to define all the needed cost functions.

Example:

```
# Moving cost function for mode 2, means 1
unitCost = 1.12
mv.2,1 = LENGTH*unitCost
```

Note that, since Nodus 8.0, transit time functions are defined in a similar way, using the '@' separator:

```
# Transit time function for mode 2, means 1
mv@2,1 = LENGTH/SPEED
```

2 The Basics of the Interface

Once a project is loaded, the Nodus main window should show something similar to Figure 1.




Figure 1: Main window

The largest main zone contains the networks and the background layers. The list of all the layers can be found on the left panel. The green bubble lights can be used to display/hide a layer. The background layers are listed at the bottom. All the layers are named by their "pretty name". The icon between the bubble light and the name of the layer gives access to the parameters of the layer. Finally, the blue arrows can be used to reorder the layers.

Just under the menu bar, four icons give access to specific modes used to interact with the map. The first (the arrow) is used to select/edit nodes and links. Just double-click on an object to open a window that allows editing the data relative to the object (Figure 2).

The fields in blue can be directly edited by the user. Those in black can only be modified using the provided controls (choice of a rendering style or allowed operations, for instance) or when the network is edited (adding, removing a node or link, attaching a link between two other nodes…).

The second icon (the hand) is used to pan the whole network panel. The compass gives access to a tool that computes the distance between two points and the pen allows the editing of the map (add, move, delete nodes, add, move, delete and split links).

The upper-left corner of the main window displays an overview of the map. To its right, several controls are available to pan, zoom and navigate over the map. The scroll button of the mouse can also be used to zoom in/out.

Finally, just above the map, a combo-box displays the name of the current scenario.




Figure 2: Edit a node

The main window also has a menu bar. The most important entries are:

2.1 Project Menu

This menu gives access to the core functionalities of the software.

2.1.1 Preferences




Figure 3: Project settings

This is the place (Figure 3) to choose a scenario, give it a description, associate a cost functions file and an OD matrix. These elements can also be set/modified with the assignment settings.

By default, the database tables created by Nodus have a name starting with the project name, followed by a suffix (such as "_vnet" for virtual network tables, for instance). This can be changed here.

"Display boundaries" adds an embedded background layer that roughly represents the world's countries.

"Display highlighted area" displays a user-defined rectangle that limits the assignment to the network it contains. This is useful for large networks that are only partially used in a project. If the highlighted area is enabled, the generation of the virtual network will only take the nodes and link within the rectangle into account, which improves the performance (duration) of the assignment.
If the HSQLDB or H2 database is used, one can also choose to compact the database when closing the project. These DBMS's data files can become rather large because empty space is not (always) reclaimed by these two DBMS's for performance reasons. If this is checked, a "shutdown compact" is run on the database just before closing. See the documentation of these DBMS's for more information.

2.1.2 Edit Cost Files

Opens a text editor with the current cost file.

2.1.3 Edit Services

Used to define lines and services. This feature is discussed in section 3.14.

2.1.4 Modal Choice Estimation

The "Project|Modal choice estimation" menu (Figure 4) fits the parameters of the embedded multinomial logit, multinomial probit and proportional models from observed modal OD matrices. This is a separate step, performed before launching an assignment.




Figure 4: Modal choice estimation

Select the source cost functions file, map each network mode ID to its observed OD table, and choose a reference mode. Its intercept is fixed at zero for logit or probit; its cost factor is fixed at one for proportional choice.

Route costs can be computed with fast or exact multi-flow routing. The estimation uses the cheapest admissible cost per OD pair and mode. A maximum detour ratio of 0 removes the detour limit. Worker threads control the route-cost computation.

Click “Estimate” to fit the selected model separately for each commodity group. Nodus saves the fitted parameters in a database table named from the cost file (for example, MNL.costs creates MNL_params), writes a diagnostic report named MNL_params.html beside the cost file, and adds @paramTable=MNL_params to the file. The HTML file also contains a series of performance measurement indicators for the estimated parameters. If that table already exists, Nodus asks before replacing its contents. For assignment, select the updated cost file: Nodus selects and locks the matching embedded modal-choice method automatically. The observed modal OD tables are used only for estimation; they do not replace the OD matrix or scenario settings selected for assignment.

2.1.5 Assignment

Opens a window dedicated to several available assignment algorithms. Please refer to the help/documentation for more info about these algorithms. Figure 5 shows the different controls the user has over multi-flow assignments[2].




Figure 5: Multiflow assignment

2.1.5.1 General Controls

These controls are present in all assignment tabs.

The user can choose the scenario ID to associate with the assignment. If the word “scenario” has a green background, the ID is still free. An orange background means that a scenario with this ID already exists and that a new assignment will overwrite the existing tables.

The number of iterations represents the number of alternative routes that will be computed for each mode of transport. For the equilibrium assignments, this value represents the maximum number of iterations to perform towards the equilibrium solution.

If the OD matrix contains more than one group of commodities, Nodus can assign them simultaneously (in parallel). The maximum parallel threads can be set here. Nodus limits the

[2]Since Nodus 9.x, the « Save paths » checkbox has been removed as the path header tables are mandatory for the modal choice module.

proposed values to the number of CPU cores the computer it runs on has. Parallel assignments drastically reduce assignment duration.

Beside the project preferences, this is also a place where the description of the scenario, the used OD table and the cost functions file can be set. The assignment can also be limited to a subset of the OD matrix defined by an SQL select statement.

If a highlighted area is defined and enabled, the user can choose to limit the assignment to this area by checking the relevant box.

If “log lost paths” is checked, the list of origin-destination pairs between which no route could be computed will be displayed in the console. This is useful for debugging: in most cases, “lost paths” are found if there is somewhere a missing link between O and D or if not all the necessary cost functions were defined.

Nodus offers the possibility of saving the details of each computed path beside the general flows of the network. If “Save paths” and “Detailed paths” are checked, it will be possible to visualize the routes and flows computed for every OD pair. For large projects, this generates huge database tables. If only “Save paths” is checked, the list of individual links of each route is not saved, but only the basic information for each path (cost, length, …) is kept.

2.1.5.2 Specific Controls

These controls are specific for multi-flow assignments only.

Two shortest path algorithms are proposed. See the pros and cons of each in the help/documentation. In most cases, the “fast” method gives good results.

Three modal split methods are proposed:

- The proportional method spreads demand in inverse proportion to costs, optionally adjusted by calibrated multiplicative cost factors for each mode.
- The multinomial logit method uses modal intercepts and a common coefficient of the logarithm of cost, with logit choice probabilities.
- The multinomial probit method uses the same utility form as the multinomial logit, with independent normal errors to compute modal probabilities.

The user can also develop its own modal split methods that will appear in the list. The way to develop such methods goes beyond the scope of this document, although an example is provided in the “MLogit” subdirectory of this demo.

For models that include intermodal transport possibilities, the user can choose to retain intermodal solutions only if they are cheaper than any other solution.

If the assignment has more than one iteration, i.e., if more than one route must be computed for each mode, a “Cost Mark-Up” can be set. This is the value by which the cost of each link

along the last computed route must be multiplied before the next iteration. More can be found on this in the help/documentation.
Finally, the value set for “Max detour” is used to limit the set of retained routes to all those that are shorter to the shortest route (all modes included) multiplied by this value. For example, if this value is set to 2, only the routes shorter than twice the length of the shortest route will we retained in the set of valid alternative routes. If the value is set to 0, all the alternatives are kept, regardless of their length.

2.1.6 Display Results

This opens a window in which the user can choose to display the OD matrix (node) or the assignment (link) of a scenario. If the “detailed paths” were kept during the assignment, one can also choose to display the route(s) computed for a given OD pair and group of commodities. For this, the user has to manually replace the “?” signs (see Figure 6) present in the proposed SQL statement by the IDs of the origin and destination nodes and the group of commodities.




Figure 6: display results

Semi-dynamic assignments can also be displayed, but this is not discussed in this document.

2.1.7 Scenarios




Figure 7: Scenarios

From this window (Figure 7), it is possible to delete or rename (change the ID) of a scenario. This affects all the tables relative to the scenario. It is also possible to compare two scenarios.

In this case, a resulting scenario is created, and the assigned flows are compared, i.e., for each link, the flow assigned in “scenario 2” is subtracted from the flow assigned in “scenario 1”. The result can thus be positive or negative. When the resulting scenario is displayed via “Display results”, the negative flows are rendered with a “dimmed” colour.

2.1.8 SQL Console

The SQL console (Figure 8) lists all the tables of the project. The user can write SQL statements in the upper right zone. The result of the query is displayed in the bottom-right zone.




Figure 8: SQL console

The console is also able to handle SQL scripts, i.e., several SQL statements, each one being terminated by a semi-column.

Several Nodus-specific extensions to standard SQL are proposed:

- **CLEARSCENARIO num**: Deletes all the tables related to the given scenario id.
- **CLRSCR** : Clears the output console.
- **DISABLEECHO** : If used, the SQL commands will not be echoed in the result area.
- **DISABLEHEADERS** : If used, the headers of SQL outputs will not be displayed.
- **DISPLAYGRID** : Forces the next SQL output to be displayed in grid format.
- **DISPLAYTEXT** : Forces the next SQL output to be displayed in text format.
- **ENABLEECHO** : If used, the SQL commands will be echoed in the result area (default).
- **ENABLEHEADERS** : If used, the headers of SQL outputs will be displayed (default).
- **EXPORTCSV tableName** : Exports a table in CSV format.
- **EXPORTCSVH tableName** : Exports a table in CSV format, the first line containing the field names (header line).

- **EXPORTDBF tableName** : Exports a table in DBF format.
- **EXPORTXLS tableName** : Exports a table in XLS format.
- **EXPORTXLSX tableName** : Exports a table in XLSX format.
- **EXTRACTSHP FROM shapefile1 TO shapefile2 WHERE sqlCondition**: Creates a new shapefile from the output of the SQL where statement performed on a shapefile.
- **IMPORTCSV tableName** : Imports a CSV file. The related empty table must exist in the database.
- **IMPORTCSVH tableName** : Imports a CSV file, ignoring the first (header) line. The related empty table must exist in the database.
- **IMPORTDBF tableName** : Imports a DBF file.
- **IMPORTXLS tableName** : Imports an XLS file. The related empty table must exist in the database unless the first row of the sheet contains the format of each column, following the DBF standard.
- **IMPORTXLSX tableName** : Imports an XLSX file. The related empty table must exist in the database unless the first row of the sheet contains the format of each column, following the DBF standard.
- **STOP** : Convenient command that stops a script. Useful for debugging.

These additional keywords are recognized by syntax highlighting.

It is also possible to use user defined variables, regardless of the DBMS that is used. Such a variable must use the @@ prefix. Example:

```
@@od := od_iww;
select count(*) from @@od;
select sum(qty) as total from @@od;
```

If a ".dbf" file of a shapefile is modified by an SQL statement, it must be exported ("exportdbf") to make the changes applicable to the loaded map. It must be clear that the SQL statements affect the table in the database, not in the ".dbf" files of the project. The changes must thus be saved (exported) to keep the content of the shapefiles synchronized with the content of the database.

The user must also be aware that direct manipulation of tables related to shapefiles can be dangerous and can potentially break the consistency of the networks. For instance, if the ID of a node is modified, the links that refer to this node must also be updated. If it is not the case, the integrity test that Nodus performs when a project is open will fail.

2.2 Control Menu

Offers several possibilities to show/hide some components and change the background colour.

2.3 Projection Menu

By default, the Mercator projection is used, but other projections are available.

2.4 Tools Menu

2.4.1 Look & Feel

By default, Nodus uses the native Look&Feel of the system it runs on. Another can be chosen.

2.4.2 Language

The interface is available in English and French.

2.4.3 Console

This opens a “Console” window that intercepts all the warning and error messages that Nodus writes to the standard output. Useful for debugging.

2.4.4 Groovy Scripts

This opens an editor for script editing. Scripts must be written in the Groovy language (http://groovy-lang.org), which is close to Java. Scripts can use the Nodus API in order to add new or project-specific functionalities to Nodus. According to what is selected in the main preferences, a Nodus editor is used or the native Groovy console is launched. Both allow running scripts.

2.4.5 Resource Monitor

Displays the memory and CPU usage of Nodus. For very large projects, more “heap” memory can be assigned to the software. Therefore, the “-Xmx” parameter found in “jvmargs.sh” or “jvmargs.bat” (created in the install directory after a first run of Nodus) can be set to a higher value. Please refer to the Java JVM documentation for further details.

It is highly recommended to use a 64-bit JVM, as the 32-bit version is limited to a heap of about 1.5 Go, which can be a limit for large projects.

3 The “demo” Project

The demo project is intended to understand the basics of Nodus. It is based on real, but partial, data fetched from the European Etisplus (http://www.etisplus.eu) project. The Belgian networks and data for the OD matrices are fetched from the project, and the values of the cost functions are a simplified version of functions that were used in the framework of ECCONET (https://www.ecconet.eu), another European research project. The OD matrices are defined at the NUTS2 level, which is much too coarse to set up a useable network model for Belgium. However, all these inputs make it possible to illustrate some basics of Nodus.

3.1 Load the Project

The project is configured in the “demo.nodus” file. It has 5 node layers and 6 link layers and it imports three .dbf tables (origin destination matrices for road, inland waterways (IWW) and rail transport). The matrices contain data for two groups of commodities). OpenMap background layers are configured in the “demo.openmap” file.

Figure 9 illustrates the project when it is loaded for the first time. During this first loading, a HSQLDB database is created in the project’s directory and all the relevant ".dbf » files are imported.




Figure 9: The "demo" project when first loaded

Before going further, it is useful to briefly describe each node and link layer of the project.

3.1.1 Node layers

- Centroids: these nodes represent the center of gravity of a region. They are the places where freight can be loaded and unloaded, and they are connected to the modal networks by connectors. Figure 10 shows the settings for a centroid: loading and unloading operations are allowed and transit operations are not permitted (to avoid traffic through centroids having more than one connector to the same modal network).
- Terminals: these nodes will be used in intermodal models. They are also connected to road and rail networks by connectors, and only transshipment operations are allowed. No transit is allowed.
- Road, IWW and Rail points: these are just nodes corresponding to the end points of all the links of the network. No operations beside simple transit are allowed.




Figure 10: Data and settings for a centroid

3.1.2 Link layers

- Road, IWW, and Rail networks: represent the physical topology of the networks for these three modes.
- Road, IWW and Rail connectors: these links don't correspond to real network chunks, and are created to connect the centroids and the terminals to the modal networks.

The networks for this demo project are located in Belgium. In Figure 11, a zoom on the networks is illustrated, using a Mercator projection. The layers are also reordered: the "labels" layer comes first (but is not yet configured), followed by the centroids, the terminals and the three modal networks. The connectors and the point layers come afterwards and are not enabled (displayed). The background layer displays the Belgian NUTS 2 regions. In Figure 12, the NUTS 2 background layer is replaced by an OpenStreetMap image fetched from a web server. Finally, Figure 13 hides the railways and inland waterways (IWW) networks and displays the names of the centroids. In order to display labels, the icon just on the left of the "Labels"

layer must be clicked, and “Query database for labels” for the “Centroids” layer must be chosen. Just select the field that must be displayed as a label.

Before creating models, it is a good idea to test the available options in the GUI. It is also interesting to have a look at the SQL Console (Figure 14), where the list of imported tables is shown: all the “.dbf” tables of the layers are present, along with the three OD matrices.




Figure 11: Zoom over Belgium with reordered layers




Figure 12: Display OpenStreetMap tiles layer




Figure 13: Display the names of the centroid




Figure 14: initial tables

3.2 Scenario 1: Road assignment

This first scenario shows how to run a simple assignment for a single mode. In Figure 15, the different settings for this assignment are illustrated:

- Set scenario ID to 1.

- Use of a fast multi-flow assignment. Note that, for this scenario, the result will be equivalent to a simple all-or-nothing assignment because only one route for a single mode is computed for each OD pair.
- The “road.costs” cost functions are used. This is a very simple cost function set: (un)loading and transit costs are set to 0 and the fastest routes are computed (moving costs = LENGTH/SPEED). Only one means (one type of vehicle) is defined.
- The OD matrix for road transport is used
- The details of each path (route) are stored in the database
- A short description is given to the scenario (“Road only”)




Figure 15: Road assignment

The assignment creates three additional tables in the database:

- demo_vnet1: The virtual network.
- demo_path1_header: The details of the computed paths (without the list of used links).
- demo_path1_detail: All the used links for each path.

The second table is generated because “Save paths” is checked, the last one because “Detailed paths” is also checked.

Figure 16 shows the resulting assignment. To obtain this, go to “Project|Display results” and select “Assigned quantities” in the list of available possibilities for links. Keep the proposed SQL query unchanged.




Figure 16: Assignment of scenario 1

Because the details of all the computed paths are saved in the database, it is possible to visualize the route computed for a given OD pair and group of commodities. Therefore, go to "Project | Display results" and select "Detailed path" among the proposed possibilities for links.

The IDs of the origin and destination nodes can be obtained by a double-click on the centroids that correspond to O and D. For instance, "Prov. Antwerpen" and "Prov. Hainaut": their "num" field contains respectively 1020201 and 1020302. In the proposed SQL query, replace the "??" signs: 0 for GRP, and the just retrieved IDs for ORG and DST, as in Figure 17. The result can be seen in Figure 18.




Figure 17: Display detailed path settings

3.3 Scenario 2: Multi-Route road assignment

Using the same basic data (cost functions and OD matrix), it is possible to obtain an assignment during which several routes are computed between every OD pair for the same transportation mode. In Figure 19, three iterations (alternative routes) are performed. Between each iteration, a cost markup of 50% is applied to each already used link. Please refer to the

help/documentation for more information on the way multi-flow assignments are implemented in Nodus. The resulting flows can be observed in Figure 20, in which the traffic is much more spread over the network than in Figure 16.




Figure 18: Route between "Antwerpen" and "Hainaut"




Figure 19: Multi-flow for road transport




Figure 20: Multi-flow assignment for road transport

3.4 Scenario 3: Inland waterways, with two types of barges

In this scenario, only one mode (IWW) is assigned again, but two means (small and large barges) are defined. The split between the two means is performed by means of a "proportional" model. Beside a change in the modal-split method and the used cost functions, the settings (Figure 21) are similar to those used for scenario 2.




Figure 21: Settings for the IWW assignment

Note that the IWW network has a “CLASS” field which corresponds to the gauge of the rivers/canals.

Knowing that the “MEANS” field specifies the “largest” vehicle that can be used on a link, the “MEANS” field is set to the value of “CLASS” divided 10. Thus, small barges (means = 2) can use all the canals/rivers of class 20+, and large barges (means= 4) can only use canals with class 40+.




Figure 22: Assignment on the IWW network

From the SQL Console, it is also possible to obtain some statistics (Figure 23). For instance, the loaded tons per mode-means can be displayed (Figure 24). One could have expected the modal share for small barges to be exactly 1/3, because a “proportional” modal-split method was used and that the use of small barges costs double than large barges per transported ton. The share of small barges is, however, slightly higher. This is because, on some routes, large barges cannot be used because some rivers/canals have a class smaller than 40.




Figure 23: Available statistics




Figure 24: Statistics in a pie chart

3.5 Scenario 4: Rail transport

In this scenario, somewhat more complex cost functions are used, with figures taken from a real project. This illustrates how user defined variables can be used and how different values can be defined for each group of commodities.




Figure 25: Setting for the rail assignment

The result is shown in Figure 27, which also displays the used origin-destination matrix. Therefore, once the flows are displayed, go back to “Project|Display results”, and select “O-D matrix” from the choices provided when “Nodes” is checked (Figure 26), leaving the SQL query unchanged.




Figure 26: Display an O-D matrix




Figure 27: Rail assignment and O-D matrix

3.6 Scenario 5: Multimodal assignment

It is now time to go for multimodal assignments. In such an assignment, the demand between each origin and destination is spread over all the available modes, using a modal-split method.

The first thing to do is to merge the three modal matrixes into a single multimodal matrix. This can be achieved by running the “MergeODs.sql” script from within the SQL Console (Figure 28). This creates the “OD” table that can be used in multimodal assignments.




Figure 28: The "MergeODs.sql" script in the SQL Console

The "uncalibrated.costs" file gives an example of how to define cost functions for several transport modes. It uses cost values grabbed from the same project as the one used for scenario 4 (railways only). Figure 29 shows the settings used for this assignment, which are very similar to what was used in the previous scenarios: the most important differences are in the cost functions and the OD matrix. The resulting assignment (Figure 30) looks, however, very strange. Indeed, it seems that most of the freight is transported by barges. This is confirmed by the statistics presented in Figure 31, while the figures of Table 1 can be retrieved from the modal OD matrices. The model must thus be calibrated.



Figure 29: Settings for a multimodal assignment




Figure 30: Uncalibrated multimodal assignment

Mode		Tons per group		Share per group	
		0	1	0	1
1	Road	7438402	17204671	90,1%	92,4%
2	IWW	728281	730319	8,8%	3,9%
3	Rail	91148	685022	1,1%	3,7%

Table 1: Reference modal shares




Figure 31: Modal shares

3.7 Scenario 6: Simple estimation of a multimodal assignment

Model estimation involves estimating the values of various constants and parameters in the model structure. Nodus embeds three simple modal choice models, among which the well-known multinomial logit. The embedded models are all based on a univariate utility function.

$$V_i = \alpha_i + \beta . \ln\left(C_i\right)$$

where V_i is the utility of mode i, C_i the total transportation cost for mode i, α_i and β the parameters to estimate. The total cost of transport being a monetary value, its associated estimated parameter β is not mode dependent. These parameters can be estimated following the settings illustrated in Figure 32.




Figure 32: Estimating the MNL model

After estimation, Nodus adds the following pointer to MNL.costs without changing its transport cost expressions:

```
@paramTable=MNL_params
```

The pointer identifies the database table containing the fitted coefficients. The sibling MNL_params.txt file contains the estimation report and parameter values. In Assignment, select MNL.costs; Nodus reads MNL_params and automatically selects and locks Multinomial logit. The assignment OD matrix and scenario settings remain independent of the observed tables used for estimation.

The values proposed in “MNL.costs” result in market shares of respectively 90.08%, 8.82% and 1.10% for group 0 and 92.40%, 3.92% and 3.68% for group 1, which is close to the reference figures found in Table 1. The resulting assignment is shown in Figure 33: road transport is clearly dominant.




Figure 33: Multimodal assignment - simple calibration

3.8 Validation of a model

While calibration involves estimating the values of various constants and parameters in the model structure, validation is the application of the estimated models and the comparison of the results against observed data. At the aggregated level, one can, for instance, compare the global observed and estimated market shares. However, market shares of two models can be close or even identical to the observation, but a closer look at disaggregated data can show large differences. At the OD level, for instance, one can compute the WAPE (Weighted Absolute Percentage Error) between the quantities assigned to each mode and the observations. A series of indicators can be computed in the “Model performance” window, accessible via the “Performance” button of the “Display results” window (Figure 34).

In the case of scenario 6, the WAPE values show that the model doesn’t perform very well, although the estimated modal market shares are very close to the observed ones.




Figure 34: Modal-choice mode performance indicators

```
WAPE by mode for demo_path6_header:
  Mode 1 (od_road): 10.49%
  Mode 2 (od_iww): 112.80%
  Mode 3 (od_rail): 170.65%
  All specified modes: 20.67%
```

3.9 Calibration of the model using “pivots”

The estimation of a model using a logit or probit model corresponds to trying to understand the behavioral dimension of a modal choice decision, based on one or more explanatory variables. Such a model is always imperfect because it remains a simplification of the reality. Therefore, it is sometimes useful to add a calibration layer above the behavioral model. Therefore, Nodus offers to estimate pivots, which are optional adjustments added to a modal choice model after its cost-related parameters have been estimated. A separate pivot is estimated for each transport mode, origin–destination pair, and commodity group to bring the model’s predicted modal flows closer to the observed flows. The reference mode’s pivot is fixed at zero, and the other pivots are kept within a user-chosen limit (±8 by default). During later assignments, the pivots remain fixed while the model responds to changes in transport costs. Once the parameters estimated with the optional pivots, the global estimated market shares for scenario 6 remain unchanged, but the WAPE values drastically improve:

```
WAPE by mode for demo_path1_header:
  Mode 1 (od_road): 0.00%
  Mode 2 (od_iww): 0.01%
  Mode 3 (od_rail): 0.02%
  All specified modes: 0.00%
```

3.10 Scenario 7: User-defined modal-choice plugin's

More sophisticated methods can be used, based on more complex multivariate utility functions, for instance. Therefore, "user defined" modal choice plugins can be developed. It goes beyond the scope of this document to explain how this can be done, but a simple plugin, based on the same utility function used in the embedded estimation module is proposed in the "Demo" project.

In this case, the "mlogit" R package was used, and the estimated values for a conditional logit model can be found in "MLogit-R.costs". These values are used by a user-defined modal-split method that uses the Nodus API. This method is embedded in the provided "MLogit.jar" file, which is a Nodus plugin, loaded with the project. This method appears along with the embedded "Multinomial logit", "Multinomial probit" and "Proportional" methods in the list of available methods (Figure 35). The R script and the Java code corresponding to the plugin are provided in the "MLogit" subdirectory, along with an explanation on how to obtain the estimators.




Figure 35: Use of a user-defined modal split method

The logit model can also be solved using the Biogeme toolbox. This is illustrated by the "MLogit.py" Python script.

Please refer to the demo/MLogit/README.md file for more information about the parameter estimation procedure.




Figure 36: Assignment with a more complex modal choice model

3.11 Scenario 8: Comparison Between Scenarios

The difference between the assigned flows of two scenarios can also be visualized using the "Project | Scenarios" tool. The settings proposed in Figure 37 will generate a new scenario 8 that compares the assignments of scenarios 6 and 7. Figure 38 illustrates the comparison between scenario 6 and another one (20), in which the embedded multinomial Probit modal choice model was used. In all the previous maps, red was used for road transport, blue for IWW and dashed gray lines for railway transport. In this figure, some links are also "dimmed", corresponding to links for which the flow in scenario 20 is higher than in scenario 6. In such a case, the resulting flow is negative, and this is visualized by a "dimmed" colour. This is very clear in the zoomed view provided by Figure 39. The figures displayed along the networks represent the difference between the flows of both scenarios. These figures can be displayed if the "Labels" layer is enabled.




Figure 37: The "scenarios" tool




Figure 38: Visualization of the comparison between two scenarios




Figure 39: Zoom with displayed flows

3.12 Scenario 9: Intermodal model

Up to now, intermodal, i.e., a route along which at least two different transportation modes are used, was not modeled. Intermodal transport needs some transshipment points (terminals) being located in the network. Transshipment cost functions must also be defined. These cost functions must exist for each possible mode/means combination. In this demo, rail-road intermodal transport will be illustrated. Transshipment costs must be defined for the road to rail and the rail to road operations. If one considers that a transshipment costs 1.5€ per ton (this is not a real value), the cost functions can be defined as:

```
# From road to rail
tp.1,1-3,1 = 1.5
# From rail to road
tp.1,3-1,1 = 1.5
```

The assignment settings are as illustrated in Figure 40. In the resulting tables, one can identify intermodal paths with the following SQL query:

```
select grp,org,dst,nbtrans from demo_path9_header where nbtrans > 0
```

The route between centroids 1020100 and 1020303 is an example, illustrated by Figure 41, in which the Brussels container terminal is used.




Figure 40: Settings for the intermodal assignment




Figure 41: Intermodal Route using the Brussels terminal

Note that, in this scenario, all the intermodal routes use only one terminal (the above presented SQL query returns only record with "nbtrans" = 1). Modeling more realistic intermodal transport (use a truck from a centroid to a terminal, then a train to another terminal, and finally a truck again from the second terminal to the final centroid) is somewhat more complex to model.

3.13 Scenario 10: More Complex Intermodal Model

A good understanding of the "Virtual Networks" method is needed to correctly model intermodal transport. An elegant solution is to make use of additional "means":

- 3 "means" can be defined for road transport:
  - Means 1: regular trucking for an OD relation (already defined)
  - Means 2: pre-haulage to a terminal
  - Means 3: post-haulage from a terminal to the final destination
- 2 "means" can be defined for rail transport:
  - Means 1: regular trains for an OD relation (already defined)
  - Means 2: trains used for intermodal transport between two terminals

All the cost functions must not be defined for the different means:

- For regular truck and rail transport, loading, transit, moving and unloading cost functions must exist, similar to what was used in all the previous scenarios.
- Only loading, transit and moving costs must be defined for pre-haulage by truck.
- Only transit, moving and unloading costs must be defined for post-haulage by truck.
- Only transit and moving costs must be defined for intermodal trains
- The transshipment costs must be defined from pre-haulage trucks to intermodal trains and from intermodal trains to post-haulage trucks.

Once all these costs are defined, the assignment algorithm from O to D can identify the following alternatives:

- A truck only route, using mode 1, means 1 from O to D
- A rail only route, using mode 3, means 1 from O to D
- An intermodal route starting with mode 1, means 2 (the only other loading possibility), followed by a transshipment to mode 3, means 2 at a first terminal, a transshipment to mode 1, means 3 at the second terminal and a final unloading at D.

As no loading and unloading cost functions are defined for intermodal trains (mode 3, means 2), they cannot be chosen at O or D. They can only be loaded and unloaded at transshipment facilities. Two additional means are needed for trucking because, otherwise, the means could be used for loading and unloading, making no difference with regular trucking.

Once all these cost functions are defined (see “intermodal2.costs”), one must also be sure that all these additional means will exist in the virtual network. Indeed, the road and rail networks that were used up to now have only one means. The following SQL statements can be run from the SQL console:

```
# Set the means on the main networks and the connectors
update road_polylines set means = 3;
update road_con set means = 3;
update rail_polylines set means = 2;
update rail_con set means = 2;
# Export the tables in the ESRI shapefiles
exportdbf road_polylines;
exportdbf road_con;
exportdbf rail_polylines;
exportdbf rail_con;
```




Figure 42: Intermodal Route with two terminals

The assignment settings are similar to those of the previous scenario. The only difference is the cost function file that is used. In the resulting scenario, the route from 1020100 to 1020303 makes use of two terminals, as illustrated in Figure 42.

3.14 Lines and Services Basics

The Nodus “doc/services” directory contains an explanation about how to create and edit service lines. A service line is a predefined path that must be followed by a vehicle of a given mode, with a frequency and optional stops or switches between services. This is typically the case for railway transport, which doesn’t work on a “free flow” basis.

The “demo” project contains a small sample of two services that can be imported using the “ImportLines.sql” script from within the SQL console. Once imported, the “Project|Edit services” menu item, also accessible via the F3 key, lists the available services. Selecting one highlights it on the map, as illustrated by Figure 43.




Figure 43: Example of a service line

An assignment that activates service lines must use adapted cost function files that implement costs and times related to stop and line switch operations, as in the provided “services.costs” file. More specifically, entries similar to these must appear:

```
# Mode and means for which services are defined
SERVICELINES.3,-1 = true

# Value of time (EUR per ton per hour)
VALUE_OF_TIME = 0.05

# Transfer cost (EUR per ton per hour)
TRANSFER_COST = 0.2
```

```
# Dwell time at stop, 10 min = 600 seconds
DWELL_TIME=600

# Cost of a stop
stp.3,1 = VALUE_OF_TIME / (3600/DWELL_TIME)

# Cost of a switch to another service, with an average waiting time
sw.3,1-3,1 = TRANSFER_COST + VALUE_OF_TIME * (52 * 7 * 24) / (2 *
FREQUENCY)

# Dwell time at a stop: 10 minutes
stp@3,1 = DWELL_TIME

# Average waiting duration in seconds
sw@3,1-3,1 = (52 * 7 * 24 * 3600) / (2 * FREQUENCY)
```

3.14.1 Scenario 11: Example of a service stop

In order to visualize a service stop, an assignment of the OD matrix between nodes 1020201 (Antwerp) and 1020304 (Luxemburg) can be performed (Figure 44).




Figure 44: Service stop assignement

The resulting assignment (with only the rail layer enabled) is represented in Figure 45, with a stop at Limburg.

3.14.2 Scenario 12: Example of a service switch

Similarly, a service switch is needed if one goes from node 1020203 (Bruges) to node 1020304 (Luxemburg), because there is no service line defined between these two nodes but the relation can be organized with a service switch at the Limburg node), as illustrated by Figure 46.




Figure 45: Stop at Limburg




Figure 46: Service switch at Limburg

4 Conclusion

This document is not a complete user manual of Nodus. The software offers much more, such as semi-dynamic assignments, the possibility to model lines and services (only briefly introduced in this document) or the development of scripts written in the Groovy language and plugins. It presents, however, a series of 12 scenarios showing the basics of multi- and intermodal transport modeling.

5 Appendix – More on cost Functions

Nodus offers many more possibilities with cost functions. This appendix gives more details about the available options.

5.1 Modes, means, groups, classes and Scenarios

The core (and mandatory) cost functions are loading (“ld”), unloading (“ul”), transit (“tr”) and moving (“mv”) costs. For intermodal transport, transshipment costs (“tp”) must also be defined. The basic usage of these functions is described in the different scenarios illustrated in the demo.

The mandatory cost functions must be defined for each mode-means combination. The user has to decide which numerical ID he assigns to each mode (from 0 to 99). The same is true for the means (type of vehicle) available for each mode. For example, if only one mode is defined (road) and only one means (general truck), the cost functions file must at least define values for these functions:

```
ld.1,1 =
ul.1,1 =
tr.1,1 =
mv.1,1 =
```

A transshipment cost function, if used, must specify the “from” mode-means and the “to” mode-means:

```
tp.1,1-2,1 =
```

Variables (and cost functions) can be defined for several “groups” (categories of commodities, for instance). The group must be defined in the OD matrix table in the “grp” field. For instance, the user-defined variable “truckLoadingCost” can be defined for groups 1 and 2 with different values:

```
truckLoadingCost = 0
truckLoadingCost.1 = 10
truckLoadingCost.2 = 12
```

~~Note that, if group-specific values are defined, the “generic” variable (i.e., without the appended group ID must also be defined (even with a value = 0).~~ **This is not anymore needed since Nodus 8.0.**

If the following cost function is defined

```
ld.1,1 =  truckLoadingCost
```

The value of ld.1,1 will be equal to 10 when “group” 1 is assigned, and 12 when “group” 2 is assigned.

In addition to the mandatory “grp” field in the OD matrix, an optional “class” field can also be defined in the OD tables. This can be useful if one needs to use different cost values for different distance classes (short, medium and long hauls, for instance). Specific class-related values can then be defined for variables or functions using the following syntax:

```
truckLoadingCost.1 = 10       # Group specific value
truckLoadingCost-1 = 12       # Class specific value
truckLoadingCost.1-1 = 13     # Group and class-specific value
```

Finally, one can also define scenario specific variables and cost functions instead of having a separate cost function file for each scenario. The scenario ID must be used as a prefix:

```
1.truckLoadingCost.1 = 10     # Scenario and group-specific value
1.truckLoadingCost-1 = 12     # Scenario and class-specific value
1.truckLoadingCost.1-1 = 13   # Scenario, group and class-specific value
```

Since Nodus 8.0, transit time (duration) functions can also be defined in the cost function file. These functions follow exactly the same structure as the regular cost functions. A transit time function uses a ‘@’ instead of a dot after the type of movement. Example: “mv.2.1=” is a moving cost function, while “mv@2.1” is a moving transit time function. The durations are stored in the “path_header” tables when an assignment is performed with “save paths” enabled (saving the detailed paths is not needed). The stored values can further be used in modal choice model estimations.

Note that, unlike what is needed for the cost function, the duration function must not be defined for all the types of movements.

5.2 Embedded variables

Nodus also has some “reserved words” for some variables (variables are case sensitive). The most important are:

- AVGLOAD : The average payload for a type of vehicle. It is used to compute the number of vehicles needed to transport a given quantity. Can be defined for each mode-means, group and scenario. “`AVGLOAG.1,1.0 = 20`” means that the average load of a vehicle of mode 1, means 1 is 20 tons when it transports goods of group 0.
- PCU : The Personal Cars Units ratio. If a truck represents 1.5 PCU, that means that it takes the place of 1.5 cars. This is used in equilibrium assignments when the capacity of the links is expressed (as usual) in PCU’s/hour. Can be defined for each mode-means, group and scenario. “`PCU.1,1 = 1.5`” means that a vehicle of mode 1, means 1 represents 1.5 cars on a road.
- *LD_DURATION, UL_DURATION, TP_DURATION : Loading, unloading and transhipment durations, expressed in hours. Can be defined for each mode-means combination, group and scenario. “LD_DURATION.1,2.0 = 4” means that one needs 4 hours to load commodities of group 0 on a vehicle of mode 1, means 2. These values, converted in*

~~*seconds, are added to the travel duration field stored in the path header tables. In this way, the duration can represent the total transit time (and not only the travel time).*~~
This has been deprecated since Nodus 8.0, as transit time functions are now defined as following the same structure as cost functions.

- MAX_DETOUR_REF_MODE **:** By default, when limiting the maximum length of routes to be considered, this is done relative to the shortest path, regardless of the mode. If this variable is specified, the maximum length will be calculated relative to the shortest path for that mode (since version 8.3, build 20260512).

Some variables can be directly used in the cost functions:

- LENGTH : the length of a link (in km). Can be used in "mv" cost functions.
- VOLUME (or FLOW for Nodus versions prior to 8.0) : This variable is available for "mv" costs during equilibrium assignments. It represents the flow assigned to the link. If the AVGLOAD and PCU variables are correctly defined, the flow is expressed in Personal Car Units. An example of cost functions suitable for equilibrium assignments is given in a next section.

The numerical fields of the ".dbf" files can also be used as variables. For example, the mandatory "SPEED" or "CAPACITY" fields that must be present in the "link" layers can be used as variables.

5.3 Cost Functions for Equilibrium Assignments

Equilibrium assignments take capacity constraints into account and spread the traffic over several routes, trying to minimize the total cost of transport. Several algorithms can be found in the literature, among which the most cited are the "incremental" method, the "Method of Successive Averages" (MSA) or the "Frank-Wolfe" algorithm. They are all implemented in Nodus.

Note, however, that the equilibrium assignment algorithms were developed in the context of urban areas (and primarily for passenger transport). Indeed, these algorithms work well if one has to examine the traffic at moments where there is a lack of capacity. This is typically the case during peak hours. To be efficient, one needs OD matrixes containing transport during the peak hours.

The same algorithms are much less useful if they are applied to large areas and/or when the demand (OD matrix) contains yearly figures, which is often the case for strategic models.

A more in-depth discussion of these algorithms can be found in Jourquin B. and Limbourg S., *Equilibrium Traffic Assignment on Large Virtual Networks, Implementation issues and limits for Multi-Modal Freight Transport*, European Journal of Transport and Infrastructure Research, Vol 6, n°3, pp. 205-228, 2006 (available in the Nodus help system).

However, here is an example cost function file that can be used with an equilibrium algorithm (MSA is the most efficient), in which the moving cost function is based on the well-known Bureau of Public Roads speed-flow relation:

```
# Example of a MSA equilibrium assignment
# Using the Bureau of Public Roads speed flow relation

# T : travel time
# T0 : free flow travel time
# alpha & beta : calibration factors
# X : volume
# C : capacity
#
# T = T0 * (1 + beta * (X/C)^alpha)

# Calibration factors
alpha = 4
beta = 1

# The VOLUME variable in Nodus can be expressed in vehicles if
# The AVGLOAD (average load) variable is defined.

# Average load per truck
AVGLOAD.1,1 = 20

# Nodus also can handle the capacity usage of a vehicle
# with the PCU (Passenger Car Units) variable.
# One truck = 1.5 PCU
PCU.1,1 = 1.5

# Load.Mode,Means
ld.1,1 = 0

# Unload.Mode,Means
ul.1,1 = 0

# Transit.Mode,Means
tr.1,1 = 0

# Move.Mode,Means (cost function that depends on the volume)
mv.1,1 = (LENGTH/SPEED) * (1 + beta *(VOLUME/CAPACITY)^alpha)
```

To run an assignment, chose the “Equilibrium” tab in the “assignment” dialog, the select one of the algorithms (MSA for instance). You also must select the maximum number of iterations to perform before stopping the process. Nodus will stop before reaching this maximum if the equilibrium solution is found before.

Since Nodus 8.0, two well-known predefined volume-delay functions are recognized: Bureau of Public Roads (BPR) and the conical function proposed by Spiess (CONICAL). They can be written as:

- BPR(VOLUME, CAPACITY, alpha, beta)
- CONICAL(VOLUME, CAPACITY, alpha)

The last lines of the previous example can thus be written as:

```
# Move.Mode,Means (cost function that depends on the volume)
mv.1,1 = (LENGTH/SPEED) * BPR(VOLUME, CAPACITY, alpha, beta)
```

The “equilibrium.costs” and “od_equilibrium.dbf” (OD matrix) are provided in the “demo” directory for testing purposes.

5.4 Other capacity constraints

Other forms of capacity constraints that are not immediately related to congestion but are linked to the characteristics of the infrastructure are often encountered and must be properly handled in transport models. It is, for instance, typically the case of the locks that can be found on inland waterway segments. There are several ways to handle this.

If the segments of your network don’t identify each lock as a separate node, you can add a field (“NBLOCKS” for instance) to the link layers “.dbf” files that contain the number of locks in the segment. You can then edit the segments with locks and update the number of locks it contains. A simple cost function file could then be something like this:

```
# Average time lost per lock (in seconds)
AvgLockTime = 1800

# Load.Mode,Means
ld.2,1 = 0

# Unload.Mode,Means
ul.2,1 = 0

# Transit.Mode,Means
tr.2,1 = 0

# Move.Mode,Means
mv.2,1 = SECONDS(LENGTH, SPEED) + NBLOCKS * AvgLockTime
```

Since Nodus 8.0, the “HOURS”, “MINUTES” and “SECONDS” functions are defined, which compute the travel time along a network link with a given LENGTH and SPEED.

This can obviously be refined. For instance:

- Adding a second field in the “.dbf” file with the average time lost per lock in the segment (instead of a global value).
- Replacing the “NBLOCKS” field with another one, representing the total average time lost in the segment.
- …

If each lock is represented by a node, one could, for instance, add a “LOCKTIME” field to the node layers, and use the content of this field in the transit cost functions (instead of the moving cost function as in the previous example):

```
# Load.Mode,Means
ld.2,1 = 0

# Unload.Mode,Means
ul.2,1 = 0

# Transit.Mode,Means
tr.2,1 = LOCKTIME

# Move.Mode,Means
mv.2,1 = SECONDS(LENGTH,SPEED)
```