



# **WEB APLIKACIJA ZA SPORTSKI CENTAR**

Završni rad

Mentor:

Dr Nenad Kojić, dipl. inž.

Student:

Jovan Ranković 145/14

Beograd, 2019.

VISOKA ŠKOLA STRUKOVNIH STUDIJA ZA INFORMACIONE I KOMUNIKACIONE  
TEHNOLOGIJE

Smer: *Internet tehnologije*

Modul: *Web programiranje*

Predmet: *Web programiranje PHP 2*

Tema: *Web aplikacija za sportski centar*

Ocena: \_\_\_\_ (\_\_\_\_)

Članovi komisije:

1. \_\_\_\_\_

2. \_\_\_\_\_

3. \_\_\_\_\_

# Sadržaj

<b>1. Uvod.....</b>	<b>8</b>
<b>2. Radno okruženje .....</b>	<b>9</b>
<b>3. Organizacija.....</b>	<b>10</b>
<b>3.1. Blok šema stranica .....</b>	<b>10</b>
<b>3.2. Stranice .....</b>	<b>11</b>
3.2.1. Home .....	11
3.2.2. Blog .....	13
3.2.3. Trainings .....	14
3.2.4. Profile .....	15
3.2.5. Reservations (form) .....	16
3.2.6. Search .....	17
3.2.7. Reservations (table).....	18
3.2.8. Payments .....	19
3.2.9. Arrivals .....	20
3.2.10. Admin CRUD .....	21
<b>4. Kod .....</b>	<b>22</b>
<b>4.1. Models .....</b>	<b>22</b>
4.1.1. Arrival.php .....	22
4.1.2. Comment.php.....	22
4.1.3. Menu.php .....	23
4.1.4. Payment.php .....	23
4.1.5. Post.php.....	24
4.1.6. Price.php.....	24
4.1.7. Reservation.php.....	24
4.1.8. Role.php.....	25
4.1.9. Service.php .....	25
4.1.10. Slider.php.....	25
4.1.11. Social.php .....	26
4.1.12. Trainer.php .....	26
4.1.13. Training.php.....	26
4.1.14. User.php .....	26
<b>4.2. Controllers.....</b>	<b>27</b>
4.2.1. API.....	27
4.2.1.1. ArrivalController.php .....	27
4.2.1.2. PaymentController.php .....	29
4.2.1.3. PriceController.php.....	31
4.2.1.4. ReservationController.php.....	32
4.2.1.5. TrainerController.php .....	33
4.2.1.6. TrainingController.php.....	34
4.2.1.7. UserController.php .....	34
4.2.2. Core .....	36
4.2.2.1. BackendController.php .....	36
4.2.2.2. FrontendController.php.....	36

4.2.3. MyAuth .....	37
4.2.3.1. LoginController.php .....	37
4.2.3.2. RegisterController.php .....	38
4.2.4. Resource .....	39
4.2.4.1. ArrivalController.php .....	39
4.2.4.2. CommentController.php .....	40
4.2.4.3. MenuController.php .....	42
4.2.4.4. PaymentController.php .....	43
4.2.4.5. PostController.php .....	44
4.2.4.6. PriceController.php .....	46
4.2.4.7. ReservationController.php .....	47
4.2.4.8. ServiceController.php .....	48
4.2.4.9. SliderController.php .....	49
4.2.4.10. SocialController.php .....	51
4.2.4.11. TrainerController.php .....	52
4.2.4.12. TrainingController.php .....	53
4.2.4.13. UserController.php .....	55
<b>4.3. Middleware .....</b>	<b>59</b>
4.3.1. Admin.php .....	59
4.3.2. LoggedIn.php .....	59
4.3.3. Privileged.php .....	60
<b>4.4. Requests .....</b>	<b>60</b>
4.4.1. ArrivalRequest.php .....	60
4.4.2. CommentRequest.php .....	61
4.4.3. ContactRequest.php .....	62
4.4.4. ImageRequest.php .....	63
4.4.5. MenuRequest.php .....	63
4.4.6. PasswordRequest.php .....	64
4.4.7. PaymentRequest.php .....	65
4.4.8. PostRequest.php .....	66
4.4.9. PriceRequest.php .....	66
4.4.10. RegisterRequest.php .....	67
4.4.11. ReservationRequest.php .....	68
4.4.12. ServiceRequest.php .....	69
4.4.13. SliderRequest.php .....	69
4.4.14. SocialRequest.php .....	70
4.4.15. TrainerRequest.php .....	71
4.4.16. TrainingRequest.php .....	71
4.4.17. UserRequest.php .....	73
<b>4.5. Views .....</b>	<b>74</b>
4.5.1. back .....	74
4.5.1.1. pages .....	74
4.5.1.1.1. admin .....	74
4.5.1.1.1.1. arrivals .....	74
4.5.1.1.1.1.1. index.blade.php .....	74
4.5.1.1.1.2. menus .....	74
4.5.1.1.1.2.1. create.blade.php .....	74
4.5.1.1.1.2.2. edit.blade.php .....	76
4.5.1.1.1.2.3. index.blade.php .....	77

4.5.1.1.1.3. payments.....	78
4.5.1.1.1.3.1. index.blade.php.....	78
4.5.1.1.1.4. posts.....	78
4.5.1.1.1.4.1. create.blade.php.....	78
4.5.1.1.1.4.2. edit.blade.php.....	80
4.5.1.1.1.4.3. index.blade.php.....	81
4.5.1.1.1.5. prices.....	83
4.5.1.1.1.5.1. create.blade.php.....	83
4.5.1.1.1.5.2. edit.blade.php.....	84
4.5.1.1.1.5.3. index.blade.php.....	85
4.5.1.1.1.6. services.....	86
4.5.1.1.1.6.1. create.blade.php.....	86
4.5.1.1.1.6.2. edit.blade.php.....	87
4.5.1.1.1.6.3. index.blade.php.....	89
4.5.1.1.1.7. sliders.....	90
4.5.1.1.1.7.1. create.blade.php.....	90
4.5.1.1.1.7.2. edit.blade.php.....	91
4.5.1.1.1.7.3. index.blade.php.....	92
4.5.1.1.1.8. socials.....	94
4.5.1.1.1.8.1. create.blade.php.....	94
4.5.1.1.1.8.2. edit.blade.php.....	95
4.5.1.1.1.8.3. index.blade.php.....	96
4.5.1.1.1.9. trainers.....	97
4.5.1.1.1.9.1. create.blade.php.....	97
4.5.1.1.1.9.2. edit.blade.php.....	98
4.5.1.1.1.9.3. index.blade.php.....	99
4.5.1.1.1.10. trainings.....	101
4.5.1.1.1.10.1. create.blade.php.....	101
4.5.1.1.1.10.2. edit.blade.php.....	103
4.5.1.1.1.10.3. index.blade.php.....	105
4.5.1.1.1.11. users.....	106
4.5.1.1.1.11.1. create.blade.php.....	106
4.5.1.1.1.12.2. edit.blade.php.....	108
4.5.1.1.1.12.3. index.blade.php.....	110
4.5.1.1.1.12. home.blade.php.....	112
4.5.1.1.2. energijapp.....	112
4.5.1.1.2.1. operator.....	112
4.5.1.1.2.1.1. arrivals.....	112
4.5.1.1.2.1.1.1. create.blade.php.....	112
4.5.1.1.2.1.1.2. edit.blade.php.....	113
4.5.1.1.2.1.2. payments.....	113
4.5.1.1.2.1.2.1. create.blade.php.....	113
4.5.1.1.2.1.2.2. edit.blade.php.....	114
4.5.1.1.2.1.3. reservations.....	114
4.5.1.1.2.1.3.1. index.blade.php.....	114
4.5.1.1.2.1.4. users.....	114
4.5.1.1.2.1.4.1. search.blade.php.....	114
4.5.1.1.2.2. user.....	115
4.5.1.1.2.2.1. reservations.....	115
4.5.1.1.2.2.1.1. create.blade.php.....	115
4.5.1.1.2.3. profile.blade.php.....	115

4.5.1.2. partials .....	116
4.5.1.2.1. admin .....	116
4.5.1.2.1.1. db_info.blade.php .....	116
4.5.1.2.1.2. sidebar.blade.php .....	120
4.5.1.2.2. common .....	123
4.5.1.2.2.1. head.blade.php .....	123
4.5.1.2.2.2. loader.blade.php .....	124
4.5.1.2.2.3. nav.blade.php .....	124
4.5.1.2.2.4. scripts.blade.php .....	125
4.5.1.2.2.5. wrapper.blade.php .....	125
4.5.1.2.3. energijapp .....	125
4.5.1.2.3.1. operator .....	126
4.5.1.2.3.1.1. sidebar.blade.php .....	126
4.5.1.2.3.2. profile .....	127
4.5.1.2.3.2.1. info.blade.php .....	127
4.5.1.2.3.2.2. tabs.blade.php .....	128
4.5.1.2.3.2.3. wrapper.blade.php .....	128
4.5.1.2.3.3. user .....	129
4.5.1.2.3.3.1. sidebar.blade.php .....	129
4.5.2. errors .....	130
4.5.2.1. 403.blade.php .....	130
4.5.2.2. 404.blade.php .....	132
4.5.2.3. 419.blade.php .....	134
4.5.3. front .....	136
4.5.3.1. pages .....	136
4.5.3.1.1. home.blade.php .....	136
4.5.3.1.2. post.blade.php .....	137
4.5.3.1.3. training.blade.php .....	138
4.5.3.2. partials .....	138
4.5.3.2.1. common .....	138
4.5.3.2.1.1. footer.blade.php .....	138
4.5.3.2.1.2. head.blade.php .....	140
4.5.3.2.1.3. nav.blade.php .....	140
4.5.3.2.1.4. preloader.blade.php .....	143
4.5.3.2.1.5. scripts.blade.php .....	143
4.5.3.2.2. home .....	144
4.5.3.2.2.1. pagination .....	144
4.5.3.2.2.1.1. posts.blade.php .....	144
4.5.3.2.2.1.2. trainings.blade.php .....	144
4.5.3.2.2.2. about.blade.php .....	145
4.5.3.2.2.3. blog.blade.php .....	146
4.5.3.2.2.4. contact.blade.php .....	146
4.5.3.2.2.5. map.blade.php .....	147
4.5.3.2.2.6. prices.blade.php .....	147
4.5.3.2.2.7. trainings.blade.php .....	148
4.5.3.2.2.8. welcome.blade.php .....	148
4.5.3.2.3. post .....	148
4.5.3.2.3.1. comments.blade.php .....	148
4.5.3.2.3.2. content.blade.php .....	150
4.5.3.2.3.3. form.blade.php .....	151
4.5.3.2.3.4. header.blade.php .....	151

4.5.3.2.4. training .....	152
4.5.3.2.4.1. content.blade.php .....	152
4.5.3.2.4.2. header.blade.php .....	152
4.5.4. layouts .....	152
4.5.4.1. back.blade.php .....	152
4.5.4.2. front.blade.php .....	153
<b>4.6. Routes .....</b>	<b>153</b>
4.6.1. api.php .....	153
4.6.2. web.php .....	154
<b>4.7. JavaScript .....</b>	<b>156</b>
4.7.1. ajax_admin.js .....	156
4.7.2. ajax.js .....	156
4.7.3. Components .....	159
4.7.3.1. admin .....	159
4.7.3.1.1. ArrivalsTable.vue .....	159
4.7.3.1.2. PaymentsTable.vue .....	162
4.7.3.2. energijapp .....	166
4.7.3.2.1. operator .....	166
4.7.3.2.1.1. arrivals .....	166
4.7.3.2.1.1.1. ArrivalCreate.vue .....	166
4.7.3.2.1.1.1. ArrivalEdit.vue .....	168
4.7.3.2.1.2. payments .....	170
4.7.3.2.1.2.1. PaymentCreate.vue .....	170
4.7.3.2.1.2.2. PaymentEdit.vue .....	171
4.7.3.2.1.3. reservations .....	173
4.7.3.2.1.3.1. ReservationsTable.vue .....	173
4.7.3.2.1.4. users .....	175
4.7.3.2.1.4.1. CardNumberSearch.vue .....	175
4.7.3.2.1.4.2. NameSearch.vue .....	175
4.7.3.2.2. profile .....	178
4.7.3.2.2.1. ChangePassword.vue .....	178
4.7.3.2.2.2. UserPaymentArrivals.vue .....	179
4.7.3.2.2.3. UserPayments.vue .....	182
4.7.3.2.3. user .....	184
4.7.3.2.3.1. reservations .....	184
4.7.3.2.3.1.1. ReservationsForm.vue .....	185
<b>5. Dizajn baze .....</b>	<b>188</b>
<b>6. Zaključak .....</b>	<b>189</b>
<b>7. Literatura .....</b>	<b>190</b>

# 1. Uvod

Cilj ovog projekta je, kao što naslov navodi, aplikacija za sportski centar.

Budući da radim u sportskom centru preko 6 godina, uz koji sam uporedo krenuo i da studiram, imao sam priliku da radim sa par aplikacija za vođenje takve vrste posla.

Kako su aplikacije takve vrste prilično zastarele sa korišćenim tehnologijama i imaju manjak savremenih mogućnosti, odnosno višak nepotrebnih, imao sam želju da napravim svoju verziju.

Ovu aplikaciju mogu korsititi 3 grupe korisnika: vežbači (korisnici), operatori (radnici za pultom) i administratori (menadžeri/direktori).

U prezentacionom delu sajta nalazi se funkcionalnost bloga, gde korisnici mogu komentarisati na objavama koje postavljaju administratori.

*Vežbači* imaju pristup svom profilu, na kojem se nalaze njihove informacije o uplatama i dolascima, mogu promeniti sliku i lozinku, a takođe imaju pristup rezervaciji treninga, gde mogu rezervisati najviše do 2 mesta u naredna 3 dana.

*Operatori* imaju pristup svom profilu, kao i profilima ostalih vežbača, gde mogu upisivati njihove uplate i dolaske, promene informacije i pošalju e-mail.

Oni takođe mogu da dodaju nove vežbače i da ih pretražuju putem barkod skenera, putem imena, aktivnom statusu i imaju mogućnost da vide listu rezervacija.

*Administratori* mogu raditi sve što i operatori, sa dodatkom pregleda liste dolazaka i uplata sa filterima, kao i dodavanja, izmene i brisanja svih ključnih entiteta u bazi podataka.



## 2. Radno okruženje

### Alati:

1. Editori:
  - Brackets – frontend
  - PhpStorm – backend
2. Lokalni server:
  - XAMPP
3. Komandna linija:
  - Cmder
4. Kontrola verzije:
  - Github

### Programski jezici i tehnologije:

- PHP (Laravel)
- JavaScript (Vue.js)
- HTML
- CSS

### Baza podataka:


- MySQL

### Dodaci i biblioteke:

- Bootstrap
- JQuery
- Laravel Telescope
- Axios
- Vue Calendar Heatmap, Vue Star Rating
- Google Maps, Font Awesome, Material Icons, Animate, Wow, Waves, Smooth Scroll

### 3. Organizacija

#### 3.1. Blok šema stranica



Slika 3.1.1. – Blok šema stranica

## 3.2. Stranice

### 3.2.1. Home


Početna stranica sajta.

Ovde korisnici mogu saznati informacije o sportskom centru.


Lista treninga i naslova blogova se menjaju putem ajax-a.



*Slika 3.2.1.1. – Izgled home stranice*



Slika 3.2.1.2. – Izgled home stranice




Slika 3.2.1.3. – Izgled home stranice

### 3.2.2. Blog

Tip stranice koju objavljuju administratori.

Korisnici mogu dodavati, menjati i brisati svoje komentare, dok administratori mogu upravljati svim komentarima.



*Slika 3.2.2.1. – Izgled blog stranice*

### 3.2.3. Trainings

Ovaj tip stranice sadrži detaljan opis svakog treninga, podeljen u 3 sekcije: opis, pogodnosti i ciljna grupa.




Slika 3.2.3.1. – Izgled trainings stranice

### 3.2.4. Profile

Ovoj stranici pristup imaju svi korisnici, s tim što je sadržaj dostupan u zavisnosti od uloge.

Vežbač može menjati svoju sliku i ima pregled svojih dolazaka i uplata i može menjati svoju lozinku.

Operator i administrator uz to mogu da dodaju vežbaču dolaske i uplate, a na svom profilu mogu promeniti lozinku.




Slika 3.2.4.1. – Izgled profile stranice

### 3.2.5. Reservations (form)

Ovu stranicu vide samo vežbači i ona služi za rezervaciju treninga.

Vežbač bira trening koji ima rezervacije i datum u naredna 3 dana i u zavisnosti šta izabere, izađe mu broj mesta za taj dan i koliko mesta je on rezervisao.

Limit je 2 treninga po vežbaču.

The screenshot shows a web application interface for making reservations. On the left is a purple sidebar with the 'EnergyApp' logo, a user profile picture, and navigation links for 'Moje mesto', 'Profil', and 'Rezervacije'. The main content area has a white background with a form. The form includes a 'Trening' dropdown menu, a 'Datum' field showing '06.12.2016', a 'Moje mesto' section with a star rating, and a 'Moje rezervacije' section with a '7' and two buttons: 'Rezervacija' (purple) and 'Otkazivanje' (orange). The footer of the sidebar contains the text '© 2016 Jovana Petrović'.

Slika 3.2.5.1. – Izgled reservations form stranice




### 3.2.6. Search

Ovoj stranici pristup imaju samo privilegovani korisnici.

Služi za pretragu vežbača i moguća je na 2 načina, putem barkod skenera i imena.

Takođe je moguća pretraga samo korisnika sa aktivnom uplatom.




Slika 3.2.6.1. – Izgled search stranice

### 3.2.7. Reservations (table)

Ovoj stranici pristup imaju samo privilegovani korisnici.

Služi za prikaz svih rezervacija po datumu.



EnergyApp

Uloguj se

Marija Marković  
m.markovic@energy.hr

Moje kartice

Moje rezervacije

Moje profile

Pregled rezervacija

01.07.2018

Broj kartice	Opis	Datum	Status
00002	Kupnja Benet	18/07	Rezervirano
00001	Plova Plova	18/07	Rezervirano

© 2018 Energy App


Slika 3.2.7.1. – Izgled reservations table stranice

### 3.2.8. Payments

Ovoj stranici pristup imaju samo administratori.

Služi za pretragu uplata po filterima i svi su međusobno reaktivni.

Takođe izračunava sumu svih uplata dobijenih rezultatom pretrage.



Administration

Pregled uplata

Startni dat: 01/01/2019 Endni dat: 01/01/2019 Poset: 0 Operator: 0

Zarada: 6900 Din.

Broj fakture	Datum	Poset	Operator	Datum uplate
00001	01/01/2019	0	Mika Majli	01/01/2019
00002	01/01/2019	0	Mika Majli	01/01/2019
00003	01/01/2019	0	Mika Majli	01/01/2019
00004	01/01/2019	0	Mika Majli	01/01/2019

1 od 1

Slika 3.2.8.1. – Izgled payments stranice

### 3.2.9. Arrivals

Ovoj stranici pristup imaju samo administratori.

Služi za pretragu dolazaka po filterima i svi su međusobno reaktivni.

Takođe izračunava ukupan broj dolazaka dobijen rezultatom pretrage.

Administracija

Pregled dolazaka

Datum od: 09/11/2018 Datum do: 09/17/2018 Training: Oscad Trener: Biljana Rankovic

Broj dolazaka: 15


Broj karata	Stan	Training	Trener	Datum dolaska
00001	Pala Pali	Oscad	Mirval Jovanovic	1.3.2018
00002	Pala Pali	HRT	Biljana Rankovic	8.3.2018
00003	Pala Pali	TBW	Biljana Rankovic	6.3.2018
00004	Pala Pali	Oscad	Mirval Jovanovic	8.3.2018
00005	Pala Pali	Pilates	Biljana Rankovic	11.3.2018
00006	Pala Pali	Oscad	Mirval Jovanovic	11.3.2018
00007	Pala Pali	HRT	Biljana Rankovic	20.3.2018
00008	Pala Pali	TBW	Biljana Rankovic	23.3.2018
00009	Pala Pali	HRT	Biljana Rankovic	23.4.2018
00010	Pala Pali	Pilates	Biljana Rankovic	17.4.2018

Slika 3.2.9.1. – Izgled arrivals stranice

### 3.2.10. Admin CRUD

Skup stranica predviđen za administratore.

Na početnoj admin stranici dostupni su svi ključni entiteti iz baze podataka, nad kojim se može izvršiti pregled, dodavanje, izmena i brisanje.



Slika 3.2.10.1. – Izgled početne admin CRUD stranice

## 4. Kod

### 4.1. Models

#### 4.1.1. Arrival.php

```
<?php
namespace App;

use Illuminate\Database\Eloquent\Model;

class Arrival extends Model
{
    protected $guarded = [];

    public function user()
    {
        return $this->belongsTo('App\User');
    }

    public function training()
    {
        return $this->belongsTo('App\Training');
    }

    public function trainer()
    {
        return $this->belongsTo('App\Trainer');
    }

    public function payment()
    {
        return $this->belongsTo('App\Payment');
    }
}
```

#### 4.1.2. Comment.php

```
<?php
namespace App;

use Illuminate\Database\Eloquent\Model;

class Comment extends Model
{
    protected $guarded = [];

    public function user()
    {
```

```

        return $this->belongsTo('App\User');
    }
}

```

### 4.1.3. Menu.php

```

<?php

namespace App;

use Illuminate\Database\Eloquent\Model;

class Menu extends Model
{
    protected $guarded = [];
}

```

### 4.1.4. Payment.php

```

<?php

namespace App;

use Illuminate\Database\Eloquent\Model;

class Payment extends Model
{
    protected $guarded = [];

    public function price()
    {
        return $this->belongsTo('App\Price');
    }

    public function user()
    {
        return $this->belongsTo('App\User');
    }

    public function operator()
    {
        return $this->belongsTo('App\User')->where('role_id', 1)-
>orWhere('role_id', 3);
    }

    public function arrivals()
    {
        return $this->hasMany('App\Arrival');
    }
}

```

#### 4.1.5. Post.php

```
<?php
namespace App;

use Illuminate\Database\Eloquent\Model;

class Post extends Model
{
    protected $guarded = [];

    public function user()
    {
        return $this->belongsTo('App\User');
    }

    public function comments()
    {
        return $this->hasMany('App\Comment');
    }
}
```

#### 4.1.6. Price.php

```
<?php
namespace App;

use Illuminate\Database\Eloquent\Model;

class Price extends Model
{
    protected $guarded = [];

    public function services()
    {
        return $this->hasMany('App\Service');
    }
}
```

#### 4.1.7. Reservation.php

```
<?php
namespace App;

use Illuminate\Database\Eloquent\Model;

class Reservation extends Model
{
    protected $guarded = [];
```



```

    public function user()
    {
        return $this->belongsTo('App\User');
    }

    public function training()
    {
        return $this->belongsTo('App\Training');
    }
}

```

#### 4.1.8. Role.php

```

<?php

namespace App;

use Illuminate\Database\Eloquent\Model;

class Role extends Model
{
    protected $fillable = [];
}

```

#### 4.1.9. Service.php

```

<?php

namespace App;

use Illuminate\Database\Eloquent\Model;

class Service extends Model
{
    protected $guarded = [];

    public function price()
    {
        return $this->belongsTo('App\Price');
    }
}

```

#### 4.1.10. Slider.php

```

<?php

namespace App;

use Illuminate\Database\Eloquent\Model;

```

```
class Slider extends Model
{
    protected $guarded = [];
}
```

#### 4.1.11. Social.php

```
<?php

namespace App;

use Illuminate\Database\Eloquent\Model;

class Social extends Model
{
    protected $guarded = [];
}
```

#### 4.1.12. Trainer.php

```
<?php

namespace App;

use Illuminate\Database\Eloquent\Model;

class Trainer extends Model
{
    protected $guarded = [];
}
```

#### 4.1.13. Training.php

```
<?php

namespace App;

use Illuminate\Database\Eloquent\Model;

class Training extends Model
{
    protected $guarded = [];
}
```

#### 4.1.14. User.php

```
<?php
```

```

namespace App;

use Illuminate\Foundation\Auth\User as Authenticatable;

class User extends Authenticatable
{
    protected $guarded = [];

    public function loginCheck($email, $passwd)
    {
        return User::where([
            'email' => $email,
            'password' => md5($passwd)
        ])->first();
    }

    public function role()
    {
        return $this->belongsTo('App\Role');
    }

    public function comments()
    {
        return $this->hasMany('App\Comment');
    }

    public function posts()
    {
        return $this->hasMany('App\Post');
    }

    public function payment()
    {
        return $this->hasMany('App\Payment');
    }
}

```

## 4.2. Controllers

### 4.2.1. API

#### 4.2.1.1. ArrivalController.php

```

<?php

namespace App\Http\Controllers\API;

use App\Arrival;
use App\Http\Requests\ArrivalRequest;
use App\Payment;
use Illuminate\Http\Request;
use App\Http\Controllers\Controller;
use Illuminate\Support\Facades\DB;

```

```

class ArrivalController extends Controller
{
    public function index(Request $request)
    {
        $date_from = '2013-05-15';
        if($request->date_from)
            $date_from = $request->date_from;

        $date_to = '2100-01-01';
        if($request->date_to)
            $date_to = $request->date_to;

        $training_operator = '=';
        if($request->training_id == null)
            $training_operator = '<>';

        $trainer_operator = '=';
        if($request->trainer_id == null)
            $trainer_operator = '<>';

        $pagination = Arrival::whereBetween('date', [$date_from, $date_to])
            ->where('training_id', $training_operator, $request->training_id)
            ->where('trainer_id', $trainer_operator, $request->trainer_id)
            ->paginate(10);

        foreach ($pagination as $entity)
        {
            $entity->user;
            $entity->training;
            $entity->trainer;
        }

        return response()->json($pagination);
    }

    public function store(ArrivalRequest $request)
    {
        $payment = Payment::find($request->payment_id);
        $arrivals = Arrival::where('user_id', $request->user_id)-
>where('payment_id', $request->payment_id)->get();
        $arrivalCount = $arrivals->count();

        if($arrivalCount < $payment->price->sessions)
        {
            Arrival::create([
                'date' => $request->date,
                'training_id' => $request->training_id,
                'trainer_id' => $request->trainer_id,
                'payment_id' => $request->payment_id,
                'user_id' => $request->user_id
            ]);

            return response('Dolazak dodat.', 201);
        }

        return response('Termini su iskorišćeni.', 422);
    }
}

```

```

    public function show($id)
    {
        return response()->json(Arrival::find($id));
    }

    public function update(ArrivalRequest $request, $id)
    {
        Arrival::find($id)->update([
            'date' => $request->date,
            'training_id' => $request->training_id,
            'trainer_id' => $request->trainer_id
        ]);

        return response('Dolazak izmenjen.', 204);
    }

    public function destroy($id)
    {
        Arrival::find($id)->delete();
        return response('Dolazak obrisan.', 204);
    }

    public function getUserArrivals($id)
    {
        $arrivalData = Arrival::select('date', DB::raw('count(id) as count'))
            ->groupBy('date')
            ->where('user_id', $id)
            ->get();

        return response()->json($arrivalData);
    }
}

```

#### 4.2.1.2. PaymentController.php

```

<?php

namespace App\Http\Controllers\API;

use App\Http\Requests\PaymentRequest;
use App\Payment;
use Illuminate\Http\Request;
use App\Http\Controllers\Controller;

class PaymentController extends Controller
{
    public function index(Request $request)
    {
        $date_from = '2013-05-15';
        if($request->date_from)
            $date_from = $request->date_from;

        $date_to = '2100-01-01';
        if($request->date_to)

```

```

        $date_to = $request->date_to;

        $price_operator = '=';
        if($request->price_id == null)
            $price_operator = '<>';

        $operator_operator = '=';
        if($request->operator_id == null)
            $operator_operator = '<>';

        $pagination = Payment::whereBetween('payment_date', [$date_from,
$date_to])
            ->where('price_id', $price_operator, $request->price_id)
            ->where('operator_id', $operator_operator, $request->operator_id)
            ->paginate(10);

        foreach ($pagination as $entity)
        {
            $entity->price;
            $entity->user;
            $entity->operator;
        }

        $query = Payment::whereBetween('payment_date', [$date_from, $date_to])
            ->where('price_id', $price_operator, $request->price_id)
            ->where('operator_id', $operator_operator, $request->operator_id)
            ->get();

        $sum = 0;
        foreach ($query as $entity)
            $sum += $entity->price->amount;

        return response()->json(array($pagination, $sum));
    }

    public function store(PaymentRequest $request)
    {
        Payment::create([
            'price_id' => $request->price_id,
            'payment_date' => $request->payment_date,
            'valid_thru' => $request->valid_thru,
            'user_id' => $request->user_id,
            'operator_id' => $request->operator_id
        ]);

        return response('Uplata izvršena.', 201);
    }

    public function show($id)
    {
        return response()->json(Payment::find($id));
    }

    public function update(PaymentRequest $request, $id)
    {
        Payment::find($id)->update([
            'price_id' => $request->price_id,

```

```

        'payment_date' => $request->payment_date,
        'valid_thru' => $request->valid_thru
    ]);

    return response('Uplata izmenjena.', 204);
}

public function destroy($id)
{
    Payment::find($id)->delete();
    return response('Uplata obrisana.', 204);
}

public function getUserPayments($id)
{
    $pagination = Payment::where('user_id', $id)->paginate(10);

    foreach ($pagination as $entity)
        $entity->price;

    $query = Payment::where('user_id', $id)->get();
    $sum = 0;

    foreach ($query as $entity)
        $sum += $entity->price->amount;

    return response()->json(array($pagination, $sum));
}

public function getUserPaymentArrivals($id)
{
    $pagination = Payment::where('user_id', $id)->paginate(7);

    foreach ($pagination as $entity)
    {
        $entity->price;
        $arrivals = $entity->arrivals;

        foreach ($arrivals as $arrival)
        {
            $arrival->training;
            $arrival->trainer;
        }
    }

    return response()->json($pagination);
}
}

```

#### 4.2.1.3. PriceController.php

```

<?php

namespace App\Http\Controllers\API;

```

```

use App\Price;
use App\Http\Controllers\Controller;

class PriceController extends Controller
{
    public function index()
    {
        return response()->json(Price::all());
    }
}

```

#### 4.2.1.4. ReservationController.php

```

<?php

namespace App\Http\Controllers\API;

use App\Http\Requests\ReservationRequest;
use App\Reservation;
use App\Training;
use Illuminate\Http\Request;
use App\Http\Controllers\Controller;

class ReservationController extends Controller
{
    public function store(ReservationRequest $request)
    {
        Reservation::create([
            'user_id' => $request->user_id,
            'training_id' => $request->training_id,
            'date' => $request->date
        ]);

        $reservations = Reservation::where('training_id', $request->training_id)-
>where('date', $request->date)->count();
        $my_reservations = Reservation::where('training_id', $request-
>training_id)->where('date', $request->date)->where('user_id', $request->user_id)-
>count();

        $isReservable = true;
        if($my_reservations >= 2)
            $isReservable = false;

        return response(array($reservations, $my_reservations, $isReservable),
201);
    }

    public function destroy($id)
    {
        Reservation::find($id)->delete();
        return response('Rezervacija obrisana.', 204);
    }

    public function getCount(ReservationRequest $request)

```



```

    {
        $capacity = Training::find($request->training_id)->capacity;
        $reservations = Reservation::where('training_id', $request->training_id)-
>where('date', $request->date)->count();
        $my_reservations = Reservation::where('training_id', $request-
>training_id)->where('date', $request->date)->where('user_id', $request->user_id)-
>count();

        $isReservable = true;
        if($my_reservations >= 2)
            $isReservable = false;

        $isDeletable = false;
        if($my_reservations > 0)
            $isDeletable = true;

        return response()->json(array($capacity, $reservations, $my_reservations,
$isReservable, $isDeletable));
    }

    public function dateSearch(Request $request)
    {
        $query = Reservation::where('date', $request->training_date)->get();

        foreach ($query as $entity)
        {
            $entity->user;
            $entity->training;
        }

        return response()->json($query);
    }

    public function deleteUserReservations($id, Request $request)
    {
        Reservation::where('training_id', $request->training_id)->where('date',
$request->date)->where('user_id', $id)->delete();

        $reservations = Reservation::where('training_id', $request->training_id)-
>where('date', $request->date)->count();
        $my_reservations = Reservation::where('training_id', $request-
>training_id)->where('date', $request->date)->where('user_id', $id)->count();

        return response(array($reservations, $my_reservations), 204);
    }
}

```

#### 4.2.1.5. TrainerController.php

```

<?php

namespace App\Http\Controllers\API;

use App\Trainer;
use App\Http\Controllers\Controller;

```

```
class TrainerController extends Controller
{
    public function index()
    {
        return response()->json(Trainer::all());
    }
}
```

#### 4.2.1.6. TrainingController.php

```
<?php

namespace App\Http\Controllers\API;

use App\Training;
use Illuminate\Http\Request;
use App\Http\Controllers\Controller;

class TrainingController extends Controller
{
    public function index()
    {
        return response()->json(Training::all());
    }

    public function getReservable()
    {
        return response()->json(Training::where('reservations', '1')->get());
    }
}
```

#### 4.2.1.7. UserController.php

```
<?php

namespace App\Http\Controllers\API;

use App\Http\Requests\PasswordRequest;
use App\User;
use Carbon\Carbon;
use Illuminate\Database\Eloquent\Builder;
use Illuminate\Http\Request;
use App\Http\Controllers\Controller;

class UserController extends Controller
{
    public function cardNumberSearch(Request $request)
    {
        $query = User::where('card_number', $request->card_number)->get();

        return response()->json($query);
    }
}
```

```

public function nameSearch(Request $request)
{
    $fn_operator = 'like';
    if($request->first_name == null)
        $fn_operator = '<>';

    $ln_operator = 'like';
    if($request->last_name == null)
        $ln_operator = '<>';

    $date_operator = '<>';
    $date_value = null;
    if($request->active == 'true')
    {
        $date_operator = '>';
        $date_value = Carbon::now()->toDateString();
    }

    $pagination = User::whereHas('payment', function (Builder $query1) use
($date_value, $date_operator) {
        $query1->where('valid_thru', $date_operator, $date_value);
    })->where('first_name', $fn_operator, '%'.$request->first_name.'%')
->where('last_name', $ln_operator, '%'.$request->last_name.'%')
->orderBy('card_number')->paginate(5);

    return response()->json($pagination);
}

public function getOperators()
{
    return response()->json(User::where('role_id', 1)->orWhere('role_id', 3)-
>get());
}

public function getPrivilege()
{
    if (session('user')->role->name == 'admin' || session('user')->role->name
== 'operator')
        return response('Privilegovan.', '200');

    return response('Nije privilegovan.', 401);
}

public function changePassword($id, PasswordRequest $request)
{
    if($request->newPassword != null || $request->newPasswordConfirm)
    {
        if ($request->newPassword == $request->newPasswordConfirm)
        {
            $password = md5($request->newPassword);
            User::find($id)->update(['password' => $password]);
            return response('Lozinka promenjena.', 204);
        }
    }
    return response('Greška.', 422);
}
}

```

## 4.2.2. Core

### 4.2.2.1. BackendController.php

```
<?php

namespace App\Http\Controllers\Core;

use App\Http\Controllers\Controller;
use App\Menu;
use App\Post;
use App\Price;
use App\Service;
use App\Slider;
use App\Social;
use App\Trainer;
use App\Training;
use App\User;

class BackendController extends Controller
{
    public function admin()
    {
        $users = User::all();
        $posts = Post::all();
        $sliders = Slider::all();
        $menus = Menu::all();
        $trainings = Training::all();
        $trainers = Trainer::all();
        $prices = Price::all();
        $services = Service::all();
        $socials = Social::all();

        return view('back.pages.admin.home', compact('users', 'posts', 'sliders',
        'menus', 'trainers', 'trainings', 'prices', 'services', 'socials'));
    }
}
```

### 4.2.2.2. FrontendController.php

```
<?php

namespace App\Http\Controllers\Core;

use App\Http\Controllers\Controller;
use App\Http\Requests\ContactRequest;
use App\Menu;
use App\Post;
use App\Price;
use App\Slider;
use App\Social;
use App\Training;
```

```

class FrontendController extends Controller
{
    public function home()
    {
        $menus = Menu::orderBy('position')->get();
        $sliders = Slider::orderBy('position')->get();
        $trainings = Training::latest('id')->paginate(3);
        $trainings->withPath('training_pagination');
        $prices = Price::orderBy('amount')->get();
        $posts = Post::latest('id')->paginate(4);
        $posts->withPath('post_pagination');
        $socials = Social::all();

        return view('front.pages.home', compact('menus', 'sliders', 'trainings',
        'prices', 'posts', 'socials'));
    }

    public function contact(ContactRequest $request)
    {
        $name = $request->conName;
        $email = $request->conEmail;
        $subject = $request->conSubject;
        $message = $request->conMsg;
        $headers = 'From: ' . $name . ' ' . $email;

        try {
            mail('jovan.rankovic.145.14@ict.edu.rs', $subject, $message,
$headers);
            \Log::info('Contact message sent.');
```

```

            return redirect('/')->with('message', 'Poruka poslata.');
```

```

        } catch (\Exception $ex) {
            \Log::error($ex->getMessage());
            return redirect('/')->with('message', 'Problem u slanju poruke.');
```

```

        }
    }

    public function sessions()
    {
        return response()->download(public_path('download/')."scr-raspored.jpg");
    }
}

```

## 4.2.3. MyAuth

### 4.2.3.1. LoginController.php

```

<?php

namespace App\Http\Controllers\MyAuth;

use App\Http\Controllers\Controller;
use App\User;

```

```

use Illuminate\Http\Request;

class LoginController extends Controller
{
    public function login(Request $request, User $user)
    {
        $email = $request->logEmail;
        $passwd = $request->logPasswd;

        $existingUser = $user->loginCheck($email, $passwd);

        if($existingUser)
        {
            $request->session()->put('user', $existingUser);
            \Log::info(session('user')->first_name.' '.session('user')->last_name.' logged in.');
```

```

            return redirect()->back()->with('message', 'Logovanje uspešno.');
```

```

        }
        else
        {
            return redirect('/')->with('message', 'Pogrešan e-mail /
lozinka.');
```

```

        }
    }

    public function logout()
    {
        \Log::info(session('user')->first_name.' '.session('user')->last_name.'
logged out.');
```

```

        session()->forget('user');
        return redirect('/');
    }
}

```

#### 4.2.3.2. RegisterController.php

```

<?php

namespace App\Http\Controllers\Auth;

use App\Http\Controllers\Controller;
use App\Http\Requests\RegisterRequest;
use App\User;
use Illuminate\Http\Request;

class RegisterController extends Controller
{
    public function register(RegisterRequest $request)
    {
        try
        {
            $user = User::create([
                'first_name' => $request->regFN,
                'last_name' => $request->regLN,
                'email' => $request->email,
                'password' => md5($request->regPasswd),
                'image' => 'images/user/new.jpg',
            ]);

```

```

        'role_id' => 2,
        'remember_token' => md5(time().$request->email),
        'email_verified_at' => date('Y-d-m H:i:s')
    ]);

    \Log::info($user->first_name.' '.$user->last_name.' registered.');
```

```

        return redirect('/')->with('message', 'Registracija uspešna.');
```

```

    }
    catch (\Exception $ex)
    {
        \Log::error($ex->getMessage());

        return redirect('/')->with('message', 'Greška, probajte ponovo
kasnije.');
```

```

    }
}

```

## 4.2.4. Resource

### 4.2.4.1. ArrivalController.php

```

<?php

namespace App\Http\Controllers\Resource;

use App\Arrival;
use App\Payment;
use Illuminate\Http\Request;
use App\Http\Controllers\Controller;

class ArrivalController extends Controller
{
    public function index()
    {
        return view('back.pages.admin.arrivals.index');
    }

    public function create($id)
    {
        $user_id = Payment::find($id)->user->id;
        return view('back.pages.energijapp.operator.arrivals.create',
compact('id', 'user_id'));
    }

    public function store(Request $request)
    {
        //
    }

    public function show($id)

```

```

{
    //

}

public function edit($id)
{
    $user_id = Arrival::find($id)->user->id;
    return view('back.pages.energijapp.operator.arrivals.edit', compact('id',
'user_id'));
}

public function update(Request $request, $id)
{
    //
}

public function destroy($id)
{
    //
}
}

```

#### 4.2.4.2. CommentController.php

```

<?php

namespace App\Http\Controllers\Resource;

use App\Http\Controllers\Controller;
use App\Http\Requests\CommentRequest;
use App\Comment;
use App\Post;

class CommentController extends Controller
{
    public function index(Post $post)
    {
        $comments = $post->comments;
        foreach ($comments as $comment)
        {
            echo $comment->content;
        }
    }

    public function create()
    {
        //
    }

    public function store(CommentRequest $request)
    {
        try

```



```

        {
            Comment::create([
                'content' => $request->input('content'),
                'post_id' => $request->post_id,
                'user_id' => $request->user_id
            ]);

            \Log::info($request->userFN.' '.$request->userLN.' commented on
'.'$request->postTitle.': '.$request->input('content'));
        }
        catch (\Exception $ex)
        {
            \Log::error($ex->getMessage());
        }
    }

    public function show()
    {
        //
    }

    public function edit()
    {
        //
    }

    public function update(CommentRequest $request)
    {
        try
        {
            Comment::where('id', $request->id)
                ->update([
                    'content' => $request->input('content'),
                ]);

            \Log::info($request->userFN.' '.$request->userLN.' updated a comment
on '.$request->postTitle.': '.$request->input('content'));
        }
        catch (\Exception $ex)
        {
            \Log::error($ex->getMessage());
        }
    }

    public function destroy()
    {
        $request = request();
        \Log::warning($request->userFN.' '.$request->userLN.' deleted a comment on
'.'$request->postTitle.': '.$request->commentContent);
        Comment::where(request(['id', 'post_id', 'user_id']))->delete();
    }
}

```

#### 4.2.4.3. MenuController.php

```
<?php

namespace App\Http\Controllers\Resource;

use App\Http\Controllers\Controller;
use App\Http\Requests\MenuRequest;
use App\Menu;

class MenuController extends Controller
{
    public function index()
    {
        $menus = Menu::orderBy('position')->paginate(6);
        return view('back.pages.admin.menus.index', compact('menus'));
    }

    public function create()
    {
        return view('back.pages.admin.menus.create');
    }

    public function store(MenuRequest $request)
    {
        Menu::create([
            'position' => $request->position,
            'name' => $request->name,
            'route' => $request->route,
        ]);

        return redirect('/admin/menus');
    }

    public function show(Menu $menu)
    {
        //
    }

    public function edit(Menu $menu)
    {
        return view('back.pages.admin.menus.edit', compact('menu'));
    }

    public function update(MenuRequest $request, Menu $menu)
    {
        $menu->update([
            'position' => $request->position,
            'name' => $request->name,
            'route' => $request->route,
        ]);

        return redirect('/admin/menus');
    }
}
```

```

    }

    public function destroy()
    {
        Menu::where(request(['id']))->delete();
    }
}

```

#### 4.2.4.4. PaymentController.php

```

<?php

namespace App\Http\Controllers\Resource;

use App\Payment;
use Illuminate\Http\Request;
use App\Http\Controllers\Controller;

class PaymentController extends Controller
{
    public function index()
    {
        return view('back.pages.admin.payments.index');
    }

    public function create($id)
    {
        return view('back.pages.energijapp.operator.payments.create',
compact('id'));
    }

    public function store(Request $request)
    {
        //
    }

    public function show($id)
    {
        //
    }

    public function edit($id)
    {
        $user_id = Payment::find($id)->user->id;
        return view('back.pages.energijapp.operator.payments.edit', compact('id',
'user_id'));
    }

    public function update(Request $request, $id)
    {
        //
    }
}

```

```

    }

    public function destroy($id)
    {
        //
    }
}

```

#### 4.2.4.5. PostController.php

```

<?php

namespace App\Http\Controllers\Resource;

use App\Http\Controllers\Controller;
use App\Http\Requests\PostRequest;
use App\Post;
use App\Social;
use Illuminate\Http\Request;
use Illuminate\Support\Facades\File;

class PostController extends Controller
{
    public function index()
    {
        $posts = Post::latest('id')->paginate(2);
        return view('back.pages.admin.posts.index', compact('posts'));
    }

    public function create()
    {
        return view('back.pages.admin.posts.create');
    }

    public function store(PostRequest $request)
    {
        $image = $request->image;

        if($image->isValid())
        {
            $imgFolder = 'images/post/';
            $imgName = time().rand().$image->getClientOriginalName();
            $image->move(public_path().'/'.$imgFolder, $imgName);

            Post::create([
                'title' => $request->title,
                'content' => $request->contentP,
                'user_id' => $request->user_id,
                'image' => $imgFolder.$imgName
            ]);
        }

        return redirect('/admin/posts');
    }
}

```

```

public function show(Post $post)
{
    $socials = Social::all();
    return view('front.pages.post', compact('post','socials'));
}

public function edit(Post $post)
{
    return view('back.pages.admin.posts.edit', compact('post'));
}

public function update(PostRequest $request, Post $post)
{
    $image = $request->image;

    if($image->isValid())
    {
        if(File::exists(public_path().'/'.$post->image))
        {
            File::delete(public_path().'/'.$post->image);
        }

        $imgFolder = 'images/post/';
        $imgName = time().rand().$image->getClientOriginalName();
        $image->move(public_path().'/'.$imgFolder, $imgName);

        $post->update([
            'title' => $request->title,
            'content' => $request->contentP,
            'user_id' => $request->user_id,
            'image' => $imgFolder.$imgName
        ]);
    }

    return redirect('/admin/posts');
}

public function destroy(Post $post)
{
    if(File::exists(public_path().'/'.$post->image))
    {
        File::delete(public_path().'/'.$post->image);
    }

    Post::where(request(['id']))->delete();
}

public function pagination(Request $request)
{
    if ($request->ajax()) {
        $posts = Post::latest('id')->paginate(4);

        return view('front.partials.home.pagination.posts', compact('posts'));
    }
}

```

```
        return abort(404);
    }
}
```

#### 4.2.4.6. PriceController.php

```
<?php

namespace App\Http\Controllers\Resource;

use App\Http\Controllers\Controller;
use App\Http\Requests\PriceRequest;
use App\Price;

class PriceController extends Controller
{
    public function index()
    {
        $prices = Price::orderBy('amount')->paginate(6);
        return view('back.pages.admin.prices.index', compact('prices'));
    }

    public function create()
    {
        return view('back.pages.admin.prices.create');
    }

    public function store(PriceRequest $request)
    {
        Price::create([
            'title' => $request->title,
            'sessions' => $request->sessions,
            'amount' => $request->amount
        ]);

        return redirect('/admin/prices');
    }

    public function show(Price $price)
    {
        //
    }

    public function edit(Price $price)
    {
        return view('back.pages.admin.prices.edit', compact('price'));
    }

    public function update(PriceRequest $request, Price $price)
    {
        $price->update([
```

```

        'title' => $request->title,
        'sessions' => $request->sessions,
        'amount' => $request->amount
    ]);

    return redirect('/admin/prices');
}

public function destroy()
{
    Price::where(request(['id']))->delete();
}
}

```

#### 4.2.4.7. ReservationController.php

```

<?php

namespace App\Http\Controllers\Resource;

use Illuminate\Http\Request;
use App\Http\Controllers\Controller;

class ReservationController extends Controller
{
    public function index()
    {
        return view('back.pages.energijapp.operator.reservations.index');
    }

    public function create($id)
    {
        return view('back.pages.energijapp.user.reservations.create',
compact('id'));
    }

    public function store(Request $request)
    {
        //
    }

    public function show($id)
    {
        //
    }

    public function edit($id)
    {
        //
    }
}

```

```

    public function update(Request $request, $id)
    {
        //
    }

    public function destroy($id)
    {
        //
    }
}

```

#### 4.2.4.8. ServiceController.php

```

<?php

namespace App\Http\Controllers\Resource;

use App\Http\Controllers\Controller;
use App\Http\Requests\ServiceRequest;
use App\Price;
use App\Service;

class ServiceController extends Controller
{
    public function index()
    {
        $services = Service::latest('id')->paginate(6);
        return view('back.pages.admin.services.index', compact('services'));
    }

    public function create()
    {
        $prices = Price::all();
        return view('back.pages.admin.services.create', compact('prices'));
    }

    public function store(ServiceRequest $request)
    {
        Service::create([
            'name' => $request->name,
            'price_id' => $request->price_id
        ]);

        return redirect('/admin/services');
    }

    public function show(Service $service)
    {
        //
    }

    public function edit(Service $service)

```



```

{
    $prices = Price::all();
    return view('back.pages.admin.services.edit', compact('service',
'prices'));
}

public function update(ServiceRequest $request, Service $service)
{
    $service->update([
        'name' => $request->name,
        'price_id' => $request->price_id
    ]);

    return redirect('/admin/services');
}

public function destroy()
{
    Service::where(request(['id']))->delete();
}
}

```

#### 4.2.4.9. SliderController.php

```

<?php

namespace App\Http\Controllers\Resource;

use App\Http\Controllers\Controller;
use App\Http\Requests\SliderRequest;
use App\Slider;
use Illuminate\Support\Facades\File;

class SliderController extends Controller
{
    public function index()
    {
        $sliders = Slider::orderBy('position')->paginate(2);
        return view ('back.pages.admin.sliders.index', compact('sliders'));
    }

    public function create()
    {
        return view('back.pages.admin.sliders.create');
    }

    public function store(SliderRequest $request)
    {
        $image = $request->image;

        if($image->isValid())
        {
            $imgFolder = 'images/slider/';

```

```

        $imgName = time().rand().$image->getClientOriginalName();
        $image->move(public_path().'/'.$imgFolder, $imgName);

        Slider::create([
            'position' => $request->position,
            'image' => $imgFolder.$imgName
        ]);
    }

    return redirect('/admin/sliders');
}

public function show(Slider $slider)
{
    //
}

public function edit(Slider $slider)
{
    return view('back.pages.admin.sliders.edit', compact('slider'));
}

public function update(SliderRequest $request, Slider $slider)
{
    $image = $request->image;

    if($image->isValid())
    {
        if(File::exists(public_path().'/'.$slider->image))
        {
            File::delete(public_path().'/'.$slider->image);
        }

        $imgFolder = 'images/slider/';
        $imgName = time().rand().$image->getClientOriginalName();
        $image->move(public_path().'/'.$imgFolder, $imgName);

        $slider->update([
            'position' => $request->position,
            'image' => $imgFolder.$imgName
        ]);
    }

    return redirect('/admin/sliders');
}

public function destroy(Slider $slider)
{
    if(File::exists(public_path().'/'.$slider->image))
    {
        File::delete(public_path().'/'.$slider->image);
    }

    Slider::where(request(['id']))->delete();
}
}

```

#### 4.2.4.10. SocialController.php

```
<?php

namespace App\Http\Controllers\Resource;

use App\Http\Controllers\Controller;
use App\Http\Requests\SocialRequest;
use App\Social;

class SocialController extends Controller
{
    public function index()
    {
        $socials = Social::latest('id')->paginate(6);
        return view('back.pages.admin.socials.index', compact('socials'));
    }

    public function create()
    {
        return view('back.pages.admin.socials.create');
    }

    public function store(SocialRequest $request)
    {
        Social::create([
            'name' => $request->name,
            'url' => $request->url,
            'icon' => strtolower($request->icon)
        ]);

        return redirect('/admin/socials');
    }

    public function show(Social $social)
    {
        //
    }

    public function edit(Social $social)
    {
        return view('back.pages.admin.socials.edit', compact('social',
'trainers'));
    }

    public function update(SocialRequest $request, Social $social)
    {
        $social->update([
            'name' => $request->name,
            'url' => $request->url,
            'icon' => strtolower($request->icon)
        ]);
    }
}
```

```

    ]);

    return redirect('/admin/socials');
}

public function destroy()
{
    Social::where(request(['id']))->delete();
}
}

```

#### 4.2.4.11. TrainerController.php

```

<?php

namespace App\Http\Controllers\Resource;

use App\Http\Requests\TrainerRequest;
use App\Trainer;
use App\Http\Controllers\Controller;

class TrainerController extends Controller
{
    public function index()
    {
        $trainers = Trainer::latest()->paginate(6);
        return view('back.pages.admin.trainers.index', compact('trainers'));
    }

    public function create()
    {
        return view('back.pages.admin.trainers.create');
    }

    public function store(TrainerRequest $request)
    {
        Trainer::create([
            'first_name' => $request->first_name,
            'last_name' => $request->last_name
        ]);

        return redirect('/admin/trainers');
    }

    public function show(Trainer $trainer)
    {
        //
    }

    public function edit(Trainer $trainer)
    {
        return view('back.pages.admin.trainers.edit', compact('trainer'));
    }
}

```

```

    }

    public function update(TrainerRequest $request, Trainer $trainer)
    {
        $trainer->update([
            'first_name' => $request->first_name,
            'last_name' => $request->last_name
        ]);

        return redirect('/admin/trainers');
    }

    public function destroy()
    {
        Trainer::where(request(['id']))->delete();
    }
}

```

#### 4.2.4.12. TrainingController.php

```

<?php

namespace App\Http\Controllers\Resource;

use App\Http\Controllers\Controller;
use App\Http\Requests\TrainingRequest;
use App\Social;
use App\Training;
use Illuminate\Http\Request;
use Illuminate\Support\Facades\File;

class TrainingController extends Controller
{
    public function index()
    {
        $trainings = Training::latest('id')->paginate(2);
        return view('back.pages.admin.trainings.index', compact('trainings'));
    }

    public function create()
    {
        return view('back.pages.admin.trainings.create');
    }

    public function store(TrainingRequest $request)
    {
        $image = $request->image;
        $logo = $request->logo;

        if($image->isValid() && $logo->isValid())
        {
            $imgFolder = 'images/training/img/';
            $imgName = time().rand().$image->getClientOriginalName();

```

```

        $image->move(public_path().'/'.$imgFolder, $imgName);

        $logoFolder = 'images/training/logo/';
        $logoName = time().rand().$logo->getClientOriginalName();
        $logo->move(public_path().'/'.$logoFolder, $logoName);

        Training::create([
            'name' => $request->name,
            'duration' => $request->duration,
            'capacity' => $request->capacity,
            'intensity' => $request->intensity,
            'target' => $request->target,
            'benefits' => $request->benefits,
            'description' => $request->description,
            'logo' => $logoFolder.$logoName,
            'image' => $imgFolder.$imgName,
            'reservations' => $request->reservations
        ]);
    }

    return redirect('/admin/trainings');
}

public function show(Training $training)
{
    $socials = Social::all();
    return view('front.pages.training', compact('training', 'socials'));
}

public function edit(Training $training)
{
    return view('back.pages.admin.trainings.edit', compact('training'));
}

public function update(TrainingRequest $request, Training $training)
{
    $image = $request->image;
    $logo = $request->logo;

    if($image->isValid() && $logo->isValid())
    {
        if(File::exists(public_path().'/'.$training->image))
        {
            File::delete(public_path().'/'.$training->image);
        }

        if(File::exists(public_path().'/'.$training->logo))
        {
            File::delete(public_path().'/'.$training->logo);
        }

        $imgFolder = 'images/training/img/';
        $imgName = time().rand().$image->getClientOriginalName();
        $image->move(public_path().'/'.$imgFolder, $imgName);

        $logoFolder = 'images/training/logo/';
        $logoName = time().rand().$logo->getClientOriginalName();
    }
}

```

```

        $logo->move(public_path().'/'.$logoFolder, $logoName);

        $training->update([
            'name' => $request->name,
            'duration' => $request->duration,
            'capacity' => $request->capacity,
            'intensity' => $request->intensity,
            'target' => $request->target,
            'benefits' => $request->benefits,
            'description' => $request->description,
            'logo' => $logoFolder.$logoName,
            'image' => $imgFolder.$imgName,
            'reservations' => $request->reservations
        ]);
    }

    return redirect('/admin/trainings');
}

public function destroy(Training $training)
{
    if(File::exists(public_path().'/'.$training->image))
    {
        File::delete(public_path().'/'.$training->image);
    }

    Training::where(request(['id']))->delete();
}

public function pagination(Request $request)
{
    if ($request->ajax()) {
        $trainings = Training::latest('id')->paginate(3);

        return view('front.partials.home.pagination.trainings',
compact('trainings'));
    }

    return abort(404);
}
}

```

#### 4.2.4.13. UserController.php

```

<?php

namespace App\Http\Controllers\Resource;

use App\Http\Controllers\Controller;
use App\Http\Requests\ImageRequest;
use App\Http\Requests\UserRequest;
use App\Role;
use App\User;
use Illuminate\Http\Request;
use Illuminate\Support\Facades\File;

```

```

class UserController extends Controller
{
    public function index()
    {
        $users = User::latest('id')->paginate(6);
        return view('back.pages.admin.users.index', compact('users'));
    }

    public function create()
    {
        $roles = Role::all();
        return view('back.pages.admin.users.create', compact('roles'));
    }

    public function store(UserRequest $request)
    {
        $password = md5($request->password);
        $request->role_id ? $role_id = $request->role_id : $role_id = 2;
        $image = $request->image;

        if($image)
        {
            if($image->isValid())
            {
                $imgFolder = 'images/user/';
                $imgName = time().rand().$image->getClientOriginalName();
                $image->move(public_path().'/'.$imgFolder, $imgName);

                $user = User::create([
                    'first_name' => $request->first_name,
                    'last_name' => $request->last_name,
                    'email' => $request->email,
                    'password' => $password,
                    'phone' => $request->phone,
                    'birth_date' => $request->birth_date,
                    'role_id' => $role_id,
                    'image' => $imgFolder.$imgName,
                    'card_number' => $request->card_number,
                    'address' => $request->address
                ]);

                if(str_replace(url('/'), '', url()->previous()) ==
'/admin/users/create')
                    return redirect('/admin/users');
                else
                    return redirect('/energijapp/profile' . '/' . $user->id);
            }
        }
        else
        {
            $user = User::create([
                'first_name' => $request->first_name,
                'last_name' => $request->last_name,
                'email' => $request->email,
                'password' => $password,
                'phone' => $request->phone,
                'birth_date' => $request->birth_date,

```



```

        'role_id' => $role_id,
        'card_number' => $request->card_number,
        'address' => $request->address
    ]);

    if(str_replace(url('/'), '', url()->previous()) ==
'/admin/users/create')
        return redirect('/admin/users');
    else
        return redirect('/energijapp/profile' . '/' . $user->id);
    }
}

public function show(User $user)
{
    if (session('user')->role->name == 'user')
        abort_if(session()->get('user')->id != $user->id, 403);
    else
    {
        if ($user->role->name != 'user')
            abort_if(session()->get('user')->id != $user->id, 403);
    }

    return view('back.pages.energijapp.profile', compact('user'));
}

public function edit(User $user)
{
    $roles = Role::all();
    return view('back.pages.admin.users.edit', compact('user', 'roles'));
}

public function update(UserRequest $request, User $user)
{
    $request->role_id ? $role_id = $request->role_id : $role_id = 2;
    $image = $request->image;

    if($image)
    {
        if($image->isValid())
        {
            if(File::exists(public_path().'/'.$user->image))
            {
                $defaultImage = public_path().'/images/user/new.jpg';

                if(public_path().'/'.$user->image != $defaultImage)
                {
                    File::delete(public_path().'/'.$user->image);
                }
            }

            $imgFolder = 'images/user/';
            $imgName = time().rand().$image->getClientOriginalName();
            $image->move(public_path().'/'.$imgFolder, $imgName);

            $user->update([
                'first_name' => $request->first_name,

```

```

        'last_name' => $request->last_name,
        'email' => $request->email,
        'phone' => $request->phone,
        'birth_date' => $request->birth_date,
        'role_id' => $role_id,
        'image' => $imgFolder.$imgName,
        'card_number' => $request->card_number,
        'address' => $request->address
    ]);
    }
}
else
{
    $user->update([
        'first_name' => $request->first_name,
        'last_name' => $request->last_name,
        'email' => $request->email,
        'phone' => $request->phone,
        'birth_date' => $request->birth_date,
        'role_id' => $role_id,
        'card_number' => $request->card_number,
        'address' => $request->address
    ]);
}

if(str_replace(url('/'), '', url()->previous()) == '/admin/users/'.$user->id.'/edit')
    return redirect('/admin/users');
else
    return redirect('/energijapp/profile' . '/' . $user->id);
}

public function destroy(User $user)
{
    if(File::exists(public_path().'/'.$user->image))
    {
        $defaultImage = public_path().'/images/user/new.jpg';

        if(public_path().'/'.$user->image != $defaultImage)
        {
            File::delete(public_path().'/'.$user->image);
        }
    }

    User::where(request(['id']))->delete();
}

public function search()
{
    return view('back.pages.energijapp.operator.users.search');
}

public function image_update(ImageRequest $request, User $user)
{
    $image = $request->imgUser;

    if ($image->isValid()) {

```

```

        if (File::exists(public_path() . '/' . $user->image)) {
            $defaultImage = public_path() . '/' . 'images/user/new.jpg';

            if (public_path() . '/' . $user->image != $defaultImage) {
                File::delete(public_path() . '/' . $user->image);
            }
        }

        $imgFolder = 'images/user/';
        $imgName = time() . rand() . $image->getClientOriginalName();
        $image->move(public_path() . '/' . $imgFolder, $imgName);

        $user->update([
            'image' => $imgFolder . $imgName
        ]);

        session('user')->update([
            'image' => $imgFolder . $imgName
        ]);

        return redirect('/energijapp/profile' . '/' . $user->id);
    }

    return redirect('/energijapp/profile' . '/' . $user->id);
}
}

```

## 4.3. Middleware

### 4.3.1. Admin.php

```

<?php
namespace App\Http\Middleware;

use Closure;

class Admin
{
    public function handle($request, Closure $next)
    {
        if (session()->has('user')) {
            if (session()->get('user')->role->name == 'admin') {
                return $next($request);
            }
        }
        return abort(403);
    }
}

```

### 4.3.2. LoggedIn.php

```

<?php
namespace App\Http\Middleware;

use Closure;

class LoggedIn
{
    public function handle($request, Closure $next)
    {
        if (session()->has('user'))
        {
            return $next($request);
        }
        return abort(403);
    }
}

```

### 4.3.3. Privileged.php

```

<?php
namespace App\Http\Middleware;

use Closure;

class Privileged
{
    public function handle($request, Closure $next)
    {
        if (session()->has('user')) {
            if (session()->get('user')->role->name == 'admin' || session()-
>get('user')->role->name == 'operator') {
                return $next($request);
            }
        }
        return abort(403);
    }
}

```

## 4.4. Requests

### 4.4.1. ArrivalRequest.php

```

<?php
namespace App\Http\Requests;

use Illuminate\Foundation\Http\FormRequest;

class ArrivalRequest extends FormRequest
{

```

```

    public function authorize()
    {
        return true;
    }

    public function rules()
    {
        return [
            'date' => 'required|date',
            'user_id' => 'numeric|not_in:0',
            'training_id' => 'required|numeric|not_in:0',
            'trainer_id' => 'required|numeric|not_in:0',
            'payment_id' => 'numeric|not_in:0'
        ];
    }

    public function messages()
    {
        return [
            'date.required' => 'Datum je obavezan.',
            'date.date' => 'Datum nije u dobrom formatu.',
            'user_id.numeric' => 'Korisnik mora biti ID.',
            'user_id.not_in' => 'Korisnik ID ne može biti 0.',
            'training_id.required' => 'Trening je obavezan.',
            'training_id.numeric' => 'Trening mora biti ID.',
            'training_id.not_in' => 'Trening ne može biti 0.',
            'trainer_id.required' => 'Trener je obavezan.',
            'trainer_id.numeric' => 'Trener mora biti ID.',
            'trainer_id.not_in' => 'Trener ID ne može biti 0.',
            'payment_id.numeric' => 'Uplata mora biti ID.',
            'payment_id.not_in' => 'Uplata ID ne može biti 0.'
        ];
    }
}

```

#### 4.4.2. CommentRequest.php

```

<?php

namespace App\Http\Requests;

use Illuminate\Foundation\Http\FormRequest;

class CommentRequest extends FormRequest
{
    public function authorize()
    {
        return true;
    }

    public function rules()
    {
        return [
            'content' => 'required|min:2',
            'post_id' => 'required|numeric|not_in:0',
            'user_id' => 'required|numeric|not_in:0'
        ];
    }
}

```

```

    }

    public function messages()
    {
        return [
            'content.required' => 'Ne možete postaviti prazan komentar.',
            'content.min' => 'Komentar mora sadržati bar 2 karaktera.',
            'post_id.required' => 'Post je obavezan.',
            'post_id.numeric' => 'Post mora biti ID.',
            'post_id.not_in' => 'Post ID ne može biti 0.',
            'user_id.required' => 'Korisnik je obavezan.',
            'user_id.numeric' => 'Korisnik mora biti ID.',
            'user_id.not_in' => 'Korisnik ID ne može biti 0.'
        ];
    }
}

```

#### 4.4.3. ContactRequest.php

```

<?php

namespace App\Http\Requests;

use Illuminate\Foundation\Http\FormRequest;

class ContactRequest extends FormRequest
{
    public function authorize()
    {
        return true;
    }

    public function rules()
    {
        return [
            'conName' => 'required|alpha',
            'conEmail' => 'required|email',
            'conSubject' => 'required|min:3',
            'conMsg' => 'required|min:3'
        ];
    }

    public function messages()
    {
        return [
            'conName.required' => 'Ime je obavezno.',
            'conName.alpha' => 'Ime može imati samo slova.',
            'conEmail.required' => 'E-mail je obavezan.',
            'conEmail.email' => 'E-mail nije u dobrom formatu.',
            'conSubject.required' => 'Naslov je obavezan.',
            'conSubject.min' => 'Naslov mora sadržati bar 3 karaktera.',
            'conMsg.required' => 'Poruka je obavezna.',
            'conMsg.min' => 'Poruka mora sadržati bar 3 karaktera.',
        ];
    }
}

```

#### 4.4.4. ImageRequest.php

```
<?php

namespace App\Http\Requests;

use Illuminate\Foundation\Http\FormRequest;

class ImageRequest extends FormRequest
{
    public function authorize()
    {
        return true;
    }

    public function rules()
    {
        return [
            'imgUser' => 'image|max:2000|dimensions:ratio=1/1|mimes:jpeg,png,jpg',
        ];
    }

    public function messages()
    {
        return [
            'imgUser.required' => 'Slika je obavezna.',
            'imgUser.image' => 'Slika nije u dobrom formatu.',
            'imgUser.max' => 'Slika može imati najviše 2MB.',
            'imgUser:dimensions' => 'Slika mora biti u razmeri 1:1.',
            'imgUser.mimes' => 'Dozvoljeni formati su: jpg, jpeg i png.'
        ];
    }
}
```

#### 4.4.5. MenuRequest.php

```
<?php

namespace App\Http\Requests;

use Illuminate\Foundation\Http\FormRequest;

class MenuRequest extends FormRequest
{
    public function authorize()
    {
        return true;
    }

    public function rules()
    {
        return [
            'name' => 'required|min:2|max:20',
            'route' => 'required|min:2|max:255',
            'position' => 'required|numeric|unique:menus|not_in:0',
        ];
    }
}
```

```

    ];
}

public function messages()
{
    return [
        'name.required' => 'Ime je obavezno.',
        'name.min' => 'Ime mora imati bar 2 karaktera.',
        'name.max' => 'Ime može imati najviše 20 karaktera.',
        'route.required' => 'Putanja je obavezna.',
        'route.min' => 'Putanja mora imati bar 2 karaktera.',
        'route.max' => 'Putanja može imati najviše 20 karaktera.',
        'position.required' => 'Pozicija je obavezna.',
        'position.numeric' => 'Pozicija mora biti broj.',
        'position.unique' => 'Pozicija već postoji.',
        'position.not_in' => 'Pozicija ne sme biti 0.'
    ];
}
}

```

#### 4.4.6. PasswordRequest.php

```

<?php

namespace App\Http\Requests;

use Illuminate\Foundation\Http\FormRequest;

class PasswordRequest extends FormRequest
{
    public function authorize()
    {
        return true;
    }

    public function rules()
    {
        return [
            'newPassword' => [
                'required',
                'min:6',
                'max:32',
                'regex:/^(?=.*[a-z])(?=.*[A-Z])(?=.*\d)[a-zA-Z\d]{6,}$/'
            ],
            'newPasswordConfirm' => [
                'required',
                'min:6',
                'max:32',
                'regex:/^(?=.*[a-z])(?=.*[A-Z])(?=.*\d)[a-zA-Z\d]{6,}$/'
            ]
        ];
    }

    public function messages()
    {
        return [
            'newPassword.required' => 'Nova lozinka je obavezna.',

```



```

        'newPassword.min' => 'Nova lozinka mora sadržati bar 6 karaktera.',
        'newPassword.max' => 'Nova lozinka može imati najviše 32 karaktera.',
        'newPassword.regex' => 'Nova lozinka mora sadržati bar jedno veliko
slovo i jedan broj.',
        'newPasswordConfirm.required' => 'Nova lozinka ponovo je obavezna.',
        'newPasswordConfirm.min' => 'Nova lozinka ponovo mora sadržati bar 6
karaktera.',
        'newPasswordConfirm.max' => 'Nova lozinka ponovo može imati najviše 32
karaktera.',
        'newPasswordConfirm.regex' => 'Nova lozinka ponovo mora sadržati bar
jedno veliko slovo i jedan broj.'
    ];
}
}

```

#### 4.4.7. PaymentRequest.php

```

<?php
namespace App\Http\Requests;

use Illuminate\Foundation\Http\FormRequest;

class PaymentRequest extends FormRequest
{
    public function authorize()
    {
        return true;
    }

    public function rules()
    {
        return [
            'payment_date' => 'required|date',
            'valid_thru' => 'required|date',
            'price_id' => 'required|numeric|not_in:0',
            'user_id' => 'numeric|not_in:0',
            'operator_id' => 'numeric|not_in:0'
        ];
    }

    public function messages()
    {
        return [
            'payment_date.required' => 'Datum uplate je obavezan.',
            'payment_date.date' => 'Datum uplate nije u dobrom formatu.',
            'valid_thru.required' => 'Datum isteka je obavezan.',
            'valid_thru.date' => 'Datum isteka nije u dobrom formatu.',
            'price_id.required' => 'Cena je obavezna.',
            'price_id.numeric' => 'Cena mora biti ID.',
            'price_id.not_in' => 'Cena ID ne može biti 0.',
            'user_id.numeric' => 'Korisnik mora biti ID.',
            'user_id.not_in' => 'Korisnik ID ne može biti 0.',
            'operator_id.numeric' => 'Operator mora biti ID.',
            'operator.not_in' => 'Operator ID ne može biti 0.'
        ];
    }
}

```

```
}  
}
```

#### 4.4.8. PostRequest.php

```
<?php  
  
namespace App\Http\Requests;  
  
use Illuminate\Foundation\Http\FormRequest;  
  
class PostRequest extends FormRequest  
{  
    public function authorize()  
    {  
        return true;  
    }  
  
    public function rules()  
    {  
        return [  
            'title' => 'required|alpha_num|min:3|max:100',  
            'contentP' => 'required',  
            'user_id' => 'required|numeric|not_in:0',  
            'image' => 'required|image|max:2000'  
        ];  
    }  
  
    public function messages()  
    {  
        return [  
            'title.required' => 'Naslov je obavezan.',  
            'title.alpha_num' => 'Naslov može sadržati samo slova i brojeve.',  
            'title.min' => 'Naslov mora imati bar 3 karaktera.',  
            'title.max' => 'Naslov može imati najviše 100 karaktera.',  
            'contentP.required' => 'Sadržaj je obavezan.',  
            'user_id.required' => 'Korisnik je obavezan.',  
            'user_id.numeric' => 'Korisnik mora biti ID.',  
            'user_id.not_in' => 'Korisnik ID ne može biti 0.',  
            'image.required' => 'Slika je obavezna.',  
            'image.image' => 'Slika nije u dobrom formatu.',  
            'image.max' => 'Slika može imati najviše 2MB.'  
        ];  
    }  
}
```

#### 4.4.9. PriceRequest.php

```
<?php  
  
namespace App\Http\Requests;  
  
use Illuminate\Foundation\Http\FormRequest;
```

```

class PriceRequest extends FormRequest
{
    public function authorize()
    {
        return true;
    }

    public function rules()
    {
        return [
            'title' => 'required|min:3|max:20',
            'sessions' => 'required|numeric|not_in:0',
            'amount' => 'required|numeric'
        ];
    }

    public function messages()
    {
        return [
            'title.required' => 'Naziv paketa je obavezan.',
            'title.min' => 'Naziv paketa mora imati bar 3 karaktera.',
            'title.max' => 'Naziv paketa može imati najviše 20 karaktera.',
            'sessions.required' => 'Broj termina je obavezan.',
            'sessions.numeric' => 'Broj termina mora biti broj.',
            'sessions.not_in' => 'Broj termina ne sme biti 0.',
            'amount.required' => 'Iznos je obavezan.',
            'amount.numeric' => 'Iznos mora biti broj.'
        ];
    }
}

```

#### 4.4.10. RegisterRequest.php

```

<?php

namespace App\Http\Requests;

use Illuminate\Foundation\Http\FormRequest;

class RegisterRequest extends FormRequest
{
    public function authorize()
    {
        return true;
    }

    public function rules()
    {
        return [
            'regFN' => 'required|alpha|min:2|max:30',
            'regLN' => 'required|alpha|min:2|max:30',
            'email' => 'required|email|max:60|unique:users',
            'regPasswd' => [
                'required',
                'min:6',
                'max:32',
                'regex:/^(?=[a-z])(?=[A-Z])(?=[\d])[a-zA-Z\d]{6,}$/'
            ]
        ];
    }
}

```

```

    ];
}

public function messages()
{
    return [
        'regFN.required' => 'Ime je obavezno.',
        'regFN.alpha' => 'Ime može imati samo slova.',
        'regFN.min' => 'Ime mora imati bar 2 slova.',
        'regFN.max' => 'Ime može imati najviše 30 slova.',
        'regLN.required' => 'Prezime je obavezno.',
        'regLN.alpha' => 'Prezime može imati samo slova.',
        'regLN.min' => 'Prezime mora imati bar 2 slova.',
        'regLN.max' => 'Prezime može imati najviše 30 slova.',
        'email.required' => 'E-mail je obavezan.',
        'email.email' => 'E-mail nije u dobrom formatu.',
        'email.max' => 'E-mail može imati najviše 60 karaktera.',
        'email.unique' => 'E-mail već postoji.',
        'regPasswd.required' => 'Lozinka je obavezna.',
        'regPasswd.min' => 'Lozinka mora sadržati bar 6 karaktera.',
        'regPasswd.max' => 'Lozinka može imati najviše 32 karaktera.',
        'regPasswd.regex' => 'Lozinka mora sadržati bar jedno veliko slovo i
jedan broj.'
    ];
}
}

```

#### 4.4.11. ReservationRequest.php

```

<?php
namespace App\Http\Requests;

use Illuminate\Foundation\Http\FormRequest;

class ReservationRequest extends FormRequest
{
    public function authorize()
    {
        return true;
    }

    public function rules()
    {
        return [
            'date' => 'required|date',
            'user_id' => 'required|numeric|not_in:0',
            'training_id' => 'required|numeric|not_in:0'
        ];
    }

    public function messages()
    {
        return [
            'date.required' => 'Datum je obavezan.',
            'date.date' => 'Datum nije u dobrom formatu.',

```

```

        'user_id.required' => 'Korisnik je obavezan.',
        'user_id.numeric' => 'Korisnik mora biti ID.',
        'user_id.not_in' => 'Korisnik ID ne može biti 0.',
        'training_id.required' => 'Trening je obavezan.',
        'training_id.numeric' => 'Trening mora biti ID.',
        'training_id.not_in' => 'Trening ID ne može biti 0.'
    ];
}
}

```

#### 4.4.12. ServiceRequest.php

```

<?php
namespace App\Http\Requests;

use Illuminate\Foundation\Http\FormRequest;

class ServiceRequest extends FormRequest
{
    public function authorize()
    {
        return true;
    }

    public function rules()
    {
        return [
            'name' => 'required|min:2|max:100',
            'price_id' => 'required|numeric|not_in:0'
        ];
    }

    public function messages()
    {
        return [
            'name.required' => 'Naziv je obavezan.',
            'name.min' => 'Naziv mora imati najmanje 2 karaktera.',
            'name.max' => 'Naziv može imati najviše 100 karaktera.',
            'price_id.required' => 'Cenovna kategorija je obavezna.',
            'price_id.numeric' => 'Cenovna kategorija mora biti ID.',
            'price_id.not_in' => 'Cenovna kategorija ID ne sme biti 0.'
        ];
    }
}

```

#### 4.4.13. SliderRequest.php

```

<?php
namespace App\Http\Requests;

use Illuminate\Foundation\Http\FormRequest;

```

```

class SliderRequest extends FormRequest
{
    public function authorize()
    {
        return true;
    }

    public function rules()
    {
        return [
            'image' => 'required|image|mimes:jpeg,png,jpg|max:2000',
            'position' => 'required|numeric|unique:sliders|not_in:0'
        ];
    }

    public function messages()
    {
        return [
            'image.required' => 'Slika je obavezna.',
            'image.image' => 'Slika nije u dobrom formatu.',
            'image.mimes' => 'Dozvoljeni formati su: jpg, jpeg i png.',
            'image.max' => 'Slika može imati najviše 2MB.',
            'position.required' => 'Pozicija je obavezna.',
            'position.numeric' => 'Pozicija mora biti broj.',
            'position.unique' => 'Pozicija već postoji.',
            'position.not_id' => 'Pozicija ne sme biti 0.'
        ];
    }
}

```

#### 4.4.14. SocialRequest.php

```

<?php

namespace App\Http\Requests;

use Illuminate\Foundation\Http\FormRequest;

class SocialRequest extends FormRequest
{
    public function authorize()
    {
        return true;
    }

    public function rules()
    {
        return [
            'name' => 'required|min:2|max:30|unique:socials',
            'url' => 'required|url|min:3|max:191|unique:socials',
            'icon' => 'required|min:2|max:30'
        ];
    }

    public function messages()
    {
        return [

```

```

        'name.required' => 'Naziv je obavezan.',
        'name.min' => 'Naziv mora imati bar 2 karaktera.',
        'name.max' => 'Naziv može imati najviše 30 karaktera.',
        'name.unique' => 'Naziv već postoji.',
        'url.required' => 'URL je obavezan.',
        'url.url' => 'URL nije u dobrom formatu.',
        'url.min' => 'URL mora imati bar 3 karaktera.',
        'url.max' => 'URL može imati najviše 30 karaktera.',
        'url.unique' => 'URL već postoji.',
        'icon.required' => 'Ikonica je obavezna.',
        'icon.min' => 'Ikonica mora imati bar 2 karaktera.',
        'icon.max' => 'Naziv može imati najviše 30 karaktera.'
    ];
}
}

```

#### 4.4.15. TrainerRequest.php

```

<?php
namespace App\Http\Requests;

use Illuminate\Foundation\Http\FormRequest;

class TrainerRequest extends FormRequest
{
    public function authorize()
    {
        return true;
    }

    public function rules()
    {
        return [
            'first_name' => 'required|alpha|min:2|max:30',
            'last_name' => 'required|alpha|min:2|max:30'
        ];
    }

    public function messages()
    {
        return [
            'first_name.required' => 'Ime je obavezno.',
            'first_name.alpha' => 'Ime može imati samo slova.',
            'first_name.min' => 'Ime mora imati bar 2 slova.',
            'first_name.max' => 'Ime može imati najviše 30 slova.',
            'last_name.alpha' => 'Prezime može imati samo slova.',
            'last_name.min' => 'Prezime mora imati bar 2 slova.',
            'last_name.max' => 'Prezime može imati najviše 30 slova.'
        ];
    }
}

```

#### 4.4.16. TrainingRequest.php

```

<?php
namespace App\Http\Requests;

use Illuminate\Foundation\Http\FormRequest;

class TrainingRequest extends FormRequest
{
    public function authorize()
    {
        return true;
    }

    public function rules()
    {
        return [
            'name' => 'required|alpha|min:3|max:20|unique:trainings',
            'duration' => 'required|numeric|digits_between:2,3',
            'capacity' => 'required|numeric|digits_between:1,2',
            'intensity' => 'required|alpha|min:3|max:30',
            'target' => 'required|min:3',
            'benefits' => 'required|min:3',
            'description' => 'required|min:3',
            'logo' => 'required|image|max:2000|dimensions:width=360,height=450',
            'image' => 'required|image|max:2000',
            'reservations' => 'boolean'
        ];
    }

    public function messages()
    {
        return [
            'name.required' => 'Naziv je obavezan.',
            'name.alpha' => 'Naziv može imati samo slova.',
            'name.min' => 'Naziv mora imati bar 3 slova.',
            'name.max' => 'Naziv može imati najviše 20 slova.',
            'name.unique' => 'Naziv već postoji.',
            'duration.required' => 'Trajanje je obavezno.',
            'duration.numeric' => 'Trajanje mora biti broj.',
            'duration.digits_between' => 'Trajanje mora imati 2 ili 3 cifre.',
            'capacity.required' => 'Kapacitet je obavezan.',
            'capacity.numeric' => 'Kapacitet mora biti broj.',
            'capacity.digits_between' => 'Kapacitet mora imati 1 ili 2 cifre.',
            'intensity.required' => 'Intenzitet je obavezan.',
            'intensity.alpha' => 'Intenzitet može imati samo slova.',
            'intensity.min' => 'Intenzitet mora imati bar 3 slova.',
            'intensity.max' => 'Intenzitet može imati najviše 30 slova',
            'target.required' => 'Ciljna grupa je obavezna.',
            'target.min' => 'Ciljna grupa mora imati bar 3 karaktera.',
            'benefits.required' => 'Pogodnosti su obavezne.',
            'benefits.min' => 'Pogodnosti moraju imati bar 3 karaktera.',
            'description.required' => 'Opis je obavezan',
            'logo.required' => 'Logo je obavezan.',
            'logo.image' => 'Logo nije u dobrom formatu.',
            'logo.max' => 'Logo može imati najviše 2MB.',
            'logo:dimensions' => 'Logo mora biti u razmeri: 360x450.',
            'image.required' => 'Slika je obavezna.',
            'image.image' => 'Slika nije u dobrom formatu.',
            'image.max' => 'Slika može imati najviše 2MB.',
            'reservations.boolean' => 'Rezervacije moraju biti tip boolean.'
        ];
    }
}

```



```

    ];
}
}

```

#### 4.4.17. UserRequest.php

```

<?php

namespace App\Http\Requests;

use Illuminate\Foundation\Http\FormRequest;

class UserRequest extends FormRequest
{
    public function authorize()
    {
        return true;
    }

    public function rules()
    {
        return [
            'first_name' => 'required|alpha|min:2|max:30',
            'last_name' => 'required|alpha|min:2|max:30',
            'email' => 'required|email|max:60|unique:users',
            'phone' => 'required|numeric|digits_between:9,10',
            'birth_date' => 'required|date',
            'image' => 'image|max:2000|dimensions:ratio=1/1|mimes:jpeg,png,jpg',
            'card_number' => 'numeric|digits:5|unique:users',
            'address' => 'required|min:5|max:100',
            'role_id' => 'numeric|not_in:0',
            'password' => [
                'min:6',
                'max:32',
                'regex:/^(?=.*[a-z])(?=.*[A-Z])(?=.*\d)[a-zA-Z\d]{6,}$/'
            ]
        ];
    }

    public function messages()
    {
        return [
            'first_name.required' => 'Ime je obavezno.',
            'first_name.alpha' => 'Ime može imati samo slova.',
            'first_name.min' => 'Ime mora imati bar 2 slova.',
            'first_name.max' => 'Ime može imati najviše 30 slova.',
            'last_name.alpha' => 'Prezime može imati samo slova.',
            'last_name.min' => 'Prezime mora imati bar 2 slova.',
            'last_name.max' => 'Prezime može imati najviše 30 slova.',
            'email.required' => 'E-mail je obavezan.',
            'email.email' => 'E-mail nije u dobrom formatu.',
            'email.max' => 'E-mail može imati najviše 60 karaktera.',
            'email.unique' => 'E-mail već postoji.',
            'phone.required' => 'Telefon je obavezan.',
            'phone.numeric' => 'Telefon može imati samo brojeve.',
            'phone.digits_between' => 'Telefon mora imati 9 ili 10 cifara.',
            'birth_date.required' => 'Datum rođenja je obavezan.',

```

```

        'birth_date.date' => 'Datum rođenja nije u dobrom formatu.',
        'image.required' => 'Slika je obavezna.',
        'image.image' => 'Slika nije u dobrom formatu.',
        'image.max' => 'Slika može imati najviše 2MB.',
        'image:dimensions' => 'Slika mora biti u razmeri 1:1.',
        'image.mimes' => 'Dozvoljeni formati su: jpg, jpeg i png.',
        'card_number.numeric' => 'Broj kartice može sadržati samo brojeve.',
        'card_number.digits' => 'Broj kartice mora imati 5 cifara.',
        'card_number.unique' => 'Broj kartice već postoji.',
        'address.required' => 'Adresa je obavezna.',
        'address.min' => 'Adresa mora imati bar 5 karaktera.',
        'address.max' => 'Adresa može imati najviše 100 karaktera.',
        'role_id.numeric' => 'Uloga mora biti ID.',
        'role_id.not_in' => 'Uloga ID ne sme biti 0.',
        'password.min' => 'Lozinka mora sadržati bar 6 karaktera.',
        'password.max' => 'Lozinka može imati najviše 32 karaktera.',
        'password.regex' => 'Lozinka mora sadržati bar jedno veliko slovo i
jedan broj.'
    ];
}
}

```

## 4.5. Views

### 4.5.1. back

#### 4.5.1.1. pages

##### 4.5.1.1.1. admin

##### 4.5.1.1.1.1. arrivals

##### 4.5.1.1.1.1.1. index.blade.php

```

@extends('layouts.back')

@section('content')
    <arrivals-table></arrivals-table>
@endsection

```

##### 4.5.1.1.1.2. menus

##### 4.5.1.1.1.2.1. create.blade.php

```

@extends('layouts.back')

@section('header')
    <div class="header">
        <h2>
            <i class="material-icons icon_left">link</i> Meni linkovi<a href="#"
onclick="history.back(-1)"><i class="material-icons pull-
right">keyboard_return</i><i class="pull-right go_back">Nazad</i></a>
            <small>Dodavanje linkova u meniju</small>
        </h2>
    </div>
@endsection

@section('content')
    <div class="body">
        <div class="row">
            <div class="col-md-4 col-md-offset-4">

                @isset($errors)
                    @foreach($errors->all() as $error)
                        <div class="alert alert-warning">
                            {{ $error }}
                        </div>
                    @endforeach
                @endisset

                <p class="lead">Dodaj link u meniju</p>
                <form action="{{ url('/admin/menus') }}" method="POST">
                    @csrf
                    <div class="form-group">
                        <div class="form-line">
                            <input name="position" id="position" type="number"
class="form-control" placeholder="Pozicija" required />
                        </div>
                    </div>
                    <div class="form-group">
                        <div class="form-line">
                            <input name="name" id="name" type="text" class="form-
control" placeholder="Ime" required />
                        </div>
                    </div>
                    <div class="form-group">
                        <div class="form-line">
                            <input name="route" id="route" type="text"
class="form-control" placeholder="Putanja" required />
                        </div>
                    </div>
                    <div class="form-group">
                        <button type="submit" name="menuBtn" id="menuBtn"
class="btn btn-dark waves-effect waves-light">Dodaj</button>
                        <a href="#" onclick="history.back(-1)" class="btn waves-
effect">Otkazi</a>
                    </div>
                </form>
            </div>
        </div>
    </div>
@endsection

```

#### 4.5.1.1.2.2. edit.blade.php

```
@extends('layouts.back')

@section('header')
    <div class="header">
        <h2>
            <i class="material-icons icon_left">link</i> Meni linkovi<a href="#"
onclick="history.back(-1)"><i class="material-icons pull-
right">keyboard_return</i><i class="pull-right go_back">Nazad</i></a>
            <small>Izmena meni linkova</small>
        </h2>
    </div>
@endsection

@section('content')
    <div class="body">
        <div class="row">
            <div class="col-md-4 col-md-offset-4">

                @isset($errors)
                    @foreach($errors->all() as $error)
                        <div class="alert alert-warning">
                            {{ $error }}
                        </div>
                    @endforeach
                @endisset

                <p class="lead">Izmeni meni link</p>
                <form action="{{ url('/admin/menus/' . $menu->id) }}" method="POST">
                    @method('PATCH')
                    @csrf
                    <div class="form-group">
                        <div class="form-line">
                            <input name="position" id="position" type="number"
class="form-control" placeholder="Pozicija" required value="{{ $menu->position }}" />
                        </div>
                    </div>
                    <div class="form-group">
                        <div class="form-line">
                            <input name="name" id="name" type="text" class="form-
control" placeholder="Ime" required value="{{ $menu->name }}" />
                        </div>
                    </div>
                    <div class="form-group">
                        <div class="form-line">
                            <input name="route" id="route" type="text"
class="form-control" placeholder="Putanja" required value="{{ $menu->route }}" />
                        </div>
                    </div>
                    <div class="form-group">
                        <button type="submit" name="menuBtn" id="menuBtn"
class="btn btn-dark waves-effect waves-light">Izmeni</button>
                        <a href="#" onclick="history.back(-1)" class="btn waves-
```

```

effect">Otkazi</a>
        </div>
    </form>
</div>
</div>
</div>
@endsection

```

#### 4.5.1.1.2.3. index.blade.php

```

@extends('layouts.back')

@section('header')
    <div class="header">
        <h2>
            <i class="material-icons icon_left">link</i> Meni linkovi<a href="#"
onclick="history.back(-1)"><i class="material-icons pull-
right">keyboard_return</i><i class="pull-right go_back">Nazad</i></a>
            <small>Prikaz svih linkova u meniju</small>
            <hr/>
            <a href="{{ url('admin/menus/create') }}" class="btn btn-dark waves-
effect"><i class="material-icons">add</i><strong>Dodaj</strong></a>
        </h2>
    </div>
@endsection

@section('content')

    @php($i = 1)

    <div class="table-responsive">
        <table class="table table-striped">
            <thead>
                <tr class="dark">
                    <th>Pozicija</th>
                    <th>Ime</th>
                    <th>Putanja</th>
                    <th>Izmeni</th>
                    <th>Obriši</th>
                </tr>
            </thead>
            <tbody>

                @foreach($menus as $menu)

                    <tr>
                        <td>{{ $menu->position }}</td>
                        <td>{{ $menu->name }}</td>
                        <td>{{ $menu->route }}</td>
                        <td><a href="{{ url('/admin/menus/' . $menu->id . '/edit') }}"
class="btn btn-dark waves-effect btn-xs"><i class="material-
icons">edit</i></a></td>
                        <td>
                            <a class="btn dtp-btn-clear waves-effect btn-xs" href="#"
data-toggle="modal" data-target="#delete-modal{{ $i }}">
                                <i class="material-icons">delete_forever</i>

```

```

        </a>
        <div class="modal fade" id="delete-modal{{ $i++ }}"
role="dialog">
            <div class="modal-dialog modal-sm text-center">
                <div class="modal-content">
                    <div class="modal-body">
                        <button type="button" class="close" data-
dismiss="modal">
                            &times;
                        </button>
                        <h4>Da li ste sigurni?</h4>
                        <button type="button" class="btn btn-
danger waves-effect" onClick="deletion({{ $menu->id }}, '{{ $menu->getTable()
}}');">
                            Obriši
                        </button>
                    </div>
                </div>
            </div>
        </div>
    </td>
</tr>
</tbody>
</table>
</div>
<div class="text-center">{{ $menus->links() }}</div>
@endsection

```

#### 4.5.1.1.1.3. payments

##### 4.5.1.1.1.3.1. index.blade.php

```

@extends('layouts.back')

@section('content')
    <payments-table></payments-table>
@endsection

```

#### 4.5.1.1.1.4. posts

##### 4.5.1.1.1.4.1. create.blade.php

```

@extends('layouts.back')

@section('header')
    <div class="header">
        <h2>

```

```

        <i class="material-icons icon_left">border_color</i> Postovi<a
href="#" onclick="history.back(-1)"><i class="material-icons pull-
right">keyboard_return</i><i class="pull-right go_back">Nazad</i></a>
        <small>Dodavanje postova</small>
    </h2>
</div>
@endsection

@section('content')

    <div class="body">
        <div class="row">
            <div class="col-md-4 col-md-offset-4">

                @isset($errors)
                    @foreach($errors->all() as $error)
                        <div class="alert alert-warning">
                            {{ $error }}
                        </div>
                    @endforeach
                @endisset

                <p class="lead">Dodaj post</p>
                <form action="{{ url('/admin/posts') }}" method="POST"
enctype="multipart/form-data">
                    @csrf
                    <div class="form-group">
                        <div class="form-line">
                            <input name="title" id="title" type="text"
class="form-control" placeholder="Naslov" required />
                        </div>
                    </div>
                    <div class="form-group">
                        <div class="form-line">
                            <textarea name="contentP" id="contentP" class="form-
control" placeholder="Sadržaj" rows="15" required ></textarea>
                        </div>
                    </div>
                    <div class="form-group">
                        <input name="user_id" id="user_id" type="hidden"
class="form-control" value="{{ session('user')->id }}" />
                    </div>
                    <div class="form-group">
                        <label for="image"><i>Slika:</i></label>
                        <input type="file" name="image" id="image" required />
                        (max. 2MB)
                    <br/>
                    </div>
                    <div class="form-group">
                        <button type="submit" name="postBtn" id="postBtn"
class="btn btn-dark waves-effect waves-light">Dodaj</button>
                        <a href="#" onclick="history.back(-1)" class="btn waves-
effect">Otkazi</a>
                    </div>
                </form>
            </div>
        </div>
    </div>
@endsection

```

#### 4.5.1.1.1.4.2. edit.blade.php

```
@extends('layouts.back')

@section('header')
    <div class="header">
        <h2>
            <i class="material-icons icon_left">border_color</i> Postovi<a
href="#" onclick="history.back(-1)"><i class="material-icons pull-
right">keyboard_return</i><i class="pull-right go_back">Nazad</i></a>
            <small>Izmena postova</small>
        </h2>
    </div>
@endsection

@section('content')
    <div class="body">
        <div class="row">
            <div class="col-md-4 col-md-offset-4">

                @isset($errors)
                    @foreach($errors->all() as $error)
                        <div class="alert alert-warning">
                            {{ $error }}
                        </div>
                    @endforeach
                @endisset

                <p class="lead">Izmeni post</p>
                <form action="{{ url('/admin/posts/' . $post->id) }}" method="POST"
enctype="multipart/form-data">
                    @method('PATCH')
                    @csrf
                    <div class="form-group">
                        <div class="form-line">
                            <input name="title" id="title" type="text"
class="form-control" placeholder="Naslov" required value="{{ $post->title }}" />
                        </div>
                    </div>
                    <div class="form-group">
                        <div class="form-line">
                            <textarea name="contentP" id="contentP" class="form-
control" placeholder="Sadržaj" rows="15" required >{{ $post->content }}</textarea>
                        </div>
                    </div>
                    <div class="form-group">
                        <input name="user_id" id="user_id" type="hidden"
class="form-control" value="{{ session('user')->id }}" />
                    </div>
                    <div class="form-group">
                        
                    </div>
                    <div class="form-group">
                        <label for="image"><i>Slika:</i></label>
                    </div>
                </div>
            </div>
        </div>
    </div>
@endsection
```



```

        <input type="file" name="image" id="image" required />
        (max. 2MB)
    </div>
    <div class="form-group">
        <button type="submit" name="postBtn" id="postBtn"
class="btn btn-dark waves-effect waves-light">Izmeni</button>
        <a href="#" onclick="history.back(-1)" class="btn waves-
effect">Otkazi</a>
    </div>
</form>
</div>
</div>
</div>
@endsection

```

#### 4.5.1.1.4.3. index.blade.php

```

@extends('layouts.back')

@section('header')
    <div class="header">
        <h2>
            <i class="material-icons icon_left">border_color</i> Postovi<a
href="#" onclick="history.back(-1)"><i class="material-icons pull-
right">keyboard_return</i><i class="pull-right go_back">Nazad</i></a>
            <small>Prikaz svih postova</small>
            <br/>
            <a href="{{ url('admin/posts/create') }}" class="btn btn-dark waves-
effect"><i class="material-icons">add</i><strong>Dodaj</strong></a>
        </h2>
    </div>
@endsection

@section('content')

    @php($i = 1)

    <br/>

    @foreach($posts as $post)

        <div class="container-fluid">
            <div class="row">
                <div class="col-lg-12 col-md-12 col-sm-12 col-xs-12">
                    <div class="card">
                        <div class="header">
                            <h2>
                                {{ $post->title }}
                            </h2>
                            <ul class="header-dropdown m-r--5">
                                <li class="dropdown">
                                    <a href="javascript:void(0);" class="dropdown-
toggle" data-toggle="dropdown" role="button" aria-haspopup="true" aria-
expanded="false">
                                        <i class="material-icons">more_vert</i>

```



```
@endsection
```

#### 4.5.1.1.1.5. prices

##### 4.5.1.1.1.5.1. create.blade.php

```
@extends('layouts.back')

@section('header')
    <div class="header">
        <h2>
            <i class="material-icons icon_left">euro_symbol</i> Cene<a href="#"
onclick="history.back(-1)"><i class="material-icons pull-
right">keyboard_return</i><i class="pull-right go_back">Nazad</i></a>
            <small>Dodavanje cena</small>
        </h2>
    </div>
@endsection

@section('content')
    <div class="body">
        <div class="row">
            <div class="col-md-4 col-md-offset-4">

                @isset($errors)
                    @foreach($errors->all() as $error)
                        <div class="alert alert-warning">
                            {{ $error }}
                        </div>
                    @endforeach
                @endisset

                <p class="lead">Dodaj cenu</p>
                <form action="{{ url('/admin/prices') }}" method="POST">
                    @csrf
                    <div class="form-group">
                        <div class="form-line">
                            <input name="title" id="title" type="text"
class="form-control" placeholder="Naziv paketa" required />
                        </div>
                    </div>
                    <div class="form-group">
                        <div class="form-line">
                            <input name="sessions" id="sessions" type="number"
class="form-control" placeholder="Broj termina" required />
                        </div>
                    </div>
                    <div class="form-group">
                        <div class="form-line">
                            <input name="amount" id="amount" type="number"
class="form-control" placeholder="Iznos" required />
                        </div>
                    </div>
                </div>
            </div>
        </div>
    </div>
endsection
```

```

        <button type="submit" name="priceBtn" id="priceBtn"
class="btn btn-dark waves-effect waves-light">Dodaj</button>
        <a href="#" onclick="history.back(-1)" class="btn waves-
effect">Otkazi</a>
    </div>
</form>
</div>
</div>
</div>
</div>
@endsection

```

#### 4.5.1.1.5.2. edit.blade.php

```

@extends('layouts.back')

@section('header')
    <div class="header">
        <h2>
            <i class="material-icons icon_left">euro_symbol</i> Cene<a href="#"
onclick="history.back(-1)"><i class="material-icons pull-
right">keyboard_return</i><i class="pull-right go_back">Nazad</i></a>
            <small>Izmena cena</small>
        </h2>
    </div>
@endsection

@section('content')

    <div class="body">
        <div class="row">
            <div class="col-md-4 col-md-offset-4">

                @isset($errors)
                    @foreach($errors->all() as $error)
                        <div class="alert alert-warning">
                            {{ $error }}
                        </div>
                    @endforeach
                @endisset

                <p class="lead">Izmeni cenu</p>
                <form action="{{ url('/admin/prices/' . $price->id) }}"
method="POST">

                    @method('PATCH')
                    @csrf
                    <div class="form-group">
                        <div class="form-line">
                            <input name="title" id="title" type="text"
class="form-control" placeholder="Naziv paketa" required value="{{ $price->title
}}"/>
                        </div>
                    </div>
                    <div class="form-group">
                        <div class="form-line">
                            <input name="sessions" id="sessions" type="number"
class="form-control" placeholder="Broj termina" required value="{{ $price-

```

```

>sessions }}" />
        </div>
    </div>
    <div class="form-group">
        <div class="form-line">
            <input name="amount" id="amount" type="number"
class="form-control" placeholder="Iznos" required value="{{ $price->amount }}" />
        </div>
    </div>
    <div class="form-group">
        <button type="submit" name="priceBtn" id="priceBtn"
class="btn btn-dark waves-effect waves-light">Izmeni</button>
        <a href="#" onclick="history.back(-1)" class="btn waves-
effect">Otkaži</a>
    </div>
</form>
</div>
</div>
</div>
@endsection

```

#### 4.5.1.1.5.3. index.blade.php

```

@extends('layouts.back')

@section('header')
    <div class="header">
        <h2>
            <i class="material-icons icon_left">euro_symbol</i> Cene<a href="#"
onclick="history.back(-1)"><i class="material-icons pull-
right">keyboard_return</i><i class="pull-right go_back">Nazad</i></a>
            <small>Prikaz svih cena</small>
            <hr/>
            <a href="{{ url('admin/prices/create') }}" class="btn btn-dark waves-
effect"><i class="material-icons">add</i><strong>Dodaj</strong></a>
        </h2>
    </div>
@endsection

@section('content')

    @php($i = 1)

    <div class="table-responsive">
        <table class="table table-striped">
            <thead>
                <tr class="dark">
                    <th>Naziv paketa</th>
                    <th>Broj termina</th>
                    <th>Iznos</th>
                    <th>Izmeni</th>
                    <th>Obriši</th>
                </tr>
            </thead>
            <tbody>

```

```

        @foreach($prices as $price)

            <tr>
                <td>{{ $price->title }}</td>
                <td>{{ $price->sessions }}</td>
                <td>{{ $price->amount }} din.</td>
                <td><a href="{{ url('/admin/prices/' . $price->id . '/edit') }}"
class="btn btn-dark waves-effect btn-xs"><i class="material-
icons">edit</i></a></td>
                <td>
                    <a class="btn dtp-btn-clear waves-effect btn-xs" href="#"
data-toggle="modal" data-target="#delete-modal{{ $i }}">
                        <i class="material-icons">delete_forever</i>
                    </a>
                    <div class="modal fade" id="delete-modal{{ $i++ }}"
role="dialog">
                        <div class="modal-dialog modal-sm text-center">
                            <div class="modal-content">
                                <div class="modal-body">
                                    <button type="button" class="close" data-
dismiss="modal">
                                        &times;
                                    </button>
                                    <h4>Da li ste sigurni?</h4>
                                    <button type="button" class="btn btn-
danger waves-effect" onClick="deletion({{ $price->id }}, '{{ $price->getTable()
}}')";">
                                        Obriši
                                    </button>
                                </div>
                            </div>
                        </div>
                    </div>
                </td>
            </tr>

        @endforeach

    </tbody>
</table>
</div>

    <div class="text-center">{{ $prices->links() }}</div>
@endsection

```

#### 4.5.1.1.1.6. services

##### 4.5.1.1.1.6.1. create.blade.php

```

@extends('layouts.back')

@section('header')
    <div class="header">
        <h2>
            <i class="material-icons icon_left">group_work</i> Usluge<a href="#"
onClick="history.back(-1)"><i class="material-icons pull-

```

```

right">keyboard_return</i><i class="pull-right go_back">Nazad</i></a>
    <small>Dodavanje usluga</small>
</h2>
</div>
@endsection

@section('content')

    <div class="body">
        <div class="row">
            <div class="col-md-4 col-md-offset-4">

                @isset($errors)
                    @foreach($errors->all() as $error)
                        <div class="alert alert-warning">
                            {{ $error }}
                        </div>
                    @endforeach
                @endisset

                <p class="lead">Dodaj uslugu</p>
                <form action="{{ url('/admin/services') }}" method="POST">
                    @csrf
                    <div class="form-group">
                        <div class="form-line">
                            <input name="name" id="name" type="text" class="form-
control" placeholder="Naziv" required />
                        </div>
                    </div>
                    <div class="form-group">
                        <select name="price_id" id="price_id">
                            <option value="0">Izaberi cenovnu
kategoriju...</option>

                                @foreach($prices as $price)
                                    <option value="{{ $price->id }}">{{ $price->amount
}} din.</option>

                                @endforeach

                                </select>
                            </div>
                            <div class="form-group">
                                <button type="submit" name="serviceBtn" id="serviceBtn"
class="btn btn-dark waves-effect waves-light">Dodaj</button>
                                <a href="#" onclick="history.back(-1)" class="btn waves-
effect">Otkazi</a>
                            </div>
                        </form>
                    </div>
                </div>
            </div>
        </div>
    @endsection

```

#### 4.5.1.1.6.2. edit.blade.php

```

@extends('layouts.back')

@section('header')
    <div class="header">
        <h2>
            <i class="material-icons icon_left">group_work</i> Usluge<a href="#"
onclick="history.back(-1)"><i class="material-icons pull-
right">keyboard_return</i><i class="pull-right go_back">Nazad</i></a>
            <small>Izmena usluga</small>
        </h2>
    </div>
@endsection

@section('content')
    <div class="body">
        <div class="row">
            <div class="col-md-4 col-md-offset-4">

                @isset($errors)
                    @foreach($errors->all() as $error)
                        <div class="alert alert-warning">
                            {{ $error }}
                        </div>
                    @endforeach
                @endisset

                <p class="lead">Izmeni uslugu</p>
                <form action="{{ url('/admin/services/' . $service->id) }}"
method="POST">
                    @method('PATCH')
                    @csrf
                    <div class="form-group">
                        <div class="form-line">
                            <input name="name" id="name" type="text" class="form-
control" placeholder="Naziv" required value="{{ $service->name }}" />
                        </div>
                    </div>
                    <div class="form-group">
                        <select name="price_id" id="price_id">
                            <option value="{{ $service->price->id }}">${{
$service->price->amount }}</option>
                            @foreach($prices as $price)
                                <option value="{{ $price->id }}">{{ $price->amount
}} din.</option>
                            @endforeach
                        </select>
                    </div>
                    <div class="form-group">
                        <button type="submit" name="serviceBtn" id="serviceBtn"
class="btn btn-dark waves-effect waves-light">Izmeni</button>
                        <a href="#" onclick="history.back(-1)" class="btn waves-
effect">Otkazi</a>
                    </div>
                </form>
            </div>
        </div>
    </div>

```



```
@endsection
```

#### 4.5.1.1.1.6.3. index.blade.php

```
@extends('layouts.back')

@section('header')
    <div class="header">
        <h2>
            <i class="material-icons icon_left">group_work</i> Usluge<a href="#"
onclick="history.back(-1)"><i class="material-icons pull-
right">keyboard_return</i><i class="pull-right go_back">Nazad</i></a>
            <small>Prikaz svih usluga</small>
            <hr/>
            <a href="{{ url('admin/services/create') }}" class="btn btn-dark
waves-effect"><i class="material-icons">add</i><strong>Dodaj</strong></a>
        </h2>
    </div>
@endsection

@section('content')

    @php($i = 1)

    <div class="table-responsive">
        <table class="table table-striped">
            <thead>
                <tr class="dark">
                    <th>Cenovna kategorija</th>
                    <th>Naziv</th>
                    <th>Izmeni</th>
                    <th>Obriši</th>
                </tr>
            </thead>
            <tbody>

                @foreach($services as $service)

                    <tr>
                        <td>{{ $service->price->amount }} din.</td>
                        <td>{{ $service->name }}</td>
                        <td><a href="{{ url('/admin/services/' . $service->id . '/edit') }}"
class="btn btn-dark waves-effect btn-xs"><i class="material-
icons">edit</i></a></td>
                        <td>
                            <a class="btn dtp-btn-clear waves-effect btn-xs" href="#"
data-toggle="modal" data-target="#delete-modal{{ $i }}">
                                <i class="material-icons">delete_forever</i>
                            </a>
                            <div class="modal fade" id="delete-modal{{ $i++ }}"
role="dialog">
                                <div class="modal-dialog modal-sm text-center">
                                    <div class="modal-content">
                                        <div class="modal-body">
                                            <button type="button" class="close" data-
dismiss="modal">
```

```

                                &times;
                                </button>
                                <h4>Da li ste sigurni?</h4>
                                <button type="button" class="btn btn-
danger waves-effect" onClick="deletion({{ $service->id }}, '{{ $service-
>getTable() }})';">
                                Obriši
                                </button>
                                </div>
                                </div>
                                </div>
                                </div>
                                </td>
                                </tr>

                                @endforeach

                                </tbody>
                                </table>
                                </div>

                                <div class="text-center">{{ $services->links() }}</div>
@endsection

```

#### 4.5.1.1.1.7. sliders

##### 4.5.1.1.1.7.1. create.blade.php

```

@extends('layouts.back')

@section('header')
    <div class="header">
        <h2>
            <i class="material-icons icon_left">burst_mode</i> Slider slike<a
href="#" onClick="history.back(-1)"><i class="material-icons pull-
right">keyboard_return</i><i class="pull-right go_back">Nazad</i></a>
            <small>Dodavanje slider slika</small>
        </h2>
    </div>
@endsection

@section('content')
    <div class="body">
        <div class="row">
            <div class="col-md-4 col-md-offset-4">

                @isset($errors)
                    @foreach($errors->all() as $error)
                        <div class="alert alert-warning">
                            {{ $error }}
                        </div>
                    @endforeach
                @endisset

                <p class="lead">Dodaj slider sliku</p>
            </div>
        </div>
    </div>

```

```

        <form action="{{ url('/admin/sliders') }}" method="POST"
    enctype="multipart/form-data">
        @csrf
        <div class="form-group">
            <div class="form-line">
                <input name="position" id="position" type="number"
    class="form-control" placeholder="Pozicija" required />
            </div>
        </div>
        <div class="form-group">
            <label for="image"><i>Slika:</i></label>
            <input type="file" name="image" id="image" required />
            (max. 2MB)
            <br/>
        </div>
        <div class="form-group">
            <button type="submit" name="sliderBtn" id="sliderBtn"
    class="btn btn-dark waves-effect waves-light">Dodaj</button>
            <a href="#" onclick="history.back(-1)" class="btn waves-
    effect">Otkazi</a>
        </div>
    </form>
</div>
</div>
</div>
@endsection

```

#### 4.5.1.1.7.2. edit.blade.php

```

@extends('layouts.back')

@section('header')
    <div class="header">
        <h2>
            <i class="material-icons icon_left">burst_mode</i> Slider slike<a
    href="#" onclick="history.back(-1)"><i class="material-icons pull-
    right">keyboard_return</i><i class="pull-right go_back">Nazad</i></a>
            <small>Izmena slider slika</small>
        </h2>
    </div>
@endsection

@section('content')
    <div class="body">
        <div class="row">
            <div class="col-md-4 col-md-offset-4">

                @isset($errors)
                    @foreach($errors->all() as $error)
                        <div class="alert alert-warning">
                            {{ $error }}
                        </div>
                    @endforeach
                @endisset

            </div>
        </div>
    </div>

```

```

        <p class="lead">Izmeni slider sliku</p>
        <form action="{{ url('/admin/sliders/' . $slider->id) }}"
method="POST" enctype="multipart/form-data">
            @method('PATCH')
            @csrf
            <div class="form-group">
                <div class="form-line">
                    <input name="position" id="position" type="number"
class="form-control" placeholder="Pozicija" required value="{{ $slider->position
}}" />
                </div>
            </div>
            <div class="form-group">
                
            </div>
            <div class="form-group">
                <label for="image"><i>Slika:</i></label>
                <input type="file" name="image" id="image" required />
                (max. 2MB)
                <br/>
            </div>
            <div class="form-group">
                <button type="submit" name="sliderBtn" id="sliderBtn"
class="btn btn-dark waves-effect waves-light">Izmeni</button>
                <a href="#" onclick="history.back(-1)" class="btn waves-
effect">Otkazi</a>
            </div>
        </form>
    </div>
</div>
</div>
@endsection

```

#### 4.5.1.1.7.3. index.blade.php

```

@extends('layouts.back')

@section('header')
    <div class="header">
        <h2>
            <i class="material-icons icon_left">burst_mode</i> Slider slike<a
href="#" onclick="history.back(-1)"><i class="material-icons pull-
right">keyboard_return</i><i class="pull-right go_back">Nazad</i></a>
            <small>Prikaz svih slider slika</small>
            <hr/>
            <a href="{{ url('admin/sliders/create') }}" class="btn btn-dark waves-
effect"><i class="material-icons">add</i><strong>Dodaj</strong></a>
        </h2>
    </div>
@endsection

@section('content')
    @php($i = 1)

```

```

<div class="table-responsive">
  <table class="table table-striped">
    <thead>
      <tr class="dark">
        <th>Pozicija</th>
        <th>Slika</th>
        <th>Izmeni</th>
        <th>Obriši</th>
      </tr>
    </thead>
    <tbody>

      @foreach($sliders as $slider)

        <tr>
          <td>{{ $slider->position }}</td>
          <td></td>
          <td><a href="{{ url('/admin/sliders/' . $slider->id . '/edit') }}"
class="btn btn-dark waves-effect btn-xs"><i class="material-
icons">edit</i></a></td>
          <td>
            <a class="btn dtp-btn-clear waves-effect btn-xs" href="#"
data-toggle="modal" data-target="#delete-modal{{ $i }}">
              <i class="material-icons">delete_forever</i>
            </a>
            <div class="modal fade" id="delete-modal{{ $i++ }}"
role="dialog">
              <div class="modal-dialog modal-sm text-center">
                <div class="modal-content">
                  <div class="modal-body">
                    <button type="button" class="close" data-
dismiss="modal">
                      &times;
                    </button>
                    <h4>Da li ste sigurni?</h4>
                    <button type="button" class="btn btn-
danger waves-effect" onClick="deletion({{ $slider->id }}, '{{ $slider->getTable()
}}')";>
                      Obriši
                    </button>
                  </div>
                </div>
              </div>
            </div>
          </td>
        </tr>

      @endforeach

    </tbody>
  </table>
</div>

<div class="text-center">{{ $sliders->links() }}</div>
@endsection

```

#### 4.5.1.1.1.8. socials

##### 4.5.1.1.1.8.1. create.blade.php

```
@extends('layouts.back')

@section('header')
    <div class="header">
        <h2>
            <i class="material-icons icon_left">share</i> Socijalne mreže<a
href="#" onclick="history.back(-1)"><i class="material-icons pull-
right">keyboard_return</i><i class="pull-right go_back">Nazad</i></a>
            <small>Dodavanje socijalnih mreža</small>
        </h2>
    </div>
@endsection

@section('content')
    <div class="body">
        <div class="row">
            <div class="col-md-4 col-md-offset-4">

                @isset($errors)
                    @foreach($errors->all() as $error)
                        <div class="alert alert-warning">
                            {{ $error }}
                        </div>
                    @endforeach
                @endisset

                <p class="lead">Dodaj socijalnu mrežu</p>
                <form action="{{ url('/admin/socials') }}" method="POST">
                    @csrf
                    <div class="form-group">
                        <div class="form-line">
                            <input name="name" id="name" type="text" class="form-
control" placeholder="Naziv" required />
                        </div>
                    </div>
                    <div class="form-group">
                        <div class="form-line">
                            <input name="url" id="url" type="url" class="form-
control" placeholder="URL" required />
                        </div>
                    </div>
                    <div class="form-group">
                        <div class="form-line">
                            <input name="icon" id="icon" type="text" class="form-
control" placeholder="Font Awesome ikonica" required />
                        </div>
                    </div>
                    <div class="form-group">
                        <button type="submit" name="socialBtn" id="socialBtn"
class="btn btn-dark waves-effect waves-light">Dodaj</button>
                        <a href="#" onclick="history.back(-1)" class="btn waves-
effect">Otkaži</a>
                    </div>
                </form>
            </div>
        </div>
    </div>
@endsection
```

```

        </div>
    </form>
</div>
</div>
</div>
@endsection

```

#### 4.5.1.1.8.2. edit.blade.php

```

@extends('layouts.back')

@section('header')
    <div class="header">
        <h2>
            <i class="material-icons icon_left">share</i> Socijalne mreže<a
href="#" onclick="history.back(-1)"><i class="material-icons pull-
right">keyboard_return</i><i class="pull-right go_back">Nazad</i></a>
            <small>Izmena socijalnih mreža</small>
        </h2>
    </div>
@endsection

@section('content')

    <div class="body">
        <div class="row">
            <div class="col-md-4 col-md-offset-4">

                @isset($errors)
                    @foreach($errors->all() as $error)
                        <div class="alert alert-warning">
                            {{ $error }}
                        </div>
                    @endforeach
                @endisset

                <p class="lead">Izmeni socijalnu mrežu</p>
                <form action="{{ url('/admin/socials/' . $social->id) }}"
method="POST">

                    @method('PATCH')
                    @csrf
                    <div class="form-group">
                        <div class="form-line">
                            <input name="name" id="name" type="text" class="form-
control" placeholder="Naziv" required value="{{ $social->name }}" />
                        </div>
                    </div>
                    <div class="form-group">
                        <div class="form-line">
                            <input name="url" id="url" type="url" class="form-
control" placeholder="URL" required value="{{ $social->url }}" />
                        </div>
                    </div>
                    <div class="form-group">
                        <div class="form-line">
                            <input name="icon" id="icon" type="text" class="form-

```

```

control" placeholder="Font Awesome ikonica" required value="{{ $social->icon }}"
/>
        </div>
    </div>
    <div class="form-group">
        <button type="submit" name="socialBtn" id="socialBtn"
class="btn btn-dark waves-effect waves-light">Izmeni</button>
        <a href="#" onclick="history.back(-1)" class="btn waves-
effect">Otkazi</a>
    </div>
</form>
</div>
</div>
</div>
</div>
@endsection

```

#### 4.5.1.1.8.3. index.blade.php

```

@extends('layouts.back')

@section('header')
    <div class="header">
        <h2>
            <i class="material-icons icon_left">share</i> Socijalne mreže<a
href="#" onclick="history.back(-1)"><i class="material-icons pull-
right">keyboard_return</i><i class="pull-right go_back">Nazad</i></a>
            <small>Prikaz svih socijalnih mreža</small>
            <hr/>
            <a href="{{ url('admin/socials/create') }}" class="btn btn-dark waves-
effect"><i class="material-icons">add</i><strong>Dodaj</strong></a>
        </h2>
    </div>
@endsection

@section('content')

    @php($i = 1)

    <div class="table-responsive">
        <table class="table table-striped">
            <thead>
                <tr class="dark">
                    <th>Naziv</th>
                    <th>Ikonica/URL</th>
                    <th>Izmeni</th>
                    <th>Obriši</th>
                </tr>
            </thead>
            <tbody>

                @foreach($socials as $social)

                    <tr>
                        <td>{{ $social->name }}</td>
                        <td><a href="{{ $social->url }}" class="fa fa-{{ $social->icon
}}"></a></td>

```



```

                <td><a href="{{ url('/admin/socials/' . $social->id . '/edit') }}"
class="btn btn-dark waves-effect btn-xs"><i class="material-
icons">edit</i></a></td>
                <td>
                    <a class="btn dtp-btn-clear waves-effect btn-xs" href="#"
data-toggle="modal" data-target="#delete-modal{{ $i }}">
                        <i class="material-icons">delete_forever</i>
                    </a>
                    <div class="modal fade" id="delete-modal{{ $i++ }}"
role="dialog">
                        <div class="modal-dialog modal-sm text-center">
                            <div class="modal-content">
                                <div class="modal-body">
                                    <button type="button" class="close" data-
dismiss="modal">
                                        &times;
                                    </button>
                                    <h4>Da li ste sigurni?</h4>
                                    <button type="button" class="btn btn-
danger waves-effect" onclick="deletion('{{ $social->id }}', '{{ $social->getTable()
}}');">
                                        Obriši
                                    </button>
                                </div>
                            </div>
                        </div>
                    </div>
                </td>
            </tr>
        </tbody>
    </table>
</div>

    <div class="text-center">{{ $socials->links() }}</div>
@endsection

```

#### 4.5.1.1.1.9. trainers

##### 4.5.1.1.1.9.1. create.blade.php

```

@extends('layouts.back')

@section('header')
    <div class="header">
        <h2>
            <i class="material-icons icon_left">sports</i> Treneri<a href="#"
onclick="history.back(-1)"><i class="material-icons pull-
right">keyboard_return</i><i class="pull-right go_back">Nazad</i></a>
            <small>Dodavanje trenera</small>
        </h2>
    </div>
@endsection

```

```

@section('content')

    <div class="body">
        <div class="row">
            <div class="col-md-4 col-md-offset-4">

                @isset($errors)
                    @foreach($errors->all() as $error)
                        <div class="alert alert-warning">
                            {{ $error }}
                        </div>
                    @endforeach
                @endisset

                <p class="lead">Dodaj trenera</p>
                <form action="{{ url('/admin/trainers') }}" method="POST">
                    @csrf
                    <div class="form-group">
                        <div class="form-line">
                            <input name="first_name" id="first_name" type="text"
class="form-control" placeholder="Ime" required />
                        </div>
                    </div>
                    <div class="form-group">
                        <div class="form-line">
                            <input name="last_name" id="last_name" type="text"
class="form-control" placeholder="Prezime" required />
                        </div>
                    </div>
                    <div class="form-group">
                        <button type="submit" name="trainerBtn" id="trainerBtn"
class="btn btn-dark waves-effect waves-light">Dodaj</button>
                        <a href="#" onclick="history.back(-1)" class="btn waves-
effect">Otkaži</a>
                    </div>
                </form>
            </div>
        </div>
    </div>

@endsection

```

#### 4.5.1.1.9.2. edit.blade.php

```

@extends('layouts.back')

@section('header')
    <div class="header">
        <h2>
            <i class="material-icons icon_left">sports</i> Cene<a href="#"
onclick="history.back(-1)"><i class="material-icons pull-
right">keyboard_return</i><i class="pull-right go_back">Nazad</i></a>
            <small>Izmena trenera</small>
        </h2>
    </div>
@endsection

```

```

@section('content')

    <div class="body">
        <div class="row">
            <div class="col-md-4 col-md-offset-4">

                @isset($errors)
                    @foreach($errors->all() as $error)
                        <div class="alert alert-warning">
                            {{ $error }}
                        </div>
                    @endforeach
                @endisset

                <p class="lead">Izmeni trenera</p>
                <form action="{{ url('/admin/trainers/'. $trainer->id) }}"
method="POST">

                    @method('PATCH')
                    @csrf
                    <div class="form-group">
                        <div class="form-line">
                            <input name="first_name" id="first_name" type="text"
class="form-control" placeholder="Ime" required value="{{ $trainer->first_name }}"
/>
                        </div>
                    </div>
                    <div class="form-group">
                        <div class="form-line">
                            <input name="last_name" id="last_name" type="text"
class="form-control" placeholder="Prezime" required value="{{ $trainer->last_name
}}"/>
                        </div>
                    </div>
                    <div class="form-group">
                        <button type="submit" name="trainerBtn" id="trainerBtn"
class="btn btn-dark waves-effect waves-light">Izmeni</button>
                        <a href="#" onclick="history.back(-1)" class="btn waves-
effect">Otkaži</a>
                    </div>
                </form>
            </div>
        </div>
    </div>

@endsection

```

#### 4.5.1.1.9.3. index.blade.php

```

@extends('layouts.back')

@section('header')
    <div class="header">
        <h2>
            <i class="material-icons icon_left">sports</i> Treneri<a href="#"
onclick="history.back(-1)"><i class="material-icons pull-
right">keyboard_return</i><i class="pull-right go_back">Nazad</i></a>
            <small>Prikaz svih trenera</small>
        </h2>
    </div>

```

```

        <hr/>
        <a href="{{ url('admin/trainers/create') }}" class="btn btn-dark
waves-effect"><i class="material-icons">add</i><strong>Dodaj</strong></a>
    </h2>
</div>
@endsection

@section('content')

    @php($i = 1)

    <div class="table-responsive">
        <table class="table table-striped">
            <thead>
                <tr class="dark">
                    <th>Ime</th>
                    <th>Prezime</th>
                    <th>Izmeni</th>
                    <th>Obriši</th>
                </tr>
            </thead>
            <tbody>

                @foreach($trainers as $trainer)

                    <tr>
                        <td>{{ $trainer->first_name }}</td>
                        <td>{{ $trainer->last_name }}</td>
                        <td><a href="{{ url('admin/trainers/' . $trainer->id . '/edit') }}"
class="btn btn-dark waves-effect btn-xs"><i class="material-
icons">edit</i></a></td>
                        <td>
                            <a class="btn dtp-btn-clear waves-effect btn-xs" href="#"
data-toggle="modal" data-target="#delete-modal{{ $i }}">
                                <i class="material-icons">delete_forever</i>
                            </a>
                            <div class="modal fade" id="delete-modal{{ $i++ }}"
role="dialog">
                                <div class="modal-dialog modal-sm text-center">
                                    <div class="modal-content">
                                        <div class="modal-body">
                                            <button type="button" class="close" data-
dismiss="modal">
                                                &times;
                                            </button>
                                            <h4>Da li ste sigurni?</h4>
                                            <button type="button" class="btn btn-
danger waves-effect" onClick="deletion({{ $trainer->id }}, '{{ $trainer-
>getTable() }}')";>
                                                Obriši
                                            </button>
                                        </div>
                                    </div>
                                </div>
                            </td>
                        </tr>

                @endforeach

```

```

        </tbody>
    </table>
</div>

<div class="text-center">{{ $trainers->links() }}</div>
@endsection

```

#### 4.5.1.1.10. trainings

##### 4.5.1.1.10.1. create.blade.php

```

@extends('layouts.back')

@section('header')
    <div class="header">
        <h2>
            <i class="material-icons icon_left">fitness_center</i> Treninzi<a
href="#" onclick="history.back(-1)"><i class="material-icons pull-
right">keyboard_return</i><i class="pull-right go_back">Nazad</i></a>
            <small>Dodavanje treninga</small>
        </h2>
    </div>
@endsection

@section('content')
    <div class="body">
        <div class="row">
            <div class="col-md-4 col-md-offset-4">

                @isset($errors)
                    @foreach($errors->all() as $error)
                        <div class="alert alert-warning">
                            {{ $error }}
                        </div>
                    @endforeach
                @endisset

                <p class="lead">Dodaj trening</p>
                <form action="{{ url('/admin/trainings') }}" method="POST"
enctype="multipart/form-data">
                    @csrf
                    <div class="form-group">
                        <div class="form-line">
                            <input name="name" id="name" type="text" class="form-
control" placeholder="Naziv" required />
                        </div>
                    </div>
                    <div class="form-group">
                        <div class="form-line">
                            <input name="duration" id="duration" type="number"
class="form-control" placeholder="Trajanje (u minutima)" required />
                        </div>
                    </div>
                    <div class="form-group">
                        <div class="form-line">

```

```

        <input name="capacity" id="capacity" type="number"
class="form-control" placeholder="Kapacitet" required />
    </div>
</div>
<div class="form-group">
    <div class="form-line">
        <input name="intensity" id="intensity" type="text"
class="form-control" placeholder="Intenzitet" required />
    </div>
</div>
<div class="form-group">
    <div class="form-line">
        <input name="target" id="target" type="text"
class="form-control" placeholder="Ciljna grupa" required />
    </div>
</div>
<div class="form-group">
    <div class="form-line">
        <textarea name="benefits" id="benefits" class="form-
control" placeholder="Pogodnosti" rows="7" required ></textarea>
    </div>
</div>
<div class="form-group">
    <div class="form-line">
        <textarea name="description" id="description"
class="form-control" placeholder="Opis" rows="7" required ></textarea>
    </div>
</div>
<div class="form-group">
    <label for="logo"><p><i>Logo:</i></p></label>
    <input type="file" name="logo" id="logo" />
    (max. 2MB, 360x450)
    <br/>
</div>
<div class="form-group">
    <label for="image"><p><i>Slika:</i></p></label>
    <input type="file" name="image" id="image" />
    (max. 2MB)
    <br/>
</div>
<div class="form-group">
    <p><b><i>Rezervacije:</i></b></p>
    <input id="reservation-1" name="reservations" type="radio"
value=1>
    <label for="reservation-1"> Da </label>
    <input id="reservation-0" name="reservations" type="radio"
value=0>
    <label for="reservation-0"> Ne </label>
</div>
<div class="form-group">
    <button type="submit" name="trainingBtn" id="trainingBtn"
class="btn btn-dark waves-effect waves-light">Dodaj</button>
    <a href="#" onclick="history.back(-1)" class="btn waves-
effect">Otkaži</a>
</div>
</form>
</div>
</div>

```

```
@endsection
```

#### 4.5.1.1.10.2. edit.blade.php

```
@extends('layouts.back')

@section('header')
    <div class="header">
        <h2>
            <i class="material-icons icon_left">fitness_center</i> Treninzi<a
href="#" onclick="history.back(-1)"><i class="material-icons pull-
right">keyboard_return</i><i class="pull-right go_back">Nazad</i></a>
            <small>Izmena treninga</small>
        </h2>
    </div>
@endsection

@section('content')
    <div class="body">
        <div class="row">
            <div class="col-md-4 col-md-offset-4">

                @isset($errors)
                    @foreach($errors->all() as $error)
                        <div class="alert alert-warning">
                            {{ $error }}
                        </div>
                    @endforeach
                @endisset

                <p class="lead">Izmeni trening</p>
                <form action="{{ url('/admin/trainings/' . $training->id) }}"
method="POST" enctype="multipart/form-data">
                    @method('PATCH')
                    @csrf
                    <div class="form-group">
                        <div class="form-line">
                            <input name="name" id="name" type="text" class="form-
control" placeholder="Naziv" required value="{{ $training->name }}" />
                        </div>
                    </div>
                    <div class="form-group">
                        <div class="form-line">
                            <input name="duration" id="duration" type="number"
class="form-control" placeholder="Trajanje (u minutima)" required value="{{
$training->duration }}" />
                        </div>
                    </div>
                    <div class="form-group">
                        <div class="form-line">
                            <input name="capacity" id="capacity" type="number"
class="form-control" placeholder="Kapacitet" required value="{{ $training-
>capacity }}" />
                        </div>
                    </div>
                </div>
            </div>
        </div>
    </div>

```

```

        <div class="form-group">
            <div class="form-line">
                <input name="intensity" id="intensity" type="text"
class="form-control" placeholder="Intenzitet" required value="{{ $training-
>intensity }}" />
            </div>
        </div>
        <div class="form-group">
            <div class="form-line">
                <input name="target" id="target" type="text"
class="form-control" placeholder="Ciljna grupa" required value="{{ $training-
>target }}" />
            </div>
        </div>
        <div class="form-group">
            <div class="form-line">
                <textarea name="benefits" id="benefits" class="form-
control" placeholder="Pogodnosti" rows="7" required >{{ $training->benefits
}}</textarea>
            </div>
        </div>
        <div class="form-group">
            <div class="form-line">
                <textarea name="description" id="description"
class="form-control" placeholder="Opis" rows="7" required >{{ $training-
>description }}</textarea>
            </div>
        </div>
        <div class="form-group">
            
        </div>
        <div class="form-group">
            <label for="logo"><p><i>Logo:</i></p></label>
            <input type="file" name="logo" id="logo" />
            (max. 2MB, 360x450)
            <br/>
        </div>
        <div class="form-group">
            
        </div>
        <div class="form-group">
            <label for="image"><p><i>Slika:</i></p></label>
            <input type="file" name="image" id="image" />
            (max. 2MB)
            <br/>
        </div>
        <div class="form-group">
            <p><b><i>Rezervacije:</i></b></p>
            <input id="reservation-1" name="reservations" type="radio"
value=1 @if($training->reservations == true) checked @endif>
            <label for="reservation-1"> Da </label>
            <input id="reservation-0" name="reservations" type="radio"
value=0 @if($training->reservations == false) checked @endif>
            <label for="reservation-0"> Ne </label>
        </div>
        <div class="form-group">
            <button type="submit" name="trainingBtn" id="trainingBtn"
class="btn btn-dark waves-effect waves-light">Izmeni</button>

```



```

                <a href="#" onclick="history.back(-1)" class="btn waves-
effect">Otkazi</a>
            </div>
        </form>
    </div>
</div>
</div>
@endsection

```

#### 4.5.1.1.10.3. index.blade.php

```

@extends('layouts.back')

@section('header')
    <div class="header">
        <h2>
            <i class="material-icons icon_left">fitness_center</i> Treninzi<a
href="#" onclick="history.back(-1)"><i class="material-icons pull-
right">keyboard_return</i><i class="pull-right go_back">Nazad</i></a>
            <small>Prikaz svih treninga</small>
            <hr/>
            <a href="{{ url('admin/trainings/create') }}" class="btn btn-dark
waves-effect"><i class="material-icons">add</i><strong>Dodaj</strong></a>
        </h2>
    </div>
@endsection

@section('content')

    @php($i = 1)

    <div class="table-responsive">
        <table class="table table-striped">
            <thead>
                <tr class="dark">
                    <th>Naziv</th>
                    <th>Trajanje</th>
                    <th>Kapacitet</th>
                    <th>Intenzitet</th>
                    <th>Ciljna grupa</th>
                    <th>Pogodnosti</th>
                    <th>Opis</th>
                    <th>Logo</th>
                    <th>Slika</th>
                    <th>Rezervacije</th>
                    <th>Izmeni</th>
                    <th>Obriši</th>
                </tr>
            </thead>
            <tbody>

                @foreach($trainings as $training)

                    <tr>
                        <td>{{ $training->name }}</td>
                        <td>{{ $training->duration }} min.</td>

```

```

        <td>{{ $training->capacity }}</td>
        <td>{{ $training->intensity }}</td>
        <td>{{ $training->target }}</td>
        <td>{{ $training->benefits }}</td>
        <td>{{ $training->description }}</td>
        <td></td>
        <td></td>
        <td>{{ $training->reservations? 'Da' : 'Ne' }}</td>
        <td><a href="{{ url('/admin/trainings/'.$training->id.'/edit')
}}" class="btn btn-dark waves-effect btn-xs"><i class="material-
icons">edit</i></a></td>
        <td>
            <a class="btn dtp-btn-clear waves-effect btn-xs" href="#"
data-toggle="modal" data-target="#delete-modal{{ $i }}">
                <i class="material-icons">delete_forever</i>
            </a>
            <div class="modal fade" id="delete-modal{{ $i++ }}"
role="dialog">
                <div class="modal-dialog modal-sm text-center">
                    <div class="modal-content">
                        <div class="modal-body">
                            <button type="button" class="close" data-
dismiss="modal">
                                &times;
                            </button>
                            <h4>Da li ste sigurni?</h4>
                            <button type="button" class="btn btn-
danger waves-effect" onClick="deletion({{ $training->id }}, '{{ $training-
>getTable() }}')">
                                Obriši
                            </button>
                        </div>
                    </div>
                </div>
            </div>
        </td>
    </tr>
</tbody>
</table>
</div>

<div class="text-center">{{ $trainings->links() }}</div>
@endsection

```

#### 4.5.1.1.11. users

##### 4.5.1.1.11.1. create.blade.php

```

@extends('layouts.back')

@section('header')

```

```

<div class="header">
  <h2>
    <i class="material-icons icon_left">person</i> Korisnici<a href="#"
onlick="history.back(-1)"><i class="material-icons pull-
right">keyboard_return</i><i class="pull-right go_back">Nazad</i></a>
    <small>Dodavanje korisnika</small>
  </h2>
</div>
@endsection

@section('content')

  <div class="body">
    <div class="row">
      <div class="col-md-4 col-md-offset-4">

        @isset($errors)
          @foreach($errors->all() as $error)
            <div class="alert alert-warning">
              {{ $error }}
            </div>
          @endforeach
        @endisset

        <p class="lead">Dodaj korisnika</p>
        <form action="{{ url('/energijapp/users') }}" method="POST"
enctype="multipart/form-data">
          @csrf
          <div class="form-group">
            <div class="form-line">
              <input name="first_name" id="first_name" type="text"
class="form-control" placeholder="Ime" required />
            </div>
          </div>
          <div class="form-group">
            <div class="form-line">
              <input name="last_name" id="last_name" type="text"
class="form-control" placeholder="Prezime" required />
            </div>
          </div>
          <div class="form-group">
            <div class="form-line">
              <input name="email" id="email" type="email"
class="form-control" placeholder="E-mail" required />
            </div>
          </div>
          <div class="form-group">
            <div class="form-line">
              <input name="password" id="password" type="password"
class="form-control" placeholder="Lozinka" required />
            </div>
          </div>
          <div class="form-group">
            <div class="form-line">
              <input name="phone" id="phone" type="tel" class="form-
control" placeholder="Telefon" required />
            </div>
          </div>
          <br/>
          <div class="form-group">

```

```

        <label for="birth_date"><p><i>Datum
rođenja:</i></p></label>
        <div class="form-line">
            <input name="birth_date" id="birth_date" type="date"
class="form-control" required />
        </div>
    </div>
    @if(session('user')->role->name == 'admin')
        <div class="form-group">
            <p><b><i>Uloga:</i></b></p>
            @foreach($roles as $role)
                <input id="role{{ $role->id }}" name="role_id"
type="radio" value="{{ $role->id }}" />
                <label for="role{{ $role->id }}"> {{
ucfirst($role->name) }} </label>
            @endforeach
        </div>
    @endif
    <div class="form-group">
        <label for="image"><p><i>Slika:</i></p></label>
        <input type="file" name="image" id="image" />
        (max. 2MB, 1:1 razmera)
        <br/>
    </div>
    <br/>
    <div class="form-group">
        <div class="form-line">
            <input name="card_number" id="card_number" type="text"
class="form-control" placeholder="Broj kartice" />
        </div>
    </div>
    <div class="form-group">
        <div class="form-line">
            <input name="address" id="address" type="text"
class="form-control" placeholder="Adresa" required />
        </div>
    </div>
    <div class="form-group">
        <button type="submit" name="userBtn" id="userBtn"
class="btn btn-dark waves-effect waves-light">Dodaj</button>
        <a href="#" onclick="history.back(-1)" class="btn waves-
effect">Otkaži</a>
    </div>
    </form>
</div>
</div>
</div>
@endsection

```

#### 4.5.1.1.12.2. edit.blade.php

```

@extends('layouts.back')

@section('header')
    <div class="header">
        <h2>

```

```

        <i class="material-icons icon_left">person</i> Korisnici<a href="#"
onclick="history.back(-1)"><i class="material-icons pull-
right">keyboard_return</i><i class="pull-right go_back">Nazad</i></a>
        <small>Izmena korisnika</small>
    </h2>
</div>
@endsection

@section('content')

    <div class="body">
        <div class="row">
            <div class="col-md-4 col-md-offset-4">

                @isset($errors)
                    @foreach($errors->all() as $error)
                        <div class="alert alert-warning">
                            {{ $error }}
                        </div>
                    @endforeach
                @endisset

                <p class="lead">Edit a user</p>
                <form action="{{ url('/energijapp/users/' . $user->id) }}"
method="POST" enctype="multipart/form-data">
                    @method('PATCH')
                    @csrf
                    <div class="form-group">
                        <div class="form-line">
                            <input name="first_name" id="first_name" type="text"
class="form-control" placeholder="Ime" value="{{ $user->first_name }}" required />
                        </div>
                    </div>
                    <div class="form-group">
                        <div class="form-line">
                            <input name="last_name" id="last_name" type="text"
class="form-control" placeholder="Prezime" value="{{ $user->last_name }}" required
/>
                        </div>
                    </div>
                    <div class="form-group">
                        <div class="form-line">
                            <input name="email" id="email" type="email"
class="form-control" placeholder="E-mail" value="{{ $user->email }}" required />
                        </div>
                    </div>
                    <div class="form-group">
                        <div class="form-line">
                            <input name="phone" id="phone" type="tel" class="form-
control" placeholder="Telefon" value="{{ $user->phone }}" required />
                        </div>
                    </div>
                    <br/>
                    <div class="form-group">
                        <label for="birth_date"><p><i>Datum
rođenja:</i></p></label>
                        <div class="form-line">
                            <input name="birth_date" id="birth_date" type="date"
class="form-control" value="{{ $user->birth_date }}" required />
                        </div>
                    </div>
                </form>
            </div>
        </div>
    </div>

```

```

        </div>
        @if(session('user')->role->name == 'admin')
            <div class="form-group">
                <p><b><i>Uloga:</i></b></p>
                @foreach($roles as $role)
                    <input id="role{{ $role->id }}" name="role_id"
type="radio" value="{{ $role->id }}" @if($user->role->id == $role->id) checked
@endif />
                    <label for="role{{ $role->id }}"> {{
ucfirst($role->name) }} </label>
                @endforeach
            </div>
        @endif
        <div class="form-group">
            
        </div>
        <div class="form-group">
            <label for="image"><p><i>Slika:</i></p></label>
            <input type="file" name="image" id="image" />
            (max. 2MB, 1:1 razmera)
            <br/>
        </div>
        <br/>
        <div class="form-group">
            <div class="form-line">
                <input name="card_number" id="card_number" type="text"
class="form-control" placeholder="Broj kartice" value="{{ $user->card_number }}"
/>
            </div>
        </div>
        <div class="form-group">
            <div class="form-line">
                <input name="address" id="address" type="text"
class="form-control" placeholder="Adresa" value="{{ $user->address }}" required />
            </div>
        </div>
        <div class="form-group">
            <button type="submit" name="userBtn" id="userBtn"
class="btn btn-dark waves-effect waves-light">Izmeni</button>
            <a href="#" onclick="history.back(-1)" class="btn waves-
effect">Otkazi</a>
        </div>
    </form>
</div>
</div>
@endsection

```

#### 4.5.1.1.12.3. index.blade.php

```

@extends('layouts.back')

@section('header')
    <div class="header">
        <h2>
            <i class="material-icons icon_left">person</i> Korisnici<a href="#"

```

```

onclick="history.back(-1)"><i class="material-icons pull-
right">keyboard_return</i><i class="pull-right go_back">Nazad</i></a>
    <small>Prikaz svih korisnika</small>
    <hr/>
    <a href="{{ url('admin/users/create') }}" class="btn btn-dark waves-
effect"><i class="material-icons">add</i><strong>Dodaj</strong></a>
    </h2>
</div>
@endsection

@section('content')

    @php($i = 1)

    <div class="table-responsive">
        <table class="table table-striped">
            <thead>
                <tr class="dark">
                    <th>Broj kartice</th>
                    <th>Ime</th>
                    <th>Prezime</th>
                    <th>E-mail</th>
                    <th>Uloga</th>
                    <th>Član od</th>
                    <th>Datum rođenja</th>
                    <th>Telefon</th>
                    <th>Adresa</th>
                    <th>Slika</th>
                    <th>Izmeni</th>
                    <th>Obriši</th>
                </tr>
            </thead>
            <tbody>

                @foreach($users as $user)

                    <tr>
                        <td>{{ $user->card_number }}</td>
                        <td>{{ $user->first_name }}</td>
                        <td>{{ $user->last_name }}</td>
                        <td>{{ $user->email }}</td>
                        <td>{{ ucfirst($user->role->name) }}</td>
                        <td>{{ $user->created_at->format('d.m.Y.') }}</td>
                        <td>{{ $user->birth_date }}</td>
                        <td>{{ $user->phone }}</td>
                        <td>{{ $user->address }}</td>
                        <td></td>
                        <td><a href="{{ url('/admin/users/' . $user->id . '/edit') }}"
class="btn btn-dark waves-effect btn-xs"><i class="material-
icons">edit</i></a></td>
                        <td>
                            <a class="btn dtp-btn-clear waves-effect btn-xs" href="#"
data-toggle="modal" data-target="#delete-modal{{ $i }}">
                                <i class="material-icons">delete_forever</i>
                            </a>
                            <div class="modal fade" id="delete-modal{{ $i++ }}"
role="dialog">
                                <div class="modal-dialog modal-sm text-center">
                                    <div class="modal-content">

```

```

        <div class="modal-body">
            <button type="button" class="close" data-
dismiss="modal">
                &times;
            </button>
            <h4>Da li ste sigurni?</h4>
            <button type="button" class="btn btn-danger
waves-effect" onclick="deletion({{ $user->id }}, '{{ $user->getTable() }}');">
                Obriši
            </button>
        </div>
    </div>
</div>
</div>
</td>
</tr>

@endforeach

</tbody>
</table>
</div>

<div class="text-center">{{ $users->links() }}</div>
@endsection

```

#### 4.5.1.1.1.12. home.blade.php

```

@extends('layouts.back')

@section('content')
    @include('back.partials.admin.db_info')
@endsection

```

#### 4.5.1.1.2. energijapp

##### 4.5.1.1.2.1. operator

##### 4.5.1.1.2.1.1. arrivals

##### 4.5.1.1.2.1.1.1. create.blade.php

```

@extends('layouts.back')

@section('header')
    <div class="header">
        <h2>
            <i class="material-icons icon_left">arrow_downward</i> Dolasci<a
href="#" onclick="history.back(-1)"><i class="material-icons pull-
right">keyboard_return</i><i class="pull-right go_back">Nazad</i></a>

```



```

        <small>Dodavanje dolazaka</small>
    </h2>
</div>
@endsection

@section('content')
    <arrival-create payment_id="{!! $id !!}" user_id="{!! $user_id !!}"></arrival-
create>
@endsection

```

#### 4.5.1.1.2.1.1.2. edit.blade.php

```

@extends('layouts.back')

@section('header')
    <div class="header">
        <h2>
            <i class="material-icons icon_left">arrow_downward</i> Dolasci<a
href="#" onclick="history.back(-1)"><i class="material-icons pull-
right">keyboard_return</i><i class="pull-right go_back">Nazad</i></a>
            <small>Izmena dolazaka</small>
        </h2>
    </div>
@endsection

@section('content')
    <arrival-edit arrival_id="{!! $id !!}" user_id="{!! $user_id !!}"></arrival-
edit>
@endsection

```

#### 4.5.1.1.2.1.2. payments

##### 4.5.1.1.2.1.2.1. create.blade.php

```

@extends('layouts.back')

@section('header')
    <div class="header">
        <h2>
            <i class="material-icons icon_left">attach_money</i> Uplate<a href="#"
onclick="history.back(-1)"><i class="material-icons pull-
right">keyboard_return</i><i class="pull-right go_back">Nazad</i></a>
            <small>Dodavanje uplata</small>
        </h2>
    </div>
@endsection

@section('content')
    <payment-create user_id="{!! $id !!}" operator_id="{!! session('user')->id
!!}"></payment-create>
@endsection

```

#### 4.5.1.1.2.1.2.2. edit.blade.php

```
@extends('layouts.back')

@section('header')
    <div class="header">
        <h2>
            <i class="material-icons icon_left">attach_money</i> Uplate<a href="#"
onclick="history.back(-1)"><i class="material-icons pull-
right">keyboard_return</i><i class="pull-right go_back">Nazad</i></a>
            <small>Izmena uplata</small>
        </h2>
    </div>
@endsection

@section('content')
    <payment-edit payment_id="{!! $id !!}" user_id="{!! $user_id !!}"></payment-
edit>
@endsection
```

#### 4.5.1.1.2.1.3. reservations

##### 4.5.1.1.2.1.3.1. index.blade.php

```
@extends('layouts.back')

@section('content')
    <reservations-table></reservations-table>
@endsection
```

#### 4.5.1.1.2.1.4. users

##### 4.5.1.1.2.1.4.1. search.blade.php

```
@extends('layouts.back')

@section('content')
    <div class="body">
        <div class="row clearfix">

            <div class="col-md-4 col-md-offset-4">

                <p class="lead text-center">Pretraga</p><br/>

                <card-number-search></card-number-search>

                <br/>

                <name-search></name-search>

            </div>

        </div>
    </div>
```

```

        </div>

    </div>
</div>
@endsection

```

#### 4.5.1.1.2.2. user

##### 4.5.1.1.2.2.1. reservations

##### 4.5.1.1.2.2.1.1. create.blade.php

```

@extends('layouts.back')

@section('content')
    <reservation-form user_id="{{ $id }}"></reservation-form>
@endsection

```

##### 4.5.1.1.2.3. profile.blade.php

```

@extends('layouts.back')

@section('content')
    @include('back.partials.energijapp.profile.info')
</div>
</div>
    <div class="col-xs-12 col-sm-8">
        <div class="card">
            <div class="body">
                <div id="app">

                    @include('back.partials.energijapp.profile.tabs')

                    <div class="tab-content">

                        @if($user->role->name == 'user')
                            <user-payment-arrivals user_id="{!! $user->id
!!}"></user-payment-arrivals>
                            @if(session('user')->role->name == 'admin' ||
session('user')->role->name == 'operator')
                                <user-payments user_id="{!! $user->id !!}"></user-
payments>
                            @endif
                        @endif
                        @if(session('user')->id == $user->id)
                            <change-password user_id="{!! session('user')->id
!!}"></change-password>
                        @endif

                    </div>
                </div>
            </div>

```

```

        </div>
    </div>
</div>
@endsection

```

## 4.5.1.2. partials

### 4.5.1.2.1. admin

#### 4.5.1.2.1.1. db\_info.blade.php

```

<div class="body">
    <div class="row clearfix">

        <div class="col-lg-3 col-md-3 col-sm-6 col-xs-12">
            <a href="{{ url('/admin/users') }}">
                <div class="info-box bg-deep-purple hover-zoom-effect waves-
effect">
                    <div class="icon">
                        <i class="material-icons">person</i>
                    </div>
                    <div class="content">
                        @if($users->count() > 1)
                            <div class="text">{{ $users->count() }}
KORISNIKA</div>
                        @elseif($users->count == 1)
                            <div class="text">1 KORISNIK</div>
                        @else
                            <div class="text">NEMA KORISNIKA</div>
                        @endif
                    </div>
                </div>
            </a>
        </div>

        <div class="col-lg-3 col-md-3 col-sm-6 col-xs-12">
            <a href="{{ url('/admin/posts') }}">
                <div class="info-box bg-deep-purple hover-zoom-effect waves-
effect">
                    <div class="icon">
                        <i class="material-icons">border_color</i>
                    </div>
                    <div class="content">
                        @if($posts->count() > 4)
                            <div class="text">{{ $posts->count() }} POSTOVA</div>
                        @elseif($posts->count() == 2 || $posts->count() == 3 ||
$posts->count() == 4)
                            <div class="text">{{ $posts->count() }} POSTA</div>
                        @elseif($posts->count() == 1)
                            <div class="text">1 POST</div>
                        @else
                            <div class="text">NEMA POSTOVA</div>
                        @endif
                    </div>
                </div>
            </a>
        </div>
    </div>
</div>

```

```

        </div>
    </a>
</div>

<div class="col-lg-3 col-md-3 col-sm-6 col-xs-12">
    <a href="{{ url('/admin/sliders') }}">
        <div class="info-box bg-deep-purple hover-zoom-effect waves-
effect">
            <div class="icon">
                <i class="material-icons">burst_mode</i>
            </div>
            <div class="content">
                @if($sliders->count() == 1 || $sliders->count() > 4)
SLIKA</div>
                <div class="text">{{ $sliders->count() }} SLIDER
                @elseif($sliders->count() == 2 || $sliders->count() == 3
|| $sliders->count() == 4)
SLIKE</div>
                <div class="text">{{ $sliders->count() }} SLIDER
                @else
                <div class="text">NEMA SLIDER SLIKA</div>
                @endif
            </div>
        </div>
    </a>
</div>

<div class="col-lg-3 col-md-3 col-sm-6 col-xs-12">
    <a href="{{ url('/admin/menus') }}">
        <div class="info-box bg-deep-purple hover-zoom-effect waves-
effect">
            <div class="icon">
                <i class="material-icons">link</i>
            </div>
            <div class="content">
                @if($menus->count() > 4)
LINKOVA</div>
                <div class="text">{{ $menus->count() }} MENI
                @elseif($menus->count() == 2 || $menus->count() == 3 ||
$menus->count() == 4)
LINKA</div>
                <div class="text">{{ $menus->count() }} MENI
                @elseif($menus->count() == 1)
                <div class="text">1 MENI LINK</div>
                @else
                <div class="text">NEMA MENI LINKOVA</div>
                @endif
            </div>
        </div>
    </a>
</div>

<div class="col-lg-3 col-md-3 col-sm-6 col-xs-12">
    <a href="{{ url('/admin/trainers') }}">
        <div class="info-box bg-deep-purple hover-zoom-effect waves-
effect">
            <div class="icon">
                <i class="material-icons">sports</i>
            </div>
            <div class="content">

```

```

        @if($trainers->count() > 1)
            <div class="text">{{ $trainers->count() }}
TRENERA</div>

        @elseif($trainers->count() == 1)
            <div class="text">1 TRENER</div>
        @else
            <div class="text">NEMA TRENERA</div>
        @endif
    </div>
</div>
</a>
</div>

<div class="col-lg-3 col-md-3 col-sm-6 col-xs-12">
    <a href="{{ url('/admin/trainings') }}">
        <div class="info-box bg-deep-purple hover-zoom-effect waves-
effect">

            <div class="icon">
                <i class="material-icons">fitness_center</i>
            </div>
            <div class="content">
                @if($trainings->count() > 1)
TRENINGA</div>
                    <div class="text">{{ $trainings->count() }}

                @elseif($trainings->count() == 1)
                    <div class="text">1 TRENING</div>
                @else
                    <div class="text">NEMA TRENINGA</div>
                @endif
            </div>
        </div>
    </a>
</div>

<div class="col-lg-3 col-md-3 col-sm-6 col-xs-12">
    <a href="{{ url('/admin/prices') }}">
        <div class="info-box bg-deep-purple hover-zoom-effect waves-
effect">

            <div class="icon">
                <i class="material-icons">euro_symbol</i>
            </div>
            <div class="content">
                @if($prices->count() == 1 || $prices->count() > 4)
                    <div class="text">{{ $prices->count() }} CENA</div>
                @elseif($prices->count() == 2 || $prices->count() == 3 ||
$prices->count() == 4)
                    <div class="text">{{ $prices->count() }} CENE</div>
                @else
                    <div class="text">NEMA CENA</div>
                @endif
            </div>
        </div>
    </a>
</div>

<div class="col-lg-3 col-md-3 col-sm-6 col-xs-12">
    <a href="{{ url('/admin/services') }}">
        <div class="info-box bg-deep-purple hover-zoom-effect waves-
effect">

            <div class="icon">

```

```

        <i class="material-icons">group_work</i>
    </div>
    <div class="content">
        @if($services->count() == 1 || $services->count() > 4)
            <div class="text">{{ $services->count() }}
USLUGA</div>
        @elseif($services->count() == 2 || $services->count() == 3
|| $services->count() == 4)
            <div class="text">{{ $services->count() }}
USLUGE</div>
        @else
            <div class="text">NEMA USLUGA</div>
        @endif
    </div>
</div>
</a>
</div>

<div class="col-lg-3 col-md-3 col-sm-6 col-xs-12">
    <a href="{{ url('/admin/socials') }}">
        <div class="info-box bg-deep-purple hover-zoom-effect waves-
effect">
            <div class="icon">
                <i class="material-icons">share</i>
            </div>
            <div class="content">
                @if($socials->count() > 4)
                    <div class="text">{{ $socials->count() }} SOCIJALNIH
MREŽA</div>
                @elseif($socials->count() == 2 || $socials->count() == 3
|| $socials->count() == 4)
                    <div class="text">{{ $socials->count() }} SOCIJALNE
MREŽE</div>
                @elseif($socials->count() == 1)
                    <div class="text">1 SOCIJALNA MREŽA</div>
                @else
                    <div class="text">NEMA SOCIJALNIH MREŽA</div>
                @endif
            </div>
        </div>
    </a>
</div>

<div class="col-lg-3 col-md-3 col-sm-6 col-xs-12">
    <a href="{{ url('/admin/arrivals') }}">
        <div class="info-box bg-deep-orange hover-zoom-effect waves-
effect">
            <div class="icon">
                <i class="material-icons">arrow_downward</i>
            </div>
            <div class="content">
                <div class="text">DOLASCI</div>
            </div>
        </div>
    </a>
</div>

<div class="col-lg-3 col-md-3 col-sm-6 col-xs-12">
    <a href="{{ url('/admin/payments') }}">
        <div class="info-box bg-deep-orange hover-zoom-effect waves-

```

```

effect">
        <div class="icon">
            <i class="material-icons">show_chart</i>
        </div>
        <div class="content">
            <div class="text">UPLATE</div>
        </div>
    </div>
</a>
</div>

</div>
</div>

```

#### 4.5.1.2.1.2. sidebar.blade.php

```

<section>
    <aside id="leftsidebar" class="sidebar">

        <!-- User info -->
        <div class="user-info">
            <div class="image">
                
            </div>
            <div class="pull-right">
                
            </div>
            <div class="info-container">
                <div class="name" data-toggle="dropdown" aria-haspopup="true"
aria-expanded="false">{{ session('user')->first_name }} {{ session('user')->
last_name }}</div>
                <div class="email">{{ session('user')->email }}</div>
            </div>
        </div>
        <!-- User info END -->

        <!-- Menu -->
        <div class="menu">
            <ul class="list">
                <li class="header">BRZI MENI</li>

                <li>
                    <a href="javascript:void(0);" class="menu-toggle">
                        <i class="material-icons">person</i>
                        <span>Korisnici</span>
                    </a>
                    <ul class="ml-menu">
                        <li>
                            <a href="{{ url('/admin/users') }}">Prikaži</a>
                        </li>
                        <li>
                            <a href="{{ url('/admin/users/create') }}">Dodaj</a>
                        </li>
                    </ul>
                </li>
            </ul>
        </div>
    </li>

```



```

<li>
  <a href="javascript:void(0);" class="menu-toggle">
    <i class="material-icons">border_color</i>
    <span>Postovi</span>
  </a>
  <ul class="ml-menu">
    <li>
      <a href="{ { url('/admin/posts') } }">Prikaži</a>
    </li>
    <li>
      <a href="{ { url('/admin/posts/create') } }">Dodaj</a>
    </li>
  </ul>
</li>

<li>
  <a href="javascript:void(0);" class="menu-toggle">
    <i class="material-icons">burst_mode</i>
    <span>Slider</span>
  </a>
  <ul class="ml-menu">
    <li>
      <a href="{ { url('/admin/sliders') } }">Prikaži</a>
    </li>
    <li>
      <a href="{ { url('/admin/sliders/create') } }">Dodaj</a>
    </li>
  </ul>
</li>

<li>
  <a href="javascript:void(0);" class="menu-toggle">
    <i class="material-icons">link</i>
    <span>Meni linkovi</span>
  </a>
  <ul class="ml-menu">
    <li>
      <a href="{ { url('/admin/menus') } }">Prikaži</a>
    </li>
    <li>
      <a href="{ { url('/admin/menus/create') } }">Dodaj</a>
    </li>
  </ul>
</li>

<li>
  <a href="javascript:void(0);" class="menu-toggle">
    <i class="material-icons">sports</i>
    <span>Treneri</span>
  </a>
  <ul class="ml-menu">
    <li>
      <a href="{ { url('/admin/trainers') } }">Prikaži</a>
    </li>
    <li>
      <a href="{ { url('/admin/trainers/create') } }">Dodaj</a>
    </li>
  </ul>

```

```

        </li>

        <li>
            <a href="javascript:void(0);" class="menu-toggle">
                <i class="material-icons">fitness_center</i>
                <span>Treninzi</span>
            </a>
            <ul class="ml-menu">
                <li>
                    <a href="{{ url('/admin/trainings') }}">Prikaži</a>
                </li>
                <li>
                    <a href="{{ url('/admin/trainings/create') }}">Dodaj</a>
                </li>
            </ul>
        </li>

        <li>
            <a href="javascript:void(0);" class="menu-toggle">
                <i class="material-icons">euro_symbol</i>
                <span>Cene</span>
            </a>
            <ul class="ml-menu">
                <li>
                    <a href="{{ url('/admin/prices') }}">Prikaži</a>
                </li>
                <li>
                    <a href="{{ url('/admin/prices/create') }}">Dodaj</a>
                </li>
            </ul>
        </li>

        <li>
            <a href="javascript:void(0);" class="menu-toggle">
                <i class="material-icons">group_work</i>
                <span>Usluge</span>
            </a>
            <ul class="ml-menu">
                <li>
                    <a href="{{ url('/admin/services') }}">Prikaži</a>
                </li>
                <li>
                    <a href="{{ url('/admin/services/create') }}">Dodaj</a>
                </li>
            </ul>
        </li>

        <li>
            <a href="javascript:void(0);" class="menu-toggle">
                <i class="material-icons">share</i>
                <span>Socialne mreže</span>
            </a>
            <ul class="ml-menu">
                <li>
                    <a href="{{ url('/admin/socials/') }}">Prikaži</a>
                </li>
                <li>
                    <a href="{{ url('/admin/socials/create') }}">Dodaj</a>
                </li>
            </ul>
        </li>
    </ul>

```

```

        </li>
    </ul>
</li>

<li>
    <a href="{{ url('/admin/arrivals') }}" class="menu-info">
        <i class="material-icons">arrow_downward</i>
        <span>Dolasci</span>
    </a>
</li>

<li>
    <a href="{{ url('/admin/payments') }}" class="menu-info">
        <i class="material-icons">show_chart</i>
        <span>Uplate</span>
    </a>
</li>

<li>
    <a href="{{ url('/energijapp/search') }}" class="menu-info">
        <i class="material-icons">apps</i>
        <span>EnergijApp</span>
    </a>
</li>

</ul>
</div>
<!-- Menu END -->

<!-- Footer -->
<div class="legal">
    <div class="copyright">
        &copy; 2019 Jovan Ranković
    </div>
</div>
<!-- Footer END -->

</aside>
</section>

```

#### 4.5.1.2.2. common

##### 4.5.1.2.2.1. head.blade.php

```

<head>
    <meta charset="UTF-8" />
    <meta http-equiv="X-UA-Compatible" content="IE=Edge" />
    <meta content="width=device-width, initial-scale=1, maximum-scale=1, user-
scalable=no" name="viewport" />
    <meta name="csrf-token" content="{{ csrf_token() }}">
    @if(str_contains(url()->current(), '/admin'))
        <title>SC Ranković | Administracija</title>
    @else
        <title>SC Ranković | EnergijApp</title>
    @endif
    <link rel="icon" href="{{ asset('images/favicon/scr.ico') }}" type="image/x-

```

```

icon" />
<link
href="https://fonts.googleapis.com/css?family=Roboto:400,700&subset=latin,cyrillic-ext" rel="stylesheet" type="text/css" />
<link href="https://fonts.googleapis.com/icon?family=Material+Icons"
rel="stylesheet" type="text/css" />
<link href="https://stackpath.bootstrapcdn.com/font-awesome/4.7.0/css/font-awesome.min.css" rel="stylesheet" integrity="sha384-
wvfXpqpZZVQGK6TAh5PV1GOfQNHSoD2xbE+QkPxCaf1NEevoEH3Sl0sibVcOQVnN"
crossorigin="anonymous">
<link href="{{ asset('back/plugins/bootstrap/css/bootstrap.min.css') }}"
rel="stylesheet" />
<link href="{{ asset('back/plugins/bootstrap-select/css/bootstrap-select.min.css') }}" rel="stylesheet" />
<link href="{{ asset('back/plugins/node-waves/waves.min.css') }}"
rel="stylesheet" />
<link href="{{ asset('back/plugins/animate-css/animate.min.css') }}"
rel="stylesheet" />
<link href="{{ asset('back/css/style.min.css') }}" rel="stylesheet" />
<link href="{{ asset('back/css/themes/theme-deep-purple.min.css') }}"
rel="stylesheet" />
<link href="{{ asset('back/css/custom.css') }}" rel="stylesheet" />
</head>

```

#### 4.5.1.2.2.2. loader.blade.php

```

<div class="page-loader-wrapper">
<div class="loader">
<div class="preloader">
<div class="spinner-layer pl-deep-purple">
<div class="circle-clipper left">
<div class="circle"></div>
</div>
<div class="circle-clipper right">
<div class="circle"></div>
</div>
</div>
</div>
<p>Momenat...</p>
</div>
</div>

```

#### 4.5.1.2.2.3. nav.blade.php

```

<div class="overlay"></div>
<nav class="navbar">
<div class="container-fluid">
<div class="navbar-header">
<a href="javascript:void(0);" class="navbar-toggle collapsed" data-
toggle="collapse" data-target="#navbar-collapse" aria-expanded="false"></a>
<a href="javascript:void(0);" class="bars"></a>

@if(str_contains(url()->current(), '/admin'))

```

```

        <b><a class="navbar-brand" href="{{ url('/admin')
}}">Administracija</a></b>
        @else
            @if(session('user')->role->name == 'user')
                <b><a class="navbar-brand" href="{{
url('/energijapp/profile/'.session('user')->id) }}">EnergijApp</a></b>
            @else
                <b><a class="navbar-brand" href="{{ url('/energijapp/search')
}}">EnergijApp</a></b>
            @endif
        @endif
    </div>
    <div class="collapse navbar-collapse" id="navbar-collapse">
        <ul class="nav navbar-nav navbar-right">
            <li><a href="{{ url('/') }}"><i class="material-
icons">directions_run</i><b class="pull-left">Izlaz</b></a></li>
        </ul>
    </div>
</div>
</nav>

```

#### 4.5.1.2.2.4. scripts.blade.php

```

<script>
    const BASE_URL = "{{ url('/admin') }}";
    const TOKEN = "{{ csrf_token() }}";
</script>
<script src="{{ secure_asset('/js/app.js') }}"></script>
<script src="{{ secure_asset('back/plugins/jquery/jquery.min.js') }}"></script>
<script src="{{ secure_asset('back/plugins/bootstrap/js/bootstrap.min.js')
}}"></script>
<script src="{{ secure_asset('back/plugins/jquery-
slimscroll/jquery.slimscroll.js') }}"></script>
<script src="{{ secure_asset('back/plugins/node-waves/waves.min.js') }}"></script>
<script src="{{ secure_asset('back/js/admin.js') }}"></script>
<script src="{{ secure_asset('back/js/ajax_admin.js') }}"></script>

```

#### 4.5.1.2.2.5. wrapper.blade.php

```

<div class="row">
    <div class="col-lg-12 col-md-12 col-sm-12 col-xs-12">
        <div class="card">
            <div id="app">
                @yield('header')
                @yield('content')
            </div>
        </div>
    </div>
</div>

```

#### 4.5.1.2.3. energijapp

#### 4.5.1.2.3.1. operator

##### 4.5.1.2.3.1.1. sidebar.blade.php

```
<section>
  <aside id="leftsidebar" class="sidebar">

    <!-- User info -->
    <div class="user-info">
      <div class="image">
        
      </div>
      <div class="pull-right">
        
      </div>
      <div class="info-container">
        <div class="name" data-toggle="dropdown" aria-haspopup="true"
aria-expanded="false">{{ session('user')->first_name }} {{ session('user')-
>last_name }}</div>
        <div class="email">{{ session('user')->email }}</div>
      </div>
    </div>
    <!-- User info END -->

    <!-- Menu -->
    <div class="menu">
      <ul class="list">
        <li class="header">BRZI MENI</li>

        <li>
          <a href="{{ url('/energijapp/search') }}" class="menu-info">
            <i class="material-icons">search</i>
            <span>Pretraga</span>
          </a>
        </li>

        <li>
          <a href="{{ url('/energijapp/reservations') }}" class="menu-
info">
            <i class="material-icons">schedule</i>
            <span>Rezervacije</span>
          </a>
        </li>

        <li>
          <a href="{{ url('/energijapp/profile').'/' . session('user')->id
}}" class="menu-info">
            <i class="material-icons">person</i>
            <span>Profil</span>
          </a>
        </li>

        @if(session('user')->role->name == 'admin')
        <li>
          <a href="{{ url('/admin') }}" class="menu-info">
```

```

                <i class="material-icons">perm_data_setting</i>
                <span>Administracija</span>
            </a>
        </li>
    @endif
</ul>
</div>
<!-- Menu END -->

<!-- Footer -->
<div class="legal">
    <div class="copyright">
        &copy; 2019 Jovan Ranković
    </div>
</div>
<!-- Footer END -->

</aside>
</section>

```

#### 4.5.1.2.3.2. profile

##### 4.5.1.2.3.2.1. info.blade.php

```

<div class="profile-header">&nbsp;</div>
<div class="profile-body">
    <div class="image-area">
        
        <form action="{{ url('/energijapp/images/user/' . $user->id) }}"
method="POST" enctype="multipart/form-data">
            @method('PATCH')
            @csrf
            <input id="imgUser" name="imgUser" class="hidden" type="file"
onchange="this.form.submit();" />
        </form>

        <h6 class="text-center">Klikni sliku za promenu</h6>
    </div>
    @isset($errors)
        @foreach($errors->all() as $error)
            <div class="alert alert-warning">
                {{ $error }}
            </div>
        @endforeach
    @endisset
    <div class="content-area">
        <h3>{{ $user->first_name.' '.$user->last_name }}</h3>
        <p>{{ $user->card_number }}</p>
    </div>
</div>
<div class="profile-footer">
    <ul>
        <li>
            <span>Član od</span>

```

```

        <span>{{ $user->created_at->format('d.m.Y.') }}</span>
    </li>
    <li>
        <span>Datum rođenja</span>
        <span>{{ Carbon\Carbon::parse($user->birth_date)->format('d.m.Y.') }}</span>
    </li>
    <li>
        <span>Telefon</span>
        <span>{{ $user->phone }}</span>
    </li>
    <li>
        <span>E-mail</span>
        <span>{{ $user->email }}</span>
    </li>
</ul>
@if(session('user')->role->name == 'admin' || session('user')->role->name == 'operator')
    <a href="{{ url('/energijapp/users/'.$user->id.'/edit') }}" class="btn btn-dark btn-lg waves-effect btn-block">IZMENI</a>
    @if($user->id != session('user')->id)
        <a class="btn btn-dark btn-lg waves-effect btn-block" href="mailto:{{ $user->email }}">POŠALJI PORUKU</a>
    @endif
@endif
</div>

```

#### 4.5.1.2.3.2.2. tabs.blade.php

```

<ul class="nav nav-tabs" role="tablist">
    @if($user->role->name == 'user')
        <li role="presentation" class="active"><a href="#user_arrivals" aria-controls="user_arrivals" role="tab" data-toggle="tab">Dolasci</a></li>
        @if(session('user')->role->name == 'admin' || session('user')->role->name == 'operator')
            <li role="presentation"><a href="#user_payments" aria-controls="user_payments" role="tab" data-toggle="tab">Uplate</a></li>
        @endif
    @endif
    @if(session('user')->id == $user->id)
        <li role="presentation"><a href="#change_password" aria-controls="change_password" role="tab" data-toggle="tab">Promeni lozinku</a></li>
    @endif
</ul>

```

#### 4.5.1.2.3.2.3. wrapper.blade.php

```

<div class="row clearfix">
    <div class="col-xs-12 col-sm-3">
        <div class="card profile-card">
            @yield('content')
        </div>
    </div>

```



#### 4.5.1.2.3.3. user

##### 4.5.1.2.3.3.1. sidebar.blade.php

```
<section>
  <aside id="leftsidebar" class="sidebar">

    <!-- User info -->
    <div class="user-info">
      <div class="image">
        
      </div>
      <div class="pull-right">
        
      </div>
      <div class="info-container">
        <div class="name" data-toggle="dropdown" aria-haspopup="true"
aria-expanded="false">{{ session('user')->first_name }} {{ session('user')->last_name }}</div>
        <div class="email font-bold">00003</div>
      </div>
    </div>
    <!-- User info END -->

    <!-- Menu -->
    <div class="menu">
      <ul class="list">
        <li class="header">BRZI MENI</li>

        <li>
          <a href="{{ url('/energijapp/profile').'/' . session('user')->id }}" class="menu-info">
            <i class="material-icons">person</i>
            <span>Profil</span>
          </a>
        </li>

        <li>
          <a href="{{ url('/energijapp/reservations/user').'/' . session('user')->id }}" class="menu-info">
            <i class="material-icons">schedule</i>
            <span>Rezervacije</span>
          </a>
        </li>

      </ul>
    </div>
    <!-- Menu END -->

    <!-- Footer -->
    <div class="legal">
      <div class="copyright">
        &copy; 2019 Jovan Ranković
      </div>
    </div>
  </aside>
</section>
```

```

    </div>
    <!-- Footer END -->

</aside>
</section>

```

## 4.5.2. errors

### 4.5.2.1. 403.blade.php

```

<style>
  body {
    background-color: #2F3242;
  }
  svg {
    position: absolute;
    top: 50%;
    left: 50%;
    margin-top: -250px;
    margin-left: -400px;
  }
  .message-box {
    height: 200px;
    width: 380px;
    position: absolute;
    top: 50%;
    left: 50%;
    margin-top: -100px;
    margin-left: 50px;
    color: #FFF;
    font-family: Calibri;
    font-weight: 300;
  }
  .message-box h1 {
    font-size: 60px;
    line-height: 46px;
    margin-bottom: 40px;
  }
  .buttons-con .action-link-wrap {
    margin-top: 40px;
  }
  .buttons-con .action-link-wrap a {
    background: #675285;
    padding: 8px 25px;
    border-radius: 4px;
    color: #FFF;
    font-weight: bold;
    font-size: 14px;
    transition: all 0.3s linear;
    cursor: pointer;
    text-decoration: none;
    margin-right: 10px
  }
  .buttons-con .action-link-wrap a:hover {
    background: #5A5C6C;
  }

```

```

        color: #fff;
    }

    #Polygon-1 , #Polygon-2 , #Polygon-3 , #Polygon-4 , #Polygon-4, #Polygon-5 {
        animation: float 1s infinite ease-in-out alternate;
    }
    #Polygon-2 {
        animation-delay: .2s;
    }
    #Polygon-3 {
        animation-delay: .4s;
    }
    #Polygon-4 {
        animation-delay: .6s;
    }
    #Polygon-5 {
        animation-delay: .8s;
    }

    @keyframes float {
        100% {
            transform: translateY(20px);
        }
    }
    @media (max-width: 450px) {
        svg {
            position: absolute;
            top: 50%;
            left: 50%;
            margin-top: -250px;
            margin-left: -190px;
        }
        .message-box {
            top: 50%;
            left: 50%;
            margin-top: -100px;
            margin-left: -190px;
            text-align: center;
        }
    }
}
</style>

<svg width="380px" height="500px" viewBox="0 0 837 1045" version="1.1"
xmlns="http://www.w3.org/2000/svg" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:sketch="http://www.bohemiancoding.com/sketch/ns">
    <g id="Page-1" stroke="none" stroke-width="1" fill="none" fill-rule="evenodd"
sketch:type="MSPage">
        <path d="M353,9 L626.664028,170 L626.664028,487 L353,642 L79.3359724,487
L79.3359724,170 L353,9 Z" id="Polygon-1" stroke="#007FB2" stroke-width="6"
sketch:type="MSShapeGroup"></path>
        <path d="M78.5,529 L147,569.186414 L147,648.311216 L78.5,687
L10,648.311216 L10,569.186414 L78.5,529 Z" id="Polygon-2" stroke="#EF4A5B" stroke-
width="6" sketch:type="MSShapeGroup"></path>
        <path d="M773,186 L827,217.538705 L827,279.636651 L773,310 L719,279.636651
L719,217.538705 L773,186 Z" id="Polygon-3" stroke="#795D9C" stroke-width="6"
sketch:type="MSShapeGroup"></path>
        <path d="M639,529 L773,607.846761 L773,763.091627 L639,839 L505,763.091627
L505,607.846761 L639,529 Z" id="Polygon-4" stroke="#F2773F" stroke-width="6"
sketch:type="MSShapeGroup"></path>
        <path d="M281,801 L383,861.025276 L383,979.21169 L281,1037 L179,979.21169

```

```

L179,861.025276 L281,801 Z" id="Polygon-5" stroke="#36B455" stroke-width="6"
sketch:type="MSShapeGroup"></path>
</g>
</svg>
<div class="message-box">
  <h1>403</h1>
  <p>Ni je vam dozvoljen pristup ovoj stranici.</p>
  <div class="buttons-con">
    <div class="action-link-wrap">
      <a onclick="history.back(-1)" class="link-button link-back-
button">Nazad</a>
    </div>
  </div>
</div>

```

#### 4.5.2.2. 404.blade.php

```

<style>
  body {
    background-color: #2F3242;
  }
  svg {
    position: absolute;
    top: 50%;
    left: 50%;
    margin-top: -250px;
    margin-left: -400px;
  }
  .message-box {
    height: 200px;
    width: 380px;
    position: absolute;
    top: 50%;
    left: 50%;
    margin-top: -100px;
    margin-left: 50px;
    color: #FFF;
    font-family: Calibri;
    font-weight: 300;
  }
  .message-box h1 {
    font-size: 60px;
    line-height: 46px;
    margin-bottom: 40px;
  }
  .buttons-con .action-link-wrap {
    margin-top: 40px;
  }
  .buttons-con .action-link-wrap a {
    background: #675285;
    padding: 8px 25px;
    border-radius: 4px;
    color: #FFF;
    font-weight: bold;
    font-size: 14px;
    transition: all 0.3s linear;
    cursor: pointer;
  }

```

```

        text-decoration: none;
        margin-right: 10px
    }
    .buttons-con .action-link-wrap a:hover {
        background: #5A5C6C;
        color: #fff;
    }

    #Polygon-1 , #Polygon-2 , #Polygon-3 , #Polygon-4 , #Polygon-4, #Polygon-5 {
        animation: float 1s infinite ease-in-out alternate;
    }
    #Polygon-2 {
        animation-delay: .2s;
    }
    #Polygon-3 {
        animation-delay: .4s;
    }
    #Polygon-4 {
        animation-delay: .6s;
    }
    #Polygon-5 {
        animation-delay: .8s;
    }

    @keyframes float {
        100% {
            transform: translateY(20px);
        }
    }
    @media (max-width: 450px) {
        svg {
            position: absolute;
            top: 50%;
            left: 50%;
            margin-top: -250px;
            margin-left: -190px;
        }
        .message-box {
            top: 50%;
            left: 50%;
            margin-top: -100px;
            margin-left: -190px;
            text-align: center;
        }
    }
</style>

<svg width="380px" height="500px" viewBox="0 0 837 1045" version="1.1"
xmlns="http://www.w3.org/2000/svg" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:sketch="http://www.bohemiancoding.com/sketch/ns">
    <g id="Page-1" stroke="none" stroke-width="1" fill="none" fill-rule="evenodd"
sketch:type="MSPage">
        <path d="M353,9 L626.664028,170 L626.664028,487 L353,642 L79.3359724,487
L79.3359724,170 L353,9 Z" id="Polygon-1" stroke="#007FB2" stroke-width="6"
sketch:type="MSShapeGroup"></path>
        <path d="M78.5,529 L147,569.186414 L147,648.311216 L78.5,687
L10,648.311216 L10,569.186414 L78.5,529 Z" id="Polygon-2" stroke="#EF4A5B" stroke-
width="6" sketch:type="MSShapeGroup"></path>
        <path d="M773,186 L827,217.538705 L827,279.636651 L773,310 L719,279.636651
L719,217.538705 L773,186 Z" id="Polygon-3" stroke="#795D9C" stroke-width="6"

```

```

sketch:type="MSShapeGroup"></path>
    <path d="M639,529 L773,607.846761 L773,763.091627 L639,839 L505,763.091627
L505,607.846761 L639,529 Z" id="Polygon-4" stroke="#F2773F" stroke-width="6"
sketch:type="MSShapeGroup"></path>
    <path d="M281,801 L383,861.025276 L383,979.21169 L281,1037 L179,979.21169
L179,861.025276 L281,801 Z" id="Polygon-5" stroke="#36B455" stroke-width="6"
sketch:type="MSShapeGroup"></path>
    </g>
</svg>
<div class="message-box">
    <h1>404</h1>
    <p>Stranica nije pronađena.</p>
    <div class="buttons-con">
        <div class="action-link-wrap">
            <a onClick="history.back(-1)" class="link-button link-back-
button">Nazad</a>
        </div>
    </div>
</div>

```

#### 4.5.2.3. 419.blade.php

```

<style>
    body {
        background-color: #2F3242;
    }
    svg {
        position: absolute;
        top: 50%;
        left: 50%;
        margin-top: -250px;
        margin-left: -400px;
    }
    .message-box {
        height: 200px;
        width: 380px;
        position: absolute;
        top: 50%;
        left: 50%;
        margin-top: -100px;
        margin-left: 50px;
        color: #FFF;
        font-family: Calibri;
        font-weight: 300;
    }
    .message-box h1 {
        font-size: 60px;
        line-height: 46px;
        margin-bottom: 40px;
    }
    .buttons-con .action-link-wrap {
        margin-top: 40px;
    }
    .buttons-con .action-link-wrap a {
        background: #675285;
        padding: 8px 25px;
        border-radius: 4px;
    }

```

```

        color: #FFF;
        font-weight: bold;
        font-size: 14px;
        transition: all 0.3s linear;
        cursor: pointer;
        text-decoration: none;
        margin-right: 10px
    }
    .buttons-con .action-link-wrap a:hover {
        background: #5A5C6C;
        color: #fff;
    }

    #Polygon-1 , #Polygon-2 , #Polygon-3 , #Polygon-4 , #Polygon-4, #Polygon-5 {
        animation: float 1s infinite ease-in-out alternate;
    }
    #Polygon-2 {
        animation-delay: .2s;
    }
    #Polygon-3 {
        animation-delay: .4s;
    }
    #Polygon-4 {
        animation-delay: .6s;
    }
    #Polygon-5 {
        animation-delay: .8s;
    }

    @keyframes float {
        100% {
            transform: translateY(20px);
        }
    }
    @media (max-width: 450px) {
        svg {
            position: absolute;
            top: 50%;
            left: 50%;
            margin-top: -250px;
            margin-left: -190px;
        }
        .message-box {
            top: 50%;
            left: 50%;
            margin-top: -100px;
            margin-left: -190px;
            text-align: center;
        }
    }
}
</style>

<svg width="380px" height="500px" viewBox="0 0 837 1045" version="1.1"
xmlns="http://www.w3.org/2000/svg" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:sketch="http://www.bohemiancoding.com/sketch/ns">
    <g id="Page-1" stroke="none" stroke-width="1" fill="none" fill-rule="evenodd"
sketch:type="MSPage">
        <path d="M353,9 L626.664028,170 L626.664028,487 L353,642 L79.3359724,487
L79.3359724,170 L353,9 Z" id="Polygon-1" stroke="#007FB2" stroke-width="6"
sketch:type="MSShapeGroup"></path>

```

```

        <path d="M78.5,529 L147,569.186414 L147,648.311216 L78.5,687
L10,648.311216 L10,569.186414 L78.5,529 Z" id="Polygon-2" stroke="#EF4A5B" stroke-
width="6" sketch:type="MSShapeGroup"></path>
        <path d="M773,186 L827,217.538705 L827,279.636651 L773,310 L719,279.636651
L719,217.538705 L773,186 Z" id="Polygon-3" stroke="#795D9C" stroke-width="6"
sketch:type="MSShapeGroup"></path>
        <path d="M639,529 L773,607.846761 L773,763.091627 L639,839 L505,763.091627
L505,607.846761 L639,529 Z" id="Polygon-4" stroke="#F2773F" stroke-width="6"
sketch:type="MSShapeGroup"></path>
        <path d="M281,801 L383,861.025276 L383,979.21169 L281,1037 L179,979.21169
L179,861.025276 L281,801 Z" id="Polygon-5" stroke="#36B455" stroke-width="6"
sketch:type="MSShapeGroup"></path>
    </g>
</svg>
<div class="message-box">
    <h1>419</h1>
    <p>Hmm... probajte opet da se ulogujete.</p>
    <div class="buttons-con">
        <div class="action-link-wrap">
            <a onclick="history.back(-1)" class="link-button link-back-
button">Nazad</a>
        </div>
    </div>
</div>

```

## 4.5.3. front

### 4.5.3.1. pages

#### 4.5.3.1.1. home.blade.php

```

@extends('layouts.front')

@section('content')
    @include('front.partials.home.welcome')
    @include('front.partials.home.about')
    @include('front.partials.home.trainings')
    @include('front.partials.home.prices')
    @include('front.partials.home.blog')
    @include('front.partials.home.contact')
    @include('front.partials.home.map')
@endsection

@section('homeNav')
    <li><a href="#welcome" class="smoothScroll">Na vrh</a></li>
@endsection

@section('moreNav')
    @foreach($menus as $menu)
        <li><a href="{{ $menu->route }}" class="smoothScroll">{{ $menu->name
    }}</a></li>
    @endforeach
@endsection

@section('moreJS')

```



```

<script src="js/jquery.nav.js"></script>
<script src="js/jquery.backstretch.min.js"></script>

<script
src="https://maps.googleapis.com/maps/api/js?key=AIzaSyBVHsEpU4NGN1fknIQtdGTDYXKr
CNnEfK&callback=initMap" async="" defer=""></script>

<script>
$(function(){
    jQuery(document).ready(function() {
        $('#welcome').backstretch([

            @foreach($sliders as $slider)
                "{{ $slider->image }}" ,
            @endforeach

        ], {duration: 2000, fade: 750});
    });
});
</script>
@endsection

```

#### 4.5.3.1.2. post.blade.php

```

@extends('layouts.front')

@section('content')
    @include('front.partials.post.header')

    <section id="blog" class="parallax-section">
        <div class="container">
            <div class="row">
                <div class="col-md-12 col-sm-12">

                    @include('front.partials.post.content')
                    @include('front.partials.post.comments')
                    @include('front.partials.post.form')

                </div>
            </div>
        </div>
    </section>
@endsection

@section('homeNav')
    <li><a href="{{ url('/') }}">Početna</a></li>
@endsection

@section('moreNav')
    <li><a href="#comments" class="smoothScroll">Komentari</a></li>
@endsection

@section('moreCSS')
    <style>
        #blog-header {
            background: url('{{ secure_asset($post->image) }}') 50% 0 repeat-y
fixed;

```

```

    }
</style>
@endsection

@section('moreJS')
    <script>
        const TOKEN = "{{ csrf_token() }}";
    </script>
@endsection

```

#### 4.5.3.1.3. training.blade.php

```

@extends('layouts.front')

@section('content')
    @include('front.partials.training.header')

    <section id="blog" class="parallax-section">
        <div class="container">
            <div class="row">
                <div class="col-md-12 col-sm-12">

                    @include('front.partials.training.content')

                </div>
            </div>
        </div>
    </section>
@endsection

@section('homeNav')
    <li><a href="{{ url('/') }}">Početna</a></li>
@endsection

@section('moreCSS')
    <style>
        #blog-header {
            background: url('{{ secure_asset($training->image) }}') 50% 0 repeat-y
fixed;
        }
    </style>
@endsection

```

#### 4.5.3.2. partials

##### 4.5.3.2.1. common

##### 4.5.3.2.1.1. footer.blade.php

```

<footer>
  <div class="container">
    <div class="row">

      <div class="wow fadeInUp col-md-4 col-sm-4" data-wow-delay="0.6s">
        <br/>

        <h4>
          Bulevar kralja Aleksandra 443a
        </h4>

        <h4>
          065/37-37-655
        </h4>

        <h4>
          scrankovic@hotmail.com
        </h4>

      </div>

      <div class="wow fadeInUp col-md-5 col-sm-4" data-wow-delay="0.9s">
        
      </div>

      <div class="wow fadeInUp col-md-3 col-sm-4" data-wow-delay="1s">
        <h2>Pratite nas</h2>
        <ul class="social-icon">

          @foreach($socials as $social)
            <li><a href="{ $social->url }" class="fa fa-{ $social-
>icon }}" wow fadeInUp" data-wow-delay="1s"></a></li>
          @endforeach

        </ul>
      </div>

      <div class="clearfix"></div>

      <div class="col-md-12 col-sm-12">
        <p class="copyright-text">&copy; 2019 <a href="#" data-
toggle="modal" data-target="#author-modal">Jovan Ranković</a></p>
      </div>

      <!-- Author modal -->
      <div id="author-modal" class="modal fade" role="dialog">
        <div class="modal-dialog">
          <div class="modal-content">
            <div class="modal-header">
              <button type="button" class="close" data-
dismiss="modal"><span aria-hidden="true">x</span><span class="sr-
only">Close</span></button>
            <h4 class="modal-title">Autor</h4>
          </div>
          <div class="modal-body">
            <br/>
            <p class="text-center"><a
href="https://www.linkedin.com/in/jovan-

```

```

rankovic/"><strong>LinkedIn</strong></a></p>
        </div>
    </div>
</div>
<!-- Author modal END -->

</div>
</div>
</footer>

```

#### 4.5.3.2.1.2. head.blade.php

```

<head>
    <title>SC Ranković</title>
    <meta name="description" content="">
    <meta name="author" content="">
    <meta charset="UTF-8">
    <meta http-equiv="X-UA-Compatible" content="IE=edge">
    <meta name="viewport" content="width=device-width, initial-scale=1, maximum-
scale=1">
    <link rel="shortcut icon" href="{{ secure_asset('images/favicon/scr.ico') }}">

    <link rel="stylesheet" href="{{ secure_asset('css/bootstrap.min.css') }}">
    <link rel="stylesheet" href="{{ secure_asset('css/animate.css') }}">
    <link rel="stylesheet" href="https://stackpath.bootstrapcdn.com/font-
awesome/4.7.0/css/font-awesome.min.css">

    <!-- Main css -->
    <link rel="stylesheet" href="{{ secure_asset('css/style.css') }}">

    <!-- Google Font -->
    <link
href='https://fonts.googleapis.com/css?family=Source+Sans+Pro:400,300,600'
rel='stylesheet' type='text/css'>
    <link href='https://fonts.googleapis.com/css?family=Lora:700italic'
rel='stylesheet' type='text/css'>

    @yield('moreCSS')
</head>

```

#### 4.5.3.2.1.3. nav.blade.php

```

<div class="navbar navbar-default navbar-fixed-top sticky-navigation"
role="navigation">
    <div class="container">

        <div class="navbar-header">
            <button class="navbar-toggle" data-toggle="collapse" data-
target=".navbar-collapse">
                <span class="icon icon-bar"></span>
                <span class="icon icon-bar"></span>
                <span class="icon icon-bar"></span>
            </button>

```

```

        <a href="{{ url('/') }}" class="navbar-brand">SC RANKOVIĆ</a>
    </div>
    <div class="collapse navbar-collapse">
        <ul class="nav navbar-nav navbar-right main-navigation">
            @yield('homeNav')
            @yield('moreNav')
            @if(session()->has('user'))

                <li class="dropdown"><a href="#" data-toggle="dropdown"
class="dropdown-toggle">{{ session('user')->first_name }} <b
class="caret"></b></a>

                    <ul class="dropdown-menu">

                        @if(session('user')->role->name == 'user')
                            <li><a href="{{
url('energijapp/profile/'.session('user')->id) }}">Profil</a></li>
                            <li><a href="{{
url('energijapp/reservations/user').'/' .session('user')->id
}}">Rezervacije</a></li>
                        @endif

                        @if(session('user')->role->name == 'admin' ||
session('user')->role->name == 'operator')
                            <li><a href="{{ url('/energijapp/search')
}}">EnergijApp</a></li>
                        @endif

                        @if(session('user')->role->name == 'admin')
                            <li><a href="{{ url('/admin') }}">Admin</a></li>
                            <li><a href="{{
secure_asset('files/dipl_php_lara_jovan_rankovic_145_14')
}}">Dokumentacija</a></li>
                        @endif

                            <li><a href="{{ url('/logout') }}">Izloguj se</a></li>
                        </ul>
                    </li>

                @else
                    <li><a href="#" data-toggle="modal" data-target=".log-
sign">Logovanje</a></li>
                @endif

            </ul>
        </div>
    </div>
</div>

@if(!session()->has('user'))
<!-- Log in/Sign up Modal -->
<div class="modal fade bs-modal-sm log-sign" id="myModal" tabindex="-1"
role="dialog" aria-labelledby="mySmallModalLabel" aria-hidden="true">
    <div class="modal-dialog modal-sm">
        <div class="modal-content">

            <div class="bs-example bs-example-tabs">
                <ul id="myTab" class="nav nav-tabs">
                    <li id="tab1" class="active tab-style login-shadow "><a
href="#signin" data-toggle="tab">Uloguj se</a></li>

```

```

        <li id="tab2" class=" tab-style "><a href="#signup" data-
toggle="tab">Registruj se</a></li>

    </ul>
</div>
<div class="modal-body">
    <div id="myTabContent" class="tab-content">

        <!-- Login Form -->
        <div class="tab-pane fade active in" id="signin">
            <form class="form-horizontal" method="POST" action="{
url('/login') }}">
                <fieldset>
                    @csrf

                    <div class="group">
                        <input class="input" type="text" id="logEmail"
name="logEmail" required /><span class="highlight"></span><span
class="bar"></span>
                        <label class="label" for="logEmail">E-
mail</label>
                    </div>

                    <div class="group">
                        <input class="input" type="password"
id="logPasswd" name="logPasswd" required /><span class="highlight"></span><span
class="bar"></span>
                        <label class="label"
for="logPass">Lozinka</label>
                    </div>
                    <em></em>

                    <div class="control-group">
                        <label class="control-label"
for="signin"></label>
                        <div class="controls">
                            <button id="logBtn" name="logBtn"
class="btn btn-primary btn-block">Potvrđi</button>
                        </div>
                    </div>
                </fieldset>
            </form>
        </div>

        <!-- Registration Form -->
        <div class="tab-pane fade" id="signup">
            <form class="form-horizontal" method="POST" action="{
url('/register') }}">
                <fieldset>
                    @csrf
                    <div class="group">
                        <input class="input" type="text" id="regFN"
name="regFN" required /><span class="highlight"></span><span class="bar"></span>
                        <label class="label"
for="regFN">Ime</label></div>

                        <div class="group">
                            <input class="input" type="text" id="regLN"
name="regLN" required /><span class="highlight"></span><span class="bar"></span>
                            <label class="label"

```



#### 4.5.3.2.2. home

##### 4.5.3.2.2.1. pagination

###### 4.5.3.2.2.1.1. posts.blade.php

```
<div class="container">
  <div class="row">

    <div class="wow fadeInUp col-md-12 col-sm-12 text-center" data-wow-
delay="0.5s">
      <h2>Blog</h2>
      <p>Saznajte sve o najnovijim dešavanjima kod nas</p>
    </div>

    @foreach($posts as $post)

      <div class="wow fadeInUp col-md-6 col-sm-12" data-wow-delay="0.9s">
        <div class="blog-thumb">
          <span class="blog-date">{{ $post->created_at->format('d.m.Y.') }}</span>
          <h3 class="blog-title"><a href="{{ url('/posts/'. $post->id) }}">{{ $post->title }}</a></h3>
          <h5 id="blog-author">{{ $post->user->first_name }} {{ $post->user->last_name }}</h5>
        </div>
      </div>

    @endforeach

  </div>
</div>

<div id="post_pagination" class="wow fadeInUp text-center" data-wow-
delay="1.2s">{{ $posts->links() }}</div>
```

###### 4.5.3.2.2.1.2. trainings.blade.php

```
<div class="container">
  <div class="row">

    <div class="wow fadeInUp col-md-12 col-sm-12" data-wow-delay="0.5s">
      <h2>Treninzi</h2>
      <p>Prelaskom preko slika saznajte više o našim treninzima</p>
    </div>

    @foreach($trainings as $training)

      <div class="wow fadeInUp col-md-4 col-sm-6" data-wow-delay="0.5s">
        <div class="trainer-thumb">
```



```

        
        <div class="trainer-overlay">
            <div class="trainer-des">
                <h2>{{ $training->intensity }} intenzitet</h2>
                <h3>{{ $training->duration }} min.

                @if($training->reservations == true)
                    <h5>Rezervacije su obavezne</h5>
                @else
                    <h5>Bez rezervacija</h5>
                @endif

                <ul class="social-icon">
                    <li><a href="{{ url('/trainings').'/'.$training->id }}" class="fa fa-info wow fadeInUp" data-wow-delay="1s"></a></li>
                </ul>
            </div>
        </div>
    </div>
</div>

    @endforeach

</div>

    <div id="training_pagination" class="wow fadeInUp text-center" data-wow-delay="1.2s">{{ $trainings->links() }}</div>
</div>

<div id="sessions">
    <a href="{{ url('/sessions') }}" class="wow fadeInUp btn btn-default" data-wow-delay="1.5s">RASPORED</a>
</div>

```

#### 4.5.3.2.2.2. about.blade.php

```

<section id="about" class="parallax-section">
    <div class="container">
        <div class="row">

            <div class="col-md-6 col-sm-12">
                
                <blockquote class="wow fadeInUp" data-wow-delay="1s">
                    <p>„Energija u pokretu“</p>
                    <p>Sa vama od 2013.</p>
                </blockquote>
            </div>

            <div class="col-md-1"></div>

            <div class="wow fadeInUp col-md-4 col-sm-12" data-wow-delay="0.5s">
                <div class="about-detail">
                    <h2>O Nama</h2>
                    <p>SC Ranković se nalazi na Bulevaru kralja Aleksandra 443a,

```

```

nedaleko od okretne tramvaja (5, 6, 7, 14) i prigradskih autobusa (300+).</p>
    <p>Sala za grupni fitnes se prostire na 200m<sup>2</sup>, sa
svlačionicama opremljenim ormarićima za stvari i brojnim rekvizitima za različite
vrste treninga.</p>
    <p>Dugogodišnje iskustvo u fitnessu, raznim vrstama sportova i
rada sa grupama vežbača širom Srbije pokrenulo je ideju da dobru energiju
prenesemo i na ljubitelje fitnesa u kraju gde smo odrasli.</p>
    </div>
</div>

<div class="col-md-1"></div>

</div>
</div>
</section>

```

#### 4.5.3.2.2.3. blog.blade.php

```

<section id="blog" class="parallax-section">

    <div id="post_data">
        @include('front.partials.home.pagination.posts')
    </div>

</section>

```

#### 4.5.3.2.2.4. contact.blade.php

```

<section id="contact" class="parallax-section">
    <div class="container">
        <div class="row">

            <div class="wow fadeInUp col-md-offset-2 col-md-8 col-sm-offset-1 col-sm-10" data-wow-delay="0.9s">
                <h2>Kontakt</h2>
                <p>Tu smo za sva vaša pitanja</p>
                <div class="contact_detail">
                    <form action="{{ url('/contact') }}" method="POST"
id="contact-signup">
                        @csrf
                        <div class="col-md-6 col-sm-6">
                            <input name="conName" type="text" class="form-control"
id="conName" placeholder="Ime" required />
                        </div>
                        <div class="col-md-6 col-sm-6">
                            <input name="conEmail" type="email" class="form-
control" id="conEmail" placeholder="E-mail" required />
                        </div>
                        <div class="col-md-6 col-sm-6">
                            <input name="conSubject" type="text" class="form-
control" id="conSubject" placeholder="Naslov" required />
                        </div>
                        <div class="col-md-6 col-sm-6">
                            <textarea class="form-control" name="conMsg"

```

```

id="conMsg" placeholder="Poruka" required ></textarea>
        </div>
        <div class="col-md-offset-3 col-md-6 col-sm-offset-2 col-sm-8">
            <input name="conBtn" type="submit" class="form-control" id="conBtn" value="POŠALJI">
        </div>
    </form>
</div>
</div>
</div>
</section>

```

#### 4.5.3.2.2.5. map.blade.php

```
<div id="map"></div>
```

#### 4.5.3.2.2.6. prices.blade.php

```

<section id="prices" class="parallax-section">
    <div class="container">
        <div class="row">
            <div class="wow fadeInUp col-md-12 col-sm-12" data-wow-delay="0.9s">
                <h2>Cene</h2>
                <p>Nudimo najpovoljnije usluge u našem kraju</p>
            </div>

            @foreach($prices as $price)

                <div class="wow fadeInUp col-md-4 col-sm-6" data-wow-delay="1s">
                    <div class="pricing__item">
                        <h3 class="pricing__title">{{ $price->title }}</h3>
                        <div class="pricing__price">{{ $price->amount }} <span
class="pricing__currency">din.</span></div>
                        <ul class="pricing__feature-list">

                            @foreach($price->services as $pService)

                                <li class="pricing__feature">{{ $pService->name
}}</li>

                            @endforeach

                        </ul>
                    </div>
                </div>

            @endforeach

        </div>
    </div>
</section>

```

#### 4.5.3.2.2.7. trainings.blade.php

```
<section id="trainings" class="parallax-section">

    <div id="training_data">
        @include('front.partials.home.pagination.trainings')
    </div>

</section>
```

#### 4.5.3.2.2.8. welcome.blade.php

```
<section id="welcome" class="parallax-section">
    <div class="container">
        <div class="row">

            <div class="col-md-offset-1 col-md-10 col-sm-12">

                @isset($errors)
                    @foreach($errors->all() as $error)
                        <div class="alert alert-warning">
                            {{ $error }}
                        </div>
                    @endforeach
                @endisset

                @if(session('message'))
                    <h3 class="wow bounceIn" data-wow-delay="0.9s">{{
session('message') }}</h3>
                @endif

                <h1 class="wow fadeInUp" data-wow-delay="1.6s">SC Ranković</h1>
                <a href="#about" id="arrowdown" class="wow fadeInUp smoothScroll
arrow" data-wow-delay="2s"><span></span></a>

            </div>
        </div>
    </section>
```

#### 4.5.3.2.3. post

##### 4.5.3.2.3.1. comments.blade.php

```
<div class="blog-comment wow fadeInUp" id="comments" data-wow-delay="1s"
xmlns="http://www.w3.org/1999/html">
    <br/>

    @if($post->comments->count() == 0)
```

```

        <h3>Nema komentara.</h3>
    @elseif($post->comments->count() == 1)
        <h3>1 komentar</h3>
    @else
        <h3>{{ $post->comments->count() }} komentara</h3>
    @endif

    @php($i=1)

    @foreach($post->comments as $comment)

        <div class="media">
            <div class="media-object pull-left col-md-2 col-sm-4 col-xs-3">
                
            </div>
            <div class="media-body">

                @if(session()->has('user'))

                    @if(session('user')->id == $comment->user->id ||
session('user')->role_id == 1)

                        <button type="button" class="close" aria-label="Close"
data-toggle="modal" data-target="#deleteWarning{{ $i }}">
                            <span aria-hidden="true">&times;</span>
                        </button>

                        <div class="modal fade" id="deleteWarning{{ $i++ }}"
role="dialog">
                            <div class="modal-dialog modal-sm text-center">
                                <div class="modal-content">
                                    <div class="modal-body">
                                        <button type="button" class="close" data-
dismiss="modal">
                                            &times;
                                        </button>
                                        <h7>Da li ste sigurni?</h7>
                                        <button type="button" class="btn btn-
default error" onclick="comment_delete('{{ $post->id }}', '{{ $comment->id }}', '{{
$comment->user->id }}', '{{ $comment->content }}', '{{ $comment->user->first_name
}}', '{{ $comment->user->last_name }}', '{{ $post->title }}');">
                                            Obriši
                                        </button>
                                    </div>
                                </div>
                            </div>
                        </div>
                    @endif

                    @if(session('user')->id == $comment->user->id)

                        <button type="button" class="close" data-toggle="modal"
data-target="#edit{{ $i }}">
                            <span aria-hidden="true"><i class="fa fa-
edit"></i></span>
                        </button>

                        <div class="modal fade" id="edit{{ $i++ }}" role="dialog">
                            <div class="modal-dialog modal-sm text-center">

```

```

        <div class="modal-content">
            <div class="modal-body">
                <button type="button" class="close" data-
dismiss="modal">
                    &times;
                </button>
                <h7>Izmeni komentar</h7>

                <fieldset>

                    <div class="group">
                        <textarea class="input"
type="text" id="editComment" name="editComment" required />{{ $comment->content
}}</textarea><span class="highlight"></span><span class="bar"></span>
                    </div>

                    <div class="control-group">
                        <div class="controls">
                            <button class="button btn
btn-primary btn-block" onclick="comment_update('{{ $post->id }}', '{{ $comment->id
}}', '{{ $comment->user->id }}', '{{ $comment->user->first_name }}', '{{ $comment-
>user->last_name }}', '{{ $post->title }}');">
                                Izmeni
                            </button>
                        </div>
                    </div>

                </fieldset>

            </div>
        </div>
    </div>
</div>

@endif

@endif

        <h4 class="media-heading">{{ $comment->user->first_name }} {{
$comment->user->last_name }} @if($comment->user->id == $post->user->id) <small
class="error">Autor</small> @endif</h4>
        <h5>{{ $comment->updated_at->format('d.m.Y. H:i') }} @if($comment-
>updated_at != $comment->created_at) <i>(izmenjeno)</i> @endif</h5>
        <p id="comment">{{ $comment->content }}</p>
    </div>
</div>

@endforeach
</div>

```

#### 4.5.3.2.3.2. content.blade.php

```

<div class="blog-content wow fadeInUp" data-wow-delay="1s">
    <span>{{ $post->created_at->format('d.m.Y.') }}</span>
    <span class="meta-author">{{ $post->user->first_name }} {{ $post->user-
>last_name }}</span>
    <div class="blog-clear"></div>

```

```
<p class="post-content">{{ $post->content }}</p>
</div>
```

#### 4.5.3.2.3.3. form.blade.php

```
@if(session()->has('user'))
    <div class="blog-comment-form wow fadeInUp" data-wow-delay="1s">
        <h3>Ostavite komentar</h3>
        <form action="#" method="POST" id="comment-form">
            @csrf
            <div class="col-md-12 col-sm-12">
                <textarea class="form-control" placeholder="Message" rows="5"
name="commentMsg" id="commentMsg" required ></textarea>
            </div>

            <input name="postId" type="hidden" class="form-control"
id="postId" value="{{ $post->id }}" />

            <input name="loggedUserId" type="hidden" class="form-control"
id="loggedUserId" value="{{ session('user')->id }}" />

            <input type="hidden" name="postTitle" class="form-control"
id="postTitle" value="{{ $post->title }}">

            <input type="hidden" name="loggedUserFN" class="form-control"
id="loggedUserFN" value="{{ session('user')->first_name }}" />

            <input type="hidden" name="loggedUserLN" class="form-control"
id="loggedUserLN" value="{{ session('user')->last_name }}" />

            <div class="col-md-3 col-sm-3">
                <input name="commentBtn" type="submit" class="form-control"
id="commentBtn" value="Submit">
            </div>

        </form>
    </div>
@else
    <div class="blog-comment-form wow fadeInUp" data-wow-delay="1s">
        <h3><a href="#" data-toggle="modal" data-target=".log-sign">Ulogujte
se</a> kako biste kometarisali.</h3>
    </div>
@endif
```

#### 4.5.3.2.3.4. header.blade.php

```
<section id="blog-header" class="parallax-section">
    <div class="container">
        <div class="row">

            <div class="col-md-offset-2 col-md-8 col-sm-12">
                <h3 class="wow bounceIn" data-wow-delay="0.9s">{{ $post->title
}}</h3>

            </div>
```

```

        </div>
    </div>
</section>

```

#### 4.5.3.2.4. training

##### 4.5.3.2.4.1. content.blade.php

```

<div class="blog-content wow fadeInUp" data-wow-delay="1s">
    <p class="post-content">{{ $training->description }}</p>
    <h4>Pogodnosti:</h4>
    <p class="post-content">{{ $training->benefits }}</p>
    <h4>Za koga je?</h4>
    <p class="post-content">{{ $training->target }}</p>
</div>

```

##### 4.5.3.2.4.2. header.blade.php

```

<section id="blog-header" class="parallax-section">
    <div class="container">
        <div class="row">
            <div class="col-md-offset-2 col-md-8 col-sm-12">
                <h3 class="wow bounceIn" data-wow-delay="0.9s">{{ $training->name }}</h3>
            </div>
        </div>
    </div>
</section>

```

#### 4.5.4. layouts

##### 4.5.4.1. back.blade.php

```

<!DOCTYPE html>
<html Lang="en">
    @include('back.partials.common.head')
    <body class="theme-deep-purple">
        @include('back.partials.common.loader')
        @include('back.partials.common.nav')

        @if(str_contains(url()->current(), '/admin'))
            @include('back.partials.admin.sidebar')
        @elseif(str_contains(url()->current(), '/energijapp/profile/') ||

```



```

(str_contains(url()->current(), '/energijapp/reservations') && session('user')-
>role->name == 'user'))
    @if(session('user')->role->name == 'user')
        @include('back.partials.energijapp.user.sidebar')
    @else
        @include('back.partials.energijapp.operator.sidebar')
    @endif
@else
    @include('back.partials.energijapp.operator.sidebar')
@endif

<section class="content" id="content">
    <div class="container-fluid">

        @if(str_contains(url()->current(), '/profile'))
            @include('back.partials.energijapp.profile.wrapper')
        @else
            @include('back.partials.common.wrapper')
        @endif

    </div>
</section>

    @include('back.partials.common.scripts')
</body>
</html>

```

#### 4.5.4.2. front.blade.php

```

<!DOCTYPE html>
<html lang="en">
    @include('front.partials.common.head')
    <body data-spy="scroll" data-target=".navbar-collapse" data-offset="50">
        @include('front.partials.common.preloader')
        @include('front.partials.common.nav')
        @yield('content')
        @include('front.partials.common.footer')
        @include('front.partials.common.scripts')
    </body>
</html>

```

## 4.6. Routes

### 4.6.1. api.php

```

<?php
Route::group(['namespace' => 'API', 'middleware' => 'loggedIn'], function () {
    Route::get('/arrivals/user/{id}', 'ArrivalController@getUserArrivals');
    Route::get('/payments/user/{id}/arrivals',
'PaymentController@getUserPaymentArrivals');
    Route::post('/reservations', 'ReservationController@store');

```

```

Route::get('/reservations/count', 'ReservationController@getCount');
Route::delete('/reservations/user/{id}',
'ReservationController@deleteUserReservations');
Route::get('/trainings/reservable', 'TrainingController@getReservable');
Route::get('/users/privilege', 'UserController@getPrivilege');
Route::patch('/users/{id}/change_password', 'UserController@changePassword');
});

Route::group(['namespace' => 'API', 'middleware' => 'privileged'], function () {
Route::get('/arrivals/{id}', 'ArrivalController@show');
Route::post('/arrivals', 'ArrivalController@store');
Route::patch('/arrivals/{id}', 'ArrivalController@update');
Route::delete('/arrivals/{id}', 'ArrivalController@destroy');
Route::get('/payments/{id}', 'PaymentController@show');
Route::post('/payments', 'PaymentController@store');
Route::patch('/payments/{id}', 'PaymentController@update');
Route::delete('/payments/{id}', 'PaymentController@destroy');
Route::get('/payments/user/{id}', 'PaymentController@getUserPayments');
Route::get('/prices', 'PriceController@index');
Route::delete('/reservations/{id}', 'ReservationController@destroy');
Route::get('/reservations/date_search', 'ReservationController@dateSearch');
Route::get('/trainings', 'TrainingController@index');
Route::get('/trainers', 'TrainerController@index');
Route::get('/users/card_number_search', 'UserController@cardNumberSearch');
Route::get('/users/name_search', 'UserController@nameSearch');
});

Route::group(['namespace' => 'API', 'middleware' => 'admin'], function () {
Route::get('/arrivals', 'ArrivalController@index');
Route::get('/payments', 'PaymentController@index');
Route::get('/users/operators', 'UserController@getOperators');
});

Route::fallback(function () {
abort(404);
});

```

## 4.6.2. web.php

```

<?php

Route::namespace('Core')->group(function () {
Route::get('/', 'FrontendController@home');
Route::post('/contact', 'FrontendController@contact');
Route::get('/sessions', 'FrontendController@sessions');
});

Route::namespace('Resource')->group(function () {
Route::get('/posts/pagination', 'PostController@pagination');
Route::get('/trainings/pagination', 'TrainingController@pagination');
});

Route::group(['prefix' => 'admin', 'middleware' => 'admin'], function () {
Route::get('/', 'Core\BackendController@admin');
Route::get('/arrivals', 'Resource\ArrivalController@index');

```

```

Route::get('/payments', 'Resource\PaymentController@index');
});

Route::namespace('MyAuth')->group(function () {
    Route::post('/login', 'LoginController@login');
    Route::get('/logout', 'LoginController@logout');
});

Route::group(['namespace' => 'MyAuth', 'prefix' => 'register'], function () {
    Route::post('/', 'RegisterController@register');
    Route::get('/{remember_token}', 'RegisterController@activate');
});

Route::group(['namespace' => 'Resource', 'prefix' => 'posts'], function () {
    Route::get('/{post}', 'PostController@show');
    Route::resource('{post}/comments', 'CommentController')->except(['show',
'index', 'create', 'edit'])->middleware('loggedIn');
});

Route::group(['namespace' => 'Resource', 'prefix' => 'trainings'], function () {
    Route::get('/{training}', 'TrainingController@show');
});

Route::group(['namespace' => 'Resource', 'prefix' => 'energijapp', 'middleware' =>
'loggedIn'], function () {
    Route::get('/profile/{user}', 'UserController@show');
    Route::patch('/images/user/{user}', 'UserController@image_update');
    Route::get('/reservations/user/{id}', 'ReservationController@create');
});

Route::group(['namespace' => 'Resource', 'prefix' => 'energijapp', 'middleware' =>
'privileged'], function () {
    Route::get('/users/create', 'UserController@create');
    Route::post('/users', 'UserController@store');
    Route::get('/users/{user}/edit', 'UserController@edit');
    Route::patch('/users/{user}', 'UserController@update');
    Route::get('/search', 'UserController@search');
    Route::get('/reservations', 'ReservationController@index');
    Route::get('/arrivals/create/payment/{id}', 'ArrivalController@create');
    Route::get('/arrivals/{id}/edit', 'ArrivalController@edit');
    Route::get('/payments/create/user/{id}', 'PaymentController@create');
    Route::get('/payments/{id}/edit', 'PaymentController@edit');
});

Route::group(['namespace' => 'Resource', 'prefix' => 'admin', 'middleware' =>
'admin'], function () {
    Route::resource('/users', 'UserController')->except('show', 'store',
'update');
    Route::resource('/posts', 'PostController')->except('show');
    Route::resource('/sliders', 'SliderController')->except('show');
    Route::resource('/menus', 'MenuController')->except('show');
    Route::resource('/trainers', 'TrainerController')->except('show');
    Route::resource('/trainings', 'TrainingController')->except('show');
});

```

```

Route::resource('/prices', 'PriceController')->except('show');
Route::resource('/services', 'ServiceController')->except('show');
Route::resource('/socials', 'SocialController')->except('show');
});

Route::fallback(function () {
    abort(404);
});

```

## 4.7. JavaScript

### 4.7.1. ajax\_admin.js

```

function deletion(id, table) {
    $.ajax({
        type: "delete",
        url: BASE_URL+"/"+table+"/"+id,
        data: {
            id : id,
            _token : TOKEN
        },
        success: function () {
            location.reload();
        },
        error: function (xhr) {
            $(".table-responsive").prepend("<div class='alert alert-warning alert-dismissible' role='alert'>" + xhr.status + ': ' + xhr.statusText + "<button type='button' class='close' data-dismiss='alert' aria-label='Close'><span aria-hidden='true'>&times;</span></button>");
        }
    });
}

```

### 4.7.2. ajax.js

```

$(document).ready(function () {
    $("#commentBtn").on("click", comment_store);
    $(document).on("click", "#training_pagination .pagination a",
training_pagination);
    $(document).on("click", "#post_pagination .pagination a", post_pagination);
});

function comment_store(e) {
    e.preventDefault();

    let commentMsg = $("#commentMsg").val();
    let postId = $("#postId").val();
    let loggedUserId = $("#loggedUserId").val();
    let postTitle = $("#postTitle").val();
    let loggedUserFN = $("#loggedUserFN").val();

```

```

    let loggedUserLN = $("#loggedUserLN").val();

    let reCommentMsg = /^[\\wĆČŽĐŠćčžđš .,!\\(\\?)'\\:\\-]{2,}$/;

    if(!commentMsg.match(reCommentMsg)){
        $(".blog-comment-form").prepend("<div class='alert alert-warning alert-dismissable' role='alert'>Bad message format.<button type='button' class='close' data-dismiss='alert' aria-label='Close'><span aria-hidden='true'>&times;</span></button>");
    }
    else{
        $.ajax({
            type: "post",
            url: BASE_URL + "/posts/"+postId+"/comments",
            data: {
                content: commentMsg,
                post_id : postId,
                user_id : loggedUserId,
                postTitle : postTitle,
                userFN : loggedUserFN,
                userLN : loggedUserLN,
                _token : TOKEN
            },
            success: function () {
                location.reload();
            },
            error: function (xhr) {
                $(".blog-comment-form").prepend("<div class='alert alert-warning alert-dismissable' role='alert'>"+xhr.status + ': ' + xhr.statusText+"<button type='button' class='close' data-dismiss='alert' aria-label='Close'><span aria-hidden='true'>&times;</span></button>");
            }
        });
    }
}

function comment_delete(post_id, comment_id, user_id, commentContent, userFN, userLN, postTitle) {
    $.ajax({
        type: "delete",
        url: BASE_URL + "/posts/"+post_id+"/comments/"+comment_id,
        data: {
            post_id : post_id,
            id : comment_id,
            user_id : user_id,
            commentContent : commentContent,
            userFN : userFN,
            userLN : userLN,
            postTitle : postTitle,
            _token : TOKEN
        },
        success: function () {
            location.reload();
        },
        error: function (xhr) {
            $(".blog-comment-form").prepend("<div class='alert alert-warning alert-dismissable' role='alert'>"+xhr.status + ': ' + xhr.statusText+"<button type='button' class='close' data-dismiss='alert' aria-label='Close'><span aria-hidden='true'>&times;</span></button>");
        }
    });
}

```

```

    });
}

function comment_update(post_id, comment_id, user_id, userFN, userLN, postTitle) {
    let editComment = $("#editComment").val();

    let reCommentMsg = /^[\\wĆČŽĐŠćčžđš .,!(\\?)':"-]{2,}$/;

    if(!editComment.match(reCommentMsg)){
        $(".blog-comment-form").prepend("<div class='alert alert-warning alert-dismissable' role='alert'>Bad message format.<button type='button' class='close' data-dismiss='alert' aria-label='Close'><span aria-hidden='true'>&times;</span></button>");
    }
    else{
        $.ajax({
            type: "patch",
            url: BASE_URL + "/posts/" + post_id + "/comments/" + comment_id,
            data: {
                post_id: post_id,
                id: comment_id,
                user_id: user_id,
                content: editComment,
                userFN: userFN,
                userLN: userLN,
                postTitle: postTitle,
                _token: TOKEN
            },
            success: function () {
                location.reload();
            },
            error: function (xhr) {
                $(".blog-comment-form").prepend("<div class='alert alert-warning alert-dismissable' role='alert'>" + xhr.status + ': ' + xhr.statusText + "<button type='button' class='close' data-dismiss='alert' aria-label='Close'><span aria-hidden='true'>&times;</span></button>");
            }
        });
    }
}

function training_pagination(e) {
    e.preventDefault();

    let pageNumber = $(this).attr("href").split("page=")[1];

    $.ajax({
        type: "get",
        url: BASE_URL + "/trainings/pagination?page=" + pageNumber,
        success: function (data) {
            $("#training_data").html(data);
        },
        error: function (xhr) {
            $("#training_data").prepend("<div class='alert alert-warning alert-dismissable' role='alert'>" + xhr.status + ': ' + xhr.statusText + "<button type='button' class='close' data-dismiss='alert' aria-label='Close'><span aria-hidden='true'>&times;</span></button>");
        }
    });
}

```

```

    });
  }
}

function post_pagination(e) {
  e.preventDefault();

  let pageNumber = $(this).attr("href").split("page=")[1];

  $.ajax({
    type: "get",
    url: BASE_URL + "/posts/pagination?page=" + pageNumber,
    success: function (data) {
      $("#post_data").html(data);
    },
    error: function (xhr) {
      $("#post_data").prepend("<div class='alert alert-warning alert-dismissible' role='alert'>" + xhr.status + ': ' + xhr.statusText + "<button type='button' class='close' data-dismiss='alert' aria-label='Close'><span aria-hidden='true'>&times;</span></button></div>");
    }
  });
}

```

## 4.7.3. Components

### 4.7.3.1. admin

#### 4.7.3.1.1. ArrivalsTable.vue

```

<template>
  <div>
    <div id="reservation-list" class="text-center">
      <p class="lead">Pregled dolazaka</p>
      <br/>
      <form class="form-inline text-center">
        <div class="form-group form-inline-elements">
          <label for="date_from">Datum od:</label>
          <input type="date" class="form-control" id="date_from"
name="date_from" v-model="date_from" />
        </div>
        <div class="form-group form-inline-elements">
          <label for="date_to">Datum do:</label>
          <input type="date" class="form-control" id="date_to"
name="date_to" v-model="date_to" />
        </div>
        <div class="form-group form-inline-elements">
          <label for="training_id">Trening</label>
          <select id="training_id" name="training_id" class="form-
control" v-model="training_id">
            <option value="">Svi</option>
            <option v-for="training in trainings"
:value="training.id">{{ training.name }}</option>

```

```

        </select>
    </div>
    <div class="form-group form-inline-elements">
        <label for="trainer_id">Trener</label>
        <select id="trainer_id" name="trainer_id" class="form-control"
v-model="trainer_id">
            <option value="">Svi</option>
            <option v-for="trainer in trainers" :value="trainer.id">{{
trainer.first_name }} {{ trainer.last_name }}</option>
        </select>
    </div>
    <div class="form-group form-inline-elements">
        <button type="button" name="arrivalBtn" id="arrivalBtn"
class="btn btn-dark waves-effect waves-light" @click="searchArrivals"><i
class="material-icons">search</i> Nađi</button>
    </div>
</form>
</div>
<br/>
<div v-if="isVisible">
    <h3 class="text-center">Broj dolazaka: {{ arrivalCount }}</h3>
    <br/>
    <div class="table-responsive">
        <table class="table table-striped">
            <thead>
                <tr class="dark">
                    <th>Broj kartice</th>
                    <th>Član</th>
                    <th>Trening</th>
                    <th>Trener</th>
                    <th>Datum dolaska</th>
                </tr>
            </thead>
            <tbody>
                <tr v-for="arrival in arrivals">
                    <td>{{ arrival.user.card_number }}</td>
                    <td>{{ arrival.user.first_name }} {{
arrival.user.last_name }}</td>
                    <td>{{ arrival.training.name }}</td>
                    <td>{{ arrival.trainer.first_name }} {{
arrival.trainer.last_name }}</td>
                    <td>{{ new Date(arrival.date).getDate()+'.'+(new
Date(arrival.date).getMonth()+1)+'.'+new Date(arrival.date).getFullYear()+'.'
}}</td>
                </tr>
            </tbody>
        </table>
        <div class="text-center">
            <button class="btn btn-dark"
@click="fetchPaginateArrivals(pagination.prev_page_url)"
:disabled="!pagination.prev_page_url">
                <
            </button>

            <span>{{ pagination.current_page }} od {{ pagination.last_page
}}</span>

            <button class="btn btn-dark"
@click="fetchPaginateArrivals(pagination.next_page_url)"
:disabled="!pagination.next_page_url">

```



```

        >
        </button>
      </div>
    </div>
    <br/>
  </div>
</div>
</template>

<script>
  export default {
    data() {
      return {
        trainings: [],
        training: {
          id: '',
          name: ''
        },
        trainers: [],
        trainer: {
          id: '',
          first_name: '',
          last_name: ''
        },
        date_from: '',
        date_to: '',
        training_id: '',
        trainer_id: '',
        arrivals: [],
        arrival: {
          date: '',
          user: {
            first_name: '',
            last_name: '',
            card_number: ''
          },
          training: {
            name: ''
          },
          trainer: {
            first_name: '',
            last_name: ''
          }
        },
        arrivalCount: 0,
        isVisible: false,
        url: '/api/arrivals',
        pagination: []
      }
    },
    mounted() {
      this.getTrainings();
      this.getTrainers();
    },
    methods: {
      getTrainings() {
        axios.get('/api/trainings').then(response => {
          this.trainings = response.data
        }).catch(error => {
          console.log(error)
        })
      }
    }
  }

```

```

    })
  },

  getTrainers() {
    axios.get('/api/trainers').then(response => {
      this.trainers = response.data
    }).catch(error => {
      console.log(error)
    })
  },

  searchArrivals() {
    let $this = this;

    axios.get(this.url, {
      params: {
        date_from: this.date_from,
        date_to: this.date_to,
        training_id: this.training_id,
        trainer_id: this.trainer_id
      }
    })
    .then(response => {
      this.isVisible = true;
      this.arrivals = response.data.data;
      this.arrivalCount = response.data.total;
      $this.pagination = response.data
    })
    .catch(error => {
      console.log(error)
    })
  },

  makePagination(data) {
    this.pagination = {
      current_page: data.current_page,
      last_page: data.last_page,
      next_page_url: data.next_page_url,
      prev_page_url: data.prev_page_url
    }
  },

  fetchPaginateArrivals(url) {
    this.url = url;
    this.searchArrivals()
  }
}
</script>

```

#### 4.7.3.1.2. PaymentsTable.vue

```

<template>
  <div>
    <div id="reservation-list" class="text-center">
      <p class="lead">Prehled uplata</p>
      <br/>
    </div>
  </div>
</template>

```

```

        <form class="form-inline text-center">
            <div class="form-group form-inline-elements">
                <label for="date_from">Datum od:</label>
                <input type="date" class="form-control" id="date_from"
name="date_from" v-model="date_from" />
            </div>
            <div class="form-group form-inline-elements">
                <label for="date_to">Datum do:</label>
                <input type="date" class="form-control" id="date_to"
name="date_to" v-model="date_to" />
            </div>
            <div class="form-group form-inline-elements">
                <label for="price_id">Paket</label>
                <select id="price_id" name="price_id" class="form-control" v-
model="price_id">
                    <option value="">Svi</option>
                    <option v-for="price in prices" :value="price.id">{{
price.title }}</option>
                </select>
            </div>
            <div class="form-group form-inline-elements">
                <label for="operator_id">Operater</label>
                <select id="operator_id" name="operator_id" class="form-
control" v-model="operator_id">
                    <option value="">Svi</option>
                    <option v-for="operator in operators"
:value="operator.id">{{ operator.first_name }} {{ operator.last_name }}</option>
                </select>
            </div>
            <div class="form-group form-inline-elements">
                <button type="button" name="earningBtn" id="earningBtn"
class="btn btn-dark waves-effect waves-light" @click="searchPayments"><i
class="material-icons">search</i> Nađi</button>
            </div>
        </form>
    </div>
    <br/>
    <div v-if="isVisible">
        <h3 class="text-center">Zarada: {{ paymentSum }} Din.</h3>
        <br/>
        <div class="table-responsive" >
            <table class="table table-striped">
                <thead>
                    <tr class="dark">
                        <th>Broj kartice</th>
                        <th>Član</th>
                        <th>Paket</th>
                        <th>Operater</th>
                        <th>Datum update</th>
                    </tr>
                </thead>
                <tbody>
                    <tr v-for="payment in payments">
                        <td>{{ payment.user.card_number }}</td>
                        <td>{{ payment.user.first_name }} {{
payment.user.last_name }}</td>
                        <td>{{ payment.price.title }}</td>
                        <td>{{ payment.operator.first_name }} {{
payment.operator.last_name }}</td>
                        <td>{{ new Date(payment.payment_date).getDate()+'.'+(new

```

```

Date(payment.payment_date).getMonth()+1)+'.'+new
Date(payment.payment_date).getFullYear()+'.' }}</td>
</tr>
</tbody>
</table>
<div class="text-center">
  <button class="btn btn-dark"
@click="fetchPaginatePayments(pagination.prev_page_url)"
:disabled="!pagination.prev_page_url">
    <
  </button>

  <span>{{ pagination.current_page }} od {{ pagination.last_page
}}</span>

  <button class="btn btn-dark"
@click="fetchPaginatePayments(pagination.next_page_url)"
:disabled="!pagination.next_page_url">
    >
  </button>
</div>
<br/>
</div>
</div>
</div>
</template>
<script>
  export default {
    data() {
      return {
        prices: [],
        price: {
          id: '',
          title: ''
        },
        operators: [],
        operator: {
          id: '',
          first_name: '',
          last_name: ''
        },
        date_from: '',
        date_to: '',
        price_id: '',
        operator_id: '',
        payments: [],
        payment: {
          payment_date: '',
          price: {
            title: ''
          },
          operator: {
            first_name: '',
            last_name: ''
          },
          user: {
            first_name: '',
            last_name: '',
            card_number: ''

```

```

        }
    },
    paymentSum: 0,
    isVisible: false,
    url: '/api/payments',
    pagination: []
  },
  mounted() {
    this.getPrices();
    this.getOperators();
  },
  methods: {
    getPrices() {
      axios.get('/api/prices').then(response => {
        this.prices = response.data
      }).catch(error => {
        console.log(error)
      })
    },

    getOperators() {
      axios.get('/api/users/operators').then(response => {
        this.operators = response.data
      }).catch(error => {
        console.log(error)
      })
    },

    searchPayments() {
      let $this = this;

      axios.get(this.url, {
        params: {
          date_from: this.date_from,
          date_to: this.date_to,
          price_id: this.price_id,
          operator_id: this.operator_id
        }
      })
      .then(response => {
        this.isVisible = true;
        this.payments = response.data[0].data;
        this.paymentSum = response.data[1];
        $this.pagination = response.data[0]
      })
      .catch(error => {
        console.log(error)
      })
    },

    makePagination(data) {
      this.pagination = {
        current_page: data.current_page,
        last_page: data.last_page,
        next_page_url: data.next_page_url,
        prev_page_url: data.prev_page_url
      }
    },
  },

```

```

        fetchPaginatePayments(url) {
            this.url = url;
            this.searchPayments()
        }
    }
}
</script>

```

## 4.7.3.2. energijapp

### 4.7.3.2.1. operator

#### 4.7.3.2.1.1. arrivals

##### 4.7.3.2.1.1.1. ArrivalCreate.vue

```

<template>
    <div class="body">
        <div class="row">
            <div class="col-md-4 col-md-offset-4">
                <p class="lead">Dodaj dolazak</p>
                <form>
                    <br/>
                    <div class="form-group">
                        <label for="date"><p><i>Datum:</i></p></label>
                        <div class="form-line">
                            <input name="date" id="date" type="date" class="form-
model="date" v-model="date" required />
                        </div>
                    </div>
                    <div class="form-group">
                        <label for="training_id"><p><i>Trening:</i></p></label>
                        <br/>
                        <select name="training_id" id="training_id" v-
model="training_id" required>
                            <option v-for="training in trainings"
:value="training.id">{{ training.name }}</option>
                        </select>
                    </div>
                    <div class="form-group">
                        <div class="form-group">
                            <label for="trainer_id"><p><i>Trener:</i></p></label>
                            <br/>
                            <select name="trainer_id" id="trainer_id" v-
model="trainer_id" required>
                                <option v-for="trainer in trainers"
:value="trainer.id">{{ trainer.first_name }} {{ trainer.last_name }}</option>
                            </select>
                        </div>
                    </div>
                    <div class="form-group">
                        <button type="button" name="arrivalBtn" id="arrivalBtn"
class="btn btn-dark waves-effect waves-light"

```

```

@click="storeArrival()">Dodaj</button>
      <a href="#" onclick="history.back(-1)" class="btn waves-
effect">Otkazi</a>
    </div>
    <div v-if="isFail" class="error">Termini su iskorićeni.</div>
  </form>
</div>
</div>
</div>
</template>

<script>
  export default {
    props: ['payment_id', 'user_id'],
    data() {
      return {
        date: '',
        training_id: 1,
        trainer_id: 1,
        trainings: [],
        training: {
          id: '',
          name: ''
        },
        trainers: [],
        trainer: {
          id: '',
          first_name: '',
          last_name: ''
        },
        isFail: false
      }
    },
    mounted() {
      this.getTrainings();
      this.getTrainers()
    },
    methods: {
      getTrainings() {
        axios.get('/api/trainings').then(response => {
          this.trainings = response.data
        }).catch(error => {
          console.log(error)
        })
      },
      getTrainers() {
        axios.get('/api/trainers').then(response => {
          this.trainers = response.data
        }).catch(error => {
          console.log(error)
        })
      },
      storeArrival() {
        axios.post('/api/arrivals', {
          date: this.date,
          training_id: this.training_id,
          trainer_id: this.trainer_id,
          payment_id: this.payment_id,

```

```

        user_id: this.user_id
    }).then(response => {
        window.location.replace('/energijapp/profile/'+this.user_id)
    }).catch(error => {
        console.log(error);
        this.isFail = true
    })
    }
}
</script>

```

#### 4.7.3.2.1.1.1. ArrivalEdit.vue

```

<template>
  <div class="body">
    <div class="row">
      <div class="col-md-4 col-md-offset-4">
        <p class="lead">Izmeni dolazak</p>
        <form>
          <br/>
          <div class="form-group">
            <label for="date"><p><i>Datum:</i></p></label>
            <div class="form-line">
              <input name="date" id="date" type="date" class="form-
control" v-model="date" required />
            </div>
          </div>
          <div class="form-group">
            <label for="training_id"><p><i>Trening:</i></p></label>
            <br/>
            <select name="training_id" id="training_id" v-
model="training_id" required>
              <option v-for="training in trainings"
:value="training.id">{{ training.name }}</option>
            </select>
          </div>
          <div class="form-group">
            <div class="form-group">
              <label for="trainer_id"><p><i>Trener:</i></p></label>
              <br/>
              <select name="trainer_id" id="trainer_id" v-
model="trainer_id" required>
                <option v-for="trainer in trainers"
:value="trainer.id">{{ trainer.first_name }} {{ trainer.last_name }}</option>
              </select>
            </div>
          </div>
          <div class="form-group">
            <button type="button" name="arrivalBtn" id="arrivalBtn"
class="btn btn-dark waves-effect waves-light"
@click="updateArrival()">Dodaj</button>
            <a href="#" onclick="history.back(-1)" class="btn waves-
effect">Otkazi</a>
          </div>
        </form>
      </div>
    </div>
  </div>

```



```

    </div>
  </div>
</template>

<script>
  export default {
    props: ['arrival_id', 'user_id'],
    data() {
      return {
        date: '',
        training_id: '',
        trainer_id: '',
        trainings: [],
        training: {
          id: '',
          name: ''
        },
        trainers: [],
        trainer: {
          id: '',
          first_name: '',
          last_name: ''
        }
      }
    },
    mounted() {
      this.getTrainings();
      this.getTrainers();
      this.getArrival()
    },
    methods: {
      getTrainings() {
        axios.get('/api/trainings').then(response => {
          this.trainings = response.data
        }).catch(error => {
          console.log(error)
        })
      },

      getTrainers() {
        axios.get('/api/trainers').then(response => {
          this.trainers = response.data
        }).catch(error => {
          console.log(error)
        })
      },

      getArrival() {
        axios.get('/api/arrivals/'+this.arrival_id).then(response => {
          this.date = response.data.date;
          this.training_id = response.data.training_id;
          this.trainer_id = response.data.trainer_id
        }).catch(error => {
          console.log(error)
        })
      },

      updateArrival() {
        axios.patch('/api/arrivals/'+this.arrival_id, {
          date: this.date,

```

```

        training_id: this.training_id,
        trainer_id: this.trainer_id
    }).then(response => {
        window.location.replace('/energijapp/profile/'+this.user_id)
    }).catch(error => {
        console.log(error)
    })
  }
}
</script>

```

#### 4.7.3.2.1.2. payments

##### 4.7.3.2.1.2.1. PaymentCreate.vue

```

<template>
  <div class="body">
    <div class="row">
      <div class="col-md-4 col-md-offset-4">
        <p class="lead">Dodaj uplatu</p>
        <form>
          <br/>
          <div class="form-group">
            <label for="price_id"><p><i>Paket:</i></p></label>
            <br/>
            <select name="price_id" id="price_id" v-model="price_id"
required>
              <option v-for="price in prices" :value="price.id">{{
price.title }}</option>
            </select>
          </div>
          <div class="form-group">
            <label for="payment_date"><p><i>Datum
update:</i></p></label>
            <div class="form-line">
              <input name="payment_date" id="payment_date"
type="date" class="form-control" v-model="payment_date" required />
            </div>
          </div>
          <div class="form-group">
            <label for="valid_thru"><p><i>Datum
isteka:</i></p></label>
            <div class="form-line">
              <input name="valid_thru" id="valid_thru" type="date"
class="form-control" v-model="valid_thru" required />
            </div>
          </div>
          <div class="form-group">
            <button type="button" name="paymentBtn" id="paymentBtn"
class="btn btn-dark waves-effect waves-light"
@click="storePayment()">Dodaj</button>
            <a href="#" onclick="history.back(-1)" class="btn waves-
effect">Otkazi</a>
          </div>
        </form>
      </div>
    </div>
  </div>

```

```

        </div>
      </div>
    </div>
  </template>

  <script>
    export default {
      props: ['user_id', 'operator_id'],
      data() {
        return {
          price_id: 1,
          payment_date: '',
          valid_thru: '',
          prices: [],
          price: {
            id: '',
            title: ''
          }
        }
      },
      mounted() {
        this.getPrices()
      },
      methods: {
        getPrices() {
          axios.get('/api/prices').then(response => {
            this.prices = response.data
          }).catch(error => {
            console.log(error)
          })
        },

        storePayment() {
          axios.post('/api/payments', {
            price_id: this.price_id,
            payment_date: this.payment_date,
            valid_thru: this.valid_thru,
            user_id: this.user_id,
            operator_id: this.operator_id
          }).then(response => {
            window.location.replace('/energijapp/profile/'+this.user_id)
          }).catch(error => {
            console.log(error)
          })
        }
      }
    }
  </script>

```

#### 4.7.3.2.1.2.2. PaymentEdit.vue

```

<template>
  <div class="body">
    <div class="row">
      <div class="col-md-4 col-md-offset-4">
        <p class="lead">Izmeni uplatu</p>
        <form>

```

```

        <br/>
        <div class="form-group">
          <label for="price_id"><p><i>Paket:</i></p></label>
          <br/>
          <select name="price_id" id="price_id" v-model="price_id"
required>
            <option v-for="price in prices" :value="price.id">{{
price.title }}</option>
          </select>
        </div>
        <div class="form-group">
          <label for="payment_date"><p><i>Datum
update:</i></p></label>
          <div class="form-line">
            <input name="payment_date" id="payment_date"
type="date" class="form-control" v-model="payment_date" required />
          </div>
        </div>
        <div class="form-group">
          <label for="valid_thru"><p><i>Datum
isteka:</i></p></label>
          <div class="form-line">
            <input name="valid_thru" id="valid_thru" type="date"
class="form-control" v-model="valid_thru" required />
          </div>
        </div>
        <div class="form-group">
          <button type="button" name="paymentBtn" id="paymentBtn"
class="btn btn-dark waves-effect waves-light"
@click="updatePayment()">Izmeni</button>
          <a href="#" onclick="history.back(-1)" class="btn waves-
effect">Otkazi</a>
        </div>
      </form>
    </div>
  </div>
</template>

<script>
  export default {
    props: ['payment_id', 'user_id'],
    data() {
      return {
        price_id: '',
        payment_date: '',
        valid_thru: '',
        prices: [],
        price: {
          id: '',
          title: ''
        }
      }
    },
    mounted() {
      this.getPrices();
      this.getPayment()
    },
    methods: {
      getPrices() {

```

```

        axios.get('/api/prices').then(response => {
            this.prices = response.data
        }).catch(error => {
            console.log(error)
        })
    },

    getPayment() {
        axios.get('/api/payments/'+this.payment_id).then(response => {
            this.price_id = response.data.price_id;
            this.payment_date = response.data.payment_date;
            this.valid_thru = response.data.valid_thru
        }).catch(error => {
            console.log(error)
        })
    },

    updatePayment() {
        axios.patch('/api/payments/'+this.payment_id, {
            price_id: this.price_id,
            payment_date: this.payment_date,
            valid_thru: this.valid_thru
        }).then(response => {
            window.location.replace('/energijapp/profile/'+this.user_id)
        }).catch(error => {
            console.log(error)
        })
    }
}
}
</script>

```

#### 4.7.3.2.1.3. reservations

##### 4.7.3.2.1.3.1. ReservationsTable.vue

```

<template>
  <div>
    <div id="reservation-list" class="text-center">
      <p class="lead">Pregled rezervacija</p>
      <form>
        <div id="date-line" class="center-block">
          <input type="date" class="form-control" id="training_date"
name="training_date" required v-model="training_date" @change="dateSearch">
        </div>
      </form>
    </div>
    <br/>
    <div class="table-responsive" v-if="isVisible">
      <table class="table table-striped">
        <thead>
          <tr class="dark">
            <th>Broj kartice</th>
            <th>Član</th>
            <th>Trening</th>
            <th>Obriši</th>

```

```

        </tr>
      </thead>
      <tbody>
        <tr v-for="(reservation, index) in reservations">
          <td>{{ reservation.user.card_number }}</td>
          <td>{{ reservation.user.first_name }} {{
reservation.user.last_name }}</td>
          <td>{{ reservation.training.name }}</td>
          <td>
            <button class="btn dtp-btn-clear waves-effect btn-xs"
@click="deleteReservation(reservation.id, index)">
              <i class="material-icons">delete_forever</i>
            </button>
          </td>
        </tr>
      </tbody>
    </table>
  </div>
</div>
</template>

<script>
  export default {
    data() {
      return {
        training_date: '',
        reservations: [],
        reservation: {
          id: '',
          user: {
            first_name: '',
            last_name: '',
            card_number: ''
          },
          training: {
            name: ''
          }
        },
        isVisible: false
      }
    },
    methods: {
      dateSearch() {
        axios.get('/api/reservations/date_search', {
          params: {
            training_date: this.training_date
          }
        })
          .then(response => {
            this.isVisible = true;
            this.reservations = response.data
          })
          .catch(error => {
            console.log(error)
          })
      },

      deleteReservation(id, index) {
        axios.delete('/api/reservations/'+id).then(response => {
          this.reservations.splice(index, 1);

```

```

        }).catch(error => {
            console.log(error)
        })
    }
}
</script>

```

#### 4.7.3.2.1.4. users

##### 4.7.3.2.1.4.1. CardNumberSearch.vue

```

<template>
  <form @submit.prevent>
    <div class="form-group">
      <div class="form-line">
        <input ref="cn" name="card_number" id="card_number" type="text"
        maxLength="5" class="form-control text-center" placeholder="Broj kartice (skener)"
        v-model="card_number" @keyup="cardNumberSearch" autofocus />
      </div>
    </div>
  </form>
</template>

<script>
  export default {
    data() {
      return {
        card_number: ''
      }
    },
    methods: {
      cardNumberSearch() {
        axios.get('/api/users/card_number_search', {
          params: {
            card_number: this.card_number
          }
        })
          .then(response => {
            if(response.data[0].id != null)
              location.replace('/energijapp/profile/' +
response.data[0].id)
          })
          .catch(error => {
            console.log(error)
          })
        }
      }
    }
  }
</script>

```

##### 4.7.3.2.1.4.2. NameSearch.vue

```

<template>
  <div>
    <form>
      <div class="form-group">
        <div class="form-line">
          <input name="first_name" id="first_name" type="text"
class="form-control" placeholder="Ime" v-model="first_name" />
        </div>
      </div>
      <div class="form-group">
        <div class="form-line">
          <input name="title" id="title" type="text" class="form-
control" placeholder="Prezime" v-model="last_name" />
        </div>
      </div>
      <div class="form-check">
        <input type="checkbox" class="form-check-input" id="active"
name="active" v-model="active" />
        <label class="form-check-label" for="active">
          Samo aktivni
        </label>
      </div>
      <br/>
      <div class="form-group">
        <button type="button" name="searchUsrBtn" id="searchUsrBtn"
class="btn btn-dark waves-effect waves-light" @click="nameSearch"><i
class="material-icons">search</i> Nadi</button>
        <a href="/energijapp/users/create" class="btn btn-dark pull-
right"><i class="material-icons">add</i> Dodaj korisnika</a>
      </div>
    </form>

    <div class="table-responsive" v-if="isVisible">
      <table class="table table-striped">
        <thead>
          <tr class="dark">
            <th>Broj kartice</th>
            <th>Ime i prezime</th>
          </tr>
        </thead>
        <tbody>
          <tr v-for="user in users">
            <td>{{ user.card_number }}</td>
            <td><a :href="'/energijapp/profile/'+user.id">{{
user.first_name }} {{ user.last_name }}</a></td>
          </tr>
        </tbody>
      </table>
      <div class="text-center">
        <button class="btn btn-dark"
@click="fetchPaginateUsers(pagination.prev_page_url)"
:disabled="!pagination.prev_page_url">
          <
        </button>

        <span>{{ pagination.current_page }} od {{ pagination.last_page
}}</span>

        <button class="btn btn-dark"
@click="fetchPaginateUsers(pagination.next_page_url)"

```



```

:disabled="!pagination.next_page_url">
    >
    </button>
  </div>
  <br/>
</div>
</div>
</template>

<script>
  export default {
    data() {
      return {
        first_name: '',
        last_name: '',
        active: '',
        users: [],
        user: {
          id: '',
          card_number: '',
          first_name: '',
          last_name: ''
        },
        isVisible: false,
        url: '/api/users/name_search',
        pagination: []
      }
    },
    methods: {
      nameSearch() {
        let $this = this;

        axios.get(this.url, {
          params: {
            first_name: this.first_name,
            last_name: this.last_name,
            active: this.active
          }
        })
        .then(response => {
          this.isVisible = true;
          this.users = response.data.data;
          $this.pagination = response.data
        })
        .catch(error => {
          console.log(error)
        })
      },

      makePagination(data) {
        this.pagination = {
          current_page: data.current_page,
          last_page: data.last_page,
          next_page_url: data.next_page_url,
          prev_page_url: data.prev_page_url
        }
      },

      fetchPaginateUsers(url) {
        this.url = url;
      }
    }
  }

```

```

        this.nameSearch()
    }
}
}
</script>

```

#### 4.7.3.2.2. profile

##### 4.7.3.2.2.1. ChangePassword.vue

```

<template>
  <div role="tabpanel" class="tab-pane fade in" id="change_password">
    <form class="form-horizontal">
      <div class="form-group">
        <label for="NewPassword" class="col-sm-3 control-label">Nova
lozinka</label>
        <div class="col-sm-9">
          <div class="form-line">
            <input type="password" class="form-control"
id="NewPassword" name="NewPassword" placeholder="Nova lozinka" v-
model="newPassword" required />
          </div>
        </div>
      </div>
      <div class="form-group">
        <label for="NewPasswordConfirm" class="col-sm-3 control-
label">Nova lozinka ponovo</label>
        <div class="col-sm-9">
          <div class="form-line">
            <input type="password" class="form-control"
id="NewPasswordConfirm" name="NewPasswordConfirm" placeholder="Nova lozinka
ponovo" v-model="newPasswordConfirm" required />
          </div>
        </div>
      </div>
      <div class="form-group">
        <div class="col-sm-offset-3 col-sm-9">
          <button type="button" class="btn btn-dark" id="btnChangePass"
name="btnChangePass" @click="changePassword">POTVRDI</button>
        </div>
      </div>
    </form>

    <div class="text-center error" v-if="isFail">Lozinke se moraju poklapati,
imati 6 karaktera i bar jedno veliko slovo i broj.</div>
    <div class="text-center text-success" v-if="isSuccess">Lozinka
promenjena.</div>
  </div>
</template>

<script>
  export default {
    props: ['user_id'],
    data() {
      return {

```

```

        newPassword: '',
        newPasswordConfirm: '',
        isSuccess: false,
        isFail : false
    }
},
methods: {
    changePassword() {
        axios.patch('/api/users/'+this.user_id+'/change_password', {
            newPassword: this.newPassword,
            newPasswordConfirm: this.newPasswordConfirm
        }).then(response => {
            this.isSuccess = true;
            this.isFail = false
        }).catch(error => {
            console.log(error.message);
            this.isFail = true;
            this.isSuccess = false
        })
    }
}
}
</script>

```

#### 4.7.3.2.2.2. UserPaymentArrivals.vue

```

<template>
    <div role="tabpanel" class="tab-pane fade in active" id="user_arrivals">
        <calendar-heatmap :values="calendarValues" :end-date="calendarEndDate"
        tooltip-unit="trainings" :range-color="['#e6e6fa', '#ffc100', '#ff9a00',
        '#ff7400', '#ff4d00', '#ff0000']" />
        <br/><br/>
        <div v-for="payment in payments" class="panel-group"
        :id="'accordion_'+payment.id" role="tablist" aria-multiselectable="true">
            <div class="panel panel-col-deep-purple">
                <div class="panel-heading" role="tab" :id="'heading_'+payment.id">
                    <h4 class="panel-title">
                        <a class="collapsed" role="button" data-toggle="collapse"
                        :data-parent="'#accordion_'+payment.id" :href="'#collapse_'+payment.id" aria-
                        expanded="false" :aria-controls="'collapse_'+payment.id">
                            {{ payment.price.title }} <p class="pull-right">{{ new
                            Date(payment.payment_date).getDate()+'. '+new
                            Date(payment.payment_date).getMonth()+1+'. '+new
                            Date(payment.payment_date).getFullYear()+'. ' }} - {{ new
                            Date(payment.valid_thru).getDate()+'. '+new
                            Date(payment.valid_thru).getMonth()+1+'. '+new
                            Date(payment.valid_thru).getFullYear()+'. ' }}</p>
                        </a>
                    </h4>
                </div>
                <div :id="'collapse_'+payment.id" class="panel-collapse collapse"
                role="tabpanel" :aria-labelledby="'heading_'+payment.id">
                    <div class="panel-body">
                        <h3><a v-if="isPrivileged"
                        :href="/energijapp/arrivals/create/payment/'+payment.id" class="btn btn-dark
                        waves-effect">Dodaj dolazak</a></h3>
                        <hr v-if="isPrivileged" />
                    </div>
                </div>
            </div>
        </div>
    </div>

```

```

        <div class="table-responsive">
            <table class="table table-striped">
                <thead class="dark">
                    <tr>
                        <th>Trening</th>
                        <th v-if="isPrivileged">Trener</th>
                        <th>Datum</th>
                        <th v-if="isPrivileged">Izmeni</th>
                        <th v-if="isPrivileged">Obriši</th>
                    </tr>
                </thead>
                <tbody>
                    <tr v-for="arrival in payment.arrivals">
                        <td>{{ arrival.training &&
arrival.training.name }}</td>
                        <td v-if="isPrivileged">{{ arrival.trainer &&
arrival.trainer.first_name }} {{ arrival.trainer &&
arrival.trainer.last_name.charAt(0)+'.' }}</td>
                        <td>{{ new
Date(arrival.date).getDate()+'.'+(new Date(arrival.date).getMonth()+1)+'.'+new
Date(arrival.date).getFullYear()+'.' }}</td>
                        <td v-if="isPrivileged"><a
:href=""/energijapp/arrivals/'+arrival.id+'/edit'" class="btn btn-dark waves-
effect btn-xs"><i class="material-icons">edit</i></a></td>
                        <td v-if="isPrivileged">
                            <button class="btn dtp-btn-clear waves-
effect btn-xs" @click="deleteArrival(arrival.id)">
                                <i class="material-
icons">delete_forever</i>
                            </button>
                        </td>
                    </tr>
                </tbody>
            </table>
        </div>
    </div>
</div>
<div class="text-center">
    <button class="btn btn-dark"
@click="fetchPaginateUserPayments(pagination.prev_page_url)"
:disabled="!pagination.prev_page_url">
        <
    </button>

    <span>{{ pagination.current_page }} od {{ pagination.last_page
}}</span>

    <button class="btn btn-dark"
@click="fetchPaginateUserPayments(pagination.next_page_url)"
:disabled="!pagination.next_page_url">
        >
    </button>
</div>
<br/>
</div>
</template>
<script>

```

```

import 'vue-calendar-heatmap/dist/vue-calendar-heatmap.css'
import { CalendarHeatmap } from 'vue-calendar-heatmap/dist/vue-calendar-heatmap.common'

export default {
  components: {
    CalendarHeatmap
  },
  props: ['user_id'],
  data() {
    return {
      isPrivileged: false,
      payments: [],
      payment: {
        id: '',
        payment_date: '',
        valid_thru: '',
        price_id: '',
        user_id: '',
        price: {
          title: '',
          sessions: ''
        },
        arrivals: [],
        arrival: {
          id: '',
          date: '',
          training: {
            name: ''
          },
          trainer: {
            first_name: '',
            last_name: ''
          }
        }
      },
      calendarEndDate: new Date(),
      calendarValues: [],
      url: '/api/payments/user/' + this.user_id + '/arrivals',
      pagination: []
    }
  },
  created() {
    this.getPrivilege();
    this.getUserArrivals();
    this.getUserPaymentArrivals()
  },
  methods: {
    getPrivilege() {
      axios.get('/api/users/privilege')
        .then(response => {
          this.isPrivileged = true
        })
        .catch(error => {
        })
    },

    getUserArrivals() {
      axios.get('/api/arrivals/user/' + this.user_id)
        .then(response => {

```

```

        this.calendarValues = response.data
    })
    .catch(error => {
        console.log(error)
    })
},

getUserPaymentArrivals() {
    let $this = this;

    axios.get(this.url)
        .then(response => {
            this.payments = response.data.data;
            $this.pagination = response.data
        })
        .catch(error => {
            console.log(error)
        })
},

deleteArrival(id) {
    axios.delete('/api/arrivals/' + id).then(response => {
        location.reload()
    }).catch(error => {
        console.log(error)
    })
},

makePagination(data) {
    this.pagination = {
        current_page: data.current_page,
        last_page: data.last_page,
        next_page_url: data.next_page_url,
        prev_page_url: data.prev_page_url
    }
},

fetchPaginateUserPayments(url) {
    this.url = url;
    this.getUserPaymentArrivals()
}
}
}
</script>

```

#### 4.7.3.2.2.3. UserPayments.vue

```

<template>
    <div role="tabpanel" class="tab-pane fade in" id="user_payments">
        <h3><a href="" /energijapp/payments/create/user/' + user_id" class="btn btn-
dark waves-effect">Dodaj uplatu</a><p class="pull-right">Ukupno uplaćeno: {{
userPaymentSum }} Din.</p></h3>
        <hr/>
        <div class="table-responsive">
            <table class="table table-striped">
                <thead class="dark">
                    <tr>

```

```

        <th>Paket</th>
        <th>Datum uplate</th>
        <th>Datum isteka</th>
        <th>Izmeni</th>
        <th>Obriši</th>
    </tr>
</thead>
<tbody>
<tr v-for="(payment, index) in payments">
    <td>{{ payment.price.title }}</td>
    <td>{{ new Date(payment.payment_date).getDate()+'.'+(new
Date(payment.payment_date).getMonth()+1)+'.'+new
Date(payment.payment_date).getFullYear()+'.' }}</td>
    <td>{{ new Date(payment.valid_thru).getDate()+'.'+(new
Date(payment.valid_thru).getMonth()+1)+'.'+new
Date(payment.valid_thru).getFullYear()+'.' }}</td>
    <td><a :href="'/energijapp/payments/'+payment.id+'/edit'"
class="btn btn-dark waves-effect btn-xs"><i class="material-
icons">edit</i></a></td>
    <td>
        <button class="btn dtp-btn-clear waves-effect btn-xs"
@click="deletePayment(payment.id, index)">
            <i class="material-icons">delete_forever</i>
        </button>
    </td>
</tr>
</tbody>
</table>
</div>
<div class="text-center">
    <button class="btn btn-dark"
@click="fetchPaginateUserPayments(pagination.prev_page_url)"
:disabled="!pagination.prev_page_url">
        <
    </button>

    <span>{{ pagination.current_page }} od {{ pagination.last_page
}}</span>

    <button class="btn btn-dark"
@click="fetchPaginateUserPayments(pagination.next_page_url)"
:disabled="!pagination.next_page_url">
        >
    </button>
</div>
<br/>
</div>
</template>

<script>
    export default {
        props: ['user_id'],
        data() {
            return {
                payments: [],
                payment: {
                    id: '',
                    payment_date: '',
                    valid_thru: '',
                    price_id: '',

```

```

        user_id: '',
        price: {
            title: ''
        }
    },
    userPaymentSum: 0,
    url: '/api/payments/user/'+this.user_id,
    pagination: []
},
created() {
    this.getUserPayments()
},
methods: {
    getUserPayments() {
        let $this = this;

        axios.get(this.url)
            .then(response => {
                this.payments = response.data[0].data;
                this.userPaymentSum = response.data[1];
                $this.pagination = response.data[0]
            })
            .catch(error => {
                console.log(error)
            })
    },

    deletePayment(id, index) {
        axios.delete('/api/payments/'+id).then(response => {
            this.payments.splice(index, 1);
        }).catch(error => {
            console.log(error)
        })
    },

    makePagination(data) {
        this.pagination = {
            current_page: data.current_page,
            last_page: data.last_page,
            next_page_url: data.next_page_url,
            prev_page_url: data.prev_page_url
        }
    },

    fetchPaginateUserPayments(url) {
        this.url = url;
        this.getUserPayments()
    }
}
}
</script>

```

#### 4.7.3.2.3. user

##### 4.7.3.2.3.1. reservations



#### 4.7.3.2.3.1.1. ReservationsForm.vue

```
<template>
  <div class="body">
    <div class="row clearfix">
      <form class="form-horizontal">
        <div class="form-group">
          <label for="training_id" class="col-sm-3 control-label">Trening:</label>
          <div class="col-sm-9" id="training_reservation">
            <select name="training_id" id="training_id" v-model="training_id" required>
              <option v-for="training in trainings" :value="training.id">{{ training.name }}</option>
            </select>
          </div>
        </div>
        <div class="form-group">
          <label for="date" class="col-sm-3 control-label">Datum:</label>
          <div class="col-sm-9">
            <div class="form-line" id="date-line">
              <input type="date" class="form-control" id="date" name="date" :min="current_date" :max="reservable_until" v-model="date" @change="getCount" required>
            </div>
          </div>
        </div>
        <div v-if="isVisible">
          <div class="form-group">
            <label class="col-sm-3 control-label">Broj mesta:</label>
            <div class="col-sm-9">
              <star-rating :rating="reservations" :max-rating="capacity" :star-size="20" inactive-color="#cdbbe9" active-color="#5b33a1" :show-rating="false" :read-only="true" :border-width="4" border-color="#d8d8d8" :rounded-corners="true" :star-points="[23,2, 14,17, 0,19, 10,34, 7,50, 23,43, 38,50, 36,34, 46,19, 31,17]"></star-rating>
            </div>
          </div>
          <div class="form-group">
            <label class="col-sm-3 control-label">Moje rezervacije:</label>
            <div class="col-sm-9">
              <h6>{{ my_reservations }}</h6>
            </div>
          </div>
          <div class="form-group">
            <div class="col-sm-offset-3 col-sm-9">
              <button v-if="isReservable" type="button" class="btn btn-dark" @click="storeReservation">REZERVIRAJ</button>
              <button v-if="isDeletable" type="button" class="btn btn-danger" @click="deleteUserReservations">OTKAŽI REZERVACIJE</button>
            </div>
          </div>
        </div>
      </form>
    </div>
  </div>
</template>
```

```

    </div>
  </div>
</template>

<script>
  import StarRating from 'vue-star-rating'

  export default {
    components: {
      StarRating
    },
    props: ['user_id'],
    data() {
      return {
        current_date: '',
        reservable_until: '',
        training_id: 4,
        date: '',
        trainings: [],
        training: {
          id: '',
          name: ''
        },
        capacity: 1,
        reservations: 0,
        my_reservations: 0,
        isVisible: false,
        isReservable: false,
        isDeletable: false
      }
    },
    mounted() {
      this.setDates();
      this.getReservableTrainings()
    },
    methods: {
      setDates() {
        let today = new Date();
        this.current_date = today.getFullYear() + '-' + ('0' +
(today.getMonth()+1)).slice(-2) + '-' + ('0' + today.getDate()).slice(-2);
        this.reservable_until = today.getFullYear() + '-' + ('0' +
(today.getMonth()+1)).slice(-2) + '-' + ('0' + (today.getDate()+2)).slice(-2)
      },

      getReservableTrainings() {
        axios.get('/api/trainings/reservable').then(response => {
          this.trainings = response.data
        }).catch(error => {
          console.log(error)
        })
      },

      getCount() {
        axios.get('/api/reservations/count', {
          params: {
            user_id: this.user_id,
            training_id: this.training_id,
            date: this.date
          }
        })
      }
    }
  }

```

```


        .then(response => {
            this.isVisible = true;
            this.capacity = response.data[0];
            this.reservations = response.data[1];
            this.my_reservations = response.data[2];
            this.isReservable = response.data[3];
            this.isDeletable = response.data[4];
        })
        .catch(error => {
            console.log(error)
        })
    },

    storeReservation() {
        axios.post('/api/reservations', {
            user_id: this.user_id,
            training_id: this.training_id,
            date: this.date
        }).then(response => {
            this.reservations = response.data[0];
            this.my_reservations = response.data[1];
            this.isReservable = response.data[2];
            this.isDeletable = true;
        }).catch(error => {
            console.log(error)
        })
    },

    deleteUserReservations() {
        axios.delete('/api/reservations/user/'+this.user_id, {
            params: {
                training_id: this.training_id,
                date: this.date
            }
        })
        .then(response => {
            this.reservations = response.data[0];
            this.my_reservations = response.data[1];
            this.isReservable = true;
            this.isDeletable = false;
        })
        .catch(error => {
            console.log(error)
        })
    }
}
</script>

```

## 5. Dizajn baze



Slika 5.1. – Struktura baze podataka

## 6. Zaključak

Uz ovaj projekat sam usavršio svoje znanje Laravel-a i naučio osnove svog prvog frontend framework-a, Vue-a, koji mi se jako svideo i koji će mi dosta koristiti u profesionalnoj karijeri.

Ostvario sam sve ključne zamišljene mogućnosti, tako da će ova aplikacija biti korišćena kao realni sajt za sportski centar sa planom usavršavanja, kako budem usavršavao svoje znanje.

## 7. Literatura

1. <https://laravel.com/docs/5.7/readme>
2. <https://vuejs.org/v2/guide/>
3. <https://laracasts.com/>
4. <https://www.udemy.com/vuejs-2-the-complete-guide/>
5. <https://stackoverflow.com/>