

DIGITAL FORENSICS LABORATORY

EXPERIMENT NO: 03

DATE: August 6, 2026

TITLE: Network Packet Sniffing and Credential Analysis Using Wireshark

1. AIM

To capture and analyze unencrypted network traffic using the Wireshark packet analyzer, isolate HTTP GET and POST request methods, and extract transmitted plain-text login credentials (username and password).

2. SOFTWARE / TOOLS REQUIRED

- **Operating System:** Windows 10/11 or Kali Linux
- **Packet Analyzer:** Wireshark v4.x (with Npcap driver installed)
- **Web Browser:** Google Chrome / Mozilla Firefox
- **Target Environment:** Acunetix Web Vulnerability Test Site (<http://testphp.vulnweb.com>)(<http://testphp.vulnweb.com>)

3. THEORY

Network packet sniffing is the process of monitoring and capturing data packets passing through a network interface card (NIC). Wireshark utilizes packet capture drivers (Npcap/libpcap) to set the system's NIC into **promiscuous mode**, allowing it to capture all frames traversing the local network segment.

When web applications transmit data using unencrypted protocols such as **HTTP (Hypertext Transfer Protocol)** over TCP port 80, the payload remains in ASCII plain text:

- **HTTP GET Method:** Appends parameters to the URL string. While used primarily for retrieving data, it leaves information visible in server logs and browser histories.
- **HTTP POST Method:** Embeds data within the body of the request header (Content-Type: application/x-www-form-urlencoded). Although hidden from the URL bar, the payload remains completely legible to network sniffers if not protected by TLS/SSL encryption (**HTTPS**).

4. PROCEDURE

Step 1: Interface Initialization

1. Launch Wireshark.
2. Select the active **Wi-Fi** network interface to begin live traffic capture.




Figure 1: Wireshark Interface Capture Selection

Step 2: Generating Network Traffic

1. Open the target web page in a browser.
2. Enter the credential details (Username: 9240040089, Password: Inba) into the form fields and submit.



Figure 2: Submitting Credentials on Test Web Page

Step 3: Filtering Protocol Traffic

Apply the http filter in the display filter bar to filter out ambient TCP, UDP, and DNS background traffic and isolate application-layer HTTP traffic.




Figure 3: Applying Display Filter for HTTP Protocol

Step 4: Inspecting HTTP GET Requests

Enter the following filter to inspect GET requests:

http.request.method == "GET"

Observation: GET packets retrieve page components (/login.aspx), but do not carry submitted form parameters in their payload.




Figure 4: Analysis of Captured HTTP GET Requests

Step 5: Extracting POST Payload and Credentials Apply the POST filter to locate form submission requests: `http.request.method == "POST"`

Select the packet containing `application/x-www-form-urlencoded`. In the **Packet Details** pane, expand the **HTML Form URL Encoded** tree to read the plain-text form variables.




Figure 5: Inspecting HTTP POST Packet Payload




Figure 6: Plain-text Credential Extraction from Form Fields

5. OBSERVATIONS & RESULTS

Extracted Form Parameters

Field Name	Captured Key	Extracted Value
Username	tbUsername	99240040059
Password	pass / tbPassword	Jovan

6. VERIFICATION OF SAVED LOGS & DIRECTORY STRUCTURE

The packet capture data (Captured_File.pcapng) and generated screen outputs have been archived in the repository.

7. PREVENTIVE COUNTERMEASURES

1. **Enforce HTTPS (TLS 1.3):** Encrypt all client-server communications so intercepted payloads appear as encrypted ciphertext.
2. **HTTP Strict Transport Security (HSTS):** Enforce browser-side HSTS policies to prevent downgrade attacks to plain HTTP.
3. **Network Isolation:** Implement VLANs and 802.1X port-based access controls to restrict unauthorized packet sniffing on local physical and wireless networks.

8. RESULT

The network traffic was successfully captured and analyzed using Wireshark. Plain-text credentials (**Username:** 99240040059, **Password:** Jovan) transmitted over HTTP were extracted from the POST request payload.