


Processor classes

- General purpose processors
- Special purpose processors
 - **DSPs**
 - Microcontrollers
 - GPUs...

Example of a typical code in DSP



```
float aryA[N];  
float aryB[N];  
float aryC[N];  
  
void conv() {  
    int i;  
    for (i = 0; i < N; ++i) {  
        aryC[i] = aryA[i] * aryB[i];  
    }  
}
```



Fixed point arithmetic


```
1.000  (-1)    int a = 0x8; //1000    _Fract a = -1.0r;  
0.011  (3/8)   int b = 0x3; //0011    _Fract b = 0.375r;
```

```
11.101000      int c = fp_mul(a, b); _Fract c = a * b;  
    << 1  
1.101000
```

```
_Fract  
long _Fract  
_Accum  
long _Accum
```

“Embedded C” - Extensions for the
programming language C to support
embedded processors

0.25r, 0.51r, 5.6k, 50.71k, 1.5r



Accumulators



$$0.5 + 0.75 - 0.3 - 0.8 - 0.6 - 0.4 - 0.25 + 0.5 = -0.6$$

$$0.5 + 0.75 = 1.25$$

$$0.5 + 0.75 - 0.3 = 0.95$$

$$0.5 + 0.75 - 0.3 - 0.8 = 0.15$$

$$0.5 + 0.75 - 0.3 - 0.8 - 0.6 = -0.45$$

$$0.5 + 0.75 - 0.3 - 0.8 - 0.6 - 0.4 = -0.85$$

$$0.5 + 0.75 - 0.3 - 0.8 - 0.6 - 0.4 - 0.25 = -1.1$$

$$0.5 + 0.75 - 0.3 - 0.8 - 0.6 - 0.4 - 0.25 + 0.5 = -0.6$$

Number of instructions 14 (11 in loop)




```
float aryA[N];  
float aryB[N];  
float aryC[N];
```

```
void conv() {  
    int i;  
    for (i = 0; i < N; ++i) {  
        aryC[i] = aryA[i] * aryB[i];  
    }  
}
```

```
_Fract aryA[N];  
_Fract aryB[N];  
_Fract aryC[N];
```

```
void conv() {  
    int i;  
    for (i = 0; i < N; ++i) {  
        aryC[i] = aryA[i] * aryB[i];  
    }  
}
```

```
_conv:  
    a1 = 0  
start:  
    a1 > 30  
    if (T) jmp end:  
        i0 = _aryA + a1  
        x0 = mem[i0]  
        i0 = _aryB + a1  
        y0 = mem[i0]  
        a0 = x0 * y0  
        i0 = _aryC + a1  
        mem[i0] = a0  
        a1 = a1 + 1  
        jmp start  
end:  
    i7 = mem[i6]  
    jmp i7
```



Address generators


```
...ary[0];  
...ary[2];  
...ary[1];  
...ary[2];  
...ary[3];  
  
p = ary;  
...*p; p+=2  
...*p--;  
...*p++;  
...*p++;  
...*p;
```

```
struct s  
{  
    int a;  
    int b;  
    int c;  
    int d;  
};
```

```
struct s* ps;  
...ps->d;  
...ps->a;  
...ps->c;  
...ps->b;
```

```
struct s  
{  
    int d;  
    int a;  
    int c;  
    int b;  
};
```

Number of instructions 14 (11 in loop)



```
_Fract aryA[N];
_Fract aryB[N];
_Fract aryC[N];

void conv() {
    int i;
    for (i = 0; i < N; ++i) {
        aryC[i] = aryA[i] * aryB[i];
    }
}
```

```
void conv() {
    int i;
    _Fract* pA = &aryA[0];
    _Fract* pB = &aryB[0];
    _Fract* pC = &aryC[0];
    for (i = 0; i < N; ++i) {
        *pC++ = *pA++ * *pB++;
    }
}
```

```
_conv:
    a1 = 0
start:
    a1 > 30
    if (T) jmp end:
        i0 = _aryA + a1
        x0 = mem[i0]
        i0 = _aryB + a1
        y0 = mem[i0]
        a0 = x0 * y0
        i0 = _aryC + a1
        mem[i0] = a0
        a1 = a1 + 1
        jmp start
end:
    i7 = mem[i6]
    jmp i7
```

```
_conv:
    a1 = 0
start:
    a1 > 30
    if (T) jmp end:
        x0 = mem[i0]
        i0 = i0 + 1
        y0 = mem[i4]
        i4 = i4 + 1
        a0 = x0 * y0
        mem[i1] = a0
        i1 = i1 + 1
        a1 = a1 + 1
        jmp start
end:
    i7 = mem[i6]
    jmp i7
```

Number of instructions

14 (11 in loop)

11 (8 in loop)



```
_Fract aryA[N];  
_Fract aryB[N];  
_Fract aryC[N];
```


```
void conv() {  
    int i;  
    for (i = 0; i < N; ++i) {  
        aryC[i] = aryA[i] * aryB[i];  
    }  
}
```


```
void conv() {  
    int i;  
    _Fract* pA = &aryA[0];  
    _Fract* pB = &aryB[0];  
    _Fract* pC = &aryC[0];  
    for (i = 0; i < N; ++i) {  
        *pC++ = *pA++ * *pB++;  
    }  
}
```

```
_conv:  
    a1 = 0  
start:  
    a1 > 30  
    if (T) jmp end:  
        x0 = mem[i0]  
        i0 = i0 + 1  
        y0 = mem[i4]  
        i4 = i4 + 1  
        a0 = x0 * y0  
        mem[i1] = a0  
        i1 = i1 + 1  
        a1 = a1 + 1  
        jmp start  
end:  
    i7 = mem[i6]  
    jmp i7
```


```
_conv:  
    a1 = 0  
start:  
    a1 > 30  
    if (T) jmp end:  
        x0 = mem[i0]; i0 += 1  
        y0 = mem[i4]; i4 += 1  
        a0 = x0 * y0  
        mem[i1] = a0; i1 += 1  
        a1 = a1 + 1  
        jmp start  
end:  
    i7 = mem[i6]  
    jmp i7
```


Harvard architecture






Harvard architecture






Harvard architecture




$c = a * b$


How many memory accesses?



Harvard architecture



```
__memA int ary1[100];  
__memB int ary2[100];
```



```
_Fract aryA[N];  
_Fract aryB[N];  
_Fract aryC[N];
```

```
void conv() {
```

```
    int i;
```

```
    _Fract* pA = &aryA[0];
```

```
    _Fract* pB = &aryB[0];
```

```
    _Fract* pC = &aryC[0];
```

```
    for (i = 0; i < N; ++i) {
```

```
        *pC++ = *pA++ * *pB++;
```

```
    }
```

```
}
```

```
    __memX __Fract aryA[N];
```

```
    __memY __Fract aryB[N]; }
```

```
    __memX __Fract aryC[N];
```

```
void conv() {
```

```
    int i;
```

```
    for (i = 0; i < N; ++i) {
```

```
        aryC[i] = aryA[i] * aryB[i];
```

```
    }
```

```
}
```

```
__memX __Fract aryA[N];
```

```
__memY __Fract aryB[N];
```

```
__memX __Fract aryC[N];
```

```
void conv() {
```

```
    int i;
```

```
    __memX __Fract* pA = &aryA[0];
```

```
    __memY __Fract* pB = &aryB[0];
```

```
    __memX __Fract* pC = &aryC[0];
```

```
    for (i = 0; i < N; ++i) {
```

```
        *pC++ = *pA++ * *pB++;
```


```
    }
```

Number of instructions

14 (11 in loop)

11 (8 in loop)

10 (7 in loop)




```
_conv:
    a1 = 0
start:
    a1 > 30
    if (T) jmp end:
        x0 = mem[i0]; i0 += 1
        y0 = mem[i4]; i4 += 1
        a0 = x0 * y0
        mem[i1] = a0; i1 += 1
        a1 = a1 + 1
        jmp start
end:
    i7 = mem[i6]
    jmp i7
```


```
_conv:
    a1 = 0
start:
    a1 > 30
    if (T) jmp end:
        x0 = xmem[i0]; i0 += 1; y0 = ymem[i4]; i4 += 1
        a0 = x0 * y0
        xmem[i1] = a0; i1 += 1
        a1 = a1 + 1
        jmp start
end:
    i7 = mem[i6]
    jmp i7
```



Hardware loops



- Loops for which the number of iteration is known in compile time
- Loops for which the number of iteration is known before the first iteration (but can vary between to encounters of the same loop)



Hardware loops

```
for (i = 0; i < NUMBER_OF_ITERATIONS; i++)
for (i = NUMBER_OF_ITERATIONS; i > 0; i--)
for (i = 0; i++ < NUMBER_OF_ITERATIONS; )
for (i = NUMBER_OF_ITERATIONS; i-- > 0; )
for (i = 0; i < NUMBER_OF_ITERATIONS; ++i)
for (i = NUMBER_OF_ITERATIONS; i>0; --i)
for (i = 0; ++i < NUMBER_OF_ITERATIONS + 1; )
for (i = NUMBER_OF_ITERATIONS + 1; --i > 0; )
```




```
__memX __Fract aryA[N];  
__memY __Fract aryB[N];  
__memX __Fract aryC[N];
```

```
void conv() {  
    int i;  
    for (i = 0; i < N; ++i) {  
        aryC[i] = aryA[i] * aryB[i];  
    }  
}
```

```
__memX __Fract aryA[N];  
__memY __Fract aryB[N];  
__memX __Fract aryC[N];
```

```
void conv() {  
    int i;  
    __memX __Fract* pA = &aryA[0];  
    __memY __Fract* pB = &aryB[0];  
    __memX __Fract* pC = &aryC[0];  
    for (i = 0; i < N; ++i) {  
        *pC++ = *pA++ * *pB++;  
    }  
}
```


Number of instructions

14 (11 in loop)

11 (8 in loop)

10 (7 in loop)

5 (3 in loop)



```
_conv:
```

```
    a1 = 0
```

```
start:
```

```
    a1 > 30
```

```
    if (T) jmp end:
```

```
        x0 = xmem[i0]; i0 += 1; y0 = ymem[i4]; i4 += 1
```

```
        a0 = x0 * y0
```

```
        xmem[i1] = a0; i1 += 1
```

```
        a1 = a1 + 1
```

```
        jmp start
```

```
end:
```

```
    i7 = mem[i6]
```

```
    jmp i7
```

```
_conv:
```

```
    hw_loop(31), end
```

```
        x0 = xmem[i0]; i0 += 1; y0 = ymem[i4]; i4 += 1
```

```
        a0 = x0 * y0
```

```
        xmem[i1] = a0; i1 += 1
```

```
end:
```

```
    i7 = mem[i6]
```

```
    jmp i7
```

Hardware supported function call stack



```
push pc  
jmp addr
```

```
call addr
```

```
pop reg  
jmp reg
```

```
ret
```

Number of instructions

14 (11 in loop)

11 (8 in loop)

10 (7 in loop)

5 (3 in loop)


4 (3 in loop)


```
_conv:
    hw_loop(31), end
        x0 = xmem[i0]; i0 += 1; y0 = ymem[i4]; i4 += 1
        a0 = x0 * y0
        xmem[i1] = a0; i1 += 1
end:
    i7 = mem[i6]
    jmp i7

_conv:
    hw_loop(31), end
        x0 = xmem[i0]; i0 += 1; y0 = ymem[i4]; i4 += 1
        a0 = x0 * y0
        xmem[i1] = a0; i1 += 1
end:
    ret

i6 += 1
xmem[i6] = pc
jmp conv
i6 -= 1
```

call conv






```
_conv:
    hw_loop(31), end
    x0 = xmem[i0]; i0 += 1; y0 = ymem[i4]; i4 += 1
    a0 = x0 * y0
    xmem[i1] = a0; i1 += 1
end:
    ret
```

Number of instructions
14 (11 in loop)

...
4 (3 in loop)
4 (2 in loop)

```
_conv:
    x0 = xmem[i0]; i0 += 1; y0 = ymem[i4]; i4 += 1
    hw_loop(31), end
    x0 = xmem[i0]; i0 += 1; y0 = ymem[i4]; i4 += 1; a0 = x0 * y0
    xmem[i1] = a0; i1 += 1
end:
    ret
```


Hardware supported circular buffer



```
__attribute__((align(128)))
```

```
p = ary;  
for (...)   
{  
    ...*p...  
    p = CIRC_INC(p, MOD128, 1);  
}
```

Vector operations GCC




```
int8_t A[200];
int8_t B[200];
int8_t C[200];
for (i = 0; i < 200; ++i)
{
    C[i] = A[i] * B[i];
}
```

```
int8_t __attribute__((vector_size(8))) A[25];
int8_t __attribute__((vector_size(8))) B[25];
int8_t __attribute__((vector_size(8))) C[25];
for (i = 0; i < 25; ++i)
{
    C[i] = A[i] * B[i];
}
```

```
int8_t __attribute__((vector_size(8))) x = {1, 2, 3, 4, 5, 6, 7, 8};
```

Vector operations GCC – ARM NEON



```
int8_t A[200];
int8_t B[200];
int8_t C[200];
for (i = 0; i < 200; ++i)
{
    C[i] = A[i] + B[i];
}
```

```
int8_t A[200];
int8_t B[200];
int8_t C[200];
for (i = 0; i < 25; i += 8)
{
    _Int8x8 a = vld1_s8(&A[i]); // int8x8_t, through typedef in header
    _Int8x8 b = vld1_s8(&B[i]);
    vst1_s8(&C[i], vadd_s8(a, b)); // although a + b is also OK here
}
```