



Laser-Induced Damage Threshold Test (LIDT) Report

According to ISO 21254
No. LIDT-2026-008

HiLASE

Prepared by: Ing. Martin Mydlář (martin.mydlar@hilase.cz)
Arindom Phukan, Ph.D. (arindom.phukan@hilase.cz)
Jovana Babic (jovana.babic@hilase.cz)
Approved by: Mihai-George Mureşan, Ph.D. (mihai@hilase.cz)
Institute: HiLASE Centre, Institute of Physics ASCR
Address: Za Radnici 828, 252 41 Dolni Brezany, Czech Republic

Customer

Name:
Sample ID:
Address:
Contact:

1. Report Identification

Report Number: LIDT-2026-008
Issue Date: 26 June 2026

2. Sample Information

Sample ID:
Description:
Date Received: 26 June 2026
Preparation:

3. Laser and Environmental Conditions

Laser Type:
Wavelength (nm):
Repetition Frequency:
Output Energy/Power:
Pulse Duration (1/e²):
Effective Pulse Duration:
Polarization:
Beam Diameter (1/e²):
Beam Profile (Near Field):
Beam Delivery:

4. Test Identification

Procedure:
Objective:
Sites / Pulses per Site:
Damage Detection:

5. Test and Procedure Specification

Environment: Standard laboratory, 22.0 °C, 40%
Vacuum: No
Focusing System: Spherical lens, f = 500 mm
Beam Energy Management: Attenuator (polarization-based, motorized)
Sample Position: In focus
Spatial Beam Shape: , ellipticity = N/A%
Measured Beam Surface: N/A
Gaussian Fit Beam Diameter: N/A

6. Error Budget

Pulse-to-pulse energy stability: $\pm 5\%$

Pulse-to-pulse spatial profile stability: $\pm 12\%$

Pulse-to-pulse temporal stability: $< 1\%$

Energy monitor calibration: $\pm N/A\%$

Energy monitor accuracy: N/A μJ

Beam profiler accuracy: N/A μm

Beam profiler calibration: $\pm N/A\%$