Telling Your Secrets Without Page Faults:

Stealthy Page Table-Based Attacks on Enclaved Execution

Jo Van Bulck¹ Nico Weichbrodt² Rüdiger Kapitza² Frank Piessens¹ Raoul Strackx¹

¹imec-DistriNet, KU Leuven ²IBR DS, TU Braunschweig

September 28, 2017

Road Map

- Introduction
- 2 Controlled-Channel Attacks and Defenses
- 3 Stealthy Page Table-Based Attacks
- 4 Precise Enclave Execution Control
- Conclusions



thehackernews.com/2015/10/windows-patch-update.html



thehackernews.com/2016/10/linux-kernel-exploit.html




thehackernews.com/2017/06/cia-linux-hacking-tool-malware.html




thehackernews.com/2015/04/rootpipe-mac-os-x-vulnerability.html

Motivation: Application Attack Surface




Layered architecture → large **trusted computing base**

Motivation: Application Attack Surface



Intel SGX promise: hardware-level isolation and attestation


Motivation: Application Attack Surface



Untrusted OS \rightarrow new class of powerful side-channels


Road Map

- 1 Introduction
- Controlled-Channel Attacks and Defenses
- 3 Stealthy Page Table-Based Attacks
- Precise Enclave Execution Contro
- Conclusions




Costan et al. "Intel SGX explained", IACR 2016 [CD16]


Note: Untrusted OS controls virtual-to-physical mapping




Costan et al. "Intel SGX explained", IACR 2016 [CD16]



Note: Additional checks *after* address translation



Page Faults as a Side-Channel



Xu et al.: "Controlled-channel attacks: Deterministic side channels for untrusted operating systems", Oakland 2015 [XCP15]

⇒ Page fault traces leak private control flow/data accesses

Page Faults as a Side-Channel










Original






Recovered






Xu et al.: "Controlled-channel attacks: Deterministic side channels for untrusted operating systems", Oakland 2015 [XCP15]


⇒ Low-noise, single-run exploitation of legacy applications




Shih et al. "T-SGX: Eradicating controlled-channel attacks against enclave programs", NDSS 2017 [SLKP17] Shinde et al. "Preventing page faults from telling your secrets", AsiaCCS 2016 [SCNS16]



Shih et al. "T-SGX: Eradicating controlled-channel attacks against enclave programs", NDSS 2017 [SLKP17] Shinde et al. "Preventing page faults from telling your secrets", AsiaCCS 2016 [SCNS16]



Defenses do not hold when attacker learns page accesses without triggering faults!



Defenses do not hold when attacker learns page accesses without triggering faults!

Road Map

- Introduction
- 2 Controlled-Channel Attacks and Defenses
- Stealthy Page Table-Based Attacks
- Precise Enclave Execution Control
- Conclusions

- 4 Attack vector: PTE status flags:
 - A(ccessed) bit
 - D(irty) bit

```
void inc_secret( void )
{
    if (secret)
        *a += 1;
    else
        *b += 1;
}
```

PTE a
PTE b

- Attack vector: PTE status flags:
 - A(ccessed) bit
 - D(irty) bit
 - → Also updated in enclave mode!

```
void inc_secret( void )
{
    if (secret)
        *a += 1;
    else
        *b += 1;
}
```


PTE a
PTE b

- Attack vector: PTE status flags:
 - A(ccessed) bit
 - D(irty) bit
 - Also updated in enclave mode!


```
void inc secret( void )
    if (secret)
       *a += 1:
    else
       *b += 1;
Table
     PTE a
      PTE b
```




- Attack vector: PTE status flags:
 - A(ccessed) bit
 - D(irty) bit
 - → Also updated in enclave mode!



- Attack vector: PTE status flags:
 - A(ccessed) bit
 - D(irty) bit
 - → Also updated in enclave mode!



- Attack vector: PTE status flags:
 - A(ccessed) bit
 - D(irty) bit
 - → Also updated in enclave mode!




- Attack vector: PTE status flags:
 - A(ccessed) bit
 - D(irty) bit
 - → Also updated in enclave mode!
- Attack vector: Unprotected page table memory:
 - Cached as regular data
 - Accessed during address translation

```
void inc_secret( void )
{
    if (secret)
        *a += 1;
    else
        *b += 1;
}
```


```
Page PTE a
```


- Attack vector: PTE status flags:
 - A(ccessed) bit
 - D(irty) bit
 - → Also updated in enclave mode!
- Attack vector: Unprotected page table memory:
 - Cached as regular data
 - Accessed during address translation
 - → Flush+Reload cache timing attack!

```
void inc_secret( void )
{
   if (secret)
      *a += 1;
   else
      *b += 1;
}
```




- Attack vector: PTE status flags:
 - A(ccessed) bit
 - D(irty) bit
 - → Also updated in enclave mode!
- Attack vector: Unprotected page table memory:
 - Cached as regular data
 - Accessed during address translation
 - → Flush+Reload cache timing attack!






- Attack vector: PTE status flags:
 - A(ccessed) bit
 - D(irty) bit
 - → Also updated in enclave mode!
- Attack vector: Unprotected page table memory:
 - Cached as regular data
 - Accessed during address translation
 - → Flush+Reload cache timing attack!




- Attack vector: PTE status flags:
 - A(ccessed) bit
 - D(irty) bit
 - → Also updated in enclave mode!
- Attack vector: Unprotected page table memory:
 - Cached as regular data
 - Accessed during address translation
 - → Flush+Reload cache timing attack!

```
void inc_secret( void )
{
    if (secret)
        *a += 1;
    else
        *b += 1;
}
```




Challenge: No #PF on memory access




SECRET = 01010


- Challenge: No #PF on memory access
 - → Monitor PTEs from concurrent spy thread




- Challenge: No #PF on memory access
 → Monitor PTEs from concurrent spy thread
- Challenge: Translation Lookaside Buffer (TLB)




- Challenge: No #PF on memory access
 - → Monitor PTEs from concurrent spy thread
- Challenge: Translation Lookaside Buffer (TLB)
 - → Directed Inter-Processor Interrupt



- Challenge: No #PF on memory access
 - → Monitor PTEs from concurrent spy thread
- Challenge: Translation Lookaside Buffer (TLB)
 - → Directed Inter-Processor Interrupt
- Challenge: Temporal resolution (IPI latency)



- Challenge: No #PF on memory access
 - → Monitor PTEs from concurrent spy thread
- Challenge: Translation Lookaside Buffer (TLB)
 - → Directed Inter-Processor Interrupt
- Challenge: Temporal resolution (IPI latency)
 - → Precise Flush+Flush technique



PTE Flush+Flush: A High-Resolution, Low-Latency Channel

Resolution Challenge

 \exists access **detection latency** \leftrightarrow #PF-attacks

Resolution Challenge

 \exists access **detection latency** \leftrightarrow #PF-attacks

Interrupt granularity:

 \odot A/D monitoring: \sim 430 nop / \sim 175 add


Resolution Challenge

 \exists access **detection latency** \leftrightarrow #PF-attacks

Interrupt granularity:

- \odot A/D monitoring: \sim 430 nop / \sim 175 add
- © Flush+Reload: might miss victim access (TLB!)

- (a) Victim PTE access
- (b) FLUSH+RELOAD hit
- (c) FLUSH+RELOAD miss




time

Resolution Challenge

 \exists access **detection latency** \leftrightarrow #PF-attacks

Interrupt granularity:

- \odot A/D monitoring: \sim 430 nop / \sim 175 add
- © Flush+Reload: might miss victim access (TLB!)
- © Flush+Flush: clflush completes earlier for uncached data




Gruss et al. "Flush+Flush: a fast and stealthy cache attack", DIMVA 2016 [GMWM16]

Resolution Challenge

 \exists access **detection latency** \leftrightarrow #PF-attacks

Interrupt granularity:

- A/D monitoring: \sim 430 nop / \sim 175 add
- Flush+Reload: might miss victim access (TLB!)
- Flush+Flush: interrupt within trigger instruction (> 99.8%)
 - (a) Victim PTE access
 - (b) FLUSH+RELOAD hit
 - (c) Flush+Reload miss
 - (d) FLUSH+FLUSH hit



```
if (mpi_is_secure (scalar)) {
        /* If SCALAR is in secure memory we assume that it is the
           secret key we use constant time operation. */
        point_init (&tmppnt);
        for (j=nbits-1; j >= 0; j--) {
             _gcry_mpi_ec_dup_point (result, result, ctx);
            _gcry_mpi_ec_add_points (&tmppnt, result, point, ctx);
            point_swap_cond (result, &tmppnt, mpi_test_bit (scalar, j), ctx);
        point_free (&tmppnt);
     else {
        for (i=nbits-1: i >= 0: i--) {
             _gcry_mpi_ec_dup_point (result, result, ctx);
14
            if (mpi_test_bit (scalar, j))
                 _gcry_mpi_ec_add_points (result, result, point, ctx);
18
```

```
if (mpi_is_secure (scalar)) {
        /* If SCALAR is in secure memory we assume that it is the
            secret key we use constant time operation. */
        point_init (&tmppnt);
        for (j=nbits-1; j >= 0; j--) {
             _gcry_mpi_ec_dup_point (result, result, ctx);
             _gcry_mpi_ec_add_points (&tmppnt, result, point, ctx);
             point_swap_cond (result, &tmppnt, mpi_test_bit (scalar, j), ctx);
        point_free (&tmppnt);
      else {
        for (i=nbits-1: i >= 0: i--) {
             _gcry_mpi_ec_dup_point (result, result, ctx);
14
            if (mpi_test_bit (scalar, j))
                 _gcry_mpi_ec_add_points (result, result, point, ctx);
17
18
```

```
if (mpi_is_secure (scalar)) {
        point_init (&tmppnt);
        for (i=nbits-1; i >= 0; i--) {
                                                                                   EdDSA secret scalar not
            _gcry_mpi_ec_dup_point (result, result, ctx);
                                                                                   stored in "secure memory"!
            _gcry_mpi_ec_add_points (&tmppnt, result, point, ctx);
            point_swap_cond (result, &tmppnt, mpi_test_bit (scalar, i), ctx);
        point_free (&tmppnt);
        for (i=nbits-1: i >= 0: i--) {
            _gcry_mpi_ec_dup_point (result, result, ctx);
14
            if (mpi_test_bit (scalar, j))
                _gcry_mpi_ec_add_points (result, result, point, ctx);
17
18
```

```
if (mpi_is_secure (scalar)) {
       point_init (&tmppnt);
       for (i=nbits-1; i >= 0; i--) {
            _gcry_mpi_ec_dup_point (result, result, ctx);
            _gcry_mpi_ec_add_points (&tmppnt, result, point, ctx);
            point_swap_cond (result, &tmppnt, mpi_test_bit (scalar, i), ctx);
       point_free (&tmppnt);
       for (i=nbits-1: i >= 0: i--) {
            _gcry_mpi_ec_dup_point (result, result, ctx);
                                                                              Secret-dependent control flow
14
           _gcry_mpi_ec_add_points (result, result, point, ctx);
17
18
```

```
if (mpi_is_secure (scalar)) {
                                                                                                    Memory layout
                                                                                                            ...
        point_init (&tmppnt);
                                                                                                                       0x0F000
                                                                                                        gcry free
        for (i=nbits-1; i >= 0; i--) {
                                                                                                            ...
             _gcry_mpi_ec_dup_point (result, result, ctx);
             _gcry_mpi_ec_add_points (&tmppnt, result, point, ctx);
                                                                                                                      0xC0000
                                                                                                        mpi add
             point_swap_cond (result, &tmppnt, mpi_test_bit (scalar, i), ctx);
                                                                                                                       0xC1000
                                                                                                      mpi test bit
        point_free (&tmppnt);
                                                                                                            ...
        for (i=nbits-1: i >= 0: i--) {
                                                                            22 Code pages
                                                                                                                       0xC9000
             _gcry_mpi_ec_dup_point (result, result, ctx);
                                                                                                     mpi ec add p
14
                                                                             per iteration
            if (mpi_test_bit (scalar, j))
                                                                                                                       0xCA000
                                                                                                     mpi ec mul p
                 _gcry_mpi_ec_add_points (result, result, point, ctx);
17
                                                                                                            •••
18
```

```
if (mpi_is_secure (scalar)) {
                                                                                                   Memory layout
                                                                              Monitor
                                                                                                           ...
        point_init (&tmppnt);
                                                                                                                      0x0F000
                                                                            triager page
                                                                                                       gcry free
        for (i=nbits-1; i >= 0; i--) {
                                                                                                           ...
             _gcry_mpi_ec_dup_point (result, result, ctx);
             _gcry_mpi_ec_add_points (&tmppnt, result, point, ctx);
                                                                                                                      0xC0000
                                                                                                        mpi add
             point_swap_cond (result, &tmppnt, mpi_test_bit (scalar, i), ctx);
                                                                                                                      0xC1000
                                                                                                      mpi test bit
        point_free (&tmppnt);
                                                                                                           ...
                                                                                   ACCESSED?
        for (i=nbits-1: i >= 0: i--) {
                                                                                                                      0xC9000
             _gcry_mpi_ec_dup_point (result, result, ctx);
                                                                                                     mpi ec add p
14
            if (mpi_test_bit (scalar, j))
                                                                                                                      0xCA000
                                                                                                     mpi ec mul p
                 _gcry_mpi_ec_add_points (result, result, point, ctx);
17
                                                                                                           ...
18
```

```
if (mpi_is_secure (scalar)) {
                                                                                                    Memory layout
                                                                                                            ...
        point_init (&tmppnt);
                                                                                                                       0x0F000
                                                                                                        gcry free
        for (i=nbits-1; i >= 0; i--) {
                                                                                                            ...
             _gcry_mpi_ec_dup_point (result, result, ctx);
             _gcry_mpi_ec_add_points (&tmppnt, result, point, ctx);
                                                                                                                      0xC0000
                                                                                                        mpi add
             point_swap_cond (result, &tmppnt, mpi_test_bit (scalar, i), ctx);
                                                                                                                       0xC1000
                                                                                                      mpi test bit
        point_free (&tmppnt);
                                                               INTERRUPT
                                                                                                            ...
        for (i=nbits-1: i >= 0: i--) {
                                                                                                                      0xC9000
             _gcry_mpi_ec_dup_point (result, result, ctx);
                                                                                                      mpi ec add p
14
            if (mpi_test_bit (scalar, j))
                                                                                                                       0xCA000
                                                                                                     mpi ec mul p
                 _gcry_mpi_ec_add_points (result, result, point, ctx);
17
                                                                                                            ...
18
```

```
if (mpi_is_secure (scalar)) {
                                                                                                  Memory layout
                                                                                                          ...
        point_init (&tmppnt);
                                                                                                                    0x0F000
                                                                                                      gcry free
                                                                               ACCESSED?
        for (i=nbits-1; i >= 0; i--) {
                                                                                                          ...
            _gcry_mpi_ec_dup_point (result, result, ctx);
            _gcry_mpi_ec_add_points (&tmppnt, result, point, ctx);
                                                                                                                    0xC0000
                                                                                                      mpi add
            point_swap_cond (result, &tmppnt, mpi_test_bit (scalar, i), ctx);
                                                                                                                    0xC1000
                                                                                                     mpi test bit
                                                                  Record page set
        point_free (&tmppnt);
                                                                         0011
                                                                                                          ...
        for (i=nbits-1: i >= 0: i--) {
                                                                                                                     0xC9000
            _gcry_mpi_ec_dup_point (result, result, ctx);
                                                                                                   mpi ec add p
14
                                                                        ACCESSED 7
            if (mpi_test_bit (scalar, j))
                                                                                                                    0xCA000
                                                                                                   mpi ec mul p
                 _gcry_mpi_ec_add_points (result, result, point, ctx);
                                                                                                          ...
18
```

```
if (mpi_is_secure (scalar)) {
                                                                                                   Memory layout
                                                                                                           ...
        point_init (&tmppnt);
                                                                                                                      0x0F000
                                                                                                       gcry free
        for (i=nbits-1; i >= 0; i--) {
                                                                                                           ...
            _gcry_mpi_ec_dup_point (result, result, ctx);
            _gcry_mpi_ec_add_points (&tmppnt, result, point, ctx);
                                                                                                                     0xC0000
                                                                                                       mpi add
            point_swap_cond (result, &tmppnt, mpi_test_bit (scalar, i), ctx);
                                                                                                                      0xC1000
                                                                                                     mpi test bit
        point_free (&tmppnt);
                                                                                                           ...
                                                                          RESUME
        for (i=nbits-1: i >= 0: i--) {
                                                                                                                     0xC9000
            _gcry_mpi_ec_dup_point (result, result, ctx);
                                                                                                     mpi ec add p
14
            if (mpi_test_bit (scalar, j))
                                                                                                                      0xCA000
                                                                                                    mpi ec mul p
                 _gcry_mpi_ec_add_points (result, result, point, ctx);
                                                                                                           •••
                                                     Full 512-bit key recovery, single run
18
```

```
if (mpi_is_secure (scalar)) {
                                                                                                    Memory layout
                                                                                                           ...
        point_init (&tmppnt);
                                                                                                                      0x0F000
                                                                                                       gcry free
        for (i=nbits-1; i >= 0; i--) {
                                                                                                           ...
             _gcry_mpi_ec_dup_point (result, result, ctx);
            _gcry_mpi_ec_add_points (&tmppnt, result, point, ctx);
                                                                                                                      0xC0000
                                                                                                        mpi add
            point_swap_cond (result, &tmppnt, mpi_test_bit (scalar, i), ctx);
                                                                                                                      0xC1000
                                                                                                      mpi test bit
        point_free (&tmppnt);
                                                                                                           ...
        for (i=nbits-1: i >= 0: i--) {
                                                                            22 Code pages
                                                                                                                      0xC9000
            _gcry_mpi_ec_dup_point (result, result, ctx);
                                                                                                     mpi ec add p
14
                                                                             per iteration
            if (mpi_test_bit (scalar, j))
                                                                                                                      0xCA000
                                                                                                     mpi ec mul p
                 _gcry_mpi_ec_add_points (result, result, point, ctx);
                                                                                                           •••
18
```

```
if (mpi_is_secure (scalar)) {
                                                                                                   Memory layout
                                                                                                           ...
        point_init (&tmppnt);
                                                                                                                      0x0F000
                                                                                                       gcry free
        for (i=nbits-1; i >= 0; i--) {
                                                                                                           ...
             _gcry_mpi_ec_dup_point (result, result, ctx);
            _gcry_mpi_ec_add_points (&tmppnt, result, point, ctx);
                                                                                                                      0xC0000
                                                                                                        mpi add
            point_swap_cond (result, &tmppnt, mpi_test_bit (scalar, i), ctx);
                                                                                                                      0xC1000
                                                                                                      mpi test bit
        point_free (&tmppnt);
                                                                                                           ...
        for (i=nbits-1: i >= 0: i--) {
                                                                           Only 11 distinct
                                                                                                                      0xC9000
            _gcry_mpi_ec_dup_point (result, result, ctx);
                                                                                                     mpi ec add p
14
                                                                           PTE cache lines
            if (mpi_test_bit (scalar, j))
                                                                                                                      0xCA000
                                                                                                     mpi ec mul p
                 _gcry_mpi_ec_add_points (result, result, point, ctx);
                                                                                                           •••
18
```

```
if (mpi_is_secure (scalar)) {
                                                                                                  Memory layout
                                                                                                     gpgrt lock
                                                                         Monitor isolated
        point_init (&tmppnt);
                                                                           trigger page
                                                                                                      errno plt
        for (i=nbits-1; i >= 0; i--) {
             _gcry_mpi_ec_dup_point (result, result, ctx);
                                                                                                      apart lock
            _gcry_mpi_ec_add_points (&tmppnt, result, point, ctx);
                                                                                                          ...
            point_swap_cond (result, &tmppnt, mpi_test_bit (scalar, i), ctx);
                                                                                                      do malloc
                                                                                  FLUSH
        point_free (&tmppnt);
                                                                                                      errno loc
        for (i=nbits-1: i >= 0: i--) {
                                                                                                       int free
            _gcry_mpi_ec_dup_point (result, result, ctx);
14
            if (mpi_test_bit (scalar, j))
                                                                                                     mpi_test_bit
                 _gcry_mpi_ec_add_points (result, result, point, ctx);
17
                                                                                                    mpi ec mul p
18
```

```
if (mpi_is_secure (scalar)) {
                                                                                                  Memory layout
                                                                                                     gpgrt lock
        point_init (&tmppnt);
                                                                                                      errno plt
        for (i=nbits-1; i >= 0; i--) {
             _gcry_mpi_ec_dup_point (result, result, ctx);
                                                                                                      apart lock
             _gcry_mpi_ec_add_points (&tmppnt, result, point, ctx);
                                                                                                          ...
            point_swap_cond (result, &tmppnt, mpi_test_bit (scalar, i), ctx);
                                                                                                      do malloc
        point_free (&tmppnt);
                                                                                                      errno loc
                                                       INTERRUPT
        for (i=nbits-1: i >= 0: i--)
                                                                                                       int free
            _gcry_mpi_ec_dup_point (result, result, ctx):
14
            if (mpi_test_bit (scalar, j))
                                                                                                    mpi_test_bit
                 _gcry_mpi_ec_add_points (result, result, point, ctx);
17
                                                                                                    mpi ec mul p
18
```

```
if (mpi_is_secure (scalar)) {
                                                                                                 Memory layout
                                                                                                     apart lock
                                                                          Record bigger
        point_init (&tmppnt);
                                                                             page set
                                                                                                      errno plt
        for (i=nbits-1; i >= 0; i--) {
                                                                                                         ...
             _gcry_mpi_ec_dup_point (result, result, ctx);
                                                                                                     gpgrt lock
            _gcry_mpi_ec_add_points (&tmppnt, result, point, ctx);
                                                                                                         ...
            point_swap_cond (result, &tmppnt, mpi_test_bit (scalar, i), ctx);
                                                                                                     do malloc
        point_free (&tmppnt);
                                                                                                      errno loc
                                                                                       RELOAD
        for (i=nbits-1: i >= 0: i--) {
                                                                                                       int free
            _gcry_mpi_ec_dup_point (result, result, ctx);
14
            if (mpi_test_bit (scalar, j))
                                                                                                    mpi test bit
                 _gcry_mpi_ec_add_points (result, result, point, ctx);
                                                                                                         ...
17
                                                                                                   mpi ec mul p
18
```


```
if (mpi_is_secure (scalar)) {
                                                                                               Memory layout
                                                                                                   apart lock
                                                                         Record bigger
        point_init (&tmppnt);
                                                                            page set
                                                                                                    errno plt
        for (i=nbits-1; i >= 0; i--) {
                                                                                                        ...
            _gcry_mpi_ec_dup_point (result, result, ctx);
                                                                                                    gpgrt lock
            _gcry_mpi_ec_add_points (&tmppnt, result, point, ctx);
                                                                                                        ...
            point_swap_cond (result, &tmppnt, mpi_test_bit (scalar, i), ctx);
                                                                                                    do malloc
        point_free (&tmppnt);
                                                                                                    errno loc
                                                                                     RELOAD
        for (i=nbits-1: i >= 0: i--) {
                                                                                                     int free
            _gcry_mpi_ec_dup_point (result, result, ctx);
14
            if (mpi_test_bit (scalar, j))
                                                                                                   mpi test bit
                _gcry_mpi_ec_add_points (result, result, point, ctx);
                                                                                                        ...
                                                                                                  mpi ec mul p
           Regex pattern match -> 485/512-bit recovery, single-run
18
```

Road Map

- Introduction
- 2 Controlled-Channel Attacks and Defenses
- 3 Stealthy Page Table-Based Attacks
- Precise Enclave Execution Control
- Conclusions

SGX-Step: Executing Enclaves One Instruction at a Time

User space APIC timer configuration and page table tracking:




strlen loop

Note: page fault-driven attacks cannot make progress

```
1  size_t strlen (char *str)
2  {
3    char *s;
4    for (s = str; *s; ++s);
6    return (s - str);
7  }
```


strlen loop

Note: page fault-driven attacks cannot make progress




strlen loop

Note: page fault-driven attacks cannot make progress




strlen loop

Note: page fault-driven attacks cannot make progress



Intel SGX Developer Guide [Int17]

"aligning specific code and data blocks to exist entirely within a single page"



Road Map

- Introduction
- 2 Controlled-Channel Attacks and Defenses
- 3 Stealthy Page Table-Based Attacks
- 4 Precise Enclave Execution Control
- Conclusions

Conclusion

Take-Away Message

Enclave memory accesses can be learned without triggering page faults.

Conclusion

Take-Away Message

Enclave memory accesses can be learned without triggering page faults.

⇒ Do not focus on attack **side-effects** (faults, frequent enclave preemptions)

Conclusion

Take-Away Message

Enclave memory accesses can be learned without triggering page faults.

- ⇒ Do not focus on attack **side-effects** (faults, frequent enclave preemptions)
- ⇒ Address root causes of information leakage:
 - Unprotected page table memory (Sanctum [CLD16])
 - Secret-dependent control flow/data access (Libgcrypt patch)

Thank you! Questions?

https://github.com/jovanbulck/sgx-pte

References I



V. Costan and S. Devadas.

Intel SGX explained.

Technical report, Computer Science and Artificial Intelligence Laboratory MIT, 2016. https://eprint.iacr.org/2016/086.pdf.



V. Costan, I. Lebedev, and S. Devadas.

Sanctum: Minimal hardware extensions for strong software isolation.

In 25th USENIX Security Symposium, pp. 857–874. USENIX Association, 2016.



D. Gruss, C. Maurice, K. Wagner, and S. Mangard.

Flush+flush: A fast and stealthy cache attack.

In Detection of Intrusions and Malware, and Vulnerability Assessment (DIMVA), 2016.



Intel Corporation.

Intel software guard extensions developer guide: protection from side-channel attacks, June 2017.

https://software.intel.com/en-us/node/703016.



S. Shinde, Z. L. Chua, V. Narayanan, and P. Saxena.

Preventing page faults from telling your secrets.

In Proceedings of the 11th ACM on Asia Conference on Computer and Communications Security (ASIA CCS), pp. 317–328, ACM, 2016



M.-W. Shih, S. Lee, T. Kim, and M. Peinado.

T-SGX: Eradicating Controlled-Channel Attacks Against Enclave Programs.

In 24th Annual Network and Distributed System Security Symposium (NDSS), 2017.

References II



C.-C. Tsai, D. E. Porter, and M. Vij.

Graphene-SGX: A practical library OS for unmodified applications on SGX.





J. Van Bulck, F. Piessens, and R. Strackx.

SGX-Step: A practical attack framework for precise enclave execution control.

In Proceedings of the 2nd Workshop on System Software for Trusted Execution (SysTEX '17). ACM, October 2017. (to appear).



J. Van Bulck, N. Weichbrodt, R. Kapitza, F. Piessens, and R. Strackx.

Telling your secrets without page faults: Stealthy page table-based attacks on enclaved execution.

In Proceedings of the 26th USENIX Security Symposium. USENIX Association, August 2017.



Y. Xu. W. Cui, and M. Peinado.

Controlled-channel attacks: Deterministic side channels for untrusted operating systems.

In 2015 IEEE Symposium on Security and Privacy, pp. 640-656, IEEE, 2015.

IPI Latency Microbenchmarks


Table: IPI latency in terms of the number of instructions executed by the victim after accessing the trigger page.

	Accessed		Fı	FLUSH+FLUSH		
Experiment	Mean	σ	Mean	σ	Zero %	
nop	431.70	34.11	0.65	17.65	99.84	
add register	176.30	14.60	0.15	6.18	99.94	
add memory	32.45	2.79	0.06	1.92	99.88	
nop nocache	0.02	0.39	_	_	_	

Putting it All Together: Inferring Page Access Patterns

Re-usable attack framework: Graphene-SGX [TPV17]


- Explicitly monitor trigger page(s)
- Capture max info in page sets ↔ #PF-sequences
- Offline analysis: extract access patterns
- ⇒ overcome measurement *noise/ latency/ granularity*



Proposed Solutions: Hiding Enclave Page Faults

Contractual execution (prototype hardware): [SCNS16]

- Inform memory requirements
- Page fault = contract violation
- 3 CPU delivers fault directly to enclave




Shinde et al. "Preventing page faults from telling your secrets", AsiaCCS 2016. [SCNS16]

Proposed Solutions: Hiding Enclave Page Faults

T-SGX (Intel x86 compatible): [SLKP17]

- Wrap enclave code in TSX transactions
- In-enclave transaction abort handler for page faults



Shih et al. "T-SGX: Eradicating controlled-channel attacks against enclave programs", NDSS 2017. [SLKP17]