#### **Telling Your Secrets Without Page Faults:**

Stealthy Page Table-Based Attacks on Enclaved Execution

Jo Van Bulck<sup>1</sup> Nico Weichbrodt<sup>2</sup> Rüdiger Kapitza<sup>2</sup> Frank Piessens<sup>1</sup> Raoul Strackx<sup>1</sup>

<sup>1</sup>imec-DistriNet, KU Leuven <sup>2</sup>IBR DS, TU Braunschweig

August 18, 2017

# Road Map

- Introduction
- 2 Controlled-Channel Attacks and Defenses
- 3 Stealthy Page Table-Based Attacks
- 4 Conclusions



thehackernews.com/2015/10/windows-patch-update.html




thehackernews.com/2016/10/linux-kernel-exploit.html




thehackernews.com/2017/06/cia-linux-hacking-tool-malware.html




thehackernews.com/2015/04/rootpipe-mac-os-x-vulnerability.html




 $\mbox{Layered architecture} \rightarrow \mbox{large } \mbox{trusted computing base}$ 



Layered architecture → large **trusted computing base** 



Intel SGX promise: hardware-level isolation and attestation




Untrusted OS  $\rightarrow$  new class of powerful **side-channels** 


#### Road Map

- Introduction
- Controlled-Channel Attacks and Defenses
- Stealthy Page Table-Based Attacks
- 4 Conclusions

## The Virtual Memory Abstraction




Costan et al. "Intel SGX explained", IACR 2016 [CD16]




Costan et al. "Intel SGX explained", IACR 2016 [CD16]


Note: Untrusted OS controls virtual-to-physical mapping




Costan et al. "Intel SGX explained", IACR 2016 [CD16]



#### **Note:** Additional checks *after* address translation



## Page Faults as a Side-Channel



Xu et al.: "Controlled-channel attacks: Deterministic side channels for untrusted operating systems", Oakland 2015 [XCP15]

⇒ Page fault traces leak private control flow/data accesses

#### Page Faults as a Side-Channel










Original






Recovered






Xu et al.: "Controlled-channel attacks: Deterministic side channels for untrusted operating systems", Oakland 2015 [XCP15]

⇒ Low-noise, single-run exploitation of legacy applications




Shih et al. "T-SGX: Eradicating controlled-channel attacks against enclave programs", NDSS 2017 [SLKP17]

Shinde et al. "Preventing page faults from telling your secrets", AsiaCCS 2016 [SCNS16]




Shih et al. "T-SGX: Eradicating controlled-channel attacks against enclave programs", NDSS 2017 [SLKP17]

Shinde et al. "Preventing page faults from telling your secrets", AsiaCCS 2016 [SCNS16]



Defenses do not hold when attacker learns page accesses without triggering faults!



Defenses do not hold when attacker learns page accesses without triggering faults!

## Road Map

- Introduction
- Controlled-Channel Attacks and Defenses
- 3 Stealthy Page Table-Based Attacks
- 4 Conclusions

- Attack vector: PTE status flags:
  - A(ccessed) bit
  - D(irty) bit

```
void inc_secret( void )
{
    if (secret)
        *a += 1;
    else
        *b += 1;
}
```

PTE a

PTE b

- Attack vector: PTE status flags:
  - A(ccessed) bit
  - D(irty) bit
  - → Also updated in enclave mode!

```
void inc_secret( void )
{
    if (secret)
        *a += 1;
    else
        *b += 1;
}
```


PTE a
PTE a
PTE b

- Attack vector: PTE status flags:
  - A(ccessed) bit
  - D(irty) bit
  - Also updated in enclave mode!


```
void inc secret( void )
    if (secret)
       *a += 1:
    else
       *b += 1;
Table
     PTE a
      PTE b
```




- Attack vector: PTE status flags:
  - A(ccessed) bit
  - D(irty) bit
  - → Also updated in enclave mode!



- Attack vector: PTE status flags:
  - A(ccessed) bit
  - D(irty) bit
  - → Also updated in enclave mode!



- Attack vector: PTE status flags:
  - A(ccessed) bit
  - D(irty) bit
  - → Also updated in enclave mode!




- Attack vector: PTE status flags:
  - A(ccessed) bit
  - D(irty) bit
  - → Also updated in enclave mode!
- Attack vector: Unprotected page table memory:
  - Cached as regular data
  - Accessed during address translation

```
void inc_secret( void )
{
    if (secret)
        *a += 1;
    else
        *b += 1;
}
```


```
Page PTE a
```


- Attack vector: PTE status flags:
  - A(ccessed) bit
  - D(irty) bit
  - → Also updated in enclave mode!
- Attack vector: Unprotected page table memory:
  - Cached as regular data
  - Accessed during address translation
  - → Flush+Reload cache timing attack!

```
void inc_secret( void )
{
    if (secret)
        *a += 1;
    else
        *b += 1;
}
```



- Attack vector: PTE status flags:
  - A(ccessed) bit
  - D(irty) bit
  - → Also updated in enclave mode!
- Attack vector: Unprotected page table memory:
  - Cached as regular data
  - Accessed during address translation
  - → Flush+Reload cache timing attack!






- Attack vector: PTE status flags:
  - A(ccessed) bit
  - D(irty) bit
  - → Also updated in enclave mode!
- Attack vector: Unprotected page table memory:
  - Cached as regular data
  - Accessed during address translation
  - → Flush+Reload cache timing attack!


```
void inc secret( void )
    if (secret)
                 Page Table
    else
       *b += 1:
          PTE a
Cache
          PTE b
```

- Attack vector: PTE status flags:
  - A(ccessed) bit
  - D(irty) bit
  - → Also updated in enclave mode!
- Attack vector: Unprotected page table memory:
  - Cached as regular data
  - Accessed during address translation
  - → Flush+Reload cache timing attack!

```
void inc_secret( void )
{
    if (secret)
        *a += 1;
    else
        *b += 1;
}
```




Challenge: No #PF on memory access




SECRET = 01010


- Challenge: No #PF on memory access
  - → Monitor PTEs from concurrent spy thread




- Challenge: No #PF on memory access
   → Monitor PTEs from concurrent spy thread
- Challenge: Translation Lookaside Buffer (TLB)



- Challenge: No #PF on memory access
  - → Monitor PTEs from concurrent spy thread
- Challenge: Translation Lookaside Buffer (TLB)
  - → Directed Inter-Processor Interrupt




- Challenge: No #PF on memory access
  - → Monitor PTEs from concurrent spy thread
- Challenge: Translation Lookaside Buffer (TLB)
  - → Directed Inter-Processor Interrupt
- Schallenge: Temporal resolution (IPI latency)



### **#PF-Less Challenges: Monitoring Repeated Accesses**

- Challenge: No #PF on memory access
  - → Monitor PTEs from concurrent spy thread
- Challenge: Translation Lookaside Buffer (TLB)
  - → Directed Inter-Processor Interrupt
- Challenge: Temporal resolution (IPI latency)
  - → Precise Flush+Flush technique



Resolution Challenge

 $\exists$  access **detection latency**  $\leftrightarrow$  #PF-attacks

Resolution Challenge

 $\exists$  access **detection latency**  $\leftrightarrow$  #PF-attacks

### Interrupt granularity:

 $\odot$  A/D monitoring:  $\sim$  430 nop /  $\sim$  175 add


#### Resolution Challenge

∃ access **detection latency** ↔ #PF-attacks

### Interrupt granularity:

- $\odot$  A/D monitoring:  $\sim$  430 nop /  $\sim$  175 add
- © Flush+Reload: might miss victim access (TLB!)

- (a) Victim PTE access
- (b) FLUSH+RELOAD hit
- (c) FLUSH+RELOAD miss




time

#### Resolution Challenge

 $\exists$  access **detection latency**  $\leftrightarrow$  #PF-attacks

#### Interrupt granularity:

- $\odot$  A/D monitoring:  $\sim$  430 nop /  $\sim$  175 add
- © Flush+Reload: might miss victim access (TLB!)
- Flush+Flush: clflush completes earlier for uncached data




Gruss et al. "Flush+Flush: a fast and stealthy cache attack", DIMVA 2016 [GMWM16]

#### Resolution Challenge

 $\exists$  access **detection latency**  $\leftrightarrow$  #PF-attacks

#### Interrupt granularity:

- A/D monitoring:  $\sim$  430 nop /  $\sim$  175 add
- Flush+Reload: might miss victim access (TLB!)
- Flush+Flush: interrupt within trigger instruction (> 99.8%)
  - (a) Victim PTE access
  - (b) FLUSH+RELOAD hit
  - (c) Flush+Reload miss
  - (d) FLUSH+FLUSH hit



```
if (mpi_is_secure (scalar)) {
        /* If SCALAR is in secure memory we assume that it is the
           secret key we use constant time operation. */
        point_init (&tmppnt);
        for (j=nbits-1; j>=0; j--) {
             _gcry_mpi_ec_dup_point (result, result, ctx);
            _gcry_mpi_ec_add_points (&tmppnt, result, point, ctx);
            point_swap_cond (result, &tmppnt, mpi_test_bit (scalar, j), ctx);
        point_free (&tmppnt);
     else {
        for (i=nbits-1: i >= 0: i--) {
             _gcry_mpi_ec_dup_point (result, result, ctx);
14
            if (mpi_test_bit (scalar, j))
                 _gcry_mpi_ec_add_points (result, result, point, ctx);
18
```

```
if (mpi_is_secure (scalar)) {
        /* If SCALAR is in secure memory we assume that it is the
           secret key we use constant time operation. */
        point_init (&tmppnt);
        for (j=nbits-1; j>=0; j--) {
             _gcry_mpi_ec_dup_point (result, result, ctx);
             _gcry_mpi_ec_add_points (&tmppnt, result, point, ctx);
             point_swap_cond (result, &tmppnt, mpi_test_bit (scalar, j), ctx);
        point_free (&tmppnt);
      else {
        for (i=nbits-1: i >= 0: i--) {
             _gcry_mpi_ec_dup_point (result, result, ctx);
14
            if (mpi_test_bit (scalar, j))
                 _gcry_mpi_ec_add_points (result, result, point, ctx);
17
18
```

```
if (mpi_is_secure (scalar)) {
        point_init (&tmppnt);
        for (i=nbits-1; i >= 0; i--) {
                                                                                   EdDSA secret scalar not
            _gcry_mpi_ec_dup_point (result, result, ctx);
                                                                                   stored in "secure memory"!
            _gcry_mpi_ec_add_points (&tmppnt, result, point, ctx);
            point_swap_cond (result, &tmppnt, mpi_test_bit (scalar, i), ctx);
        point_free (&tmppnt);
        for (i=nbits-1: i >= 0: i--) {
            _gcry_mpi_ec_dup_point (result, result, ctx);
14
            if (mpi_test_bit (scalar, j))
                _gcry_mpi_ec_add_points (result, result, point, ctx);
17
18
```

```
if (mpi_is_secure (scalar)) {
       point_init (&tmppnt);
       for (i=nbits-1; i >= 0; i--) {
            _gcry_mpi_ec_dup_point (result, result, ctx);
            _gcry_mpi_ec_add_points (&tmppnt, result, point, ctx);
            point_swap_cond (result, &tmppnt, mpi_test_bit (scalar, i), ctx);
       point_free (&tmppnt);
       for (i=nbits-1: i >= 0: i--) {
            _gcry_mpi_ec_dup_point (result, result, ctx);
                                                                              Secret-dependent control flow
14
           _gcry_mpi_ec_add_points (result, result, point, ctx);
17
18
```

```
if (mpi_is_secure (scalar)) {
                                                                                                   Memory layout
                                                                                                          ...
        point_init (&tmppnt);
                                                                                                                     0x0F000
                                                                                                       gcry free
        for (i=nbits-1; i >= 0; i--) {
                                                                                                          ...
             _gcry_mpi_ec_dup_point (result, result, ctx);
             _gcry_mpi_ec_add_points (&tmppnt, result, point, ctx);
                                                                                                                     0xC0000
                                                                                                       mpi add
             point_swap_cond (result, &tmppnt, mpi_test_bit (scalar, i), ctx);
                                                                                                                     0xC1000
                                                                                                     mpi test bit
        point_free (&tmppnt);
                                                                                                           ...
        for (i=nbits-1: i >= 0: i--) {
                                                                           22 Code pages
                                                                                                                     0xC9000
             _gcry_mpi_ec_dup_point (result, result, ctx);
                                                                                                    mpi ec add p
14
                                                                            per iteration
            if (mpi_test_bit (scalar, j))
                                                                                                                     0xCA000
                                                                                                    mpi ec mul p
                 _gcry_mpi_ec_add_points (result, result, point, ctx);
17
                                                                                                           •••
18
```

```
if (mpi_is_secure (scalar)) {
                                                                                                  Memory layout
                                                                              Monitor
                                                                                                          ...
        point_init (&tmppnt);
                                                                                                                     0x0F000
                                                                           triager page
                                                                                                      gcry free
        for (i=nbits-1; i >= 0; i--) {
                                                                                                          ...
            _gcry_mpi_ec_dup_point (result, result, ctx);
            _gcry_mpi_ec_add_points (&tmppnt, result, point, ctx);
                                                                                                                     0xC0000
                                                                                                       mpi add
            point_swap_cond (result, &tmppnt, mpi_test_bit (scalar, j), ctx);
                                                                                                                     0xC1000
                                                                                                     mpi test bit
        point_free (&tmppnt);
                                                                                                          ...
                                                                                   ACCESSED ?
        for (i=nbits-1: i >= 0: i--) {
                                                                                                                     0xC9000
            _gcry_mpi_ec_dup_point (result, result, ctx);
                                                                                                    mpi ec add p
14
            if (mpi_test_bit (scalar, j))
                                                                                                                     0xCA000
                                                                                                    mpi ec mul p
                 _gcry_mpi_ec_add_points (result, result, point, ctx);
17
                                                                                                          ...
18
```

```
if (mpi_is_secure (scalar)) {
                                                                                                   Memory layout
                                                                                                           ...
        point_init (&tmppnt);
                                                                                                                     0x0F000
                                                                                                       gcry free
        for (i=nbits-1; i >= 0; i--) {
                                                                                                           ...
             _gcry_mpi_ec_dup_point (result, result, ctx);
             _gcry_mpi_ec_add_points (&tmppnt, result, point, ctx);
                                                                                                                     0xC0000
                                                                                                       mpi add
             point_swap_cond (result, &tmppnt, mpi_test_bit (scalar, i), ctx);
                                                                                                                     0xC1000
                                                                                                     mpi test bit
        point_free (&tmppnt);
                                                               INTERRUPT
                                                                                                           ...
        for (i=nbits-1: i >= 0: i--) {
                                                                                                                     0xC9000
             _gcry_mpi_ec_dup_point (result, result, ctx);
                                                                                                    mpi ec add p
14
            if (mpi_test_bit (scalar, j))
                                                                                                                     0xCA000
                                                                                                    mpi ec mul p
                 _gcry_mpi_ec_add_points (result, result, point, ctx);
17
                                                                                                           ...
18
```

```
if (mpi_is_secure (scalar)) {
                                                                                                 Memory layout
                                                                                                         ...
        point_init (&tmppnt);
                                                                                                                   0x0F000
                                                                                                     gcry free
                                                                               ACCESSED?
        for (i=nbits-1; i >= 0; i--) {
                                                                                                         ...
            _gcry_mpi_ec_dup_point (result, result, ctx);
            _gcry_mpi_ec_add_points (&tmppnt, result, point, ctx);
                                                                                                                   0xC0000
                                                                                                      mpi add
            point_swap_cond (result, &tmppnt, mpi_test_bit (scalar, i), ctx);
                                                                                                                   0xC1000
                                                                                                    mpi test bit
                                                                  Record page set
        point_free (&tmppnt);
                                                                        0011
                                                                                                         ...
        for (i=nbits-1: i >= 0: i--) {
                                                                                                                   0xC9000
            _gcry_mpi_ec_dup_point (result, result, ctx);
                                                                                                   mpi ec add p
14
                                                                       ACCESSED 7
            if (mpi_test_bit (scalar, j))
                                                                                                                   0xCA000
                                                                                                   mpi ec mul p
                _gcry_mpi_ec_add_points (result, result, point, ctx);
                                                                                                         ...
18
```

```
if (mpi_is_secure (scalar)) {
                                                                                                  Memory layout
                                                                                                          ...
        point_init (&tmppnt);
                                                                                                                     0x0F000
                                                                                                      gcry free
        for (i=nbits-1; i >= 0; i--) {
                                                                                                          ...
            _gcry_mpi_ec_dup_point (result, result, ctx);
            _gcry_mpi_ec_add_points (&tmppnt, result, point, ctx);
                                                                                                                     0xC0000
                                                                                                       mpi add
            point_swap_cond (result, &tmppnt, mpi_test_bit (scalar, i), ctx);
                                                                                                                     0xC1000
                                                                                                     mpi test bit
        point_free (&tmppnt);
                                                                                                          ...
                                                                          RESUME
        for (i=nbits-1: i >= 0: i--) {
                                                                                                                     0xC9000
            _gcry_mpi_ec_dup_point (result, result, ctx);
                                                                                                    mpi ec add p
14
            if (mpi_test_bit (scalar, j))
                                                                                                                     0xCA000
                                                                                                    mpi ec mul p
                 _gcry_mpi_ec_add_points (result, result, point, ctx);
17
                                                                                                          •••
                                                     Full 512-bit key recovery, single run
18
```

```
if (mpi_is_secure (scalar)) {
                                                                                                   Memory layout
                                                                                                          ...
        point_init (&tmppnt);
                                                                                                                     0x0F000
                                                                                                       gcry free
        for (i=nbits-1; i >= 0; i--) {
                                                                                                          ...
             _gcry_mpi_ec_dup_point (result, result, ctx);
             _gcry_mpi_ec_add_points (&tmppnt, result, point, ctx);
                                                                                                                     0xC0000
                                                                                                       mpi add
             point_swap_cond (result, &tmppnt, mpi_test_bit (scalar, i), ctx);
                                                                                                                     0xC1000
                                                                                                     mpi test bit
        point_free (&tmppnt);
                                                                                                           •••
        for (i=nbits-1: i >= 0: i--) {
                                                                           22 Code pages
                                                                                                                     0xC9000
             _gcry_mpi_ec_dup_point (result, result, ctx);
                                                                                                    mpi ec add p
14
                                                                            per iteration
            if (mpi_test_bit (scalar, j))
                                                                                                                     0xCA000
                                                                                                    mpi ec mul p
                 _gcry_mpi_ec_add_points (result, result, point, ctx);
17
                                                                                                           •••
18
```

```
if (mpi_is_secure (scalar)) {
                                                                                                   Memory layout
                                                                                                          ...
        point_init (&tmppnt);
                                                                                                                     0x0F000
                                                                                                       gcry free
        for (i=nbits-1; i >= 0; i--) {
                                                                                                          ...
             _gcry_mpi_ec_dup_point (result, result, ctx);
             _gcry_mpi_ec_add_points (&tmppnt, result, point, ctx);
                                                                                                                     0xC0000
                                                                                                       mpi add
             point_swap_cond (result, &tmppnt, mpi_test_bit (scalar, i), ctx);
                                                                                                                     0xC1000
                                                                                                     mpi test bit
        point_free (&tmppnt);
                                                                                                           •••
        for (i=nbits-1: i >= 0: i--) {
                                                                           Only 11 distinct
                                                                                                                     0xC9000
             _gcry_mpi_ec_dup_point (result, result, ctx);
                                                                                                    mpi ec add p
14
                                                                           PTE cache lines
            if (mpi_test_bit (scalar, j))
                                                                                                                     0xCA000
                                                                                                    mpi ec mul p
                 _gcry_mpi_ec_add_points (result, result, point, ctx);
17
                                                                                                           •••
18
```

```
if (mpi_is_secure (scalar)) {
                                                                                                  Memory layout
                                                                                                     gpgrt lock
                                                                         Monitor isolated
        point_init (&tmppnt);
                                                                           trigger page
                                                                                                      errno plt
        for (i=nbits-1; i >= 0; i--) {
             _gcry_mpi_ec_dup_point (result, result, ctx);
                                                                                                      apart lock
            _gcry_mpi_ec_add_points (&tmppnt, result, point, ctx);
                                                                                                          ...
            point_swap_cond (result, &tmppnt, mpi_test_bit (scalar, i), ctx);
                                                                                                      do malloc
                                                                                  FLUSH
        point_free (&tmppnt);
                                                                                                      errno loc
        for (i=nbits-1: i >= 0: i--) {
                                                                                                       int free
            _gcry_mpi_ec_dup_point (result, result, ctx);
14
            if (mpi_test_bit (scalar, j))
                                                                                                     mpi_test_bit
                 _gcry_mpi_ec_add_points (result, result, point, ctx);
17
                                                                                                    mpi ec mul p
18
```

```
if (mpi_is_secure (scalar)) {
                                                                                                  Memory layout
                                                                                                     gpgrt lock
        point_init (&tmppnt);
                                                                                                      errno plt
        for (i=nbits-1; i >= 0; i--) {
             _gcry_mpi_ec_dup_point (result, result, ctx);
                                                                                                     apart lock
             _gcry_mpi_ec_add_points (&tmppnt, result, point, ctx);
                                                                                                          ...
            point_swap_cond (result, &tmppnt, mpi_test_bit (scalar, i), ctx);
                                                                                                     do malloc
        point_free (&tmppnt);
                                                                                                      errno loc
                                                       INTERRUPT
        for (i=nbits-1: i >= 0: i--)
                                                                                                       int free
            _gcry_mpi_ec_dup_point (result, result, ctx):
14
            if (mpi_test_bit (scalar, j))
                                                                                                    mpi_test bit
                 _gcry_mpi_ec_add_points (result, result, point, ctx);
17
                                                                                                    mpi ec mul p
18
```

```
if (mpi_is_secure (scalar)) {
                                                                                                 Memory layout
                                                                                                     apart lock
                                                                          Record bigger
        point_init (&tmppnt);
                                                                             page set
                                                                                                      errno plt
        for (i=nbits-1; i >= 0; i--) {
                                                                                                         ...
             _gcry_mpi_ec_dup_point (result, result, ctx);
                                                                                                     gpgrt lock
            _gcry_mpi_ec_add_points (&tmppnt, result, point, ctx);
                                                                                                         ...
            point_swap_cond (result, &tmppnt, mpi_test_bit (scalar, i), ctx);
                                                                                                     do malloc
        point_free (&tmppnt);
                                                                                                      errno loc
                                                                                       RELOAD
        for (i=nbits-1: i >= 0: i--) {
                                                                                                       int free
            _gcry_mpi_ec_dup_point (result, result, ctx);
14
            if (mpi_test_bit (scalar, j))
                                                                                                    mpi test bit
                 _gcry_mpi_ec_add_points (result, result, point, ctx);
                                                                                                         ...
17
                                                                                                   mpi ec mul p
18
```

```
if (mpi_is_secure (scalar)) {
                                                                                                Memory layout
                                                                                                    apart lock
                                                                         Record bigger
        point_init (&tmppnt);
                                                                            page set
                                                                                                     errno plt
        for (i=nbits-1; i >= 0; i--) {
                                                                                                        ...
            _gcry_mpi_ec_dup_point (result, result, ctx);
                                                                                                    gpgrt lock
            _gcry_mpi_ec_add_points (&tmppnt, result, point, ctx);
                                                                                                        ...
            point_swap_cond (result, &tmppnt, mpi_test_bit (scalar, i), ctx);
                                                                                                    do malloc
        point_free (&tmppnt);
                                                                                                     errno loc
                                                                                     RELOAD
        for (i=nbits-1: i >= 0: i--) {
                                                                                                     int free
            _gcry_mpi_ec_dup_point (result, result, ctx);
14
            if (mpi_test_bit (scalar, j))
                                                                                                   mpi test bit
                 _gcry_mpi_ec_add_points (result, result, point, ctx);
                                                                                                        ...
17
                                                                                                  mpi ec mul p
           Regex pattern match -> 485/512-bit recovery, single-run
18
```

### Road Map

- Introduction
- 2 Controlled-Channel Attacks and Defenses
- 3 Stealthy Page Table-Based Attacks
- Conclusions

### Conclusion

### Take-Away Message

Enclave memory accesses can be learned without triggering page faults.

#### Conclusion

### Take-Away Message

Enclave memory accesses can be learned without triggering page faults.

⇒ Do not focus on attack **side-effects** (faults, frequent enclave preemptions)

### Conclusion

#### Take-Away Message

Enclave memory accesses can be learned without triggering page faults.

- ⇒ Do not focus on attack **side-effects** (faults, frequent enclave preemptions)
- ⇒ Address root causes of information leakage:
  - Unprotected page table memory (Sanctum [CLD16])
  - Secret-dependent control flow/data access (Libgcrypt patch)

# Thank you! Questions?

https://github.com/jovanbulck/sgx-pte

#### References I



V. Costan and S. Devadas.

Intel SGX explained.

Technical report, Computer Science and Artificial Intelligence Laboratory MIT, 2016. https://eprint.iacr.org/2016/086.pdf.



V. Costan, I. Lebedev, and S. Devadas.

Sanctum: Minimal hardware extensions for strong software isolation.

In 25th USENIX Security Symposium, pp. 857–874. USENIX Association, 2016.



D. Gruss, C. Maurice, K. Wagner, and S. Mangard.

Flush+flush: A fast and stealthy cache attack.

In Detection of Intrusions and Malware, and Vulnerability Assessment (DIMVA), 2016.



S. Shinde, Z. L. Chua, V. Narayanan, and P. Saxena.

Preventing page faults from telling your secrets.

In Proceedings of the 11th ACM on Asia Conference on Computer and Communications Security (ASIA CCS), pp. 317–328, ACM, 2016.



M.-W. Shih, S. Lee, T. Kim, and M. Peinado.

T-SGX: Eradicating Controlled-Channel Attacks Against Enclave Programs.

In 24th Annual Network and Distributed System Security Symposium (NDSS), 2017.



C.-C. Tsai, D. E. Porter, and M. Vii.

Graphene-SGX: A practical library OS for unmodified applications on SGX.

In 2017 USENIX Annual Technical Conference (USENIX ATC), USENIX Association, 2017.

### References II



Y. Xu, W. Cui, and M. Peinado.

Controlled-channel attacks: Deterministic side channels for untrusted operating systems.

In 2015 IEEE Symposium on Security and Privacy, pp. 640-656. IEEE, 2015.

### **IPI Latency Microbenchmarks**

Table: IPI latency in terms of the number of instructions executed by the victim after accessing the trigger page.

	Accessed		Fı	FLUSH+FLUSH		
Experiment	Mean	$\sigma$	Mean	$\sigma$	Zero %	
nop	431.70	34.11	0.65	17.65	99.84	
add register	176.30	14.60	0.15	6.18	99.94	
add memory	32.45	2.79	0.06	1.92	99.88	
nop nocache	0.02	0.39	_	_	_	

### Putting it All Together: Inferring Page Access Patterns

### Re-usable attack framework: Graphene-SGX [TPV17]

- Explicitly monitor trigger page(s)
- Capture max info in **page sets** ↔ #PF-sequences
- Offline analysis: extract access patterns
- ⇒ overcome measurement *noise/ latency/ granularity*

