VISOKA ŠKOLA STRUKOVNIH STUDIJA ZA INFORMACIONE I KOMUNIKACIONE TEHNOLOGIJE INTERNET TEHNOLOGIJE

DOKUMENTACIJA

pozoriste

Predmet: Web programiranje PHP1 Student: Darija Šošdean 18/16

Beograd, jun 2022

Sadržaj

Uvod	5
Korišćeni programski jezici i tehnologije:	5
Opis funkcionalnosti	5
Template	6
Organizacija	6
Organizaciona šema	6
Šema baze	6
Stranice	7
Home	7
Performances	8
Performance	8
Repertoire	9
Kupovina	10
Tickets	11
Kontakt	11
Registracija I logovanje	12
Ativacija	12
Admin Performances	13
Admin New Performance	14
Admin Edit Performance	14
Admin Repertoire	15
Admin Add Repertoire	15
Korisnici	16
Messages	16
Anketa	17
Autor	17
Kodovi	18
Root	18
Index.php	18
Activation	18
Performance.php	19

Performances.php	19
Repertoire.php	19
Tickets.php	20
Seats.php	20
Contact.php	21
Author.php	21
Login.php	21
Activation.php	22
View/fixed	23
Footer.php	23
Head.php	24
Header.php	24
View/pages	25
Index.php	25
Performance.php	27
Performances.php	28
Repertoire.php	28
Tickets.php	29
Seats.php	30
Contact.php	34
Author.php	37
Activation.php	39
Models	40
Activation.php	40
addPerformance.php	41
addReprtoire.php	43
allPerformances.php	45
buyTickets.php	45
cancelTickets.php	47
connection.php	47
deleteMessage.php	48
deletePerformance.php	49

	deleteRepertoire.php	49
	disablePoll.php	50
	editPerfromance.php	51
	enablePoll.php	54
	getEditPerformance.php	54
	get Messages Admin. php	55
	getNav.php	56
	getTickets.php	56
	getUsersAdmin.php	57
	login.php	58
	message.php	60
	next.php	61
	parameters.php	62
	performance.php	62
	performances.php	63
	poll.php	64
	pollRez.php	65
	register.php	66
	repertoire.php	68
	repertoireAdmin.php	69
	seats.php	70
	vote.php	71
N	lain.js	72
ςı	ayla ccc	98

Uvod

Korišćeni programski jezici i tehnologije:

HTML, CSS, JavaScript, Jquery, PHP, Bootstrap

Opis funkcionalnosti

- 1. Dinamičko ispisivanje menija iz baze na svim stranama.
- 2. Dinamičko ispisivanje footer-a na svim stranama.
- 3. Ispisivanje sledeće predstave na repertoaru.
- 4. Pretraga i straničenje svih predstava.
- 5. Prikaz pojedinačne predstave
- 6. Prikaz repertoara za tekući mesec.
- 7. Mogućnost kupovine (otkazivanja) karata za ulogovane korisnike.
- 8. Prikaz ankete na kontakt strani. Samo ulogovani korisnici mogu glasati (samo jednom). Ukoliko je korisnik već glasao, dugme za glasanje je disable-ovano.
- 9. Kontakt strana za slanje poruke administratoru. Vrši se klijentska i serverska validacija podataka(ispisivanje poruke o greškama).
- 10. Logovanje i registracija korisnika(ispisivanje poruke o greškama). Slanje mejla za aktivaciju naloga(ne radi na web000).
- 11. Admin panel-prikaz svih predstava sa linkovima za brisanje i ažuriranje. Klikom na link za ažuriranje prikazuje se forma sa popunjenim podacima za odabranu predstavu. Mogućnost dodavanja predstave.
- 12. Admin panel-prikaz repertoara sa linkom za brisanje. Klikom na link za ažuriranje prikazuje se forma sa popunjenim podacima. Mogućnost dodavanja predstave na repertoar.
- 13. Admin panel-prikaz rezulata ankete (mogućnost disable-ovanja)
- 14. Admin panel-prikaz svih korisnika.
- 15. Admin panel-prikaz svih poruka (mogućnost brisanja).

Template


Template je koriscen za admin panel.

Organizacija

Organizaciona šema

Svakoj stranici može se pristupiti sa svake stranice, pojedinačnoj predstavi je moguće pristupiti sa stranice sa svim predstavama. Pristup stranicama zavisi od uloge korisnika.

Šema baze



Stranice

Home





Next in the repertoire

I GO ON THE WAY AND HUG THE TREE

Wednesday 29.06.

BUY TICKET

About



'Theater' is the youngest theater in Serbia, with its headquarters in Belgrade, Banovo Brdo. It is located between the wooded Kosutnjak and Ada Ciganlija, two favorite resorts of Belgraders.

'Theater' was a dream, realized with the help of people who had a vision and enthusiasm, and most of all love for the theater, culture and the community in which they live.

Today, we are one of the most visited stages in Belgrade, and our performances are at the top of viewership and popularity in the entire region.

Tens of thousands of people follow our guest appearances and look forward to our performances.

Contact E-mail: theatre@gmail.com

Phone: 011/123-123

Cash desk opening hours

Monday - Friday: 10h - 20h


Saturday - Sunday: 16h - 20h

Author Documentation

Admin panel


Pocetna strana sa prikazom naredne predstave na repertoaru, dinamički ispis hedera(sa navigacijom) i futera (na svim stranama)

Performances




Prikaz svih predstava uz mogućnost straničenja I pretrage

Performance




Prikaz jedne predstave sa njenim detaljima (naziv, slika, opis, trajanje I datum premijere)

Repertoire




Prikaz repertoara za tekući mesec sa linkom za kupovinu karte

Kupovina




Prikaz 'forme' za kupovinu karata. Prikazana su sedista u pozoristu. Prelaskom misa preko sedista, prikazuju se njegovi detalji (red, pozicija I broj sedista). Klikom na dugme 'Buy' prikazuje se pop up sa podacima o izabranim mestim I klikom na dugme 'buy' kupuju se karte.




Prikaz pop up-a za kupovinu. Ukoliko korisnik nije izabrao sedista ili nije ulogovan ispisuje se odgovarajuca poruka. Nakon kupovine, ta sedista vise nije moguce kupiti.

Tickets




Prikaz kupljenih karata, moguce je otkazivanje kupovine.

Kontakt




Prikaz kontakt forme za slanje poruke adminu . Popunjavanjem forme ispisuje se odgovarajuća poruka. Vrši se klijentska I serverska validacija podataka. Prikaz ankete. Mogu glasati samo ulogovani korisnici, kada korisnik glasa, ispise mu se poruka I on ne moze ponovo da glasa.

Registracija I logovanje




Prikaz formi za logovanje I registraciju. Vrsi se klijenska I serverska validacija I ispisuju odgovarajuce poruka. Slanje mejla ne radi na web000 pa je nalog odmah aktivan.






Admin Performances




Prikaz svih predstava. Predstava se moze azurirati (klikom na link za azuriranje ispisuje se forma za odabranu predstavu) i obrisati.

Admin New Performance




Prikaz forme za dodavanje predstave. Sva polja su obavezna

Admin Edit Performance




Prikaz forme za editovanje predstave. Sva polja su obavezna osim slike

Admin Repertoire




Prikaz repertoara za predstave koje sledece. Moguce je skloniti predstavu sa repertoara

Admin Add Repertoire




Forma za dodavanje predstave na repertoar. Vrsi se provera da li se tog dana vec ne igra neka predstava

Korisnici




Prikaz svih korisnika

Messages



Prikaz poruka poslatih adminu preko kontakt forme sa linkom za brisanje

Anketa



Prikaz rezultata ankete. Moze se disejblovati i enejblovati

Autor





Darija Šošdean 18/16 Internet technologies

Contact
E-mail: theatre@gmail.com
Phone: 011/123-123

Cash desk opening hours

Monday - Friday: 10h - 20h

Saturday - Sunday: 16h - 20h

Author Documentation Kodovi

Root

Index.php

```
    require_once "view/fixed/head.php";

    require_once "view/fixed/header.php";

    require_once "view/pages/index.php";

    require_once "view/fixed/footer.php";

?>
```

Activation.php

```
require_once "view/fixed/head.php";

require_once "view/fixed/header.php";

if(!isset($_SESSION['user'])){
    require_once "view/pages/activation.php";
}
else{
    echo "<main><h1 class='text-center my-5'>No Access</h1></main>";
}

require_once "view/fixed/footer.php";

?>
```

Performance.php

```
    require_once "view/fixed/head.php";

    require_once "view/fixed/header.php";

    require_once "view/pages/performance.php";

    require_once "view/fixed/footer.php";

?>
```

Performances.php

```
    require_once "view/fixed/head.php";

    require_once "view/fixed/header.php";

    require_once "view/pages/performances.php";

    require_once "view/fixed/footer.php";

?>
```

Repertoire.php

```
require_once "view/fixed/head.php";
require_once "view/fixed/header.php";
require_once "view/pages/repertoire.php";
require_once "view/fixed/footer.php";

require_once "view/fixed/footer.php";
```

Tickets.php

```
require_once "view/fixed/head.php";

require_once "view/fixed/header.php";

if(isset($_SESSION['user'])){
    require_once "view/pages/tickets.php";
}
else{
    echo "<main><div class='text-center'><h1>No access</h1></div></main>";
}

require_once "view/fixed/footer.php";

?>
```

Seats.php

```
require_once "view/fixed/head.php";

require_once "view/fixed/header.php";

require_once "view/pages/seats.php";

require_once "view/fixed/footer.php";

?>
```

Contact.php

```
<?php

require_once "view/fixed/head.php";

require_once "view/fixed/header.php";

require_once "view/pages/contact.php";

require_once "view/fixed/footer.php";

?>
```

Author.php

```
    require_once "view/fixed/head.php";

    require_once "view/fixed/header.php";

    require_once "view/pages/author.php";

    require_once "view/fixed/footer.php";

    require_once "view/fixed/footer.php";

}
```

Login.php

```
<?php

require_once "view/fixed/head.php";

require_once "view/fixed/header.php";

if(isset($_SESSION['user'])){
    echo "<h1 class='text-center my-3'>No access</h1>";
```

```
}
else{
    require_once "view/pages/login.php";
}
require_once "view/fixed/footer.php";
?>
```

Activation.php

```
require_once "view/fixed/head.php";

require_once "view/fixed/header.php";

if(!isset($_SESSION['user'])){
    require_once "view/pages/activation.php";
}
else{
    echo "<main><h1 class='text-center my-5'>No Access</h1></main>";
}

require_once "view/fixed/footer.php";

?>
```

View/fixed

Footer.php

```
<?php?>
<footer>
    <div class="container-fluid">
        <div class="row justify-content-between text-center">
            <div class="col-12">
                <hr class="m-0">
            </div>
            <div class="col-3 py-3">
                <h3>Contact</h3>
                E-mail: theatre@gmail.com
                Phone: 011/123-123
            </div>
            <div class="col-3 py-3">
                <h3>Cash desk opening hours</h3>
                Monday - Friday: 10h - 20h
                Saturday - Sunday: 16h - 20h
            <div class="col-3 py-3">
                <a href="author.php" class="fs-5">Author</a>
                <a href="doc.pdf" class="fs-5">Documentation</a>
            </div>
        </div>
    </div>
</footer>
    <script src="https://code.jquery.com/jquery-3.5.1.min.js" integrity="sha256-</pre>
9/aliU8dGd2tb6OSsuzixeV4y/faTqgFtohetphbbj0=" crossorigin="anonymous"></script>
src="https://cdn.jsdelivr.net/npm/bootstrap@5.0.2/dist/js/bootstrap.bundle.min.js
 integrity="sha384-
MrcW6ZMFY1zcLA8N1+NtUVF0sA7MsXsP1UyJoMp4YLEuNSfAP+JcXn/tWtIaxVXM"
crossorigin="anonymous"></script>
    <script src="assets/js/main.js" type="text/javascript"></script>
</body>
</html>
```

Head.php

```
<?php
    session start();
<!DOCTYPE html>
<html lang="en">
<head>
    <meta charset="UTF-8">
    <meta name="viewport" content="width=device-width, initial-scale=1.0">
    <link rel="preconnect" href="https://fonts.googleapis.com">
    <link rel="preconnect" href="https://fonts.gstatic.com" crossorigin>
    link
href="https://fonts.googleapis.com/css2?family=Anek+Latin:wght@300&display=swap"
rel="stylesheet">
    link
href="https://cdn.jsdelivr.net/npm/bootstrap@5.1.3/dist/css/bootstrap.min.css"
rel="stylesheet" integrity="sha384-
1BmE4kWBq78iYhFldvKuhfTAU6auU8tT94WrHftjDbrCEXSU1oBoqyl2QvZ6jIW3"
crossorigin="anonymous">
    <link rel="stylesheet" href="https://site-</pre>
assets.fontawesome.com/releases/v6.1.1/css/all.css">
    <link rel="stylesheet" href="assets/css/style.css" type="text/css">
    <meta name="keywords" content="Theatre, Performances, Repertoire, Tickets,</pre>
Belgrade"/>
    <meta name="description" content="'Theater' is the youngest theater in</pre>
Serbia, with its headquarters in Belgrade, Banovo Brdo."/>
    <title>Theatre</title>
    <link rel="shortcut icon" href="assets/images/logo.png">
</head>
<body>
```

Header.php

View/pages

Index.php

```
<?php
   require_once "models/next.php";
   <div class="container">
       <div class="row justify-content-center p-2">
          <?php
              if($next):
              <div class="col-3">
                 <img src="assets/images/<?=$next['poster']?>" class="img-
fluid" alt="<?=$next['name']?>"/>
              </div>
              <div class="col-3 next">
                 <div>
                     Next in the repertoire
                     <h1 class="mt-2 mb-4"><?=$next['name']?></h1>
                     <?php
                         $date=new DateTime($next['datePerforming']);
                     <?=$date->format('1')?>
```

```
<?=$date->format('d.m.')?>
                  </div>
                  <div class="my-1">
                  <a class="fs-5 text-light py-2 px-3 buy text-uppercase"</pre>
href="seats.php?id=<?=$next['id']?>">Buy ticket</a>
                  </div>
               </div>
           <?php
              else:
              <?=$data?>
           <?php
              endif;
       </div>
   </div>
   <div class="container-fluid bg-light py-4 my-5">
       <div class="row justify-content-between">
           <div class="col-12 text-center mb-3">
               <h2>About</h2>
           </div>
           <div class="col-6">
               <img src="assets/images/teatar.jpg" alt="Theatre"/>
           </div>
           <div class="col-6">
               'Theater' is the youngest theater in Serbia, with
its headquarters in Belgrade, Banovo Brdo. It is located between the wooded
Kosutnjak and Ada Ciganlija, two favorite resorts of Belgraders.
               'Theater' was a dream, realized with the help of
people who had a vision and enthusiasm, and most of all love for the theater,
culture and the community in which they live.
               Today, we are one of the most visited stages in
Belgrade, and our performances are at the top of viewership and popularity in the
entire region.
               Tens of thousands of people follow our guest
appearances and look forward to our performances.
           </div>
       </div>
   </div>
</main>
```

Performance.php

```
<?php
    require_once "models/performance.php";
    <div class="container">
        <div class="row justify-content-between">
                <?php
                    if($code!=200):
                    <div class="col-12 text-center">
                        <h1><?=$data?></h1>
                    </div>
                <?php
                    else:
                    <div class="col-12 text-center">
                        <h1>
                            <?=$data['name']?>
                        </h1>
                    </div>
                    <div class="col-4 my-4">
                        <img class="img-fluid"</pre>
src="assets/images/<?=$data['poster']?>" alt="<?=$data['name']?>"/>
                    </div>
                    <div class="col-6 my-4">
                        <?=$data['description']?>
                        Duration: <?=$data['duration']?>
                            <?php
                                $date=new DateTime($data['premier']);
                        Premier: <?=$date->format('d.m.Y.')?>
                    </div>
                <?php
                    endif;
        </div>
    </div>
</main>
```

Performances.php

```
<?php
    <div class="container">
        <div class="row">
            <div class="col-3 my-2">
                <form action="#">
                    <input id="search" class="form-control" type="search"</pre>
placeholder="Search performance..."/>
                </form>
            </div>
        </div>
        <div class="row" id="performances">
        </div>
        <div class="row">
            <div class="col-10 text-center mx-auto" id="pagination">
            </div>
        </div>
    </div>
 /main>
```

Repertoire.php

```
<?php
                              $date=new DateTime($r['datePerforming']);
                          <?=$date->format('d.m.')?>
                          <?=$date->format('l')?>, 20:00
                          <hr class="text-success border-3 opacity-75"/>
                          <h2 class="fs-1"><?=$r['name']?></h2>
                          <a class="fs-5 text-light py-2 px-3 buy text-
uppercase" href="seats.php?id=<?=$r['id']?>">Buy ticket</a>
                      </div>
                      <div class="col-3">
                          <img class="img-fluid"</pre>
src="assets/images/<?=$r['poster']?>" alt="<?=$p['name']?>"/>
                       </div>
                   </div>
               </div>
           <?php
               endforeach;
           <?php
               else:
               <?=$message?>
           <?php
               endif;
       </div>
   </div>
</main>
```

Tickets.php

Seats.php

```
<?php
   require_once "models/seats.php";
   <div class="container">
       <div class="row">
          <?php
              if($code!=200):
              <h1 class="text-center"><?=$data?></h1>
          <?php
              else:
          <div class="col-12">
              <div class="row justify-content-between align-items-end">
                  <div class="col-6">
                     <h1 class="m-0"><?=$performance['name']?></h1>
                  </div>
                  <div class="col-6 text-end">
                     <?php
                         $date=new DateTime($performance['datePerforming']);
                     <?=$date->format('d.m.Y.')?>
20:00h
                 </div>
              </div>
          </div>
           <div class="col-12">
              <div class="scena">
                  Scena
              </div>
          </div>
          <div class="col-12 parter mx-auto my-3">
                  Parterre left
              </div>
              <div>
                  Parterre right
              </div>
          </div>
          <div class="col-12 mx-auto text-end">
                  <form action="#">
                     <div class="px-3 py-1">
```

```
<input type="button" id="checkSeats" class="fs-4</pre>
text-bold px-3 py-1 kupi text-light border-0" value="Buy" data-bs-toggle="modal"
data-bs-target="#modalTickets">
                             <input type="hidden" id="repertoire"</pre>
value="<?=$_GET['id']?>"/>
                         </div>
                     </form>
            </div>
            <div class="col-12 mx-auto">
                <?php
                     for($i=1;$i<=10;$i++):
                         $jMax=10;
                     <div class="redDrzac">
                         <div class="red">
                             <span><?=$i?></span>
                         </div>
                         <div id="places">
                     <?php
                         for($j=1;$j<=$jMax;$j++):</pre>
                 <!-- POSITION!!!!! -->
                <!-- 1 levo -->
                <!-- 2 desno -->
                 <!-- 3 sredina -->
                             <a href="#" class="places
                                 foreach($data as $d):
                                     if($d['position']==1 && $d['row']==$i &&
$d['place']==$j):
                                     purchased
                                 <?php
                                     endif;
                                 endforeach;
                             " data-position="1" data-row="<?=$i?>" data-
place="<?=$j?>"><?=$j?><span class="popup">
                                 Row: <span class="font-weight-
bold"><?=$i?></span><br>
```

```
Seat: <span class="font-weight-</pre>
bold"><?=$j?></span><br>
                                 Parterre left <br>
                                 Price : <?=$performance['price']?>
                             </span></a>
                <?php
                         endfor;
                <?php
                         if($i%2==0):
                         <a href="#" class="places
                                 <?php
                                 foreach($data as $d):
                                     if($d['position']==3 && $d['row']==$i &&
$d['place']==$j):
                                     purchased
                                 <?php
                                     endif;
                                 endforeach;
                             " data-position="3" data-row="<?=$i?>" data-
place="11">11<span class="popup">
                                 Row: <span class="font-weight-
bold"><?=$i?></span><br>
                                 Seat: <span class="font-weight-</pre>
bold">11</span><br>
                                 Middle <br>
                                 Price : <?=$performance['price']?>
                             </span></a>
                         endif;
                 <?php
                         for($j=$jMax;$j>=1;$j--):
                             <a href="#" class="places
                                 foreach($data as $d):
                                     if($d['position']==2 && $d['row']==$i &&
$d['place']==$i):
```

```
purchased
                                 <?php
                                     endif;
                                 endforeach;
                                 ?>" data-position="2" data-row="<?=$i?>" data-
place="<?=$j?>"><?=$j?><span class="popup">
                                 Row: <span class="font-weight-
bold"><?=$i?></span><br>
                                 Seat: <span class="font-weight-</pre>
bold"><?=$j?></span><br>
                                 Parterre right <br>
                                 Price : <?=$performance['price']?>
                             </span></a>
                <?php
                         endfor;
                         </div>
                         <div class="red desno">
                             <span><?=$i?></span>
                         </div>
                     </div>
                <?php
                     endfor;
            </div>
            <div class="modal fade" id="modalTickets" tabindex="-1" aria-</pre>
labelledby="exampleModalLabel" aria-hidden="true">
            <div class="modal-dialog">
                <div class="modal-content">
                <div class="modal-header">
                     <h5 class="modal-title" id="exampleModalLabel">Tickets</h5>
                     <button type="button" class="btn-close" data-bs-</pre>
dismiss="modal" aria-label="Close"></button>
                </div>
```

```
<div class="modal-body">
                    <div id="seatsMessage">
                    </div>
                    <div id="buyMessage"></div>
                </div>
                <div class="modal-footer">
                    <button type="button" class="btn btn-secondary" data-bs-</pre>
dismiss="modal">Close</button>
                    <button type="button" id="buy" class="btn</pre>
btnBuy">Buy</button>
                </div>
                </div>
            </div>
            </div>
            <?php
                endif;
        </div>
        <?php
            if($code==200):
        <div class="col-12">
            <span class="boja nedostupna"></span> Seats are not available
            <span class="boja dostupna"></span> Available seats
            <span class="boja izabrana"></span> Selected seats
        </div>
        <?php
            endif;
    </div>
</main>
```

Contact.php

```
<div class="row justify-content-between">
           <div class="col-5">
               <form action="#" onSubmit="return sendMessage()">
                   <div class="row messageDiv">
                       <div class="col-12 mt-2">
                           <label for="email">E-mail</label>
                           <input type="text" id="email" class="form-control">
                           E-mail formats: petar.petrovic.123.21@ict.edu.rs
or petar@gmail.com
                       </div>
                       <div class="col-12 mt-2">
                           <label for="title">Subject</label>
                           <input type="text" id="subject" class="form-control">
                           You have to write subject
                       </div>
                       <div class="col-12 mt-2">
                           <label for="message">Message</label>
                           <textarea class="col-12 form-control"
id="message"></textarea>
                           Message has 10 words minimum
                       </div>
                       <div class="col-12 mt-2">
                       </div>
                       <div class="col-12 mt-2">
                           <input type="submit" id="btnMessage" class="btn"</pre>
value="Send">
                           <div class="my-2">
                               </div>
                       </div>
                   </div>
               </form>
           </div>
           <div class="col-5">
               <h2>Poo1</h2>
                   if(isset($_SESSION['user'])):
               <form action="#">
                   <?php
                       if(isset($message)):
                           <?=$message?>
                   <?php
```

```
else:
                   <h4><?=$aktivna['question']?></h4>
                       foreach($odgovori as $o):
                       <input type="radio" value="<?=$o['id']?>" name="odg"
class="odg"/>
                       <span class="mx-2"><?=$o['answer']?></span>
                   <?php
                       endforeach;
                       <input type="button" value="Vote" id="vote"</pre>
                   <?php
                       if(isset($obavestenje)):
                           disabled="disabled"
                       <?php
                       endif;
                           class="btn btn-primary mt-2">
                       <?php
                           if(isset($obavestenje)):
                               <?=$obavestenje?>
                           <?php
                           endif;
                           <?php
                       endif;
               </form>
               <?php
                   else:
                   <h3>Log in to see our poll!</h3>
               <?php
                   endif;
           </div>
       </div>
    </div>
</main>
```

Author.php

```
<?php?>
    <div class="container">
        <div class="row my-3">
            <div class="col-12 text-center">
                <h1>Author</h1>
            </div>
        </div>
        <div class="row justify-content-around">
            <div class="col-4">
                <img class="img-fluid" src="assets/images/author.jfif"</pre>
alt="Author">
            </div>
            <div class="col-4">
                <h2>Darija Šošdean</h2>
                <h3>18/16</h3>
                Internet technologies
            </div>
        </div>
    </div>
</main>
```

```
<input type="password" id="password" class="form-</pre>
control">
                        Password must be at least 8 characters long.
                    </div>
                    <div id="messageLogin" class="my-2"></div>
                    <div class="my-3">
                        <input type="submit" id="btnLogin" value="Login"</pre>
class="btn">
                    </div>
                    <div class="text-center">
                        <a href="#" id="regBtn" class="green">Don't have an
account? Sign up</a>
                    </div>
                </form>
            </div>
            <div class="col-5 mx-auto d-none" id="regDiv">
                <h2 class="text-center">Sign Up</h2>
                <form action="#" onSubmit="return register()">
                    <div>
                        <label for="fname">First name</label>
                        <input type="text" id="firstName" class="form-control">
                        First name has capital letter, 3 letter minimum,
30maximum
                    </div>
                    <div>
                        <label for="lName">Last name</label>
                        <input type="text" id="lastName" class="form-control">
                        Last name has capital letter, 3 letter minimum,
30maximum
                    </div>
                    <div>
                        <label for="email">E-mail</label>
                        <input type="text" id="emailReg" class="form-control">
                        E-mail formats: petar.petrovic.123.21@ict.edu.rs or
petar@gmail.com
                    </div>
                    <div>
                        <label for="pass">Password</label>
                        <input type="password" id="pass" class="form-control">
                        Password must be at least 8 characters long.
                    </div>
                    <div>
                        <label for="passConfirm">Confirm password</label>
```

```
<input type="password" id="passConfirm" class="form-</pre>
control">
                         Passwords do not match
                    </div>
                    <div id="messageRegister" class="my-2"></div>
                    <div class="my-3">
                         <input type="submit" id="btnRegister" value="Register"</pre>
class="btn">
                    </div>
                    <div class="text-center">
                         <a href="#" id="logBtn" class="green">Have an account?
Log in</a>
                    </div>
                </form>
            </div>
        </div>
    </div>
</main>
```

Activation.php

Models

Activation.php

```
<?php
    require_once "connection.php";
    if(isset($_GET['code'])){
        $code=$_GET['code'];
        $query="SELECT * FROM users WHERE activationcode=:code";
        $prepare=$connection->prepare($query);
        $prepare->bindParam(":code",$code);
        try{
            $prepare->execute();
            if($prepare->rowCount()==1){
                $korisnik=$prepare->fetch();
                $aktivan=1;
                $query2="UPDATE users SET active=:active WHERE
activationcode=:code";
                $prepare2=$connection->prepare($query2);
                $prepare2->bindParam(":active",$aktivan);
                $prepare2->bindParam(":code",$code);
                try{
                    $prepare2->execute();
                    $message="Account activated";
                catch(PDOException $e){
                    $message="Server error";
            else{
                $message="Code Not Found";
        catch(PDOException $e){
            $message=$e->getMessage();
    else{
        $message="No Access";
```

addPerformance.php

```
<?php
    require_once "connection.php";
    $code=200;
    $data="Inserted";
    $name=$_POST['name'];
    $duration=$_POST['duration'];
    $premier=$_POST['premier'];
    $price=$_POST['price'];
    $description=$_POST['description'];
    $err=0;
    if(strlen($name)<1){</pre>
        $data="Name has 1 letter minimum";
        $err++;
    if(!isset($_FILES['file'])){
        $data="You have to choose image";
        $err++;
    if(strlen($description)<15){</pre>
        $data="Description has 15 letter minimum";
        $err++;
    if($duration>180 || $duration==""){
        $data="Duration is number (minutes), values 180 maximum";
        $err++;
    if($premier==""){
        $data="You have to choose premier date";
        $err++;
    if($price==""){
        $data="You have to choose price";
        $err++;
    if($err==0){
        $code=201;
        $ifNameExists="SELECT * FROM performances WHERE name like :name";
```

```
$prepareTest=$connection->prepare($ifNameExists);
        $namePrepare="%".$name."%";
        $prepareTest->bindParam(":name",$namePrepare);
        try{
            $prepareTest->execute();
            if($prepareTest->rowCount()==1){
                $code=200;
                $data="Name already exists";
            else{
                $slika=$_FILES['file'];
                $tmpName=$slika['tmp_name'];
                $size=$slika['size'];
                $tip=$slika['type'];
                $nameImage=$slika['name'];
                $naziv=time().$nameImage;
                $putanja="../assets/images/$naziv";
                move_uploaded_file($tmpName,$putanja);
                $query="INSERT INTO performances VALUES
(null,:name,:description,:poster,:premier,:duration) ";
                $prepare=$connection->prepare($query);
                $prepare->bindParam(":name",$name);
                $prepare->bindParam(":description",$description);
                $prepare->bindParam(":poster",$naziv);
                $prepare->bindParam(":premier",$premier);
                $prepare->bindParam(":duration",$duration);
                $prepare->execute();
                $id=$connection->lastInsertId();
                $inserQuery="INSERT INTO prices VALUES
(null,:price,:dateFrom,:idPerformance)";
                $prepare2=$connection->prepare($inserQuery);
```

```
$date=date("Y-m-d");

$prepare2->bindParam(":price",$price);
$prepare2->bindParam(":dateFrom",$date);
$prepare2->bindParam(":idPerformance",$id);
$prepare2->execute();
$data="Inserted";
}

}

catch(PDOException $e){
    $data=$e->getMessage();
    $code=500;
}
}

echo json_encode($data);
http_response_code($code);

}
```

addReprtoire.php

```
<?php
    require_once "connection.php";

if(isset($_POST['btn'])){
    $code=200;

$idPerformance=$_POST['idPerformance'];

$err=0;
    if($idPerformance==0){
        $data="You have to choose performance";
        $err++;
    }
    if(!isset($_POST['date']) || strtotime($_POST['date'])<time()){
        $data="You have to choose date in future";
        $err++;
    }

if($err==0){
        $date=$_POST['date'];
}
</pre>
```

```
$query="SELECT * FROM repertoire WHERE
datePerforming=:datePerforming";
            $prepare=$connection->prepare($query);
            $prepare->bindParam(":datePerforming",$date);
            try{
                $prepare->execute();
                if($prepare->rowCount()==1){
                    $data="Date already reserved!";
                }
                else{
                    $query2="INSERT INTO repertoire VALUES (NULL, :id,
:datePerforming)";
                    $prepare2=$connection->prepare($query2);
                    $prepare2->bindParam(":id",$idPerformance);
                    $prepare2->bindParam(":datePerforming",$date);
                    $prepare2->execute();
                    $code=201;
                    $data="Added to repertoire";
            catch(Exception $e){
                $code=500;
                $data="Server error";
    else{
        $code=404;
        $data="Not found";
echo json_encode($data);
http_response_code($code);
```

allPerformances.php

```
<?php
    require_once "connection.php";
    if(isset($_GET['btn'])){
        $code=200;
        $query="SELECT *,pr.id FROM performances p INNER JOIN prices pr
                ON p.id=pr.idPerformance";
        try{
            $performances=$connection->query($query);
            $data=$connection->query($query)->fetchAll();
        catch(Exception $e){
            $code=500;
            $data="Server error";
    else{
        $code=404;
        $data="Not found";
echo json_encode($data);
http_response_code($code);
```

buyTickets.php

```
<?php
session_start();
    require_once "connection.php";

$data="";
$code=200;

if(isset($_POST['btnBuy'])){</pre>
```

```
$tickets=$ POST['tickets'];
        if(isset($_SESSION['user'])){
            $idUser=$ SESSION['user']['id'];
            $query="INSERT INTO tickets VALUES (NULL, :idRepertoire, :idUser,
:placeRow, :place, :position, :purchaseDate)";
            foreach($tickets as $t){
                try{
                    $prepare=$connection->prepare($query);
                    $date=date("Y-m-d H:i:s");
                    $prepare->bindParam(":idRepertoire",$t['idRepertoire']);
                    $prepare->bindParam(":idUser",$idUser);
                    $prepare->bindParam(":placeRow",$t['row']);
                    $prepare->bindParam(":place",$t['place']);
                    $prepare->bindParam(":position",$t['position']);
                    $prepare->bindParam(":purchaseDate",$date);
                    $prepare->execute();
                    $code=201;
                    $data="Tickets were successfully purchased";
                catch(PDOException $e){
                    $data="Server error";
                    $code=500;
                }
        else{
           $data="Login to buy";
           $code=401;
    else{
        $data= "NOT FOUND";
        $code=404;
echo json encode($data);
http response code($code);
```

?>

cancelTickets.php

```
<?php
    require_once "connection.php";
    $code=200;
    if(isset($_POST['cancelBtn'])){
        $query="DELETE FROM tickets WHERE id=:id";
        $priprema=$connection->prepare($query);
        $priprema->bindParam(":id",$_POST['id']);
        try{
            $priprema->execute();
            $data="Deleted";
        catch(PDOException $e){
            $data="Server error";
            $code=500;
            // $data=$e->getMessage();
    else{
        $code=404;
        $data="Not found";
echo json_encode($data);
http_response_code($code);
```

connection.php

```
<?php
    require_once "parameters.php";
    try{</pre>
```

deleteMessage.php

```
<?php
    require_once "connection.php";
    $code=200;
    if(isset($ POST['id'])){
        $query="DELETE FROM messages WHERE id=:id";
        $priprema=$connection->prepare($query);
        $priprema->bindParam(":id",$ POST['id']);
        try{
            $priprema->execute();
            $data="Deleted";
        catch(PDOException $e){
            $data="Server error";
            $code=500;
            // $data=$e->getMessage();
    else{
        $code=404;
        $data="Not found";
echo json_encode($data);
http_response_code($code);
```

deletePerformance.php

```
<?php
    require_once "connection.php";
    $code=200;
    if(isset($_POST['id'])){
        $query="DELETE FROM performances WHERE id=:id";
        $priprema=$connection->prepare($query);
        $priprema->bindParam(":id",$_POST['id']);
        try{
            $priprema->execute();
            $data="Deleted";
        catch(PDOException $e){
            $data="Server error";
            $code=500;
            // $data=$e->getMessage();
    else{
        $code=404;
        $data="Not found";
echo json_encode($data);
http_response_code($code);
```

deleteRepertoire.php

```
<?php
    require_once "connection.php";
    $code=200;
    if(isset($_POST['id'])){
        $query="DELETE FROM repertoire WHERE id=:id";
        $priprema=$connection->prepare($query);
        $priprema->bindParam(":id",$_POST['id']);
        try{
            $priprema->execute();
            $data="Deleted";
        catch(PDOException $e){
            $data="Server error";
            $code=500;
            // $data=$e->getMessage();
    else{
        $code=404;
        $data="Not found";
echo json_encode($data);
http_response_code($code);
```

disablePoll.php

```
<?php

require_once "connection.php";

$code=200;
$data="";

$upit="UPDATE poll set active=0";

try{</pre>
```

```
$connection->query($upit);
    $code=204;
}
catch(PDOException $e){
    $code=500;
    $data="Server error";
}
echo json_encode($data);
http_response_code($code);
}>
```

editPerfromance.php

```
<?php
    require_once "connection.php";
    $code=200;
    $data="Inserted";
    $name=$ POST['name'];
    $duration=$_POST['duration'];
    $premier=$_POST['premier'];
    $price=$_POST['price'];
    $description=$_POST['description'];
    $id=$ POST['id'];
    $err=0;
    if(strlen($name)<1){</pre>
        $data="Name has 1 letter minimum";
        $err++;
    if(strlen($description)<15){</pre>
        $data="Description has 15 letter minimum";
        $err++;
    if($duration>180 || $duration==""){
        $data="Duration is number (minutes), values 180 maximum";
        $err++;
    if($premier==""){
        $data="You have to choose premier date";
```

```
if($price==""){
        $data="You have to choose price";
        $err++;
    if($err==0){
        $code=201;
        $ifNameExists="SELECT * FROM performances WHERE name like :name AND
id!=:id";
        $prepareTest=$connection->prepare($ifNameExists);
        $namePrepare="%".$name."%";
        $prepareTest->bindParam(":name",$namePrepare);
        $prepareTest->bindParam(":id",$id);
        try{
            $prepareTest->execute();
            if($prepareTest->rowCount()==1){
                $code=200;
                $data="Name already exists";
            else{
                if(isset($_FILES['file'])){
                    $slika=$ FILES['file'];
                    $tmpName=$slika['tmp name'];
                    $size=$slika['size'];
                    $tip=$slika['type'];
                    $nameImage=$slika['name'];
                    $naziv=time().$nameImage;
                    $putanja="../assets/images/$naziv";
                    move uploaded file($tmpName,$putanja);
                    ///upis sa slikom
                    $query="UPDATE performances set
name=:name,description=:description,poster=:poster,premier=:premier,duration=:dur
ation where id=:id";
                    $prepare=$connection->prepare($query);
                    $prepare->bindParam(":poster",$naziv);
```

```
else{
                    ///upit bez slike
                    $query="UPDATE performances set
name=:name,description=:description,premier=:premier,duration=:duration where
id=:id";
                    $prepare=$connection->prepare($query);
                $prepare->bindParam(":name",$name);
                $prepare->bindParam(":description",$description);
                $prepare->bindParam(":premier",$premier);
                $prepare->bindParam(":duration",$duration);
                $prepare->bindParam(":id",$id);
                $prepare->execute();
                $priceQuery="UPDATE prices SET price=:price,dateFrom=:dateFrom
WHERE idPerformance=:id";
                $prepare2=$connection->prepare($priceQuery);
                $date=date("Y-m-d");
                $prepare2->bindParam(":price",$price);
                $prepare2->bindParam(":dateFrom",$date);
                $prepare2->bindParam(":id",$id);
                $prepare2->execute();
                $data="Updated";
        catch(PDOException $e){
            $data=$e->getMessage();
            $code=500;
    echo json_encode($data);
    http_response_code($code);
```

enablePoll.php

```
<?php

require_once "connection.php";

$code=200;
$data="";

$upit="UPDATE poll set active=1";

try{
    $connection->query($upit);
    $code=204;
}
catch(PDDException $e){
    $code=500;
    $data="Server error";
}

echo json_encode($data);
http_response_code($code);

}
```

getEditPerformance.php

getMessagesAdmin.php

```
    require_once "connection.php";

    $code=200;

    $query="select * from messages";

    try{
        $data=$connection->query($query)->fetchAll();

}

catch(PDOException $e){
        $data="Server error";
        $code=500;
        // $data=$e->getMessage();
    }

echo json_encode($data);
http_response_code($code);
```

?>

getNav.php

```
<?php
    require_once "connection.php";

$query="SELECT * FROM navigations WHERE preview=1";

if(isset($_SESSION['user'])){
    $query.=" OR preview=3";

    if($_SESSION['user']['idRole']==1){
        $query.=" OR preview=4";
    }
} else{
        $query.=" OR preview=2";
}

$query.=" OR preview=2";
}

$query.=" ORDER BY priority";

try{
        $nav=$connection->query($query)->fetchAll();
}
catch(PDOException $e){
        $nav=$e->getMessage();
}
}

}
```

getTickets.php

```
ORDER BY datePerforming";
        $idUser=$_SESSION['user']['id'];
        $prepare=$connection->prepare($query);
        $prepare->bindParam(":idUser",$idUser);
        try{
            $prepare->execute();
            $data=$prepare->fetchAll();
            $code=200;
        catch(Exception $e){
            $code=500;
            $data=$e->getMessage();
    else{
        $data="No access";
        $code=404;
echo json_encode($data);
http_response_code($code);
```

getUsersAdmin.php

```
<?php
    require_once "connection.php";

$code=200;

$query="select * from users";

try{
    $data=$connection->query($query)->fetchAll();
```

```
}
catch(PDOException $e){
    $data="Server error";
    $code=500;
    // $data=$e->getMessage();
}
echo json_encode($data);
http_response_code($code);
?>
```

login.php

```
<?php
    session_start();
    require_once "connection.php";
    $data="";
    $code=200;
    if(isset($_POST['btnLogin'])){
        $mail=$ POST['email'];
        $pass=$_POST['password'];
        pregEmail="/^\w[.\d\w]*\@[a-z]{2,10}(\.[a-z]{2,3})+$/";
        $regPass="/^.{8,50}$/";
        $greske=[];
        if(!preg match($regEmail,$mail)){
            array_push($greske,"E-mail formats: petar.petrovic.123.21@ict.edu.rs
or petar@gmail.com. <br>");
        if(!preg_match($regPass,$pass) && strlen($pass)<8){</pre>
            array_push($greske,"Password must be at least 8 characters long.
<br>");
        }
        if(count($greske)==0){
            $aktivan=1;
```

```
$daLiPostojiKorisnik="SELECT * FROM users WHERE email=:email AND
active=:aktivan";
            $priprema=$connection->prepare($daLiPostojiKorisnik);
            $priprema->bindParam(":email",$mail);
            $priprema->bindParam(":aktivan",$aktivan);
            try{
                $priprema->execute();
                if($priprema->rowCount()==1){
                    $upit="SELECT *,u.id FROM users u INNER JOIN roles r ON
u.idrole=r.id WHERE email=:email AND password=:pass";
                    $pass=md5($pass);
                    $priprema2=$connection->prepare($upit);
                    $priprema2->bindParam(":email",$mail);
                    $priprema2->bindParam(":pass",$pass);
                    try{
                        $priprema2->execute();
                        $code=200;
                        if($priprema2->rowCount()==1){
                            $korisnik=$priprema2->fetch();
                            $_SESSION['user']=$korisnik;
                            $code=200;
                            $data="ok";
                        else{
                            $data="The password is incorrect";
                    catch(PDOException $e){
                        $code=500;
                        $data=$e->getMessage();
                else{
                    $code=200;
                    $data="No user with that email address was found or the
account was not activated";
            catch(PDOException $e){
                $code=500;
                $data="Server error";
        else{
            $data=$greske;
```

```
$code=422;
}

}

else{
    $data="Sorry bit the page you are looking for does not exist, have been removed or you have to log in.";
    $code=404;
}

echo json_encode($data);
http_response_code($code);

?>
```

message.php

```
<?php
    require_once "connection.php";
if(isset($_POST["btnMessage"])){
    $code=200;
    $email=$_POST["email"];
    $subject=$_POST["subject"];
    $message=$ POST["message"];
    pregEmail="/^w[.\d\w]*\@[a-z]{2,10}(\.[a-z]{2,3})+$/";
    $regSubject="/^[\w\s]+$/";
    $error=0;
    if(!preg_match($regEmail,$email)){
        $error++;
        $data="E-mail format: pera.peric.55.19@ict.edu.rs or pera@gmail.com";
    if(!preg_match($regSubject,$subject)){
        $error++;
        $data="You have to write title";
    if(count($message)<10){</pre>
        $error++;
        $data="Message have 10 words minimum";
    if($error==0){
        $message=implode($message," ");
```

```
$datum=date("Y-m-d H:i:s");
        $insert="INSERT INTO messages
VALUES(null,:email,:subject,:message,:datum)";
        $prepare=$connection->prepare($insert);
        $prepare->bindParam(":email",$email);
        $prepare->bindParam(":subject",$subject);
        $prepare->bindParam(":message",$message);
        $prepare->bindParam(":datum",$datum);
        try{
            $prepare->execute();
            $date="Message successfuly sent";
            $code=201;
        catch(PDOException $e){
            $date="Server error";
            $code=500;
    }
    else{
        $code=422;
        $date=$data;
else{
    $code=404;
    $date="Error";
echo json encode($date);
http_response_code($code);
```

next.php

```
$data=$connection->query($query);
if($data->rowCount()==0){
        $data="There is nothing in the repertoire";
}
else{
        $next=$data->fetch();
}
$code=200;
}
catch(PDOException $e){
    $data="Server error";
    $code=500;
}
```

parameters.php

```
$baza="pozoriste";
$user="root";
$pass="";
$host="localhost";

?>
```

performance.php

```
c?php
  require_once "connection.php";

if(isset($_GET['id'])){
    $id=$_GET['id'];

  $query="SELECT * FROM performances WHERE id=:id";

  $prepare=$connection->prepare($query);
  $prepare->bindParam(":id",$id);
  try{
    $prepare->execute();
    if($prepare->rowCount()==1){
        $data=$prepare->fetch();
        $code=200;
    }
}
```

performances.php

```
$query="SELECT *,p.id FROM performances p INNER JOIN prices pr
                ON p.id=pr.idPerformance WHERE name like '%$search%'";
        try{
            $performances=$connection->query($query);
            if($performances->rowCount()!=0){
                $sum=$performances->rowCount();
                $data['sumPages']=ceil($sum/$limit);
                $query.=" LIMIT $limit OFFSET $offset";
                $data['performances']=$connection->query($query)->fetchAll();
                $data['currentPage']=$page+1;
            else{
                $data['performances']=[];
        catch(Exception $e){
            $code=500;
            $data="Server error";
    else{
        $code=404;
        $data="Not found";
echo json_encode($data);
http_response_code($code);
```

poll.php

```
$aktivna = $anketa->fetch();
        $idAnkete = $aktivna['id'];
        $upit2 = "SELECT * FROM answers WHERE idPoll=$idAnkete";
        $odg = $connection->query($upit2);
        if ($odg->rowCount() != 0)
            $odgovori = $odg->fetchAll();
            if (isset($_SESSION['user']))
                $user = $_SESSION['user'];
                $id = $user['id'];
                $upit3 = "SELECT * FROM useranswers ua INNER JOIN answers a on
ua.idAnswer=a.id WHERE idPoll=$idAnkete AND idUser=$id";
                $odgovorKorisnika = $connection->query($upit3);
                if ($odgovorKorisnika->rowCount() == 1)
                    $test = $odgovorKorisnika->fetch();
                    $obavestenje = "You have already voted!";
            else
                $obavestenje = "Login to vote!";
    else
        $message = "There is no active poll currently";
catch(PDOException $e)
    $message = "Server error";
```

pollRez.php

```
<?php
    require_once "connection.php";

$upit="SELECT * FROM poll";</pre>
```

register.php

```
require_once "connection.php";

$data="";

if(isset($_POST['btnRegister'])){

    $firstName=$_POST['firstName'];
    $lastName=$_POST['lastName'];
    $email=$_POST['email'];
    $password=$_POST['password'];
    $passwordConf=$_POST['passConfirm'];

    $regName="/^[A-ZZŠĐŽČĆ][a-zzšđžčć]{2,29}$/";
    $regEmail="/^\w[.\d\w]*\@[a-z]{2,10}(\.[a-z]{2,3})+$/";
    $regPass="/^.{8,50}$/";
    $greske=[];
    if(!preg_match($regName,$firstName)){
```

```
array_push($greske,"First name has capital letter,3 letter minimum,
30maximum<br>");
        if(!preg match($regName,$lastName)){
            array_push($greske,"Last name has capital letter,3 letter minimum,
30maximum<br>");
        if(!preg_match($regEmail,$email)){
            array_push($greske,"E-mail formats: petar.petrovic.123.21@ict.edu.rs
or petar@gmail.com<br>");
        if(!preg match($regPass,$password)){
            array_push($greske,"Password must be at least 8 characters
long<br>");
        if($passwordConf!=$password){
           array_push($greske, "Passwords do not match<br>");
        $mailProvera="SELECT email FROM users WHERE email=:mail";
        $priprema=$connection->prepare($mailProvera);
        $priprema->bindParam(":mail",$email);
        try{
            $priprema->execute();
            $rez=$priprema->fetch();
            if($priprema->rowCount()==1){
                $data="There is already a user with that email address";
                $code=200;
            else{
                if(count($greske)==0){
                    $insert="INSERT INTO users
VALUES(NULL,:ime,:prezime,:mail,:pass,:aktivan,:aktivacionikod,:regDate,:iduloge)
                    $password=md5($password);
                    $uloga=2;
                    $aktivan=1;
                    $kod=md5(time().md5($email));
                    //mail($mail, "Account
activation","http://127.0.0.1/pozoriste/activation.php?code=".$kod);
                    $date=date("Y-m-d H:i:s");
```

```
$priprema2=$connection->prepare($insert);
                    $priprema2->bindParam(":ime",$firstName);
                    $priprema2->bindParam(":prezime",$lastName);
                    $priprema2->bindParam(":mail",$email);
                    $priprema2->bindParam(":pass",$password);
                    $priprema2->bindParam(":aktivan",$aktivan);
                    $priprema2->bindParam(":aktivacionikod",$kod);
                    $priprema2->bindParam(":regDate",$date);
                    $priprema2->bindParam(":iduloge",$uloga);
                    try{
                        $uspesno=$priprema2->execute();
                        $code=201;
                        $data="You have successfully registered, check your email
to activate your account";
                    catch(PDOException $e){
                        $code=500;
                        $data="Server error";
                }
                else{
                    $data=$greske;
                    $code=422;
        catch(PDOException $e){
            $data= "Server error";
            $code=500;
    else{
        $code=404;
        $data="Error";
echo json_encode($data);
http response code($code);
```

repertoire.php

```
<?php
    require_once "connection.php";</pre>
```

```
$query="SELECT *,r.id FROM repertoire r INNER JOIN prices p
ON r.idPrice=p.id INNER JOIN performances pe
ON p.idPerformance=pe.id
WHERE MONTH(datePerforming)=MONTH(CURRENT_DATE) AND
datePerforming>=CURRENT_DATE
ORDER BY datePerforming";

$code=200;
try{
    $repertoire=$connection->query($query)->fetchAll();
}
catch(Exception $e){
    $code=500;
    // $message="Server error";
    $message=$e->getMessage();
}
}
```

repertoireAdmin.php

```
<?php
    require_once "connection.php";
    if(isset($ GET['btn'])){
        $query="SELECT *,r.id FROM repertoire r INNER JOIN prices p
        ON r.idPrice=p.id INNER JOIN performances pe
        ON p.idPerformance=pe.id
        WHERE datePerforming>=CURRENT_DATE
        ORDER BY datePerforming";
        $code=200;
        try{
            $data=$connection->query($query)->fetchAll();
        catch(Exception $e){
            $code=500;
            $data="Server error";
            // $data=$e->getMessage();
    else{
        $code=404;
```

```
$data="Not found";
}
echo json_encode($data);
http_response_code($code);
?>
```

seats.php

```
<?php
    require_once "connection.php";
    if(isset($_GET['id'])){
        $id=$_GET['id'];
        $query="SELECT * FROM tickets WHERE idRepertoire=:id";
        $query2="SELECT * FROM performances p INNER JOIN prices pr
                ON p.id=pr.idPerformance INNER JOIN repertoire re
                ON re.idPrice=pr.id WHERE re.id=:id
                AND datePerforming>=CURRENT DATE";
        $prepare=$connection->prepare($query);
        $prepare2=$connection->prepare($query2);
        $prepare->bindParam(":id",$id);
        $prepare2->bindParam(":id",$id);
        $code=200;
        try{
            // $performances=$connection->query($query)->fetchAll();
            $prepare->execute();
            $prepare2->execute();
            if($prepare2->rowCount()==0){
                $data="No access";
                $code=404;
            else{
                $code=200;
                $data=$prepare->fetchAll();
                $performance=$prepare2->fetch();
```

```
}
catch(Exception $e){
    $code=500;
    $message="Server error";
}
}
else{
    $code=404;
    $message="Page not found";
}
```

vote.php

```
<?php
session start();
require_once "connection.php";
    $code = 200;
    $id = $ POST['id'];
    $user = $ SESSION['user'];
    $idUser = $user['id'];
    $upit = "INSERT INTO useranswers VALUES (null,:id,:idUser)";
    $priprema = $connection->prepare($upit);
    $priprema->bindParam(":id", $id);
    $priprema->bindParam(":idUser", $idUser);
    try
        $priprema->execute();
        $code = 201;
        $data = "Successfully voted!";
    catch(PDOException $e)
        $code = 500;
        $data = $e->getMessage();
http_response_code($code);
echo json_encode($data);
```

Main.js

```
var url=location.href;
if(url.indexOf("seats.php")!=-1){
    $("#buy").click(buyTickets)
    $("#checkSeats").click(checkSeats)
    $(".places").click(markPlace)
if(url.indexOf("performances.php")!=-1){
    getPerformances()
    $("#search").keyup(getPerformances)
if(url.indexOf("login.php")!=-1){
    $("#logBtn").click(showRegDiv)
    $("#regBtn").click(showLogDiv)
    $(".divLogReg p").hide()
if(url.indexOf("tickets.php")!=-1){
    getTickets()
if(url.indexOf("contact.php")!=-1){
    $(".messageDiv p").hide()
    $("#vote").click(vote)
if(url.indexOf("admin/index.php")!=-1){
    $("#performances").click(adminPerformances)
    $("#addPerformance").click(addPerformance)
    $("#repertoire").click(adminRepertoire)
    $("#addRepertoire").click(addRepertoire)
    $("#users").click(getUsers)
    $("#messages").click(getMessages)
    $("#poll").click(getPoll)
function getPoll(e){
    e.preventDefault()
    getPollRes()
function adminPerformances(e){
    e.preventDefault()
```

```
getPerformancesAdmin()
function adminRepertoire(e){
    e.preventDefault()
    getRepertoire()
function showRegDiv(e){
    e.preventDefault()
    $("#logDiv").removeClass("d-none")
    $("#regDiv").addClass("d-none")
function showLogDiv(e){
    e.preventDefault()
    $("#logDiv").addClass("d-none")
    $("#regDiv").removeClass("d-none")
let errors=[]
function validate(input, regex){
    let br=0
    if(!regex.test(input.val())){
        input.addClass("border-danger")
        input.removeClass("border-success")
        input.parent().find("p").show()
        br++
    else{
        input.removeClass("border-danger")
        input.addClass("border-success")
        input.parent().find("p").hide()
    return br
function login(){
    var email=$("#email")
    var password=$("#password")
    var regEmail=/^w[.\d\w]^*\@[a-z]{2,10}(\.[a-z]{2,3})+$/;
    var regPass=/^.{8,50}$/;
    var error=0
```

```
error=validate(email,regEmail)
    error=validate(password, regPass)
    if(error==0){
        $.ajax({
            url:'models/login.php',
            method:"POST",
            dataType:"json",
            data:{
                "email":email.val(),
                "password":password.val(),
                "btnLogin":true
            },
            success:function(data){
                if(data=="ok"){
                    window.location.href="index.php"
                else{
                    $("#messageLogin").html(data)
            },
            error:function(xhr){
                var error=JSON.parse(xhr.responseText)
                let print=''
                for(let e of error){
                    print+=`${e}`
                $("#messageLogin").html(print)
        })
    return false;
function getPerformances(){
    var search=$("#search").val()
    $.ajax({
        url:'models/performances.php',
        method:"get",
        dataType:"json",
```

```
data:{
            "btn":true,
            "search": search
        },
        success:function(data){
            if(data['performances'].length!=0){
                 printPerformances(data['performances'])
                printPagination(data)
            else{
                $("#performances").html("<h2 class='text-primary'>There is no
matching data</h2>")
        },
        error:function(xhr){
    })
function printPerformances(data){
    let print=''
    for(let d of data){
        print+=`<div class="col-3 performance text-center">
        <a href="performance.php?id=${d.id}">
            <img class="img-fluid" src="assets/images/${d.poster}"</pre>
alt="${d.name}"/>
            <h2 class="green fs-4">${d.name}</h2>
        </a>
    </div>`
    $("#performances").html(print)
function printPagination(data){
    let print='';
    if(data.currentPage!=1){
        print+=`<a href="#" class="page" data-id="${data.currentPage-</pre>
1}">Previous</a>`
    if(data.sumPages!=1){
        for(let i=1;i<=data.sumPages;i++){</pre>
            if(i<=data.sumPages){</pre>
```

```
print+=`<a href="#" class="page links`</pre>
                if(i==data.currentPage){
                    print+=` active`
                print+=`" data-id="${i}">${i}</a>`
    if(data.currentPage!=data.sumPages){
        print+=`<a href="#" class="page" data-</pre>
id="${data.currentPage+1}">Next</a>`
    $("#pagination").html(print)
    $(".page").click(changePage)
function changePage(e){
    e.preventDefault()
    var page=this.dataset.id
    var search=$("#search").val()
    $.ajax({
        url:"models/performances.php",
        method:"get",
        dataType:"json",
        data:{
            "page": page,
            "search": search,
            "btn":true
        },
        success:function(data){
            if(data.performances.length!=0){
                printPerformances(data.performances)
                printPagination(data)
            else{
                $("#performances").html("<h2 class='text-primary'>There is no
matching data</h2>")
        error:function(xhr){
            //err
```

```
function markPlace(e){
    e.preventDefault()
    if($(this).hasClass("addToCart")){
        $(this).removeClass("addToCart")
    else{
        $(this).addClass("addToCart")
function checkSeats(){
    var seats=$(".addToCart")
    $("#buyMessage").html("")
    if(seats.length!=0){
        $("#buy").removeAttr("disabled")
        let print=''
        for(let s of seats){
            if(s.dataset.position==1){
                var position="Parterre left"
            else if(s.dataset.position==2){
               var position="Parterre right"
            else{
                var position="Middle"
            print+=`Row: <b>${s.dataset.row}</b>
                Place: <b>${s.dataset.place}</b>
                Position: ${position}
                <hr>>`
        $("#seatsMessage").html(print)
    else{
        $("#buy").attr("disabled","disabled")
        $("#seatsMessage").html("<h3>You have to choose seats</h3>")
function buyTickets(){
    var seats=$(".addToCart")
    if(seats.length!=0){
        var repertoire=$("#repertoire").val()
        var seatsForSend=[]
        for(let s of seats){
```

```
var obj={
                "idRepertoire":repertoire,
                "row":s.dataset.row,
                "place":s.dataset.place,
                "position":s.dataset.position
            seatsForSend.push(obj)
        $.ajax({
            url:'models/buyTickets.php',
            method:"POST",
            dataType:"json",
            data:{
                "tickets":seatsForSend,
                "btnBuy":true
            },
            success:function(data){
                console.log(seats)
                $("#buyMessage").html(data)
                $("#buy").attr("disabled","disabled")
                for(let s of seats){
                    s.classList.add("purchased")
                    s.classList.remove("addToCart")
            },
            error:function(xhr){
                alert(JSON.parse(xhr.responseText))
        })
    else{
        alert("Choose seats")
function register(){
    var email=$("#emailReg")
    var password=$("#password")
    var firstName=$("#firstName")
    var lastName=$("#lastName")
    var password=$("#pass")
```

```
var passConf=$("#passConfirm")
var regEmail=/^\w[.\d\w]*\@[a-z]{2,10}(\.[a-z]{2,3})+$/;
var regPass=/^.{8,50}$/;
var regName=/^[A-ZZŠĐŽČĆ][a-zzšđžčć]{2,29}$/;
var regPass=/^.{8,50}$/;
var regPass=/^.{8,50}$/;
var error=0
error=validate(email, regEmail)
error=validate(firstName,regName)
error=validate(lastName, regName)
error=validate(password, regPass)
if(password.val()!=passConf.val() || password.val()==""){
    passConf.addClass("border-danger")
    passConf.removeClass("border-success")
    passConf.parent().find("p").show()
else{
    passConf.removeClass("border-danger")
    passConf.addClass("border-success")
    passConf.parent().find("p").hide()
if(error==0){
    $.ajax({
        url:'models/register.php',
        method:"POST",
        dataType:"json",
        data:{
            "firstName":firstName.val(),
            "lastName":lastName.val(),
            "email":email.val(),
            "password":password.val(),
            "passConfirm":passConf.val(),
            "btnRegister":true
        },
        success:function(data){
                $("#messageRegister").html(data)
        },
        error:function(xhr){
            var error=JSON.parse(xhr.responseText)
```

```
let print=''
                  for(let e of error){
                      print+=`${e}`
                $("#messageRegister").html(print)
        })
    return false;
function sendMessage(){
    var email=$("#email")
    var subject=$("#subject")
    var message=$("#message")
    var regEmail=/^w[.\d\w]*\@[a-z]{2,10}(\.[a-z]{2,3})+$/;
    var regSubject=/^[\w\s]+$/;
    var error=0;
    message=message.val().split(" ")
    error+=validate(email, regEmail)
    error+=validate(subject, regSubject)
    if(message.length<10){</pre>
        $("#message").addClass("border-danger")
        $("#message").removeClass("border-success")
        $("#message").parent().find("p").show()
        error++;
    else{
        $("#message").removeClass("border-danger")
        $("#message").addClass("border-success")
        $("#message").parent().find("p").hide()
    if(error==0){
        $.ajax({
            url:'models/message.php',
            method:"POST",
            dataType:"json",
```

```
data:{
                "email":email.val(),
                "message":message,
                "subject":subject.val(),
                "btnMessage":true
            },
            success:function(data){
               $("#alertMessage").html(data)
               $("#alertMessage").show()
            },
            error:function(xhr){
               $("#alertMessage").html(JSON.parse(xhr.responseText))
               $("#alertMessage").show()
       })
    return false;
function getTickets(){
    $.ajax({
        url:'models/getTickets.php',
       method:"POST",
        dataType:"json",
        data:{
            "ticketsBtn":true
        },
        success:function(data){
            printTickets(data)
        },
        error:function(xhr){
            $("#table").html(JSON.parse(xhr.responseText))
    })
function printTickets(data){
    let print=''
    let br=1
    if(data.length!=0){
        print+=`
```

```
No
            Performance
            Date
            Info
            Price
            Cancel
         `
      for(let d of data){
         if(d.position==1){
            d.position="Parterre Left"
         else if(d.position==2){
            d.position="Parterre Rigth"
         else{
            d.position="Middle"
         print+=`
            ${br}
               ${d.name}
               ${d.datePerforming.split("-
')[2]}.${d.datePerforming.split("-")[1]}
               Row: ${d.row} <br> Seat: ${d.place} <br>
${d.price}
               <a class="cancel" href="#" data-</pre>
id="${d.id}"><i class="fa-solid fa-xmark text-danger fs-4"></i>
            print+=``
   else{
      print=`<h2 class="text-center">There are no tickets yet!</h2>`
      $("#table").html(print)
   $("#table").html(print)
   $(".cancel").click(cancelTicket)
```

```
function cancelTicket(e){
    e.preventDefault()
    var id=this.dataset.id
    var row=$(this).parent().parent()
    $.ajax({
        url:'models/cancelTicket.php',
        method:"POST",
        dataType:"json",
        data:{
            "id":id,
            "cancelBtn":true
        },
        success:function(data){
            row.remove()
        },
        error:function(xhr){
            $("#table").html(JSON.parse(xhr.responseText))
        }
    })
function vote(){
    var answer=$(".odg:checked").val()
    if(answer){
        $.ajax({
            url:"models/vote.php",
            method:"post",
            dataType:"json",
            data:{
                "id":answer
            },
            success:function(data){
                $("#obavestenje").html(data)
                $("#vote").attr("disabled","disabled")
            },
            error:function(xhr){
                $("#obavestenje").html(JSON.parse(xhr.responseText))
        })
    else{
        $("#obavestenje").html("You have to choose answer!")
```

```
// ADMIN
function getUsers(e){
   e.preventDefault()
   $.ajax({
      url:'../models/getUsersAdmin.php',
      method:"GET",
      dataType:"json",
      success:function(data){
          printUsersAdmin(data)
      },
      error:function(xhr){
          $("#content").html(JSON.parse(xhr.responseText))
   })
function printUsersAdmin(data){
   var print=''
   print+=`<h1>Users</h1>`
   print+=`
          No
             E-mail
             First Name
             Last Name
             Active
             Registration Date
          `
   let br=1;
   for(let d of data){
      print+=`
                ${br++}
                ${d.email}
                ${d.firstname}
                ${d.lastname}
                `
                if(d.active==1){
                    print+=`Yes`
                else{
                   print+=`No`
```

```
print+=`
            ${d.registrationDate}
            `
      print+=``
   $("#content").html(print)
function getMessages(e){
   e.preventDefault()
   $.ajax({
      url:'../models/getMessagesAdmin.php',
      method:"GET",
      dataType:"json",
      success:function(data){
         printMessagesAdmin(data)
      },
      error:function(xhr){
         $("#content").html(JSON.parse(xhr.responseText))
   })
function printMessagesAdmin(data){
   var print=''
   print+=`<h1>Messages</h1>`
   print+=`
         E-mail
            Title
            Message
            Date
            Delete
         `
   for(let d of data){
      print+=`
               ${d.email}
               ${d.subject}
               ${d.message}
               ${d.sendingDate}
               <a href="#" class="delete" data-
id="${d.id}"><i class="fa-regular fa-xmark"></i></a>
```

```
`
        print+=``
    $("#content").html(print)
    $(".delete").click(deleteMessage)
function deleteMessage(e){
    e.preventDefault()
    var id=this.dataset.id
    var row=$(this).parent().parent()
    $.ajax({
        url:'../models/deleteMessage.php',
        method:"POST",
        dataType:"json",
        data:{
            "id":id
        },
        success:function(data){
            row.remove()
        },
        error:function(xhr){
            $("#content").html(JSON.parse(xhr.responseText))
    })
function getPerformancesAdmin(){
    $.ajax({
        url:'../models/performances.php',
        method:"GET",
        dataType:"json",
        data:{
            "btn":true
        success:function(data){
            printPerformancesAdmin(data)
        },
        error:function(xhr){
            $("#content").html(JSON.parse(xhr.responseText))
    })
```

```
function printPerformancesAdmin(data){
   let print=``
   print+=`
            No
            Name
            Poster
            Premier
            Price
            Update
            Delete
         `
   let br=(data.currentPage-1)*4+1
   for(let d of data.performances){
      print+=`
               $\{\br++}\
               ${d.name}
               <img class="img-fluid" src="../assets/images/${d.poster}"</pre>
alt="${d.name}"/>
               ${d.premier}
               ${d.price}
               <a href="#" class="update" data-
id="${d.id}"><i class="fa-regular fa-pen-to-square"></i>
               <a href="#" class="delete" data-
id="${d.id}"><i class="fa-regular fa-xmark"></i>
            `
   print+=''
   print+=`<div id="pagination" class="text-center">`
   if(data.currentPage!=1){
      print+=`<a href="#" class="page" data-id="${data.currentPage-</pre>
1}">Previous</a>`
   if(data.sumPages!=1){
      for(let i=1;i<=data.sumPages;i++){</pre>
         if(i<=data.sumPages){</pre>
            print+=`<a href="#" class="page links`</pre>
            if(i==data.currentPage){
               print+=` active`
```

```
print+=`" data-id="${i}">${i}</a>`
    if(data.currentPage!=data.sumPages){
        print+=`<a href="#" class="page" data-</pre>
id="${data.currentPage+1}">Next</a>`
    print+=`</div>`
    $("#content").html(print)
    $(".delete").click(deletePerformance)
    $(".update").click(updatePerformance)
    $(".page").click(changePageAdmin)
function updatePerformance(e){
    e.preventDefault()
    var id=this.dataset.id
    $.ajax({
        url:'../models/getEditPerformance.php',
        method:"POST",
        dataType:"json",
        data:{
            "id":id
        },
        success:function(data){
            printFormEditPerformance(data)
        error:function(xhr){
            $("#content").html(JSON.parse(xhr.responseText))
    })
function printFormEditPerformance(data){
    let print=`<h2>Edit Performance</h2>
                <form action="#" enctype="multipart/form-data">
                    <div>
                         <label for="name">Name</label>
```

```
<input type="text" id="name" value="${data['name']}"</pre>
class="form-control">
                    </div>
                    <div class="mt-2">
                         <label for="poster">Poster</label>
                        <input type="file" id="file">
                    </div>
                    <div class="mt-2">
                        <label for="premier">Premier Date</label>
                        <input type="date" id="premier"</pre>
value="${data['premier']}" class="form-control">
                    </div>
                    <div class="mt-2">
                        <label for="duration">Duration</label>
                        <input type="number" id="duration"</pre>
value="${data['duration']}" class="form-control">
                    </div>
                    <div class="mt-2">
                        <label for="description">Description</label>
                        <textarea class="form-control"</pre>
id="description">${data['description']}</textarea>
                    </div>
                    <div class="mt-2">
                        <label for="price">Price</label>
                        <input type="number" class="form-control" id="price"</pre>
value="${data['price']}">
                    </div>
                    <div class="mt-2">
                        <input type="submit" id="update" value="Update</pre>
performance class="form-control">
                    </div>
                    <div class="mt-2">
                        </div>
                    <input type="hidden" value="${data['id']}" id="id">
                </form>`
    $("#content").html(print)
    $("#update").click(doUpdatePerformance)
```

```
function doUpdatePerformance(){
    var name=$("#name").val()
    var file=$("#file")[0].files[0]
    var premier=$("#premier").val()
    var duration=$("#duration").val()
    var description=$("#description").val()
    var price=$("#price").val()
    var id=$("#id").val()
    var podaciZaSlanje = new FormData()
    podaciZaSlanje.append("name", name)
    podaciZaSlanje.append("file",file)
    podaciZaSlanje.append("premier", premier)
    podaciZaSlanje.append("duration", duration)
    podaciZaSlanje.append("description",description)
    podaciZaSlanje.append("price",price)
    podaciZaSlanje.append("id",id)
    $.ajax({
        url:"../models/editPerformance.php",
        method:"post",
        dataType:"json",
        processData:false,
        contentType:false,
        data:podaciZaSlanje,
        success:function(data){
            $("#messageInsert").html(data)
        },
        error:function(xhr){
            $("#messageInsert").html(JSON.parse(xhr.responseText))
    })
    return false
function deletePerformance(e){
    e.preventDefault()
    var id=this.dataset.id
    $.ajax({
        url:'../models/deletePerformance.php',
        method:"POST",
        dataType:"ison",
```

```
data:{
            "id":id
        },
        success:function(data){
            getPerformancesAdmin()
        },
        error:function(xhr){
            $("#content").html(JSON.parse(xhr.responseText))
    })
function changePageAdmin(e){
    e.preventDefault()
    var page=this.dataset.id
    $.ajax({
        url:"../models/performances.php",
        method:"get",
        dataType:"json",
        data:{
            "page": page,
            "btn":true
        },
        success:function(data){
            if(data.performances.length!=0){
                printPerformancesAdmin(data)
            else{
                $("#content").html("<h2 class='text-primary'>There is no matching
data</h2>")
        },
        error:function(xhr){
    })
function addRepertoire(e){
    e.preventDefault()
    $.ajax({
        url:'../models/allPerformances.php',
        method:"GET",
        dataType:"json",
        data:{
            "btn":true
```

```
success:function(data){
            printFormRepertoire(data)
        },
        error:function(xhr){
            $("#content").html(JSON.parse(xhr.responseText))
    })
function printFormRepertoire(data){
    let print=`<h2>Add Repertoire</h2>
    <form action="#">
        <div>
            <label for="performance">Performance</label>
            <select id="idPerformance" class="form-control">
                <option value="0">Choose performance</option>`
            for(let d of data){
               print+=`<option value="${d.id}">${d.name}</option>`
        print+=`</select>
        </div>
        <div class="mt-2">
            <label for="date">Date Performing</label>
            <input type="date" id="date" class="form-control">
        </div>
        <div class="mt-2">
            <input type="submit" id="add" value="Add repertoire" class="form-</pre>
control">
       </div>
        <div class="mt-2">
            </div>
    </form>`
    $("#content").html(print)
    $("#add").click(addOnRepertoire)
function addOnRepertoire(){
    var idPerformance=$("#idPerformance").val()
    var date=$("#date").val()
    $.aiax({
```

```
url:'../models/addRepertoire.php',
        method: "POST",
       dataType:"json",
       data:{
            "btn":true,
           "idPerformance":idPerformance,
           "date":date
       },
       success:function(data){
           $("#messageInsert").html(data)
       },
       error:function(xhr){
           $("#content").html(JSON.parse(xhr.responseText))
   })
    return false
function getRepertoire(){
   $.ajax({
       url:'../models/repertoireAdmin.php',
       method:"GET",
       dataType:"json",
       data:{
           "btn":true
       },
       success:function(data){
           printRepertoire(data)
       },
       error:function(xhr){
           $("#content").html(JSON.parse(xhr.responseText))
    })
function printRepertoire(data){
   let br=1
   let print=''
   if(data.length==0){
       print="<h2>There's nothing on repertoire</h2>"
   else{
        print=`
```

```
No
              Name
              Date Performing
              Delete
          `
       for(let d of data){
          print+=`
                     ${br++}
                     ${d.name}
                     ${d.datePerforming}
                     <a href="#" class="delete" data-
id="${d.id}"><i class="fa-regular fa-xmark"></i></rr>
                 `
       }
   $("#content").html(print)
   $(".delete").click(deleteRepertoire)
function deleteRepertoire(e){
   e.preventDefault()
   var id=this.dataset.id
   $.ajax({
       url:'../models/deleteRepertoire.php',
       method:"POST",
       dataType:"json",
       data:{
          "id":id
       },
       success:function(data){
          getRepertoire()
       },
       error:function(xhr){
          $("#content").html(JSON.parse(xhr.responseText))
   })
function getPollRes(){
   $.ajax({
       url:'../models/pollRez.php',
       method:"POST",
       dataType:"json",
```

```
data:{
            "btn":true
        },
        success:function(data){
            printPoll(data)
        },
        error:function(xhr){
            $("#content").html(JSON.parse(xhr.responseText))
    })
function printPoll(data){
    let print="<div class='text-center'>"
    print+=`<h2 class="my-2">${data['question']}</h2>`
    for(let d of data['voting']){
        print+=`${d.answer}: ${d.answers} answers``
    if(data['active']==1){
        print+=`<a href="#" id="disable" class="text-center">Disable poll</a>`
    else{
        print+=`<a href="#" id="enable" class="text-center">Enable poll</a>`
    print+="</div>"
    $("#content").html(print)
    $("#disable").click(disablePoll)
    $("#enable").click(enablePoll)
function disablePoll(e){
    e.preventDefault()
    $.ajax({
        url:"../models/disablePoll.php",
        method:"post",
        dataType:"json",
        success:function(data){
            getPollRes()
        },
        error:function(xhr){
            console.log(xhr)
    })
function enablePoll(e){
    e.preventDefault()
```

```
$.ajax({
        url:"../models/enablePoll.php",
        method:"post",
        dataType:"json",
        success:function(data){
            getPollRes()
        },
        error:function(xhr){
            console.log(xhr)
    })
function addPerformance(e){
    e.preventDefault()
    let print=`<h2>Add Performance</h2>
                <form action="#" enctype="multipart/form-data">
                         <label for="name">Name</label>
                         <input type="text" id="name" class="form-control">
                    <div class="mt-2">
                         <label for="poster">Poster</label>
                         <input type="file" id="file">
                    </div>
                    <div class="mt-2">
                         <label for="premier">Premier Date</label>
                         <input type="date" id="premier" class="form-control">
                    </div>
                    <div class="mt-2">
                         <label for="duration">Duration</label>
                         <input type="number" id="duration" class="form-control">
                    </div>
                    <div class="mt-2">
                         <label for="description">Description</label>
                         <textarea class="form-control"</pre>
id="description"></textarea>
                    </div>
                    <div class="mt-2">
                         <label for="price">Price</label>
                         <input type="number" class="form-control" id="price">
                    </div>
                    <div class="mt-2">
                         <input type="submit" id="add" value="Add performance"</pre>
class="form-control">
                    </div>
```

```
<div class="mt-2">
                        </div>
                </form>`
    $("#content").html(print)
    $("#add").click(addNewPerformance)
function addNewPerformance(){
    var name=$("#name").val()
    var file=$("#file")[0].files[0]
    var premier=$("#premier").val()
    var duration=$("#duration").val()
    var description=$("#description").val()
    var price=$("#price").val()
    var podaciZaSlanje = new FormData()
    podaciZaSlanje.append("name", name)
    podaciZaSlanje.append("file",file)
    podaciZaSlanje.append("premier",premier)
    podaciZaSlanje.append("duration",duration)
    podaciZaSlanje.append("description",description)
    podaciZaSlanje.append("price",price)
    $.ajax({
        url:"../models/addPerformance.php",
        method:"post",
        dataType:"json",
        processData:false,
        contentType:false,
        data:podaciZaSlanje,
        success:function(data){
            $("#messageInsert").html(data)
        },
        error:function(xhr){
            $("#messageInsert").html(JSON.parse(xhr.responseText))
    })
```

```
return false
}
```

Style.css

```
margin: 0px;
    padding: 0px;
    box-sizing: border-box;
body{
    font-family: 'Anek Latin', sans-serif;
a{
    text-decoration: none;
a:hover{
    color: unset;
.nav-item a{
    color: green;
img{
    width: 100%;
#pagination ul li{
    list-style-type: none;
    margin: 0px 5px;
#pagination ul li a{
    text-decoration: none;
.places{
    padding: 5px 10px;
    background-color: greenyellow;
    position: relative;
.places{
    color: aliceblue;
.purchased{
    color: rgb(156, 156, 156);
    pointer-events: none;
.purchased{
```

```
background-color: gray;
.popup{
   visibility: hidden;
   position: absolute;
   z-index: 99;
   width: 130px;
   background-color: rgb(255, 237, 103);
   padding: 5px;
   margin-left: 5px;
.places:hover .popup{
   visibility: visible;
.red{
   width: 100px;
   text-align: center;
.redDrzac{
   width: 100%;
   display: flex;
   justify-content: space-between;
   margin: 15px 0px;
.addToCart{
   background-color: green;
.parter{
   display: flex;
   justify-content: space-between;
.scena{
   padding: 50px;
   text-align: center;
   background-color: grey;
.kupi{
   background-color: green;
.font-weight-bold{
   font-weight: bold;
.boja{
   padding: 0px 10px;
   margin-right: 10px;
```

```
.dostupna{
    background-color: greenyellow;
.izabrana{
    background-color: green;
.nedostupna{
    background-color: gray;
main{
    margin-top: 80px;
    margin-bottom: 10px;
.repertoire{
    border-top: 2px solid black;
.buy{
    background-color: rgb(20, 106, 20);
.next{
    display: flex;
    flex-direction: column;
    justify-content: space-between;
#pagination a{
    font-size: 20px;
    margin: 0px 5px;
    color: green;
#pagination .active{
    color: greenyellow;
input[type=submit]{
    background-color: greenyellow;
.green,footer a{
    color: green;
.divLogReg{
    min-height: 450px;
.sidebar .nav-item .nav-link i{
    font-size: 20px!important;
```

```
.sidebar .nav-item .nav-link{
    font-size: 25px;
}
#logo img{
    width: 45px;
}
.mainAdmin{
    min-height: 480px;
}
#pagination a{
    text-decoration: none;
}
.btn{
    border-radius: 0px;
}
.btnBuy{
    background-color: green;
    color: white;
}
.modal .btn:hover{
    color: white;
}
```