UPGRAD GSP 3.0

Design system

The specification for developers: foundations, layout, page patterns, components, writing, every role's pages, and accessibility.

Version of 5 November 2026 · from `designs/agency/DESIGN-SYSTEM.md`

GSP 3.0 design system: the specification for developers

This is the reference to build GSP 3.0 from. It covers, for every role and page of the prototype in `designs/agency/`:

- the foundations: type, colour, spacing, radius, sizes, elevation, motion and icons;
- the layout and grid;
- the page patterns;
- every shared component;
- the writing rules and accessibility.

Every value here is read from the code (5 Nov 2026). Where the code and this page disagree, **the code wins**; please report it so this page can be fixed. Section 12 lists the known gaps, each with its fix.

How to use this page

- **Building a screen:** start from its role and page in section 8, follow the page pattern in section 4, then take each component's specs from section 5.
- **Looking up a value:** foundations are in section 2. Each colour table lists both light and dark values.
- **Each rule is written once.** Where a rule matters in more than one place, the other places point to it ("section 5.10").

Keeping this page current

- **This file is the master copy.** The PDF (`docs/GSP-Design-System.pdf`) is made from it.
- **Change it in the same commit** whenever a token, a component or a design rule changes. That applies to designers, developers and Claude sessions alike.
- **Regenerate the PDF** after changing this file:
  1. once only: `pip install markdown` (Playwright's Chromium must also be installed, as for the browser tests);
  2. then, in `designs/agency`: `npm run build:design-pdf`.
- **Fixed gaps:** when a gap in section 12 is fixed, remove it and update the section it belongs to.
- **The Figma library** (GSP Designs) is built from the same code: the Color (Light and Dark) and Dimension variables, whose code syntax is the CSS variable; the text and effect styles; the 67 icons; the components with their variants; every role's sidebar, notifications and announcements (Navigation); expandable pop-ups and confirmations (Overlays and Feedback); a Validation and Errors page (field states, messages, sign-in errors, banners, empty states); and an Inbox page (mail tags, the link or forward nudge). When a token, component, state or role changes here, change it there in the same task.

Where	What
`src/styles/tokens.css`	Every design token, light and dark. **Use tokens, never raw values.**
`src/styles/base.css`	Reset, body type, focus ring, `.num`, `.vh`, the owner chip `.who`
`src/components/`	Shared components (section 5)
`src/shell/`	The app frame (`AppShell`) and the sign-in scene (`AuthScene`)
`README.md`	Every screen, state and control, page by page
`REVIEW.md`	Every agreed change, by page; open questions
`PLAN.md`	The numbered design decisions

Open the prototype with `npm run build:artifact` and then open `dist-artifact/gsp-partner-portal.html`. Pick the role with **Role** at the bottom right. **Prototype** switches light and dark mode and the 390 px phone frame.

Contents

1. Principles
2. Foundations: type, colour, spacing, radius, sizes, elevation, layers, motion, icons, glass
3. Layout and grid
4. Page anatomy
5. Components
6. Patterns: who has it, status, SLA, tiles, filters, tables, settings, confirmations, logs, mail threads
7. Writing
8. Roles and pages
9. Accessibility
10. Light and dark
11. Prototype-only: don't build
12. Known gaps to resolve

1. Principles

These come from the brief and the review meetings. Every screen follows them.

1. **Every screen says what to do now.** The summary and the next action come first; detail is one click away.
2. **Show who has it, in colour and words:**
   - amber is the agency (RP);
   - violet is GSP;
   - blue is the university.

   Colour never stands alone.
3. **The frame never changes with the state.** Tabs and sections stay in place; empty ones say so.
4. **People act, and the system moves the status.** There are no tickets to create.
5. **Warn, don't block.** Only hard rules stop an action, and every warning explains itself.
6. **Every automatic step is visible** in Logs, with who or what did it.
7. **Minimal for agencies.** No internal statuses or jargon.
8. **One component everywhere.** The same dropdown, pop-up, confirmation and table in every role (Decision 34).
9. **No tabs inside tabs** (a Decision). Record pages have **one** row of tabs.
10. **Every remove, delete, deactivate or unlink asks first.**

2. Foundations

2.1 Typeface

- **Family:** `--font-sans: "CircularXX TT", "Figtree", "Noto Sans", system-ui, -apple-system, "Segoe UI", Roboto, sans-serif`.
  - **Production uses CircularXX TT**, which is licensed; add its `@font-face` files.
  - The prototype has no CircularXX files, so it shows **Figtree**, loaded from Google Fonts at weights 400, 500, 600 and 800, as a stand-in at the same sizes.
- **Tracking:** `--tracking: -0.01em` on the body and headings. Page titles tighten to `-0.022em`.

- **Weights:**
  - `--fw-book` 400: body text;
  - `--fw-medium` 500: labels, buttons, headings h1 to h4 by default;
  - `--fw-semi` 600: titles, emphasis, counts.

  Weight 800 is loaded but not used in the UI.
- **Numbers:** add class `.num` (`font-variant-numeric: tabular-nums`) to every number in tables, counts, dates and money, so the digits line up.
- **Body defaults** (`base.css`): `--t-body` on `--lh-body` , colour `--text-2` , antialiased, `text-rendering: optimizeLegibility` .
  - Headings use `text-wrap: balance` ; paragraphs use `text-wrap: pretty` .

2.2 Type scale

Token	Size / line height	px	Use
`--t-display` / `--lh-display`	2rem / 2.5rem	32 / 40	Page title (h1). Drops to 1.625rem / 2rem (26 / 32) at a container width of 600 px or less
`--t-title` / `--lh-title`	1.25rem / 1.75rem	20 / 28	Pop-up title, card title
`--t-subtitle` / `--lh-subtitle`	1.0625rem / 1.5rem	17 / 24	Section and panel titles (h2), the one-line lead under the page title (line height 1.625rem), confirmation title
`--t-body` / `--lh-body`	0.9375rem / 1.375rem	15 / 22	Body, buttons, nav items, switch and checkbox labels
`--t-input` / `--lh-input`	1rem / 1.5rem	16 / 24	Text in inputs and dropdowns. **Keep it at 16 px so phones don't zoom.**
`--t-label` / `--lh-label`	0.875rem / 1.25rem	14 / 20	Field labels, table cells, small buttons, chips, menus, facts
`--t-caption` / `--lh-caption`	0.8125rem / 1.125rem	13 / 18	Hints, table headers, secondary lines in cells (`.cfg__sub`), notes
`--t-micro` / `--lh-micro`	0.75rem / 1rem	12 / 16	Owner chips, document pills, group headers in lists (uppercase, `0.04em`)

Other sizes in use:

- the record-page title is 1.625rem / 2.125rem (26 / 34), with `-0.015em` tracking, dropping to 1.375rem at 640 px or less;
- the numbers on tiles are 2rem / 2.25rem semibold with `-0.02em` tracking;
- the phone tab-bar labels are 0.6875rem / 0.875rem (11 / 14).

2.3 Colour: neutrals and brand

Each token has a light and a dark value; the app switches them by theme (section 10). Always use the token, never the hex code.

Token	Light	Dark	Use
`--bg`	`#F5F6F8`	`#0B0F17`	Page background
`--surface`	`#FFFFFF`	`#121823`	Cards, pop-ups, inputs
`--surface-2`	`#F0F2F5`	`#171F2C`	Sunk areas: table headers, pop-up footers, hovered rows, chip counts
`--surface-3`	`#E8EBF0`	`#1E2836`	Disabled primary buttons, pressed states

Token	Light	Dark	Use
`--line`	`#E4E7EC`	`#232D3C`	Card borders, row dividers
`--line-strong`	`#CDD2DA`	`#364256`	Secondary-button and chip borders, decorative edges
`--line-input`	`#8A93A2`	`#5F6B80`	**Form control borders** (3.1:1 on white, WCAG 1.4.11)
`--text`	`#0B0F19`	`#F1F4F8`	Headings, values, strong text
`--text-2`	`#344054`	`#C9D0DA`	Body text, labels
`--text-3`	`#5D6676`	`#9AA4B4`	Meta text, hints, table headers (5.9:1 on white)
`--text-3-glass`	`#485061`	`#B4BDCA`	Meta text on glass (keeps 4.5:1 over the darkest glass)
`--placeholder`	`#6A7383`	`#7F899A`	Input placeholders, empty dropdowns
`--primary`	`#0E2C4C`	`#DCE8F7`	**Main buttons**, checked boxes, the current page in the pager. Navy, from the GSP logo blue. **In dark mode it turns light blue, so primary buttons invert**
`--primary-hover`	`#173F68`	`#FFFFFF`	Primary hover
`--primary-press`	`#0A2038`	`#C2D5EE`	Primary pressed
`--on-primary`	`#FFFFFF`	`#0B1F38`	Text on primary
`--primary-soft`	`#E8EFF7`	`#16263C`	Avatars, removable chips, ticked rows, inline actions
`--link`	`#1A4F86`	`#8EC0F2`	Links, link buttons, the active nav icon
`--focus`	`#2B7AB3`	`#6CA8E0`	Focus ring and focused input border
`--brand-red`	`#EE2C3C`	`#FF4A5A`	upGrad red: **the logo only** (and brand phrases)
`--brand-red-text`	`#BE2330`	`#FF7A86`	Red text at small sizes, such as the required `*`
`--logo-red`	`#FF0031`	`#FF2D4F`	From the official logo file
`--gsp-1…4`	`#AC225E` `#5E2D77` `#2B7AB3` `#04A5CB`	`#E0508C` `#A274E0` `#4FA3E0` `#36C9E6`	The GSP logo gradient. **Logo only:** keep it away from the owner chips
`--switch-on`	`#0E2C4C`	`#4F8FD6`	A switch that's on
`--switch-off`	`#E3E7ED`	`#263042`	A switch that's off (with `--switch-off-line` `#8A93A2` / `#5F6B80`)
`--scrim`	`rgba(11,15,25,.48)`	`rgba(3,6,12,.66)`	Behind pop-ups

2.4 Colour: who has it (owner colours)

The brief's rule: **amber is the agency, violet is GSP, blue is the university.** Always pair the colour with words ("With you", "With GSP", "With the university"). Each owner colour has four tokens.

Owner	Theme	Text `--x`	Background `--x-bg`	Line `--x-line`	Dot `--x-dot`
Agency / RP (`you`)	Light	`#8F4E00`	`#FFF1DB`	`#F2C27E`	`#E08A00`
	Dark	`#F6B95C`	`rgba(224,138,0,.16)`	`rgba(246,185,92,.36)`	`#F2A23A`
GSP (`gsp`)	Light	`#5B33A6`	`#F1EBFC`	`#D5C4F5`	`#7C4DDB`
	Dark	`#C2A6F6`	`rgba(124,77,219,.2)`	`rgba(194,166,246,.34)`	`#A27CEE`

Owner	Theme	Text `--x`	Background `--x-bg`	Line `--x-line`	Dot `--x-dot`
University (`uni`)	Light	`#1A55AE`	`#E5EFFC`	`#BCD3F5`	`#2F74E0`
	Dark	`#8DBBF7`	`rgba(47,116,224,.2)`	`rgba(141,187,247,.34)`	`#5A97EE`

How the four tokens are used:

- text sits on the `-bg` ;
- the dot uses `-dot` ;
- borders and selected tiles use `-line` .

Do not use amber or violet for anything else, such as warnings, decoration or AI. That's why "Due soon" pills are grey with a red dot.

2.5 Colour: status

Status	Theme	Text	Background	Line	Dot
Done, OK, verified, on track (`ok`)	Light	`#17703F`	`#E3F4EA`	`#A9DABD`	`#2E9E5B`
	Dark	`#74D7A0`	`rgba(46,158,91,.18)`	`rgba(116,215,160,.34)`	`#4CC183`
Problem, breached, error, danger (`bad`)	Light	`#B4231B`	`#FDECEA`	`#F4B8B2`	`#E5483B`
	Dark	`#FF968C`	`rgba(229,72,59,.18)`	`rgba(255,150,140,.36)`	`#F26B5F`
Neutral, ended, paused, completed (`neutral`)	Light	`#5D6676`	`#EEF0F3`		`--line-strong`
	Dark	`#A9B2C1`	`rgba(154,164,180,.14)`		`--line-strong`

Red is for errors, breaches and destructive actions. Green is for done, and for the "Mark as completed" action.

2.6 Colour: AI (GSP Assist)

AI has its own look, so it never reads as the brand navy or an owner colour. Always label it with text.

- **Gradient:** `--ai-grad` is `linear-gradient(120deg, s1, s2 38%, s3 72%, s4)` (magenta, plum, blue, cyan).

Token	Light	Dark
`--ai-s1` … `--ai-s4` (gradient stops)	`#C2246B` `#7A2E91` `#2F6FD0` `#0AA6C9`	`#F05A9B` `#B07CF0` `#5AA2F5` `#3FD3EC`
`--ai` (small text)	`#7E2470`	`#F0A6DB`
`--ai-bg`	`#F8EEF6`	`rgba(194,36,107,.16)`
`--ai-line`	`#E6C6E0`	`rgba(240,166,219,.3)`

- **Gradient text:** `--ai-grad-text` .
- **Surfaces:** a pastel aurora (`--aur-*` , `--ai-base`) under light liquid glass (`--ai-glass*`).
- **The chat frame:** `--chat-bg` , `--chat-bezel` , `--chat-rim` , `--chat-glass` .
- **Working state:** show one for anything slower than about 400 ms ("Reading agreement…").

2.7 Spacing

The upGrad uG scale. Use only these values: `--sp-2` 2, `--sp-4` 4, `--sp-6` 6, `--sp-8` 8, `--sp-10` 10, `--sp-12` 12, `--sp-16` 16, `--sp-20` 20, `--sp-24` 24, `--sp-32` 32, `--sp-40` 40, `--sp-48` 48, `--sp-64` 64.

`--sp-14` is **not** defined. The code writes `var(--sp-14, 14px)` for table cells and chips. Either add the token or keep the fallback.

Where	Spacing
Label to control, inside a field	6
Between fields in a form	16 vertical, 16 to 20 horizontal
Inside a card or section	20 to 24 (16 on phones)
Between cards and sections on a page	16 to 24 (section 3.5)
Page title to its lead	6
Buttons in a row	8 to 12

2.8 Radius

Token	Value	Use
`--r-ctl`	12 px	Inputs, dropdown fields
`--r-sm`	12 px	Small cards, tiles, dropdown lists, multi-select panels
`--r-card`	16 px	Cards, menus
`--r-lg`	24 px	Pop-ups, confirmations, the sidebar, flyouts
`--r-pill`	999 px	Buttons, chips, pills, tabs, nav items, the tab bar

Smaller fixed radii also appear:

- 10 px on menu items, pager buttons and toast icons;
- 6 px on dropdown options and inline actions;
- 5 px on checkboxes;
- 14 px on toasts and the record-head mark;
- 28 px on the top corners of bottom sheets;
- 32 px on the sign-in panel.

2.9 Sizes

Token	Value	Use
`--h-input`	48 px	Text inputs, dropdowns, multi-selects (44 px inside filter bars and tables)
`--h-btn`	44 px	Buttons
`--h-btn-sm`	36 px	Small buttons
`--sidebar-w`	272 px	The sidebar

Other sizes:

- icon buttons are 32 px, with a 44 px tap target;
- nav items are 42 px;
- chips are 36 px (40 in view switchers, 44 in toolbars);

- tabs are 40 px;
- pager buttons are at least 36 px;
- checkboxes are 20 px;
- the switch is 38 × 22;
- avatars are 36 px;
- the phone tab bar is 56 px.

2.10 Elevation

Token	Light	Dark	Use
`--shadow-xs`	`0 1px 2px rgba(9,30,66,.06), 0 2px 6px rgba(9,30,66,.04)`	`0 1px 2px rgba(0,0,0,.4)`	Cards, tiles, the theme-toggle thumb
`--shadow-card`	`0 2px 4px rgba(9,30,66,.04), 0 12px 32px rgba(9,30,66,.06)`	`0 1px 2px rgba(0,0,0,.3), 0 12px 32px rgba(0,0,0,.28)`	Selected tiles, raised cards
`--shadow-pop`	`0 18px 48px rgba(9,30,66,.16), 0 2px 8px rgba(9,30,66,.06)`	`0 18px 48px rgba(0,0,0,.5), 0 2px 8px rgba(0,0,0,.3)`	Pop-ups, menus, dropdown lists, confirmations
`--input-glow`	`0 0 0 4px rgba(43,122,179,.14)`	`0 0 0 4px rgba(108,168,224,.2)`	Focused input (red version `0 0 0 4px var(--bad-bg)` when invalid)

Light shadows are navy-tinted and soft; dark ones are black and stronger. The primary button's hover adds `0 8px 24px rgba(14,44,76,.18)`.

2.11 Layers (z-index)

Layer	z-index
Shell content	0 to 8
Phone top bar, tab bar	20
Inline combobox lists (country, city, search pick)	30
The overlay layer `#layer` (pop-ups, dropdown lists, menus, flyouts)	60
Confirmation (inside `#layer`, above pop-ups)	2 within the layer
Toast	70
Multi-select panel	80
Skip link	100
Prototype controls (don't build)	200

Pop-ups, dropdown lists, menus and the multi-select panel render into `#layer`, a `position: fixed; inset: 0` element at the end of the app. That way they're never clipped by a card or a scrolling table.

2.12 Motion

From the animation library: fast and calm, transform and opacity only, built with `motion/react`.

- **Tokens:**
  - durations: `--dur-1` 120 ms, `--dur-2` 200 ms, `--dur-3` 320 ms;
  - easing: `--ease-out` `cubic-bezier(.2,.8,.2,1)` is the default; also `--ease-in` `(.4,0,1,1)` and `--ease-in-out` `(.65,0,.35,1)`.
- **Values used in code:**

What moves	Duration	How
Page (route) change	0.28 s	scale 0.995
Section change	0.22 s	y 8 → exit y −4
Pop-up	0.32 s	side panel from x 40; centred from y 12 at scale 0.97; modal from y 18; phone from y 48
Pop-up scrim	0.24 s	fade
Confirmation	0.2 s	scrim 0.18 s
Menus, flyouts	0.18 s	exit 0.12 s
Toast	0.22 s	from x −12 at scale 0.98
Dropdown list	`--dur-2`	from y −4 at scale 0.99
Nav and tab lens	spring	stiffness 520, damping 40 to 42
Switch knob	420 ms	spring `cubic-bezier(.3,1.5,.5,1)`

- **Reduced motion is respected everywhere:**
  - `useReducedMotion()` switches to opacity only, or duration 0;
  - `base.css` cuts every CSS animation and transition to 1 ms under `prefers-reduced-motion`.
- **Peaks** (submitted, offer, enrolled, payout) get one considered moment (`Celebrate`). Everything else stays quiet.

2.13 Icons

- One set, in `components/Icon.tsx` (`<Icon name size />`):
  - 24 px viewBox, 1.6 stroke, round caps, `currentColor` ;
  - 20 px by default (14 to 18 in small buttons, 22 in the tab bar);
  - always `aria-hidden` ; the button or link carries the words.
- **The 67 names:** check, checkCircle, lock, chevronDown, chevronRight, sort, arrowRight, arrowLeft, mail, phone, chat, info, alert, close, search, file, building, user, clock, shield, edit, refresh, sun, moon, monitor, mobile, sliders, upload, globe, wallet, people, home, doc, share, copy, cap, eye, eyeOff, key, partner, logout, capslock, plus, folder, download, minus, trash, image, grip, external, expand, collapse, more, attach, pin, calendar, award, star, briefcase, bell, tag, inbox, archive, reply, forward, send, megaphone.
- **Common uses:**
  - plus: Add or Create;
  - edit: Edit;
  - close: remove or close;
  - more: the ⋯ menu;
  - check: My work, Save Changes;
  - download: CSV;
  - bell: notifications;
  - megaphone: announcements.

2.14 Liquid Glass

Glass is used in the **frame only**:

- sign-in and registration;
- the sidebar;
- the phone top bar and tab bar;
- the bell and megaphone circles;

- the account menu;
- GSP · Admin's flyout.

Content areas stay solid white cards.

- **Spec** (`components/glass.css`):
  - tint `rgba(255,255,255,.78)` with `blur(28px) saturate(1.6) brightness(1.1)` (the sidebar uses `.5` with `blur(24px) saturate(1.8)`);
  - a 1.5 px gradient rim (`GlassRim`);
  - dark tint `rgba(18,24,36,.66)` .
  - `.glass--clear` is for use over photos only.
- **Fallback:** a solid `--surface` with a `--line-strong` ring under `prefers-reduced-transparency` , `prefers-contrast: more` , or when a browser has no `backdrop-filter` .
- Glass overrides `--text-3` with `--text-3-glass` to keep contrast.

---

3. Layout and grid

3.1 The frame (`AppShell`)

Wide (container wider than 900 px):

- **Grid:** `calc(var(--sidebar-w) + var(--sp-12)) minmax(0, 1fr)` , so a 284 px column plus the page.
- **Sidebar:**
  - a glass panel, 272 px wide;
  - sticky at top 12, height `calc(100dvh - 24px)` , margin `12px 0 12px 12px` ;
  - padding `24px 16px 16px` , radius 24.
- **Inside the sidebar, top to bottom:**
  1. the brand lockup (34 px high), with the role's label beside the logo;
  2. a divider;
  3. the nav, with 2 px between items. Each item is 42 px high, with 12 px padding, a pill shape, `--t-body` text and a 20 px icon. The current page sits on a sliding glass "lens", with its icon in `--link` ;
  4. the account menu and the theme toggle at the foot.
- **Top strip:** the bell and megaphone in their own 44 px glass circles at the top right.
  - Padding `16px 40px 8px 32px` , so the strip is 68 px high.
  - **The page scrolls under the strip, not behind it,** fading at its top edge (`mask-image: linear-gradient(to bottom, transparent, #000 16px)`).
- **Page padding** (`.shell__scroll`): top 16, bottom 64, left 32, right 40, with safe-area insets.

Narrow (container 900 px or less; phones and tablets):

- The sidebar and strip are hidden.
- **Top bar:** sticky, glass, about 60 px high, with a 28 px lockup and the bell and megaphone at 36 px.
- **Page padding:** top 20, bottom 24, sides 16.
- **Tab bar:** floating glass at the bottom, 12 px in from the edges, pill-shaped.
  - It always holds **five** tabs, each 56 px high, with a 22 px icon and an 11 px label.
  - Each role's five are listed in section 8.

Responsive rules use container queries (`@container app (max-width: …)`) on `.app` , so the layout follows the app's width rather than the window's. **Keep** `.app { container: app / inline-size }` . In the prototype it lives in `proto/stage.css` ; move it into the product CSS.

3.2 Page widths

Max width	Pages
760 px	RP Admin's simple sections (`.page`)
1160 px	Home, Students, Find courses, the student record (`.home` , `.stu` , `.find` , `.record`)
1240 px	Applications, the application page, and every GSP · Institution, Admin and RP Ops page (`.apps` , `.aapp` , `.ipage`)
None	RP Admin's Profile (`.page--full`), Inbox (`.mbx`)

3.3 Breakpoints

Container breakpoints (the main ones, measured on the app's width):

≤ width	What changes
1420	Students and Applications tables tighten; the application side column narrows to 290 px
1360	Course facts go to 3 columns
1280	The application row's destination becomes a flag only
1180	Application tools go to 3 columns; the application body and header stack
1100	Home grid → 1 column; Find courses filters move into a bottom sheet; the student record goes to 1 column (its side nav becomes horizontal); config grids → 1 column
900	**Phone frame: top bar and tab bar; pop-ups become bottom sheets; the toast moves**
760	Students table → cards; owner tiles → 2 columns; filters → 2 columns; the record header reflows
700	Simple tables become blocks; 2-column forms in tables → 1 column
600	Titles shrink to 26/32; 2-column forms → 1 column; confirmations dock at the bottom with buttons sharing the width; 3-up tiles → 1 column

Viewport (`@media`) breakpoints:

- 480, 560 and 640 px: small components;
- 600 px: Admin's Work forms;
- 900 px: My work tiles → 1 column;
- 1100 px: wide tables get a `min-width` and scroll sideways.

A few `@media` rules follow the window, not the phone frame (section 12).

3.4 Grids

- **Two-column forms:** `repeat(2, minmax(0, 1fr))` , going to one column on phones.

Class	Gap	One column at
`.grid2`	20 / 16	600
`.iform__grid`	16	640
`.wk-form`	16 / 20	600
`.ops-form--2`	16 / 20	

A full-width field spans both columns (`.wk-form__wide` , `grid-column: 1 / -1`).

- **Page with a side column:** Home `1fr 320px` (gap 24); Announcements `1fr 320px`; the student record `276px 1fr` (gap 20).
- **Tiles:**
  - owner tiles: `repeat(4, 1fr)`, gap 12;
  - status tiles: `repeat(auto-fit, minmax(180px, 1fr))`;
  - My work tiles: `repeat(3, 1fr)`, gap 16.
- **Facts (label and value):** `repeat(auto-fill, minmax(min(100%, 240px), 1fr))`, gap 12 / 20.
- **Card lists:** `auto-fill minmax(...)`, from 180 px (types) up to 400 px (files).

3.5 Vertical rhythm

Between	Spacing
Blocks on a list page (`.stu`, `.find`, `.ipage`, `.mbx`)	20
Blocks on a record or settings page (`.irecord`, `.record`, `.cfg`, `.irpanel`)	16
Blocks on an RP section page (`.page`)	24
Home: head to content	32 (24 at 900 or less)
Home: main column	24 (20 at 600 or less)
Home: side column	16
Page head: title to lead	6
Page head: titles to actions	16 / 24

3.6 Card padding

- `.card` itself has no padding. Its parts set it:
  - surface background, 1 px `--line` border, radius 16, `--shadow-xs`.
- **24:** onboarding cards, the agreement card, confirmations, pop-up bodies.
- **20 / 24:** sections (`.irsec`), record heads (`.irhead`), the home summary.
- **20:** settings panels (`.cfg__panel`).
- **16:** small tiles and stats.
- **Phones:** 16 to 20.
- **Tables:**
  - the toolbar is 16 / 20 / 12;
  - cells are 14 / 12, with 20 on the first and last columns;
  - headers are 10 / 12 on `--surface-2`;
  - the pager bar is 12 / 20.

---

4. Page anatomy

4.1 The page head (every page)

`PageHead({ title, lead, children })`, in `institution/records/parts.tsx`:

```
[ h1 Title                          ]          [ Secondary ] [ + Main action ]
[ One-line lead, what the page is for ]
```

- **Title:** `.page__title`, `--t-display`, semibold, `-0.022em`.

- **Lead:** `.stu__lead`, `--t-subtitle`, line height 1.625rem, `--text-2`, at most 60ch. It's **one line**, never a paragraph.
- **Actions:** on the right (`margin-left: auto`), with 8 px between them. **The main action comes last** and is a primary button with an icon, such as "+ Create Queue".
- **Layout:** the head uses flex with `align-items: flex-end`.

4.2 List pages

Example: Recruitment partners, Applications, Students, My work. Top to bottom:

1. The page head.
2. **Tiles** that count and filter: `Tiles` / `.atiles`. They are toggle buttons with `aria-pressed`; clicking the active tile again clears it.
3. **One card** (`.card.stable`, padding 0) holding:
   - **the toolbar** (`.stools`):
     - a search box (`.ssearch`, 200 to 300 px);
     - filters, each a `Filter` / `MultiPick`, 44 px high, 130 to 190 px wide;
     - on the right, "Export as CSV" where the list is exported;
     - a count ("N partners").
   - **the table** (`.itab`, section 5.17);
   - **the pager: 20 rows a page**, "Showing 1–20 of N", the first and last pages, the current page ±1, and the current page in navy.
4. **No results:** `NoMatch`, "No {things} match" with a **Clear filters** button.

4.3 Record pages

Example: a partner, university, course, recruitment partner or Master Partner.

1. A **back link** (`.rback`).
2. The **header card** (`RecordHead`, `.irhead`):
   - a 52 px mark;
   - the name (26 / 34);
   - key facts;
   - the status pill and "Last updated by … on …" on the right.
3. **One row of tabs** (`RecordTabs`, section 5.14). **Never tabs inside tabs.**
4. The tab's **sections** (`Section`, `.card.irsec`), each with an h2 title, a note and an action on the right.
5. Each section reads as **Facts** until **Edit** (section 6.7).
6. **Logs** is the last tab or a fold: a timeline of who did what and when.

4.4 Settings pages (GSP · Admin)

1. The page head, in Title Case.
2. **Panels** (`Panel`, `.card.cfg__panel`): a title (subtitle size, semibold), a note (`--t-label`, `--text-3`), and an action on the right.
3. **The panel is read-only until Edit** (the rule is in section 6.7; the component is `EditActions` in `admin/config/parts.tsx`).
4. Under the panel, **Logs (N)**: a fold with the last 10 changes (section 6.9).

4.5 Pop-ups

Every pop-up is a `Sheet`, almost always centred. Its rules, sizes and behaviour are in **section 5.10**, and confirmations are in **section 5.11**. On a page, a pop-up opens from the button that names it ("Create Queue", "Edit", "Assign").

4.6 Empty states

- **Nothing yet:**
  - a short title ("Nothing assigned to you");
  - a line saying where things come from ("New tasks appear here when a task rule fires.");
  - centred, padded 40 / 20 to 24.
- **No match:** "No {things} match" and **Clear filters** (`NoMatch` , `.snone`).
- **First run** (Applications): a path of owner-coloured stops explaining the stages (`.aempty`).
- **Empty sections stay in place** and say so; never hide them.

---

5. Components

All of these live in `src/components/` unless a path is given. CSS class prefixes follow each name.

5.1 Button: `Button` (`button.css` , `.btn`)

- **Props:** `variant` (`primary` by default, `secondary` , `ghost` , `link`), `size` (`md` , `sm`), `loading` , `block` , `iconLeft` , `iconRight` . The `type` defaults to `button` .
- **Base:**
  - height `--h-btn` 44, padding `0 24px` , radius pill, 1 px transparent border;
  - `--t-body` medium text, 8 px gap to the icon;
  - pressing scales it to 0.98.
- **Small:** 36 high, padding `0 16px` , `--t-label` .
- **Block:** full width.

Variant	Background	Text	Border	Hover	Disabled
primary	`--primary`	`--on-primary`	none	`--primary-hover` + shadow	`--surface-3` / `--text-3`
secondary	`--surface`	`--text`	`--line-strong`	border `--text-3` , bg `--surface-2`	text `--text-3`
ghost	transparent	`--text`	none	bg `--surface-2`	text `--text-3`
link	none, auto height, padding `2px 0`	`--link`	none	underline at `currentColor`	

- **Loading:** the button is disabled with `aria-busy` , and a 16 px spinner (700 ms) replaces the left icon.
- **Rules:**
  - **one primary button per area**;
  - Cancel is always secondary;
  - destructive confirmations say what they do ("Delete Queue"), not "OK".
- **Icon-only button (`.icon-btn`):** 32 × 32, pill, `--text-3` .
  - Hover: `--surface-2` background with `--text` .
  - It has a **44 px tap target** (`::after inset -6px`) and needs an `aria-label` .
- **Row actions in tables:** link buttons (Edit, Reassign, Assign).
  - "Mark as completed" is a link button in **`--ok` green**.
  - When there are two actions, they stack on two lines, aligned right.

5.2 Field: `Field` (`forms.tsx` / `forms.css` , `.field`)

- **Props:** `id` , `label` , `optional` , `required` , `hint` , `error` , `success` .
- **Layout:** a grid with 6 px between the label, the control and the message.
- **Label:** `--t-label` medium, `--text-2` .
  - Required fields add a `*` in `--brand-red-text` , plus a visually hidden "(required)".
- **Hint or message:** `--t-caption` , `--text-3` .
  - An error is `--bad` with the alert icon and `role="alert"` .
  - Success is `--ok` with the checkCircle icon.
- **Ids:** `${id}-hint` and `${id}-error` , wired through `aria-describedby` (the `describedBy()` helper).
- **Errors show after the first submit,** not while the person is typing.

5.3 Text input: `TextInput` (`.control`)

- **Box:** 48 high, `--surface` background, 1 px `--line-input` border, radius 12.
- **Input:** padding `0 16px` , `--t-input` (16 px), `--text` , placeholder in `--placeholder` .
- **Optional parts:** a leading icon (`--text-3`) and trailing items, such as `.inline-action` (36 high, `--primary-soft` , `--link`) or the password toggle.

State	Look
Hover	border `--text-3`
Focus	border `--focus` + `--input-glow`
Invalid	border `--bad-dot` ; when focused, a glow of `--bad-bg`
Valid	border `--ok-dot`
Disabled, read-only	`--surface-2` background; disabled uses a `--line` border and `--text-3` text

- **There's no shared Textarea:** use `.control` with `height: auto` , a `min-height` of 84 px and `resize: vertical` .

5.4 Dropdown: `SelectInput` , `Dropdown` , `SelectMenu` (`SelectMenu.tsx` , `combobox.css` , `.smenu` / `.cbx__*`)

Never use the browser's own select list.

- **API:** `SelectInput` is written like a native select (`<option>` , `<optgroup>` , `value` , `onChange(e)`).
  - It renders a button, plus a hidden native `<select class="dd__native">` that holds the id, the value and the change event.
  - The visible button's id is `#<id>-field` .
- **Field:** like `.control` , 48 high, `--t-input` , a chevron on the right (12 px in), `--placeholder` when empty.
  - When open: a `--focus` border with the glow, and the chevron rotated 180°.
- **List:**
  - a white panel, padding 6, 1 px `--line` border, radius 12, `--shadow-pop` ;
  - at most 300 to 320 px high;
  - as wide as the field, and at least 200 px;
  - it drops from the field, and opens upward when there's under 220 px below.
- **Options:** at least 40 high, padding `0 10px` , radius 6.
  - The highlighted option is `--surface-2` .
  - The picked one is medium weight with a `--link` tick.
  - Group headers are uppercase `--t-micro` in `--text-3` .
- **Keyboard:**

    - ↓, ↑, Enter or Space opens it;
    - arrows move, skipping disabled options;
    - Home and End jump;
    - typing jumps to a match;
    - Enter picks;
    - **Escape closes the list only** (it never closes the pop-up behind it);
    - Tab or a click outside closes it.
- **It renders into `#layer`.**
- **Long lists** use the searchable version: `CountryCombobox`, `CityCombobox`, `SearchPick`.

5.5 Searchable pickers: `CountryCombobox`, `CityCombobox`, `SearchPick` (`.cbx`)

All three are editable comboboxes (ARIA 1.2). Typing filters the list; arrow keys move; Enter or a click picks; **Escape puts back the last pick**.

- **Country:** the main markets first, then every country in groups. It also matches dial codes.
- **City:** lists the country's cities with their state, and picking one fills the state. A city that isn't listed can still be kept ("Use '…'").
- **SearchPick:** a generic `{ value, label, note }` list. Prefix matches come first. It's used for picking a person, for example to assign a task.
- **The list is inline** (absolute, z 30), not in `#layer`. Give the pop-up enough room: an assign pop-up's body has a minimum height of 340 px.

5.6 Multi-select: `MultiPick` (`multipick.css`, `.imp`)

Use it wherever several values can be picked: filters, members, countries.

- **Props:** `id`, `label`, `value[]`, `options[]`, `onChange`, `empty` (what an empty field shows, such as "All queues" or "Anyone"), `search`, `all`.
- **Field:** a `.control`, at least 48 high (44 in filter bars), the value in `--t-label`. It reads "A, B" or "A, B and N more", and shows `empty` in `--placeholder` when nothing is picked.
- **Panel:**
    - fixed position, z 80, at least 260 wide;
    - padding 10, 1 px `--line-strong` border, radius 12;
    - an optional search box (36 high);
    - checkbox rows, each at least 34 high, with a list at most 220 px high;
    - footer links **Clear** and **Done**.
- **Behaviour:** renders into `#layer`. Escape closes it and returns focus. Unticking doesn't ask first.

5.7 Switch: `Switch` (`.switch`)

- A `role="switch"` button.
- The label is on the left (`--t-body`, `--text-2`) and the switch on the right.
- **Track:** 38 × 22, pill-shaped.
    - Off: `--switch-off` with a `--switch-off-line` ring.
    - On: `--switch-on` (navy).
- **Knob:** 18 px, white, sliding 16 px on a 420 ms spring.
- **Tap target:** 44 × 32.
- **Use it for on and off** (a task rule, a setting). It saves straight away and logs the change.

5.8 Checkbox: `Checkbox` (`.check`)

- The native input is visually hidden.

- **Box:** 20 × 20, radius 5, a 1.5 px `--line-input` border.
  - Checked: `--primary` with a `--on-primary` tick.
- **Label:** `--t-body`, `--text-2`, 12 px from the box. An optional hint sits under it in `--t-caption`.
- **In tables** it's the first column (52 px wide), with an empty label and a visually hidden "Tick …".
  - The header checkbox ticks **every open row shown, across pages**.
  - Ticked rows turn `--primary-soft`.

Radio buttons have no shared component yet: use 18 px native inputs with `accent-color: var(--primary)` (`.cfg__radios`).

5.9 Phone number: `PhoneInput` (`phone.css`)

One `.control` holding:

- a dial-code dropdown, with a list at least 300 wide grouped into "Where most partners are" and "All countries";
- a number field (`type="tel"`, digits, spaces and dashes only).

5.10 Pop-up: `Sheet` (`sheet.css`, `.sheet`)

- **Props:**
  - required: `open`, `onClose`, `title`;
  - content slots: `sub`, `lead`, `band`, `nav`, `footer`;
  - layout flags: `center`, `modal`, `wide`, `expandable`, `keepCentre`;
  - `className`.

Variant	Width	Use
`center` (default choice)	`min(720px, 100%)`; forms often set `min(680px, 100%)`	**Almost every pop-up**
`modal`	`min(1040px, 100%)`; scrolls as one, close button pinned	The course dialog, large forms
`expandable`	toggles to fill the window	Add a student, New application
default (side panel)	`min(480px, 100% - 24px)`, 12 px from the edges, radius 24	Find courses filters, document panels
`wide`	640 px side panel	

- **Head:** padding `24px 24px 16px`, bottom border `--line`.
  - Title: `--t-title` semibold.
  - Sub: `--t-label`, `--text-3`.
  - Close icon at the top right.
- **Body:** padding `20px 24px 24px`; it scrolls.
- **Foot:** padding `16px 24px 20px`, `--surface-2` background, top border.
  - Buttons sit at the right with 12 px between them, **Cancel first and the main action last**.
  - A note can fill the left.
- **The rules for every pop-up:**
  - the title is at the top left;
  - a **close icon** sits in the **top-right corner**;
  - the **buttons sit at the bottom right**: Cancel (secondary) first, the main action last;
  - **"* Required"** sits above the form when any field is required;
  - **hints** are one short line under the field;
  - use `center` unless the form is long (`modal`) or needs the whole window (`expandable`). The side panel is only for filters and document panels.
- **Phones** (container 900 px or less; 600 with `keepCentre`): a bottom sheet.

- It's at most 90% high, with radius `28px 28px 0 0` and a 40 × 5 grabber.
- Padding becomes 12 / 16 / 20, with the safe area at the bottom.
- The buttons share the width.

- **Behaviour:**
  - it renders into `#layer`, with `role="dialog"` and `aria-modal`;
  - focus moves to the close button and is trapped;
  - Escape or the scrim closes it, and focus returns to the opener;
  - the shell behind it is `inert`.

5.11 Confirmation: `ConfirmDialog` / `useConfirm()` (`confirm.css`, `.confirm`)

Use it for **every remove, delete, deactivate or unlink of something saved.**

- **How to write it:**
  - the title is the question ("Delete Nepal Admissions?");
  - the body says what happens next ("Its 4 kinds of work go to the Admin queue…");
  - the confirm button uses the action's own words ("Delete Queue"), never "OK".
- **Props:** `open`, `title`, `children` (what happens), `confirm` (the action word), `cancel` ("Cancel", or "Keep" in GSP · Admin), `onConfirm`, `onCancel`.
- **Box:** `min(440px, 100%)`, padding 24, radius 24, `--shadow-pop`.
  - Title: `--t-subtitle` semibold.
  - Text: `--t-label`, `--text-2`.
  - A close icon sits at the top right.
  - Buttons sit at the right: Cancel (secondary), then confirm (primary).
- **Phones** (600 or less): it docks at the bottom, with the buttons in two columns.
- **Behaviour:** `role="alertdialog"`. **Cancel gets focus first.** Escape or the scrim cancels.
- **Doesn't need to ask:** removing a file just picked in a form before it's saved, unticking in a multi-select, unstarring a course, or taking a person out of a list being edited.

5.12 The ⋯ menu: `MoreMenu` (`menu.css`, `.mmore` / `.mmenu`)

- **Props:** `id`, `label` (an accessible name, such as "More for India Admissions"), `items: { id, label, icon, danger, checked, onPick }[]`.
- **Trigger:** a 40 × 40 circle. Variants: a word, a small button, a 44 px tool.
- **Menu:**
  - at least 220 wide, padding 6, radius 16, `--shadow-pop`;
  - items 42 high, radius 10, `--t-label` medium, icons in `--text-3`;
  - a danger item is `--bad`.
- **Behaviour:**
  - it renders into `#layer`, aligned right, and opens above when there's no room below;
  - arrows wrap, and Home and End jump;
  - Escape closes it and returns focus.
- **A menu has no close icon:** a click outside closes it.
- **Order:** Edit first, destructive actions last.

5.13 Chips: `.ichip` (`institution/institution.css`)

A toggle button (`aria-pressed`) for views and filters, such as "Assigned to me 5".

- **Base:** 36 high, padding `0 14px`, pill, 1 px `--line-strong` border, `--surface` background, `--t-label` medium, `--text-2`.

- **Pressed:** inverted, with `--text` background and border and `--surface` text.
- **Count badge:** a 20 px pill in `--surface-2` (`--t-micro`).
- **Height:** 40 in view switchers; 44 in toolbars.
- **Chips are filters, not tabs.**

Removable chip: `.cfg__chip` , 28 high, `--primary-soft` , `--link` , with an × button.

5.14 Tabs: `RecordTabs` + `TabPanel` (`.atabs` / `.itabs`)

- **Track:** a pill-shaped `--surface-2` track, padding 4, 4 px between tabs. It scrolls sideways on phones.
- **Tab:** 40 high, padding `0 16px` , `--t-label` medium.
  - The selected tab sits on a white lens with a soft shadow, sliding on a spring.
  - An optional count (`--text-3`) or badge (a 20 px pill) follows the label.
- **Behaviour:** `role="tablist"` with a roving tabindex. Left and right arrows wrap; Home and End jump.
- **Rules:**
  - **one row per page**;
  - labels follow the role's case (Title Case in GSP · Admin);
  - empty tabs stay and say so.

5.15 Pills and status tags

Class / component	Size	Use
`.who` (`base.css`)	20 high, `--t-micro` medium, 6 px dot	**Who has it:** `--you` , `--gsp` , `--uni` , `--ok` , `--end`
`Pill({ tone })` / `.dpill`	24 high, `--t-micro` medium, 6 px dot	Record and document status. Tones: ok (Live, Verified), gsp (Checking, Setting up), you (Missing, Paused), bad, uni, grey (Ended, Hidden)
`.cfg__state`	26 high, `--t-caption` semibold, 7 px dot	Active or inactive in settings; `.is-on` is green
`.cfg__tag`	22 high, `--t-caption` medium	Labels; `--soft` is navy-soft; `--dl` is violet
SLA pill (`.mw-pill` , `.gw-pill` …)	26 high, `--t-caption` semibold, 7 px dot	On track (green), Due soon (grey with a red dot), Breached (red), Paused and Completed (grey)
`RankTag` / `.arank` (`components/RankTag.tsx` , 6 Nov)	22 high, `--t-caption` medium	An application's rank for its student: **Primary** (`--primary-soft` , `--link` , a 12 px filled star) or **Secondary** (`--surface-2` , `--text-2` , a 1 px `--line` ring). Under the student's name in applications lists (`.arow__rank`) and on the application page (`AppRank` , `.ahead__rank`), where GSP · Admin and GSP · Admissions get a **Mark as Primary** link (`--t-caption` medium, `--link`), asked first
`.astat` + `.smeter`		Application status in tables: the owner word with a dot, the status, and a 9 × 6 segment stage meter

Every pill has a dot **and** a word. Labels (`.cfg__tag` , `.arank`) are a word only.

5.16 Tiles

- **Owner tiles** (`.atiles` / `.atile`): **4 across**, gap 12; 2 across at 760 px or less.
  - Each tile is a button, padding `16px 16px 14px 20px`, 1 px `--line` border, radius 16, `--shadow-xs`.
  - A **4 px coloured bar** runs down the left (`--tone`).
  - The number is 2rem semibold; the label is `--t-label` semibold.
  - Pressed: a `--tone-line` border, a gradient from `--tone-bg`, and `--shadow-card`.
- **Status tiles** (`Tiles` in `institution/records/parts.tsx`, `.itiles`):
  - `auto-fit minmax(180px, 1fr)` ;
  - tones ok, you, gsp, bad, uni, grey;
  - a sub line in `--t-caption` ;
  - clicking the pressed tile again clears it.
- **Count tiles** (My work):
  - 3 across, gap 16 (1 across at 900 px or less);
  - padding `20px 24px` ;
  - the number is `--t-display` semibold, with the label and sub line under it.
  - The number turns `--bad` when there's something breached.

5.17 Tables: `.itab` (+ `.cfg__tab` in GSP · Admin)

- **Table:** full width, collapsed borders, `--t-label`.
- **Header:** padding `10px 12px`, `--surface-2` background, bottom border, `--t-caption` medium, `--text-3`, no wrapping.
- **Cell:** padding `14px 12px`, bottom border `--line`, `--text`, aligned to the top when cells hold two lines.
- **First and last columns** are padded 20.
  - The first column is at least 240 px (180 in settings). **Set `min-width: 0` when the first column is a tick box.**
- **Two lines in a cell:** the main value in `.cfg__strong` / `.gw-strong`, and a sub line in `.cfg__sub` (`--t-caption`, `--text-3`).
- **Clickable rows** (`.irow`): a light hover, and the name underlined on hover.
- **Actions** sit in the last column, aligned right, 1% wide.
- **Wide tables** use `table-layout: fixed` with pixel widths on the side columns, so the main column gets the rest.
  - Under 1,100 px they keep a `min-width` and scroll inside `.stab-wrap` (`overflow-x: auto`).
- **Long words** (emails) wrap: `overflow-wrap: anywhere`.
- **Numbers** use `.num` and don't wrap.
- **Rows:** `.is-off` is grey with a line through the name; `.is-changed` is navy-soft while it's being edited.

5.18 Pager: `Pager` / `usePaged` (`.ipager`, `.cfg__pager`)

- **20 rows a page** (`PER_PAGE = 20`); 40 on logs.
- **Behaviour:**
  - hidden when there's only one page;
  - it goes back to page 1 when a filter changes;
  - it shows the first and last pages, the current page ±1, and "…" gaps.
- **Bar:** space-between, padding `12px 20px`, top border, with "Showing 1–20 of N {things}" in `--t-label`.
- **Buttons:** at least 36 × 36, 1 px `--line` border, radius 10, `--t-label` medium.
  - The current page is `--primary` with `--on-primary` text.
  - Disabled buttons drop to 0.4 opacity.
- There are two copies of the same logic (section 12).

5.19 Cards and sections

Component	Classes	Spec
`.card`		`--surface`, 1 px `--line`, radius 16, `--shadow-xs`, no padding
`Section`	`.card.irsec`	Padding 20 / 24 (16 at 640 or less); h2 at `--t-subtitle` semibold; note at `--t-caption`, max 72ch; action on the right
`Panel` (Admin)	`.card.cfg__panel`	Padding 20, gap 16. `flush` puts a table edge to edge, with the head padded `20px 20px 16px` and a bottom border
`Fold`	`details.card.ifold`	A head at least 60 px high, a 24 px count pill, a rotating chevron
`Facts`	`.ifacts`	Label `--t-caption` `--text-3`; value `--t-label` `--text`. "Not added" shows in grey

5.20 Toast: `Toast` (`toast.css`)

- **Where: the bottom left**, beside the sidebar: fixed, z 70, `left: calc(sidebar + 36px)`, bottom 24, at most 420 wide.
  - On phones: left 16, bottom 150.
- **Card:** padding 12, radius 14, 1 px `--line` border, a soft drop shadow. The icon, the words and × are **centred on one line**, whether the message has one line or two.
  - A 34 px icon tile: grey, green (`ok`) or amber (`star`).
  - The title is `--t-label` semibold; an optional line sits under it in `--t-caption`.
  - An optional link, and a × button.
- **Behaviour:** it goes after 6 seconds. `aria-live="polite"`.
- **Say what happened, in past tense:** "Nepal Admissions deleted."

5.21 Frame components

- **`AppShell`** (`shell/`): section 3.1. Props: `sidebar`, `footer`, `topEnd`, `corner`, `tabbar`, `inert`, `brand`.
- **`AuthScene`:** sign-in and registration.
  - A crossfading photo on the left and a glass panel on the right.
  - Panel width `clamp(420px, 34cqw, 500px)`; registration uses `clamp(500px, 40cqw, 600px)`.
  - Radius 32. The panel padding is `clamp(32px, 3.9cqw, 56px)`, and its top and bottom bars are 52 px.
  - Narrow (900 px or less): the photo becomes a 360 px band on top (196 px for registration) and the panel stacks below.
- **`AccountMenu`:** at the sidebar foot.
  - A 36 px avatar with initials, the name and role.
  - It opens a glass menu upward: "Signed in as", the email, and Sign out.
- **`ThemeToggle`:** a pill-shaped radio group, Light (sun) and Dark (moon), with a sliding thumb. The choice is remembered (`gsp-theme`).
- **The bell and megaphone:** 44 px glass circles with an unread count. Each opens a glass panel that also has a close icon.
- **GSP · Admin's flyout** (`admin/portal/Flyout.tsx`, `.pfly`):
  - choosing a menu group opens a glass menu 10 px to the right of the sidebar, level with the group;
  - at least 260 wide, padding 8, radius 24;
  - items 42 high, radius 12;
  - `role="menu"`; Escape or ← closes it.

5.22 Other shared pieces

- `DocView`: Preview and Download icon buttons (32 px) and a paper preview pop-up.
- `CodeInput`: the email code at registration.
- `PasswordInput`: shows and hides the password, and warns about Caps Lock.

- `RangeSlider`.
- `CounsellorPicker`.
- `ContactCard`.
- `BrandLockup`: the logo plus the role label, 34 px high (28 on phones).
- `Celebrate`: peak moments.
- `ErrorBoundary`.

---

6. Patterns

6.1 Who has it, and the 8 stages

- **The stages:** New → Pre-screening → Application → Offer → Verification → Acceptance → Visa → Enrolment (`STAGES`, `data/applications.ts`).
- **Every status** has one owner (`you`, `gsp` or `uni`, or `done` or `end`) and plain words.
- **In tables:** the owner word with its dot, then the status, then the stage meter (`.astat`, `.smeter`).
- **On the application page:** the header names the next step and who has it. The chat shows the same.
- **Agencies never see internal statuses or staff checks.**

6.2 SLA status (My work, every GSP role)

Status	Pill	Line under it
On track	green	"Due in N working hours" (today) or "Due Fri 6 Nov"
Due soon (within a working day)	grey with a red dot	"Due in N working hours" or "Due today"
Breached	red	"Late by N working days"
Paused (GSP · Admissions)	grey	"Paused while the RP answers: {what was asked}"
Completed	grey	"Done in time", or "Done N late"

- **Times count working time** on the record's calendar (GSP · Admin › Work › Working Days), always in IST.
- **Short forms in tables:** `wh` (working hours), `wd` (working days), `days` (calendar days).
- **Escalated tasks** add "· Escalated to {queue}" under the task.

6.3 Filters

- Every filter is a dropdown, or a **multi-select** where several values fit.
- Filters sit in the toolbar, left to right, after the search.
- The empty value names the whole set: "All queues", "Any SLA status", "Anyone".
- **"Clear filters"** (a link button) appears once any filter is set.
- Ticks and pagers reset when the filters change.

6.4 Bulk actions

- A tick box is the first column, and the header box ticks every open row shown.
- Once anything is ticked, a bar appears above the table: "**N** ticked", then **Assign N** (a small primary button), then **Clear**.
- The bulk pop-up is titled "Assign N tasks" and says "To one person. Only these tasks move."

6.5 Assigning people

- Pick from the people in the task's queue, with a searchable list (`SearchPick`).
- Mark the leader "(leader)" and yourself "(you)".

- The main button reads **Assign** or **Reassign**, and stays off until someone new is picked.

6.6 Forms

- Ask only what's needed now, and prefill what's known.
- Use two columns on wide screens and one on phones. A full-width field spans both columns.
- Validate on submit, show messages under the field, and keep **Save** on while errors show.
- Use **number steppers** (− and +, 168 px wide, 36 px round buttons) for small whole numbers, such as an SLA or escalation days.
- Use time fields for times, in IST.

6.7 Read-only until Edit

- Settings and record sections show **Facts** until **Edit** (secondary, with the edit icon).
- While editing, the panel shows **Cancel** and **Save Changes**, which is off until something changes.
- An edited row is tinted navy-soft.
- Saving logs who changed what, and when.

6.8 Confirmations

Every remove, delete, deactivate or unlink of something saved asks first. How to write and build the confirmation, and what doesn't need one, is in **section 5.11**.

6.9 Logs

- "Change log" and "Activity" are both called **Logs**.
- Every record and setting has one: a timeline of who did what and when, the newest first, with 40 shown before "Show N older" (10 in settings folds).
- Automatic steps name the system as the actor.

6.10 Mail threads (Inbox, every GSP role)

- **In the list:** a thread's row names who wrote, in order ("me" once you've replied), and a count pill after the subject (`.mbx__n-msgs`, 18 px, `--surface-3`).
- **Reading it:**
  - the subject, with an "N messages" tag (`--primary-soft`, `--link`);
  - the actions (Reply, Reply all, Forward, Archive, Mark as unread, Summarise) act on the thread;
  - the earlier messages, **oldest first**, each **folded to one line** in a bordered card (`.mbx__msg`, radius 12): avatar, who, the first words, an attachment icon, when. A click opens it, with a chevron to fold it again;
  - **Expand all** / **Collapse all** (a link button) over the list;
  - the **Latest** message last, always open, with a stronger border and `--shadow-xs`.
- **Replying:** a reply joins the thread as its latest message (a copy goes to Sent). A forward starts a new mail.
- **Quoted text** under a reply isn't shown in the thread; each message shows only its own words.

6.11 Notifications and announcements

- **The bell:** System, Chat and Mail notifications.
- **The megaphone:** universities' announcements (Intakes, Courses, Scholarships, Entry).
- Both sit at the top right on every page, with unread counts and a glass panel.
- A notification about another role's action also shows as a toast.

6.12 Mail categories (Inbox, every GSP role)

- **GSP sorts each mail as it arrives** into one of four categories:
  - **Not linked:** GSP couldn't place it. It waits for someone to link it or forward it;

- **Linked to an application:** matched to one, or linked by hand. The mail shows the application's card;
- **Forwarded:** sent on to another of GSP's inboxes;
- **Others:** miscellaneous, not about an application (training, finance runs, invites, course data).

- **Picking one:** a **Category** dropdown in the toolbar, after the email group: All categories, then the four, each with its count in the current folder, group and search. Neither dropdown shows a label above it; the value says what it is (the label is there for screen readers). The count sits before the arrow, never under it. The list's heading adds the category ("Inbox · All inboxes · Not linked").
- **In the list:** a **Not linked** tag (`--you-bg` , `--you` : it's with you), the application's number on a linked mail, and a forward icon with the inbox on a forwarded one.
- **The nudge** on a Not linked mail, above its text (`.mbx__nudge` , radius 14, `--you-line` border on a `--you-bg` wash):
  - an icon, **Not linked to an application**, and one line on what to do;
  - **Link it to an application:** a dropdown of applications (student · university, the number as its note; students the mail names come first) and **Link** (primary, with the attach icon);
  - an **"or" divider** between the two (a line with "OR" in a small pill, `--you-line`), so it reads as one choice, not two fields to fill;
  - **Forward it to another inbox:** a dropdown of GSP's other inboxes and **Forward** (secondary, with the forward icon);
  - **both buttons are 128 px**, so both dropdowns are the same width. Stacked, with the divider across; side by side, with the divider standing between them, from 900 px; under 480 px each button goes under its dropdown, full width;
  - pressing Link or Forward with nothing chosen shows the field's error ("Choose the application this mail is about.").
- **After linking:** the nudge goes, the application's card shows, and the mail moves to Linked to an application. **After forwarding:** a grey note says where it went and who sent it ("Forwarded to GSP Commission by you, 2:14 pm"); the inbox it went to gets a copy, unread and Not linked, with a note saying where it came from.

---

7. Writing

- **Plain, short words, in UK spelling:** colour, organise, enrolment.
- **Curly apostrophes and quotes in UI copy:** ’ “ ”.
- **Every word on a page comes from a defined data field.** Don't add decorative copy.
- **One-line leads** under page titles. **One-line hints** under fields.
- **Case:**
  - **GSP · Admin's own pages use Title Case** for page titles, the menu, pop-up titles, tabs and every button: "Create Queue", "Save Changes", "Mark as Completed".
  - **Every other role uses sentence case:** "Create queue", "Mark as completed", "My work".
  - Pages GSP · Admin borrows from GSP · Institution keep sentence case.
- **Buttons say what they do:** "Delete Queue", "Send agreement", "Assign 3". Use **Cancel** for leaving a form and **Keep** for declining a delete (GSP · Admin).
- **Words fixed by review:**
  - **"Pending on you"**, not "Pending from you";
  - **"Program Level"** and **"Study Area"**;
  - **"entry requirements"**, never "assessment criteria";
  - **Logs**.
- **Never guess pronouns.** Use the name, or they/them.
- **Dates:** "Fri 6 Nov", "5 Nov 2026". **Times:** "9:30 am IST".

---

8. Roles and pages

Twelve roles share the same tokens, frame and components, plus a reference copy of RP Admin (below). Only the content, the menu and the text case differ. A change for one role never reaches the others unless the change says "every role".

Role (code key)	For	Signed in as	Label by the logo	Folder	Case
RP Admin (`rp-admin`)	The agency's admin	Asha Menon, BrightPath Overseas	Partner Portal	`src/screens`	sentence
RP Admin (Backup - not for Engineering) (`rp-admin-backup` , 6 Nov)	A reference copy of RP Admin as it stood on 6 Nov; **don't build from it**	Asha Menon	Partner Portal	`src/screens` (the same portal)	sentence
GSP Branch Manager (`rp-branch` , 6 Nov)	An agency branch's manager	Meghna Rao (Mumbai branch)	Partner Portal	`src/screens` (RP Admin's portal, `seat`)	sentence
GSP Counsellor (`rp-counsellor` , 6 Nov)	An agency counsellor	Karthik Nair	Partner Portal	`src/screens` (RP Admin's portal, `seat`)	sentence
GSP · Admissions (`gsp-team`)	GSP's admissions officers	Freddy Forrest	GSP Admissions	`src/gsp`	sentence
GSP · Institution (`institution-partner`)	GSP's Institution Team	Raj Shamani	Institution Team	`src/institution`	sentence
GSP · Admin (`gsp-admin`)	GSP's admins	Ishaan Verma	GSP Admin	`src/admin`	**Title Case**
GSP · RP Ops (`rp-ops`)	GSP's team for recruitment partners	Rohan Desai	GSP RP Ops	`src/rpops`	sentence
GSP · Finance (`gsp-finance`)	GSP's Finance team	Rhythm Jain	GSP Finance	`src/finance`	sentence
GSP · Global Ops (`gsp-globalops`)	GSP's Global Ops team	Neha Kulkarni	GSP Global Ops	`src/globalops`	sentence
GSP · Recruitment (`gsp-recruitment`)	GSP's Recruitment team	Aditya Rao	GSP Recruitment	`src/recruitment`	sentence
GSP · Institution Ops (`gsp-instops`)	GSP's Institution Ops team	Riya Sen	GSP Institution Ops	`src/instops`	sentence
GSP · View Only (`gsp-view`)	GSP people who only need to look	Tanvi Kapoor	GSP View Only	`src/institution` (with `viewOnly`)	sentence

8.1 RP Admin (the agency portal)

Menu: Home, Find courses, Applications*, Students*, Earnings*, Profile.

- The starred items are locked until GSP verifies the agency: a lock icon, and a locked page that says when they open.
- **Phone tabs:** Home, Find courses, Applications, Students, Earnings.

Page	Patterns
Sign in, Become a partner, Check your email	`AuthScene` : photo and glass panel; forgotten password; email code (`CodeInput`)

Page	Patterns
Home while registering	Setup steps (`.sstep` / `.scard`), verification track (`.vtrack`), document list (`.ldoc`), partner agreement (`.agr`), the GSP contact
Home once verified	Summary: 4 KPI tiles (`.hkpi`), to-do rows, stage bar
Find courses	One forgiving search (`.fsearch`); sticky filters (a bottom sheet at 1,100 px or less); course cards; compare; shortlist; Student view hides earnings; course dialog (`modal` , `expandable`) with tabs Overview, Costs, Eligibility and documents, University
Applications	Page head; 4 owner tiles; toolbar; application table (`.astat`)
Application	Header (`.ahead`) with stages and next step; tabs Chat, Documents, Logs; side column; GSP Assist
New application	Centred, expandable pop-up with an eligibility check
Students	Page head; empty state; table (cards at 760 px or less)
Student record	Header (`.rhead`); side nav (Personal details, Documents, Applications)
Add a student	Centred, expandable pop-up; passport autofill; duplicate check
Earnings	Locked until the agreement is accepted
Profile	Tabs Business details (Facts), Documents, Branches and team (table + 520 px pop-up), Email preferences

8.1a GSP Branch Manager and GSP Counsellor

The agency's own people (Nesil, 6 Nov, from the access sheet; the two columns are the same): RP Admin's portal with a **seat**.

- **Menu:** Home, Find courses, Applications, Students. No Earnings (commission –), no agency Profile (the initials open the person's account), no My work, Mail or GSP pages.
- **E:** Find courses (**commission –**: no Base commission, commission sort, Compare row or Student view switch), Students (list, record, documents), Applications (list, record, **Chat**, **Documents**). **–:** an application's Mail and Submission (RP Admin has neither) and commission (no Base commission).
- **Whose:** the Branch Manager sees the students (and their applications) whose counsellor is in their branch; the Counsellor, only their own.
- **Code:** `Seat` in `src/screens/portal/Portal.tsx` (`kind` , `member` , `title`); the seats are set in `App.tsx` .

8.2 GSP · Admissions

Menu (6 Nov, Nesil's access sheet): Home, Inbox, **My work**, Find courses, Applications, Students, **Recruitment partners**, **Universities**, **Courses**. No Earnings, no agency Profile (the initials open the officer's account), no Master Partners, Institution partners or Announcements.

- **Phone tabs:** Home, Inbox, Find courses, Applications, Students.

Page	Patterns
Home	Greeting, tiles
Inbox	`MailInbox` (`.mbx`): shared GSP mailboxes, list and reading pane
My work (`src/gsp/work` , prefix `gw-`)	3 count tiles; views Assigned to me, My team, Waiting on others; SLA status and Assigned to filters; tick to assign; Reassign above a green Mark as completed; the record is the application (GSP number, university · region); paused SLAs
Applications, Application	As RP Admin, plus the status pop-up with reasons, document review (accept, or send back with a reason), mail to universities, Submission, census and fees, document requests; tabs Chat, Mail, Documents, Submission, Logs
Find courses, Students	As RP Admin; **no commission** in Find courses (cards, pop-up, Compare, sort, no Student view switch)

Page	Patterns
Recruitment partners (RP Ops' page)	View only: list and record (Overview and Logs); no Documents and agreements, Branches, Team, commission statements email or Master Partner
Universities, **Courses** (GSP · Institution's pages)	View only, every tab (Scholarships, Territory, Submission and contacts; Academic, English); no Update QS ranking

- **Access, by the 6 Nov sheet:** E for My work, Mail, Find courses, Students (list, record, documents) and Applications (list, record, Chat, Mail, Documents, Submission); V for Recruitment partners, Universities and Courses; commission – everywhere (no Base commission on an application). The view-only pages carry the line "View only: Admissions can look at this page, not change it."

8.3 GSP · Institution

Menu: Home, Inbox, **My work**, Students, Applications, Course search, Recruitment partners, **Master Partners** (6 Nov), Institution partners, Universities, Courses, Announcements.

- **Phone tabs:** Home, Applications, Universities, Courses, Institution partners.
- **Access, by the 6 Nov sheet:** E for My work, Course search (commission –), Institution partners (Documents, Commission), Universities (Update QS ranking, Scholarships, Territory, Submission and contacts); V for **Mail**, **Students** (list, record, documents), **Applications** (list, record, Chat, Mail, Submission; Documents and commission –), **Recruitment partners** (RP Ops' page: Documents, Agreement, Branches, Team; commission –), **Master Partners** (Documents and Commission –), **Courses** (Academic, English) and **Announcements**. The view-only pages carry "View only: the Institution Team can look at this page, not change it." GSP · View Only has the same menu, all view only but Course search, without the sheet's hidden items.

Page	Patterns
Home	Work queue: Tiles, Filter, table, Pager
My work (`src/institution/work` , `iw-`)	As Admissions; the Institution queue; the record is the institution partner; Queues filter
Students, Applications	List page with Pager (20 a page)
Recruitment partners	RP Ops' page since 6 Nov, view only: Overview (with Branches and Team), Documents (with agreements), Logs
Master Partners	RP Ops' page, view only: Overview, RPs, Logs
Institution partners	List; record tabs Overview, Universities, Documents, Commission, Contacts
Universities	List + CSV import; record tabs Overview, Campuses, Images, Courses, Scholarships, Territory, Submission, Logs
Courses	List; record tabs Basics, Intakes, Fees, Academic, English, Logs, each read-only until Edit
Announcements	List; form with preview (`.ianbody` , `1fr 320px`), System info and Logs folds

8.4 GSP · Admin

Menu:

- Home, Inbox and **My Work** on their own.
- Then **8 groups**, each opening a flyout:
  - **User Modules:** Course Search, Students, Applications;
  - **Institution:** Recruitment Partners, Institution Partners, Universities, Courses, Announcements;
  - **User Roles:** Create Roles, Sales Regions, Permission Roles, Emails;
  - **Work:** Queues, SLA and Escalation; Task Rules;

- **Recruitment:** BDM Assignment;
- **Course Configuration:** Currency Exchange, Living Costs and Fees, Course Tags, Program Level Configuration, Grade Conversion, English Test Equivalence;
- **Application Configuration:** Application Routing, Document Configuration;
- **Other Configurations:** Logs.

The group holding the current page wears the lens.

- **Phone tabs:** Home, Applications, Universities, Application Routing, Logs.

Page	Patterns
My Work (`src/admin/config/MyWork.tsx`, `mw-`)	Tiles; views Assigned to me, All work, Waiting on others; multi-select Queues, SLA status, Assigned to; tick to assign; Reassign above a green Mark as Completed
User Modules, Institution	GSP · Institution's own pages (sentence case)
Every configuration page (`src/admin/config/*`)	Page head, `Panel`, table, `EditActions` (Edit → Cancel and Save Changes), Logs fold, Pager, confirmations
Sales Regions	Tabs Sales Regions and Nationality Map
Queues, SLA and Escalation	Tabs Queues (3 groups; Create and Edit Queue pop-ups listing members), Kinds of Work (Add and Edit pop-ups with a Due in stepper), Working Days (one full-width card per calendar: days, regions, holidays), Reminders and Escalation (5 steps, read-only until Edit, steppers)
Task Rules	Area chips (filters); a table per area (#, when and task, goes to, starts after, SLA, RP reminded, On switch, Edit); short Edit pop-up with time fields (working hours, working days or calendar days); Requests People Can Raise
Logs	Table with Source, Role and Sales region filters; CSV

8.5 GSP · RP Ops

Menu: Home, Inbox, **My work**, Applications, Students, Course search, Recruitment partners, Master Partners, **Institution partners** (6 Nov).

- **Phone tabs:** Home, Inbox, Applications, Recruitment partners, Master Partners.
- **Access, by the 6 Nov sheet:** E for My work, Course search (commission –), Recruitment partners (record, **Commission**, Documents, Agreement, Branches, Team), Master Partners (Documents, Commission) and **Institution partners** (Documents, Commission); V for **Mail** (the Inbox reads and searches), **Students** (list, record, documents) and **Applications** (list, record, Chat, Documents); – for an application's Mail, Submission and commission, Universities, Courses, Announcements. The view-only pages carry "View only: RP Ops can look at this page, not change it."

Page	Patterns
Home	Queue: Tiles, filters, table
My work (`src/rpops/work`, `rw-`)	As Institution's; the RP Ops queue; the record is RP and its region
Applications, Students, Course search	GSP · Institution's pages
Recruitment partners	Toolbar (`.ops-tools`); record head; tabs Overview, Documents (Verify, or Reject and send back with a note), Agreement (send, then accept or send back the signed copy, with versions), Logs
Master Partners	List; New Master Partner; tabs Overview, RPs (Link an RP), Documents, Commission terms, Logs
Institution partners	GSP · Institution's page, to use (6 Nov)

8.6 GSP · View Only

Menu: GSP · Institution's, as it is: Home, Inbox, My work, Students, Applications, Course search, Recruitment partners, Institution partners, Universities, Courses, Announcements.

- **Everything is view only except Course search.** Pages show what's there; every way to change something is left out: add, edit, delete, status changes, assign, send, upload, link, forward, archive, connect. Looking, searching, filtering, sorting, opening records and tabs, previewing and downloading stay.
- **The view-only line** at the top of every page but Course search: `.iviewonly` (the eye icon, `--surface-2`, caption text), "View only: you can look at everything here. Course search is the one page you can use."
- **What goes, by place:**
  - list pages: Add, Import CSV, Update QS ranking, New announcement;
  - records: status actions (Go live, Pause, Resume, Publish, Hide, Change status), Edit, Edit profile, Add/Remove in each section, the territory, image and submission editors, the partner and counsellor pickers (the counsellor shows as a name);
  - forms that open from a record (an announcement) show locked, without the formatting bar; an empty student section reads instead of opening for editing;
  - applications: Change status, Review, Accept/Reject, Request, Upload, Withdraw, the editable dates; Chat shows its messages with "View only: you can read this chat, not write in it." in place of the message box;
  - My work: no tick column and no actions column;
  - Inbox: read and search only; no New mail, Connect inboxes, Reply, Forward, Archive, Mark as unread or the link-or-forward nudge; a draft opens to read.
- **Course search** works as in GSP · Institution, Apply included; an application started there opens its form, and then reads like the rest.
- **Code:** `ViewOnlyProvider`, `useViewOnly` and `EditOnly` (`src/proto/viewOnly.tsx`). The portal turns it on for every page but Course search; a control that changes something is wrapped in `<EditOnly>` or reads `useViewOnly()`. Every other role is outside the provider, so nothing changes for them.

8.7 GSP · Finance

Menu: Home, Inbox, My work, Students, Applications, Course search, Recruitment partners, **Master Partners**, Institution partners, Universities, Courses. No Announcements. Recruitment partners and Master Partners are RP Ops' pages.

Page	Access
Inbox, My work (`src/finance/work`: the Finance queue's commission claims, invoices, remittances and payouts)	Use
Students	Use; a student's **Documents** view only
Course search	Use, **without commission** (no Base commission on cards, in the pop-up or in Compare, no commission sort, no Student view switch)
Applications	View. The application page has only **Commission** (can be changed) and **Logs**: no Chat, Mail, Documents or Submission, and no document banners
Recruitment partners	View (Overview with branches and team, Documents with the agreements, Logs); a **Commission** tab (can be changed)
Master Partners	View; the **Commission** tab can be changed
Institution partners, Courses	View
Universities	View, without QS ranking, Scholarships, Territory, or Submission and contacts

- **The view-only line** on every page Finance only looks at: "View only, except commission: Inbox, My work, Students and Course search are yours to use."

- **Commission, on an application** (`CommissionTab` , `.acom__*`): Status (Not due, Due, Claimed, Invoiced, Paid, On hold, Not payable, as pills), the amount (from the course's base commission until saved), the invoice number, invoiced and paid dates, a note, who changed it last. **Edit** opens the fields in place; Invoiced and Paid need the invoice number, Paid needs the date; Save writes to Logs.
- **Commission, on a recruitment partner** (`RpCommissionTab`): payouts Paying or **On hold** (with why; held to begin with while no agreement is accepted), the plan (Standard, Tiered, Custom), the partner's share (%), how often it's paid, statements email, tax ID, bank account (last four digits shown). Edit in place; Save writes to Logs.
- **Code:** `AccessProvider` with `hide` and `show` lists, read with `useHides` and `useShows` (`src/proto/viewOnly.tsx`); the Finance portal sets them with `ViewOnlyProvider` per page (`EDIT` in `src/finance/portal/model.ts`), and a Commission tab re-opens editing inside a view-only page with `<ViewOnlyProvider on={false}>` .

8.8 GSP · Global Ops

Menu: GSP · Institution's, with **Master Partners** after Recruitment partners: Home, Inbox, My work, Students, Applications, Course search, Recruitment partners, Master Partners, Institution partners, Universities, Courses, Announcements. Built from Nesil's access sheet (E edit, V view, – not shown):

Page	Access
My work (`src/globalops/work` : the Global Ops queue), Inbox	E
Course search	E; commission –
Students (list, record, documents)	E
Applications (list, record, Chat, Mail, Documents, Submission)	E; commission – (no Base commission in Key details)
Recruitment partners (RP Ops' page)	V; Documents and agreements, Branches, Team, commission – (the record is Overview and Logs)
Master Partners (RP Ops' page)	V; Documents and Commission – (Overview, RPs, Logs)
Institution partners	V, Documents V; Commission –
Universities	List V (no Update QS ranking, no Add a university); record E; Scholarships E; **Territory V**; Submission and contacts E
Courses	List and record V; **Academic E, English E**
Announcements	E

- **The view-only line** on the pages it only looks at: "View only: Global Ops can look at this page, not change it."
- **Code:** `src/globalops` (portal, model, user, My work); `VIEW` lists the view-only pages, `HIDE` and `SHOW` what's left out and what's re-opened for editing (`course.academic` , `course.english`) inside a view-only page; a section that's view only inside an editable record (Territory) sits in `<ViewOnlyProvider on>` .

8.9 GSP · Recruitment

Menu: Home (RP Ops' queue of partners), My work, Students, Applications, Course search, Recruitment partners, Master Partners, Institution partners. From Nesil's access sheet (E edit, V view, – not shown):

Page	Access
My work (`src/recruitment/work` : the Recruitment queue)	E
Mail (Inbox)	– (no Inbox in the menu)
Course search	E; commission –

Page	Access
Students (list, record, documents)	V
Applications	List and record V; **Chat E**; Documents V; **Commission V** (the Commission tab, without Edit); Mail and Submission –
Recruitment partners (RP Ops' page)	List and record E; **Branches E, Team E**; Documents and agreements V; **Commission V**
Master Partners	V, Documents and Commission V
Institution partners	V, Documents and Commission V
Universities, Courses, Announcements	–

- **The view-only line:** "View only: Recruitment can look at this page, not change it" (on Applications: ", except an application's chat").
- **Commission, editable or not:** the Commission tabs are view only unless a role opens them: Finance shows `app.commission`, `rp.commission` and `mp.commission.edit`; Recruitment shows the tabs and keeps them view only (`app.commission.view`, `rp.commission.view`).

8.10 GSP · Institution Ops

Menu: Home, Inbox, My work, Course search, Institution partners, Universities, Courses, Announcements. From Nesil's access sheet (E edit, V view, – not shown):

Page	Access
My work (`src/instops/work`: the Institution Ops queue), Mail	E
Course search	E; commission –; with Students and Applications –, **no student picker, Shortlist or Apply**
Students, Applications, Recruitment partners, Master Partners	–
Institution partners	V (Documents and Commission too)
Universities (Update QS ranking, Scholarships, Territory, Submission and contacts), Courses (Academic, English), Announcements	E

- A link to a page it doesn't have (a notification about an application) opens Home.
- **Code:** `src/instops`; `courses.students` hides Course search's student, shortlist and Apply.

8.11 How roles share code

- GSP · Admin and GSP · RP Ops use GSP · Institution's pages (Students, Applications, Course search, Universities…). GSP · View Only is GSP · Institution's portal with `viewOnly` on. GSP · Finance (`src/finance`) GSP · Global Ops (`src/globalops`), GSP · Recruitment (`src/recruitment`) and GSP · Institution Ops (`src/instops`) use GSP · Institution's and RP Ops' pages with access set per page.
- When a role needs a page to differ, it gets **its own copy** in its folder, and the original stays as it was. Examples: RP Ops' Recruitment partners, and each role's My work.
- **CSS is global, so prefix class names per area:**
  - `i*`: Institution;
  - `g*`: Admissions;
  - `ops-`: RP Ops;
  - `cfg__`, `wk-`, `mw-`, `fx__`, `lc__`, `lg__`: Admin;
  - `gw-`, `iw-`, `rw-`: the My work copies.

9. Accessibility

- **Focus:** `:focus-visible` is a 2 px `--focus` outline, offset 2, radius 6. Inputs show focus with a `--focus` border plus `--input-glow`. **Never remove focus styles.**
- **Skip link** to `#main`. The page's main area is focused on navigation.
- **Visually hidden text:** use `.vh` for labels that are only for screen readers, such as "(required)", "Tick {task}", "Unread:" or "Actions" column headers.
- **Target sizes:**
  - buttons 44 (small 36);
  - inputs 48 (44 in toolbars);
  - icon buttons 32, with a 44 tap area;
  - nav items 42;
  - tab-bar tabs 56;
  - the switch's tap area 44 × 32.
- **Contrast:**
  - text tokens are tuned (`--text-3` is 5.9:1);
  - control borders meet 3:1 (`--line-input`);
  - glass swaps in `--text-3-glass` ;
  - small red text uses `--brand-red-text` .
- **Colour is never the only signal:** every owner and status colour carries a word.
- **ARIA:**

Component	Pattern
Pop-ups	`dialog` + `aria-modal`, focus trap, focus returns to the opener
Confirmations	`alertdialog`, Cancel focused first
Tabs	`tablist`, roving tabindex
Nav	`aria-current="page"`
Chips, tiles	`aria-pressed`
Pager	`nav` + `role="status"`
Toast	`aria-live="polite"`
Dropdowns	ARIA 1.2 combobox / listbox
Menus	`menu` / `menuitem`
Switch	`role="switch"`
Field errors	`role="alert"`, linked by `aria-describedby`

- **Motion:** respects `prefers-reduced-motion` (section 2.12).
- **Glass:** respects `prefers-reduced-transparency` and `prefers-contrast: more` (section 2.14).
- **Phones:** inputs are 16 px so iOS doesn't zoom, and safe-area insets are used in the frame and the bottom sheets.

10. Light and dark

- Every screen works in both. **Light is the default.** There's no "match my device" mode, and the choice is stored in `gsp-theme`.

- Dark values sit under `:root[data-theme="dark"]` in `tokens.css`. **Use tokens, and dark mode follows for free.** Never write a colour in a component.
- **Every dark value is listed beside its light value** in the colour tables: neutrals and brand (2.3), owner colours (2.4), status (2.5), AI (2.6), and shadows (2.10). Glass has its own dark tint (2.14).
- **What changes in dark mode:**
  - the primary colour turns light blue, so **primary buttons invert** (light button, dark text);
  - owner and status backgrounds become translucent tints, and their text gets lighter;
  - shadows turn black and stronger.
- **What stays light in both themes:** document "paper" previews stay white.
- **Check every screen in both themes** before it's done.

---

11. Prototype-only: don't build

- **`src/proto/`**:
  - the **Role** and **Prototype** buttons at the bottom right;
  - review states, the theme and device switches, and reset;
  - **Connect** and **Side by side**;
  - the phone frame (`stage.css`), except the `.app` container rule, which the product needs.
- **Review presets** (`*/presets.ts`) and hash links (`#portal-verified` …) in `App.tsx` ; `data/testing.ts` .
- **The "Prototype: the RP uploads the signed copy" button** in RP Ops' Recruitment partners.
- **Sample data** in `src/data/` and each role's `data/` folders. People's names in GSP · Admin come from the PM's staff list.
- **State:** it's held in memory and resets on reload. Only these are kept in `localStorage` : the role, the theme, Connect, and the registration draft.
- **Watch for leaks into the product:** two prototype styles are used by product screens (section 12, D10).

---

12. Known gaps to resolve

These were found while writing this page. Fix them while building, following this page.

#	What's wrong	The fix
D1	**Two copies of shared helpers:** `Pager` / `usePaged` / `useAsk` are in both `institution/records/parts.tsx` and `admin/config/parts.tsx` ; `MultiPick` is in `components/` and `institution/records/`	Build one of each, in the shared components
D2	**My work is built four times** (`admin/config/MyWork.tsx` , `gsp/work` , `institution/work` , `rpops/work`), and its heads differ from the standard: `-0.01em` tracking with a `--t-body` lead	Build one component, configured per role (its views, queue, record column and text case), using `PageHead` (`-0.022em` , `--t-subtitle` lead)
D3	**`--sp-14`** is used through a fallback but isn't a token	Add `--sp-14: 14px` to `tokens.css`
D4	**Motion durations** in JS are hard-coded (0.18 to 0.32 s, and more), not taken from `--dur-*`	Map them to tokens (section 2.12)
D5	**`--shell-top: 64px`** , but the top strip is 68 px	Set it to 68 px
D6	**Some `@media` rules** follow the window, not the app container	Move them to `@container app`
D7	**`rpops/records/Confirm.tsx`** is a separate confirmation, without the close icon	Use `ConfirmDialog`
D8	**No shared Textarea or Radio** component	Add both, matching `TextInput` and `Checkbox`

#	What's wrong	The fix
D9	**Stacked pop-ups** share the id `sheet-title`	Give each pop-up a unique id
D10	**Prototype styles leak:** `.proto__close` is used by the product chat; the phone toast sits at `bottom: 150px` to clear the prototype buttons	Give the chat a product class; lower the toast (section 11)
D11	**Stale comments:** `tokens.css` and `applications.css` call the AI colour "teal"	Correct them: it's the magenta-to-cyan gradient

Last updated 5 Nov 2026. Keep this page in step with `tokens.css` and the components (see "Keeping this page current" at the top).